





RF EXPOSURE REPORT

Applicant	The House of Marley. LLC
Address	3000 Pontiac Trail, Commerce Township, Michigan 48390 United States

Manufacturer or Supplier	The House of Marley. LLC		
Address	3000 Pontiac Trail, Commerce Township, Michigan 48390 United States		
Product	Revolution with speakers, Revolution		
Brand Name	Marley, M A R L E Y		
Model	EM-JT304		
Additional Model & Model Difference	EM-JT004, see item 1		
Date of tests	Apr. 25, 2024 ~ May 28, 2024		

- **⊠** IEEE C95.1

CONCLUSION: The submitted sample was found to <u>COMPLY</u> with the test requirement

Tested by Niko Zhang	Approved by Glyn He
Project Engineer / EMC Department	Assistant Manager / EMC Department
Wiko	A

Date: Jul. 22, 2024

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@bureauveritas.com



Table of Contents

REL	EASE CONTROL RECORD	3
1.	CERTIFICATION	4
2.	RF EXPOSURE LIMIT	5
3.	MPE CALCULATION FORMULA	5
	CLASSIFICATION	
5.	ANTENNA GAIN	6
6.	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@bureauveritas.com



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM2403WDG0249	Original release	Jul. 22, 2024



1. CERTIFICATION

FCC ID:	PVB-EMJT304		
PRODUCT:	Revolution with speakers, Revolution		
BRAND NAME:	Marley, MARLEY		
MODEL NO.:	EM-JT304		
ADDITIONAL NO.:	EM-JT004		
APPLICANT:	The House of Marley. LLC		
STANDARDS:	FCC Part 2 (Section 2.1091)		
	KDB 447498 D01 V06		
	IEEE C95.1		

NOTE: Additional models (see below table) are identical with the test model EM-JT304 except the external speakers, product name and model no. for trading purpose.

Product Name	Model No.	Different
Revolution with speakers	EM-JT304	With External Speakers
Revolution	EM-JT004	Without External Speakers



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)			AVERAGE TIME (minutes)				
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE							
300-1500 F/1500 30							
1500-100,000			1.0	30			

F = Frequency in MHz

3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Chain 0	0.26	PCB Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
GFSK	2402-2480	0	±2	-2	2
8DPSK	2402-2480	0	±2	-2	2

The measured conducted Average Power

io modeli od odnadotod morago i omo:					
Mode Frequency (MHz)		Averaged Power (dBm)			
GFSK	2480	1.17			
8DPSK	2480	0.83			

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
2402-2480	2	0.26	20	0.000335	1.0

--- END ---