



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1



Certificate # 3517.01

TEST REPORT

Applicant	The House of Marley.LLC
Address	3000 Pontiac Trail, Commerce Township, Michigan 48390 United States

Manufacturer or Supplier	The House of Marley.LLC
Address	3000 Pontiac Trail, Commerce Township, Michigan 48390 United States
Product	GET TOGETHER MINI
Brand Name	
Model	EM-JA013A
Additional Model & Model Difference	N/A
Date of tests	Mar. 19, 2021 ~ Apr. 19, 2021

the tests have been carried out according to the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Evans He Project Engineer / EMC Department	Approved by David Huang Assistant Manager / EMC Department

Date: Apr. 21, 2021

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	5
1 SUMMARY OF TEST RESULTS.....	6
2 MEASUREMENT UNCERTAINTY.....	7
3 GENERAL INFORMATION.....	8
3.1 GENERAL DESCRIPTION OF EUT	8
3.2 DESCRIPTION OF TEST MODES	9
3.2.1. CONFIGURATION OF SYSTEM UNDER TEST.....	10
3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	10
3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS	12
3.4 DESCRIPTION OF SUPPORT UNITS	12
4 TEST TYPES AND RESULTS	13
4.1. CONDUCTED EMISSION MEASUREMENT	13
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	13
4.1.2 TEST INSTRUMENTS.....	13
4.1.3 TEST PROCEDURES	14
4.1.4 DEVIATION FROM TEST STANDARD	14
4.1.5 TEST SETUP	15
4.1.6 EUT OPERATING CONDITIONS	15
4.1.7 TEST RESULTS.....	16
4.2. RADIATED EMISSION AND BANDEdge MEASUREMENT.....	18
4.2.1 LIMITS OF RADIATED EMISSION AND BANDEdge MEASUREMENT	18
4.2.2 TEST INSTRUMENTS	19
4.2.3 TEST PROCEDURES	20
4.2.4 DEVIATION FROM TEST STANDARD	21
4.2.5 TEST SETUP	21
4.2.6 EUT OPERATING CONDITIONS	22
4.2.7 TEST RESULTS	23
4.3 NUMBER OF HOPPING FREQUENCY USED	31
4.3.1 LIMIT OF HOPPING FREQUENCY USED.....	31
4.3.2 TEST SETUP	31
4.3.3 TEST INSTRUMENTS	31
4.3.4 TEST PROCEDURES	32
4.3.5 DEVIATION FROM TEST STANDARD	32



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

4.3.6	TEST RESULTS	32
4.4	DWELL TIME ON EACH CHANNEL	34
4.4.1	LIMIT OF DWELL TIME USED	34
4.4.2	TEST SETUP	34
4.4.3	TEST INSTRUMENTS	34
4.4.4	TEST PROCEDURES	34
4.4.5	DEVIATION FROM TEST STANDARD	35
4.4.6	TEST RESULTS	35
4.5	CHANNEL BANDWIDTH	38
4.5.1	LIMITS OF CHANNEL BANDWIDTH	38
4.5.2	TEST SETUP	38
4.5.3	TEST INSTRUMENTS	38
4.5.4	TEST PROCEDURE	38
4.5.5	DEVIATION FROM TEST STANDARD	38
4.5.6	EUT OPERATING CONDITION	38
4.5.7	TEST RESULTS	39
4.6	HOPPING CHANNEL SEPARATION	43
4.6.1	LIMIT OF HOPPING CHANNEL SEPARATION	43
4.6.2	TEST SETUP	43
4.6.3	TEST INSTRUMENTS	43
4.6.4	TEST PROCEDURES	43
4.6.5	DEVIATION FROM TEST STANDARD	43
4.6.6	TEST RESULTS	44
4.7	CONDUCTED OUTPUT POWER	48
4.7.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	48
4.7.2	TEST SETUP	48
4.7.3	TEST INSTRUMENTS	48
4.7.4	TEST PROCEDURES	48
4.7.5	DEVIATION FROM TEST STANDARD	48
4.7.6	EUT OPERATING CONDITION	48
4.7.7	TEST RESULTS	49
4.8	OUT OF BAND EMISSION MEASUREMENT	50
4.8.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	50
4.8.2	TEST INSTRUMENTS	50
4.8.3	TEST PROCEDURE	50
4.8.4	DEVIATION FROM TEST STANDARD	50
4.8.5	EUT OPERATING CONDITION	50



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

4.8.6 TEST RESULTS	50
5 PHOTOGRAPHS OF THE TEST CONFIGURATION.....	57
6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING	
CHANGES TO THE EUT BY THE LAB.....	58



Test Report No.: RF2103WSZ0060-1

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF2103WSZ0060-1	Original release	Apr. 21, 2021



Test Report No.: RF2103WSZ0060-1

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output Power	PASS	Meet the requirement of limit.
15.247(d)& 15.209	Transmitter Radiated Emission	PASS	Meet the requirement of limit.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

NOTE: 1. Test Lab Information:

Lab A: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

Test Lab Address: Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao'an District Shenzhen, Guangdong, 518108, People's Republic of China

Lab B: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

Test Lab Address: No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.

2. Except for Transmitter Radiated Emission, which is tested in Lab B, the others are tested in Lab A.



2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.70dB
Radiated emissions	9KHz ~ 30MHz	2.16dB
	30MHz ~ 1GHz	3.74dB
	1GHz ~ 18GHz	4.66dB
	18GHz ~ 40GHz	4.67dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	GET TOGETHER MINI
MODEL NO.	EM-JA013A
ADDITIONAL MODEL	N/A
FCC ID	PVB-GTMINIA
POWER SUPPLY	DC 7.4V from Li-ion Battery or DC 5V from USB
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, $\pi/4$ -DQPSK, 8 DPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
PEAK OUTPUT POWER	1.419 mW (Max. Measured)
ANTENNA TYPE	FPC Antenna, 1.6dBi Gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB Line: Unshielded Detachable 1.1m

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
3. Please refer to the EUT photo document (Reference No.: 2103WSZ0060) for detailed product photo.
4. Wireless function can not be used normally when the product charging.
5. The EUT was powered by the following adapter:

Adapter	
BRAND:	N/A
MODEL:	ASSA107w-050200
INPUT:	AC 100-240V, 50/60Hz 0.45A
OUTPUT:	DC 5.0V, 2.0A 10.0W
DC LINE:	Unshielded, Detachable 1.1m



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

3.2.1. CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case was found when positioned on X axis for radiated emission.

Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	√	√	DC 5V from Adapter

Where **RE<1G:** Radiated Emission below 1GHz
PLC: Power Line Conducted Emission

RE≥1G: Radiated Emission above 1GHz
APCM: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	39	FHSS	GFSK	DH5

For the test results, only the worst case was shown in test report.

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	Hopping	FHSS	GFSK	DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	25deg. C, 55%RH	DC 5V from Adapter	Aaron Liang
RE≥1G	25deg. C, 55%RH	DC 5V from Adapter	Aaron Liang
PLC	25deg. C, 60%RH	DC 5V from Adapter	Aaron Liang
APCM	25deg. C, 60%RH	DC 5V from Adapter	Aaron Liang



Test Report No.: RF2103WSZ0060-1

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. Section 15.247

KDB 558074 D01 15.247 Meas Guidance v05r02

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit without any other necessary accessory or support units.



Test Report No.: RF2103WSZ0060-1

4 TEST TYPES AND RESULTS

4.1. CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCS30	8471241027	Mar. 10, 22
Artificial Mains Network	SCHWARZBECK	8127	8127713	Mar. 10, 22
ISN	Com-Power	ISN T800	34373	Mar. 10, 22
Test software	EZ-EMC	ICP-03A1	N/A	N/A

NOTE:

1. The test was performed in shielded room 843.
2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD


No deviation.



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- Turned on the power and connected of all equipment.
- EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

4.1.7 TEST RESULTS


CONDUCTED WORST-CASE DATA:

PHASE		Line	6dB BANDWIDTH	9kHz
-------	--	------	---------------	------

NO.	P/L	FREQUENCY (MHZ)	READING (DBUV)	DETECTOR	CORRECTED (DB)	RESULT (DBUV)	LIMIT (DBUV)	MARGIN (DB)
1	L1	0.1617	40.82	QP	10.17	50.99	65.38	-14.39
2	L1	0.1617	22.84	AVG	10.17	33.01	55.38	-22.37
3	L1	0.3021	27.70	QP	10.17	37.87	60.18	-22.31
4	L1	0.3021	12.73	AVG	10.17	22.90	50.18	-27.28
5	L1	0.6609	19.78	QP	10.18	29.96	56.00	-26.04
6	L1	0.6609	5.81	AVG	10.18	15.99	46.00	-30.01
7	L1	1.3590	17.40	QP	10.21	27.61	56.00	-28.39
8	L1	1.3590	3.83	AVG	10.21	14.04	46.00	-31.96
9	L1	2.9112	14.99	QP	10.25	25.24	56.00	-30.76
10	L1	2.9112	2.51	AVG	10.25	12.76	46.00	-33.24
11	L1	17.4105	24.75	QP	10.67	35.42	60.00	-24.58
12	L1	17.4105	16.92	AVG	10.67	27.59	50.00	-22.41

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





BUREAU
VERITAS


Test Report No.: RF2103WSZ0060-1

PHASE	Neutral	6dB BANDWIDTH	9kHz
-------	---------	---------------	------

NO.	P/L	FREQUENCY (MHZ)	READING (DBUV)	DETECTOR	CORRECTED (DB)	RESULT (DBUV)	LIMIT (DBUV)	MARGIN (DB)
1	N	0.1656	36.52	QP	10.14	46.66	65.18	-18.52
2	N	0.1656	17.79	AVG	10.14	27.93	55.18	-27.25
3	N	0.2592	28.25	QP	10.15	38.40	61.46	-23.06
4	N	0.2592	15.00	AVG	10.15	25.15	51.46	-26.31
5	N	0.5010	25.74	QP	10.17	35.91	56.00	-20.09
6	N	0.5010	15.37	AVG	10.17	25.54	46.00	-20.46
7	N	1.5852	16.70	QP	10.26	26.96	56.00	-29.04
8	N	1.5852	3.71	AVG	10.26	13.97	46.00	-32.03
9	N	9.3804	17.62	QP	10.63	28.25	60.00	-31.75
10	N	9.3804	6.25	AVG	10.63	16.88	50.00	-33.12
11	N	18.6702	23.32	QP	10.83	34.15	60.00	-25.85
12	N	18.6702	18.49	AVG	10.83	29.32	50.00	-20.68

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





4.2. RADIATED EMISSION AND BANDEdge MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEdge MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESL6	1300.5001K06 -100262-eQ	Mar. 10, 22
Bilog Antenna	Sunol Sciences	JB6	A110712	Jul. 21, 21
Active Antenna	CMO-POWER	AL-130	121031	Jun. 30, 21
Signal Amplifier	HP	8447E	443008	Mar. 10, 22
Signal and Spectrum Analyzer	R&S	FSV40	101094	Mar. 19, 22
MXA signal analyzer	Agilent	N9020A	MY49100060	Mar. 24, 22
Horn Antenna	COM-POWER	AH-118	71259	Apr. 17, 21
Horn Antenna	COM-POWER	AH-118	71283	Jul. 21, 21
SHF-EHF Horn	Schwarzbeck	BBHA9170	BBHA9170147	May 10, 21
SHF-EHF Horn	Schwarzbeck	BBHA9170	BBHA9170242	May 10, 21
SHF-EHF Horn	Schwarzbeck	BBHA 9170	01023	Dec. 26, 21
SHF-EHF Horn	Schwarzbeck	BBHA 9170	01024	Dec. 26, 21
AMPLIFIER	EM Electronic Corporation	EM01G26G	60613	Mar. 10, 22
Pre-amplifier	Rohde&Schwarz	SCU40	100437	Nov. 17, 21
3m Semi-anechoic Chamber	SAEMC	9m*6m*6m	N/A	Oct. 17, 21
Frequency Analyzer	Keysight	N9010B	MY60240432	Dec. 22, 21
Test Software	EZ-EMC	ICP-03A1	N/A	N/A

NOTE:

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments is 12 months (except 3m Semi-anechoic Chamber). And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 535293.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters(above 1GHz) and 0.8 meters(below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. For below 1GHz was used bilog antenna, and above 1GHz was used horn antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.
- g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.



BUREAU
VERITAS


Test Report No.: RF2103WSZ0060-1

4.2.4 DEVIATION FROM TEST STANDARD


No deviation.

4.2.5 TEST SETUP

Below 30MHz test setup




Below 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).



Above 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:


GFSK

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 m								
No.	Frequency MHz	Factor dB/m	Reading dBuV	Emission dBuV/m	Limit dBuV/m	Margin dB	Tower / Table cm deg	
1	224.31	-19.26	35.31	16.05	46.00	-29.95	100	238
2	323.80	-13.46	29.59	16.13	46.00	-29.87	100	227
3	463.70	-10.07	28.89	18.82	46.00	-27.18	100	216
4	648.69	-5.74	28.76	23.02	46.00	-22.98	100	205
5	737.29	-3.55	28.38	24.83	46.00	-21.17	100	194
*	839.89	-2.28	28.58	26.30	46.00	-19.70	100	182

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value



This data is for evaluation purposes only. It cannot be used for EMC approvals unless it contains the approved signature. If you have any questions regarding the test data, you can write your comments to DGSERVICE@CN.BUREAUVERITAS.COM



BUREAU
VERITAS


Test Report No.: RF2103WSZ0060-1

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 m								
No.	Frequency	Factor	Reading	Emission	Limit	Margin	Tower / Table	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	cm	deg
1	33.11	-13.22	31.83	18.61	40.00	-21.39	100	223
2	146.59	-17.88	30.64	12.76	43.50	-30.74	100	237
3	222.76	-19.44	35.06	15.62	46.00	-30.38	100	206
4	312.92	-13.75	31.75	18.00	46.00	-28.00	100	188
5	510.34	-9.08	29.32	20.26	46.00	-25.74	100	175
6	751.28	-3.42	30.38	26.96	46.00	-19.04	100	164

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. 9KHz~30MHz have been test and test data more than 20dB margin.
5. Margin value = Emission level – Limit value



This data is for evaluation purposes only. It cannot be used for EMC approvals unless it contains the approved signature.
If you have any questions regarding the test data, you can write your comments to DGServicen@cn.bureauveritas.com



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

ABOVE 1GHz DATA

BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
No.	Frequency MHz	Factor dB/m	Reading dBuV	Emission dBuV/m	Limit dBuV/m	Margin dB	Tower / Table	cm	deg
1	2390.00 (PK)	5.06	42.63	47.69	74.00	-26.31	100	225	
2	2390.00 (AV)	5.06	33.53	38.59	54.00	-15.41	100	225	
i	3 2402.00 (PK)	5.13	95.41	100.54	74.00	26.54	100	225	
*i	4 2402.00 (AV)	5.13	94.11	99.24	54.00	45.24	100	225	
5	4804.00 (PK)	10.61	43.98	54.59	74.00	-19.41	100	0	
6	4804.00 (AV)	10.61	30.57	41.18	54.00	-12.82	100	0	
7	7206.00 (PK)	16.87	42.75	59.62	74.00	-14.38	100	0	
8	7206.00 (AV)	16.87	28.61	45.48	54.00	-8.52	100	0	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M									
No.	Frequency MHz	Factor dB/m	Reading dBuV	Emission dBuV/m	Limit dBuV/m	Margin dB	Tower / Table	cm	deg
1	2390.00 (PK)	5.06	41.18	46.24	74.00	-27.76	100	108	
2	2390.00 (AV)	5.06	32.10	37.16	54.00	-16.84	100	108	
i	3 2402.00 (PK)	5.13	91.58	96.71	74.00	22.71	100	108	
*i	4 2402.00 (AV)	5.13	91.12	96.25	54.00	42.25	100	108	
5	4804.00 (PK)	10.61	42.67	53.28	74.00	-20.72	100	0	
6	4804.00 (AV)	10.61	30.17	40.78	54.00	-13.22	100	0	
7	7206.00 (PK)	16.87	41.36	58.23	74.00	-15.77	100	0	
8	7206.00 (AV)	16.87	27.97	44.84	54.00	-9.16	100	0	

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
No.	Frequency	Factor	Reading	Emission	Limit	Margin	Tower / Table		
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	cm	deg	
i	1 2441.00 (PK)	5.34	93.68	99.02	74.00	25.02	100	156	
*i	2 2441.00 (AV)	5.34	93.08	98.42	54.00	44.42	100	156	
3	4882.00 (PK)	10.92	40.34	51.26	74.00	-22.74	100	0	
4	4882.00 (AV)	10.92	28.23	39.15	54.00	-14.85	100	0	
5	7323.00 (PK)	17.19	39.06	56.25	74.00	-17.75	100	0	
6	7323.00 (AV)	17.19	25.99	43.18	54.00	-10.82	100	0	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M									
No.	Frequency	Factor	Reading	Emission	Limit	Margin	Tower / Table		
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	cm	deg	
i	1 2441.00 (PK)	5.34	90.28	95.62	74.00	21.62	100	79	
*i	2 2441.00 (AV)	5.34	89.00	94.34	54.00	40.34	100	79	
3	4882.00 (PK)	10.92	42.30	53.22	74.00	-20.78	100	0	
4	4882.00 (AV)	10.92	29.25	40.17	54.00	-13.83	100	0	
5	7323.00 (PK)	17.19	36.98	54.17	74.00	-19.83	100	0	
6	7323.00 (AV)	17.19	25.09	42.28	54.00	-11.72	100	0	

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



Test Report No.: RF2103WSZ0060-1

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Frequency	Factor	Reading	Emission	Limit	Margin	Tower / Table	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	cm	deg
i	1 2480.00 (PK)	5.55	91.91	97.46	74.00	23.46	100	301
*i	2 2480.00 (AV)	5.55	91.23	96.78	54.00	42.78	100	301
3	2483.50 (PK)	5.57	59.01	64.58	74.00	-9.42	100	301
4	2483.50 (AV)	5.57	45.43	51.00	54.00	-3.00	100	301
5	4960.00 (PK)	11.24	45.14	56.38	74.00	-17.62	100	0
6	4960.00 (AV)	11.24	32.81	43.85	54.00	-10.15	100	0
7	7440.00 (PK)	17.52	42.84	60.36	74.00	-13.64	100	0
8	7440.00 (AV)	17.52	29.26	46.78	54.00	-7.22	100	0

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Frequency	Factor	Reading	Emission	Limit	Margin	Tower / Table	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	cm	deg
i	1 2480.00 (PK)	5.55	91.45	97.00	74.00	23.00	100	69
*i	2 2480.00 (AV)	5.55	90.81	96.36	54.00	42.36	100	69
3	2483.50 (PK)	5.57	57.68	63.25	74.00	-10.75	100	69
4	2483.50 (AV)	5.57	45.30	50.87	54.00	-3.13	100	69
5	4960.00 (PK)	11.24	42.78	54.02	74.00	-19.98	100	0
6	4960.00 (AV)	11.24	31.53	42.77	54.00	-11.23	100	0
7	7440.00 (PK)	17.52	40.59	58.11	74.00	-15.89	100	0
8	7440.00 (AV)	17.52	25.74	43.26	54.00	-10.74	100	0

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Frequency MHz	Factor dB/m	Reading dBuV	Emission dBuV/m	Limit dBuV/m	Margin dB	Tower / Table cm deg	
1	2390.00 (PK)	5.06	39.10	44.16	74.00	-29.84	100 188	
2	2390.00 (AV)	5.06	31.89	36.95	54.00	-17.05	100 188	
i	3 2402.00 (PK)	5.13	91.55	96.68	74.00	22.68	100 188	
*i	4 2402.00 (AV)	5.13	90.62	95.75	54.00	41.75	100 188	
5	4804.00 (PK)	10.61	45.75	56.36	74.00	-17.64	100 0	
6	4804.00 (AV)	10.61	31.54	42.15	54.00	-11.85	100 0	
7	7206.00 (PK)	16.87	43.68	60.55	74.00	-13.45	100 0	
8	7206.00 (AV)	16.87	28.60	45.47	54.00	-8.53	100 0	

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Frequency MHz	Factor dB/m	Reading dBuV	Emission dBuV/m	Limit dBuV/m	Margin dB	Tower / Table cm deg	
1	2390.00 (PK)	5.06	38.16	43.22	74.00	-30.78	100 85	
2	2390.00 (AV)	5.06	29.04	34.10	54.00	-19.90	100 85	
i	3 2402.00 (PK)	5.13	88.13	93.26	74.00	19.26	100 85	
*i	4 2402.00 (AV)	5.13	87.05	92.18	54.00	38.18	100 85	
5	4804.00 (PK)	10.61	45.08	55.69	74.00	-18.31	100 0	
6	4804.00 (AV)	10.61	30.16	40.77	54.00	-13.23	100 0	
7	7206.00 (PK)	16.87	42.94	59.81	74.00	-14.19	100 0	
8	7206.00 (AV)	16.87	26.22	43.09	54.00	-10.91	100 0	

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Frequency	Factor	Reading	Emission	Limit	Margin	Tower / Table	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	cm	deg
i	1 2441.00 (PK)	5.34	85.69	91.03	74.00	17.03	100	134
*i	2 2441.00 (AV)	5.34	84.12	89.46	54.00	35.46	100	134
	3 4882.00 (PK)	10.92	44.56	55.48	74.00	-18.52	100	0
	4 4882.00 (AV)	10.92	30.26	41.18	54.00	-12.82	100	0
	5 7323.00 (PK)	17.19	42.29	59.48	74.00	-14.52	100	0
	6 7323.00 (AV)	17.19	27.91	45.10	54.00	-8.90	100	0

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Frequency	Factor	Reading	Emission	Limit	Margin	Tower / Table	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	cm	deg
i	1 2441.00 (PK)	5.34	83.13	88.47	74.00	14.47	100	66
*i	2 2441.00 (AV)	5.34	81.16	86.50	54.00	32.50	100	66
	3 4882.00 (PK)	10.92	42.12	53.04	74.00	-20.96	100	0
	4 4882.00 (AV)	10.92	29.86	40.78	54.00	-13.22	100	0
	5 7323.00 (PK)	17.19	40.50	57.69	74.00	-16.31	100	0
	6 7323.00 (AV)	17.19	24.96	42.15	54.00	-11.85	100	0

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Frequency	Factor	Reading	Emission	Limit	Margin	Tower / Table	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	cm	deg
i 1	2480.00 (PK)	5.55	89.07	94.62	74.00	20.62	100	101
*i 2	2480.00 (AV)	5.55	87.95	93.50	54.00	39.50	100	101
3	2483.50 (PK)	5.57	61.88	67.45	74.00	-6.55	100	101
4	2483.50 (AV)	5.57	44.85	50.42	54.00	-3.58	100	101
5	4960.00 (PK)	11.24	40.01	51.25	74.00	-22.75	100	0
6	4960.00 (AV)	11.24	24.98	36.22	54.00	-17.78	100	0
7	7440.00 (PK)	17.52	39.84	57.36	74.00	-16.64	100	0
8	7440.00 (AV)	17.52	24.63	42.15	54.00	-11.85	100	0

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Frequency	Factor	Reading	Emission	Limit	Margin	Tower / Table	
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	cm	deg
i 1	2480.00 (PK)	5.55	88.71	94.26	74.00	20.26	100	77
*i 2	2480.00 (AV)	5.55	87.50	93.05	54.00	39.05	100	77
3	2483.50 (PK)	5.57	60.00	65.57	74.00	-8.43	100	77
4	2483.50 (AV)	5.57	43.78	49.35	54.00	-4.65	100	77
5	4960.00 (PK)	11.24	38.61	49.85	74.00	-24.15	100	0
6	4960.00 (AV)	11.24	24.35	35.59	54.00	-18.41	100	0
7	7440.00 (PK)	17.52	37.99	55.51	74.00	-18.49	100	0
8	7440.00 (AV)	17.52	22.66	40.18	54.00	-13.82	100	0

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB).
3. The emission levels of other frequencies were greater than 20dB margin.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



BUREAU
VERITAS


Test Report No.: RF2103WSZ0060-1

4.3 NUMBER OF HOPPING FREQUENCY USED

4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Next Cal.
Wireless Connectivity Tester	R&S	CMW270	1201.0002K75	Dec. 22, 21
MXA VEXTOR SIGNAL	Agilent	n5182a	MY50140530	Mar. 07, 22
MXA signal analyzer	Agilent	n9020a	MY49100060	Mar. 24, 22
RF Control Unit	Tonscend	JS0806-2	188060112	Mar. 07, 22
Signal Generation	Agilent	E4421B	US40051152	Dec. 22, 21
DC Power Supply	Agilent	E3640A	MY40004013	Mar. 14, 22
Programmable Temperature & Humidity Chamber	Hongjin	HYC-TH-225 DH	DG-180746	Mar. 10, 22
Test System	Tonscend	JS 1120-3	N/A	N/A
Power Splitter	Weinschel	1580-1	TL177	Mar. 27, 22

NOTE:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRR/CHINA and NIM/CHINA.



4.3.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were completed.

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.




BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

GFSK



8DPSK



Bureau Veritas (Shenzhen)
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology
Park, South Side of Zhoushi Road, Bao'an District,
Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800
Email: customerservice.sz@bureauveritas.com



4.4 DWELL TIME ON EACH CHANNEL

4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.4.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency to be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 TEST RESULTS

GFSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	3.16	32	320	0.417	133.44	400	PASS
DH3	79	31.6	3.16	11	110	1.673	184.03	400	PASS
DH5	79	31.6	3.16	5	50	2.919	145.95	400	PASS

8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
3DH1	79	31.6	3.16	30	300	0.412	123.6	400	PASS
3DH3	79	31.6	3.16	12	120	1.395	167.4	400	PASS
3DH5	79	31.6	3.16	9	90	2.913	262.17	400	PASS

NOTE: Test plots of the transmitting time slot are shown on next page.




BUREAU
VERITAS


Test Report No.: RF2103WSZ0060-1

GFSK


DH1



DH3



DH5



Bureau Veritas (Shenzhen)
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology
Park, South Side of Zhoushi Road, Bao'an District,
Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800
Email: customerservice.sz@bureauveritas.com




BUREAU
VERITAS


Test Report No.: RF2103WSZ0060-1

8DPSK


3DH1



3DH3



3DH5



Bureau Veritas (Shenzhen)
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology
Park, South Side of Zhoushi Road, Bao'an District,
Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800
Email: customerservice.sz@bureauveritas.com




4.5 CHANNEL BANDWIDTH

4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.5.4 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

4.5.7 TEST RESULTS

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.942
39	2441	0.870
78	2480	0.942

CH 0





BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

CH 39



CH 78





BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.251
39	2441	1.239
78	2480	1.254

CH 0





BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

CH 39



CH 78






4.6 HOPPING CHANNEL SEPARATION

4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.6.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

4.6.6 TEST RESULTS

GFSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.002	0.942	0.942	PASS
39	2441	1.002	0.87	0.87	PASS
78	2480	1.002	0.942	0.942	PASS

CH 0






BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

CH 39



CH 78





BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

8DPSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.002	1.251	0.83	PASS
39	2441	1.002	1.239	0.83	PASS
78	2480	1.002	1.254	0.84	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0





BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

CH 39



CH 78






4.7 CONDUCTED OUTPUT POWER

4.7.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

4.7.2 TEST SETUP



4.7.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.7.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A peak power meter was used to read the response of the peak power sensor. Record the peak power level.

4.7.5 DEVIATION FROM TEST STANDARD

No deviation.

4.7.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

4.7.7 TEST RESULTS

MAXIMUM PEAK OUTPUT POWER

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	1.23	1.327	1000	PASS
39	2441	1.36	1.368	1000	PASS
78	2480	1.28	1.343	1000	PASS

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	1.36	1.368	125	PASS
39	2441	1.45	1.396	125	PASS
78	2480	1.52	1.419	125	PASS

AVERAGE OUTPUT POWER(FOR REFERENCE)

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	0.98	1.253
39	2441	0.84	1.213
78	2480	0.77	1.194

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	1.03	1.268
39	2441	0.99	1.256
78	2480	1.18	1.312



4.8 OUT OF BAND EMISSION MEASUREMENT

4.8.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz RBW).

4.8.2 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. of Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

4.8.5 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.8.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.




BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

GFSK

CH 0



CH 39






BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1



CH 78



Bureau Veritas (Shenzhen)
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology
Park, South Side of Zhoushi Road, Bao'an District,
Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800
Email: customerservice.sz@bureauveritas.com




BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1

8DPSK

CH 0



CH 39



Bureau Veritas (Shenzhen)
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology
Park, South Side of Zhoushi Road, Bao'an District,
Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800
Email: customerservice.sz@bureauveritas.com





BUREAU
VERITAS

Test Report No.: RF2103WSZ0060-1



CH 78



Bureau Veritas (Shenzhen)
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology
Park, South Side of Zhoushi Road, Bao'an District,
Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800
Email: customerservice.sz@bureauveritas.com




BUREAU
VERITAS


Test Report No.: RF2103WSZ0060-1

GFSK


Hopping off Low Channel




Hopping off High Channel



Hopping on Low Channel



Hopping on High Channel



Bureau Veritas (Shenzhen)
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology
Park, South Side of Zhoushi Road, Bao'an District,
Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800
Email: customerservice.sz@bureauveritas.com




BUREAU
VERITAS


Test Report No.: RF2103WSZ0060-1

8DPSK


Hopping off Low Channel




Hopping off High Channel



Hopping on Low Channel



Hopping on High Channel



Bureau Veritas (Shenzhen)
Consumer Products Services Co., Ltd.

Zone A, Floor 1, Building 2, Wan Ye Long Technology
Park, South Side of Zhoushi Road, Bao'an District,
Shenzhen Guangdong, 518108, China.

Tel: +86-755-26014629 Ext.800
Email: customerservice.sz@bureauveritas.com



Test Report No.: RF2103WSZ0060-1

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF2103WSZ0060-1

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---