2006-11-23 Reference: cBProject-0502-18 (3)

Attn: Reviewing Engineer

Federal Communications Commission 7435 Oakland Mills Road Columbia, MD 21046

RE: PART 15 UNLICENSED MODULAR TRANSMITTER APPROVAL

To Whom It May Concern:

We, connectBlue AB, hereby requests a **Limited Modular Approval** of our OEM-Bluetooth module, described as follows:

Brand name: connectBlue AB Model name: cB-OEMSPA310i Type number: cB-0907-01 FCC ID: PVH090701S

In FCC Public Notice DA 00-1407 released June 26, 2000 there are eight numbered requirements that our OEM-Bluetooth module complies with.

1. The modular transmitter must have its own shielding.

The module does not have an own shielding. Nethertheless this module fulfils the emission requirements of the FCC rules without additional shielding.

2. The modular transmitter must have buffered modulation/data inputs

The module has a memory management unit inside of the IC. It buffers the data inputs from UART and USB terminal.

3. The modular transmitter must have its own power supply regulation

The IC contains an own voltage regulation. In case of changes in the supply voltage VCC (for example caused by temperature changes or other effects), the internal voltage will be stabilized.

4. The modular transmitter must comply with the antenna requirements of Section 15.203 and 15.204c

The module is equipped with an onboard Bluetooth Chip Antenna. For further details please refer to the antenna data sheet included in the filing.

5. The modular transmitter must be tested in a stand-alone configuration

The EUT was tested in a stand-alone configuration.

connectBlue ab residence: malmö

VAT no. se 556589-0851-01

Norra Vallgatan 64 3V se-211 22 malmö sweden tel.+46 (0)40-6307100 fax.+46 (0)40-237137 e-mail: info@connectBlue.se

6. The modular transmitter must be labelled with its own FCC ID number

The EUT will be labelled with its own FCC ID number. The label is specified in Exhibit D. If the module is installed inside of an end-product, the label will not be visible. In this case the OEM customer will be instructed to how to apply the exterior label.

7. The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements.

The EUT is compliant with all applicable FCC rules. Detail instructions are given in the product Users Guide

8. The modular transmitter must comply with any applicable RF exposure requirements.

The maximum measured power output of about 2.3 mW (~3.62 dBm) with an antenna gain of 0 dBi [equal to a numeric gain 1] is far below the low threshold as defined in the TCB exclusion list. Therefore there are no specific operating conditions to be defined to satisfy RF Exposure compliance.