

ANNEX D RESULTS OF THE RECEIVER MEASUREMENTS


1 RADIATED EMISSIONS (RECEIVER)

1.1 Preliminary radiated emission measurement with external patch antenna

Ambient temperature	21 °C	Relative humidity	37 %
---------------------	-------	-------------------	------


Position of EUT:	The EUT was set-up on a non-conducting table of a height of 0.8 m. The distance between EUT and antenna was 3 m.
Cable guide:	The cables of the EUT were fixed on the non-conducting table. For further information of the cable guide refer to the pictures in annex A of this test report.
Test record:	All results are shown in the following. The test was carried out in test mode 5 of the EUT. The method of measurement is described in subclause 5.7.1 of the test report.
Supply voltage:	During all measurements the EUT was supplied with 5.0 V DC via the carrier board.
Remark:	As pre-tests have shown, the emissions in the frequency range 9 kHz to 1 GHz are not depending on the receiver operation mode. The highest emissions in this frequency range were emitted if an external antenna is used. Therefore the emissions in this frequency range were measured only with the receiver operates in operation mode 10 and the external patch antenna type Huber+Suhner SPA 2400/70/9/0/RCP, because this antenna has the highest gain all antennas in question. The results were shown below.

111592_159.wmf: Receiver emissions from 9 kHz to 150 kHz (operation mode 10):




ANNEX D RESULTS OF THE RECEIVER MEASUREMENTS

111592_158.wmf: Receiver emissions from 150 kHz to 1 MHz (operation mode 10):



111592_157.wmf: Receiver emissions from 1 MHz to 30 MHz (operation mode 10):




No significant frequencies above the noise floor of the system were found during the preliminary radiated emission test, so no measurements were carried out on the outdoor test site.

TEST EQUIPMENT USED FOR THE TEST:


29, 31 – 36, 43, 44, 49, 55

ANNEX D RESULTS OF THE RECEIVER MEASUREMENTS

111592_144.wmf: Receiver emissions from 30 MHz to 230 MHz (operation mode 10):



111592_145.wmf: Receiver emissions from 230 MHz to 1 GHz (operation mode 10):




The following frequencies were found during the preliminary radiated emission test:

- 144.000 MHz and 176.000 MHz, 288.000


These frequencies have to be measured on the open area test site. The results were presented in the following.

ANNEX D RESULTS OF THE RECEIVER MEASUREMENTS

111592_142.wmf: Receiver emissions from 1 GHz to 4 GHz (operation mode 10):



111592_143.wmf: Receiver emissions from 4 GHz to 12.5 GHz (operation mode 10):



The following frequencies were found during the preliminary radiated emission test:

- 2.4394 GHz and 4.8788 GHz.

These frequencies have to be measured in a final measurement. The results were presented in the following.


ANNEX D RESULTS OF THE RECEIVER MEASUREMENTS

1.2 Final radiated emission measurement (30 MHz to 1 GHz) with external patch antenna

Ambient temperature	21 °C	Relative humidity	66 %
---------------------	-------	-------------------	------

Position of EUT:	The EUT was set-up on a non-conducting table of a height of 0.8 m. The distance between EUT and antenna was 3 m.
Cable guide:	The cables of the EUT were fixed on the non-conducting table. For further information of the cable guide refer to the pictures in annex A of this test report.
Test record:	All results are shown in the following. The test was carried out in test mode 5 of the EUT.
Supply voltage:	During all measurements the EUT was supplied with 5.0 V DC via the carrier board.
Test method:	Refer clause 5.7 of the test report F111592E3.

The measured points and the limit line in the following diagram refer to the standard measurement of the emitted interference in compliance with the above mentioned standard. The measured points marked by an x are the measured results of the standard subsequent measurement on the open area test site.



Data record name: 111592_2RX

ANNEX D RESULTS OF THE RECEIVER MEASUREMENTS

The results of the standard subsequent measurement on the open area test site are indicated in the table below. The limits as well as the measured results (levels) refer to the above mentioned standard while taking account of the specified requirements for a 3 m measuring distance.

The measurement time with the quasi-peak measuring detector is 1 second.

Result measured with the quasipeak detector:
(These values are marked in the diagram by an x)

Spurious emissions outside restricted bands										
Frequency MHz	Result dBμV/m	Limit dBμV/m	Margin dB	Readings dBμV	Antenna factor dB/m	Cable loss dB	Height cm	Azimuth deg	Pol.	Pos.
144.000	29.7	43.5	13.8	16.6	11.8	1.3	100.0	86.0	Vert.	1
176.000	22.0	43.5	21.5	10.7	9.8	1.5	100.0	160.0	Vert.	1
288.000	32.5	46.0	13.5	17.7	12.9	1.9	107.0	90.0	Hor.	1
Measurement uncertainty					+2.2 dB / -3.6 dB					

The test results were calculated with the following formula:

Result [dBμV/m] = reading [dBμV] + cable loss [dB] + antenna factor [dB/m]

Test: Passed

TEST EQUIPMENT USED FOR THE TEST:

14 – 20

ANNEX D RESULTS OF THE RECEIVER MEASUREMENTS

1.3 Final radiated emission measurement (1 GHz to 25 GHz) with external patch antenna

Ambient temperature	21 °C	Relative humidity	37 %
---------------------	-------	-------------------	------

Position of EUT: The EUT was set-up on a non-conducting table of a height of 0.8 m. The distance between EUT and antenna was 3 m.

Cable guide: The cable of the EUT is running vertically to the false floor. For detail information of test set-up and the cable guide refer to the pictures in annex A of this test report.

Test record: All results are shown in the following.

Supply voltage: During all measurements the EUT was supplied with 3.3 V DC by the carrier board.

Resolution bandwidth: For all measurements a resolution bandwidth of 1 MHz was used.

Remark: The emission measurement in this frequency range was carried out by using the external patch antenna type Huber+Suhner SPA 2400/70/9/0/RCP, because of this antenna has the highest antenna gain of all external patch antennas in question. Additional pre-tests have shown that this antenna causes the highest emissions of all patch antennas in question.

Result measured with the peak detector:

Frequency GHz	Corr. value dBμV/m	Limit dBμV/m	Margin dB	Readings dBμV	Antenna factor 1/m	Preamp. dB	Cable loss dB	Height cm	Pol.	Pos.
2.4394	37.7	74.0	36.3	32.1	28.4	26.5	3.7	150	Hor.	2
4.8788	44.9	74.0	29.1	32.5	32.8	25.7	5.3	150	Hor.	2
Measurement uncertainty						+2.2 dB / -3.6 dB				

Result measured with the average detector:

Frequency GHz	Corr. value dBμV/m	Limit dBμV/m	Margin dB	Readings dBμV	Antenna factor 1/m	Preamp. dB	Cable loss dB	Height cm	Pol.	Pos.
2.4394	25.8	54.0	28.2	20.2	28.4	26.5	3.7	150	Hor.	2
4.8788	36.1	54.0	17.9	23.7	32.8	25.7	5.3	150	Hor.	2
Measurement uncertainty						+2.2 dB / -3.6 dB				


Test: Passed

TEST EQUIPMENT USED FOR THE TEST:
29, 31 –34, 36, 44, 49


ANNEX D RESULTS OF THE RECEIVER MEASUREMENTS

1.4 Preliminary radiated emission measurement (1 GHz to 12.5 GHz) with internal antenna

111592_149.wmf: Receiver emissions from 1 GHz to 4 GHz (operation mode 10):



111592_148.wmf: Receiver emissions from 4 GHz to 12.5 GHz (operation mode 10):



No significant frequencies above the noise floor of the system were found during the preliminary radiated emission test, so no final measurements were carried out inside the fully anechoic chamber.

TEST EQUIPMENT USED FOR THE TEST:


29, 31 –34, 36, 44, 49

ANNEX D RESULTS OF THE RECEIVER MEASUREMENTS


1.5 Preliminary radiated emission measurement with external monopole antenna

Remark: As pre-tests have shown, the highest emissions in this frequency range were emitted if the external monopole antenna type Huber+Suhner SOA 2400/360/6/0/V is used. The results were shown below.

111592_146.wmf: Receiver emissions from 1 GHz to 4 GHz (operation mode 10):



111592_147.wmf: Receiver emissions from 4 GHz to 12.5 GHz (operation mode 10):



No significant frequencies above the noise floor of the system were found during the preliminary radiated emission test, so no final measurements were carried out inside the fully anechoic chamber.


TEST EQUIPMENT USED FOR THE TEST:

29, 31 –34, 36, 44, 49


ANNEX D RESULTS OF THE RECEIVER MEASUREMENTS

1.6 Preliminary radiated emission measurement with EPA antenna

111592_150.wmf: Receiver emissions from 1 GHz to 4 GHz (operation mode 10):



111592_151.wmf: Receiver emissions from 4 GHz to 12.5 GHz (operation mode 10):



The following frequencies were found during the preliminary radiated emission test:

- 1.048 GHz, 1.080 GHz and 1.125 GHz.

These frequencies have to be measured in a final measurement. The results were presented in the following.

TEST EQUIPMENT USED FOR THE TEST:

29, 31 –34, 36, 44, 49

ANNEX D RESULTS OF THE RECEIVER MEASUREMENTS

1.7 Final radiated emission measurement (1 GHz to 25 GHz) with EPA antenna

Ambient temperature	21 °C	Relative humidity	37 %
---------------------	-------	-------------------	------

Position of EUT: The EUT was set-up on a non-conducting table of a height of 0.8 m. The distance between EUT and antenna was 3 m.

Cable guide: The cable of the EUT is running vertically to the false floor. For detail information of test set-up and the cable guide refer to the pictures in annex A of this test report.

Test record: All results are shown in the following.

Supply voltage: During all measurements the EUT was supplied with 3.3 V DC by the carrier board.

Resolution bandwidth: For all measurements a resolution bandwidth of 1 MHz was used.

Result measured with the peak detector:

Frequency GHz	Corr. value dBμV/m	Limit dBμV/m	Margin dB	Readings dBμV	Antenna factor 1/m	Preamp. dB	Cable loss dB	Height cm	Pol.	Pos.
1.048	34.1	74.0	39.9	34.1	24.2	26.5	2.3	150	Hor.	3
1.080	34.6	74.0	39.4	34.3	24.4	26.5	2.4	150	Hor.	3
1.125	33.2	74.0	40.8	32.6	24.6	26.5	2.5	150	Hor.	3
Measurement uncertainty						+2.2 dB / -3.6 dB				

Result measured with the average detector:

Frequency GHz	Corr. value dBμV/m	Limit dBμV/m	Margin dB	Readings dBμV	Antenna factor 1/m	Preamp. dB	Cable loss dB	Height cm	Pol.	Pos.
1.048	24.1	54.0	29.9	24.1	24.2	26.5	2.3	150	Hor.	3
1.080	23.4	54.0	30.6	23.1	24.4	26.5	2.4	150	Hor.	3
1.125	20.3	54.0	33.7	19.7	24.6	26.5	2.5	150	Hor.	3
Measurement uncertainty						+2.2 dB / -3.6 dB				

Test: Passed

TEST EQUIPMENT USED FOR THE TEST:
29, 31 –34, 36, 44, 49