

APPLICATION CERTIFICATION FCC Part 15C

On Behalf of
EKEN (HK) Electronics Co., Ltd.

7 INCH TABLET
Model No.: X70, GT70X , GC70XG ,K7A20-4

FCC ID: PVVX70

Prepared for : EKEN (HK) Electronics Co., Ltd.
Address : Building 2F-2B, HuaFeng Science Park GongHe Road,
XiXiang, Baoan District, ShenZhen, China

Prepared by : ACCURATE TECHNOLOGY CO., LTD
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20131533
Date of Test : July 17-23, 2013
Date of Report : July 23, 2013

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT).....	5
1.2. Carrier Frequency of Channels	6
1.3. Special Accessory and Auxiliary Equipment	6
1.4. Description of Test Facility	6
1.5. Measurement Uncertainty	7
2. MEASURING DEVICE AND TEST EQUIPMENT	8
3. OPERATION OF EUT DURING TESTING	9
3.1. Operating Mode	9
3.2. Configuration and peripherals	10
4. TEST PROCEDURES AND RESULTS	11
5. 6DB BANDWIDTH MEASUREMENT	12
5.1. Block Diagram of Test Setup.....	12
5.2. The Requirement For Section 15.247(a)(2).....	12
5.3. EUT Configuration on Measurement	12
5.4. Operating Condition of EUT	12
5.5. Test Procedure	12
5.6. Test Result	12
6. MAXIMUM PEAK OUTPUT POWER	20
6.1. Block Diagram of Test Setup.....	20
6.2. The Requirement For Section 15.247(b)(3).....	20
6.3. EUT Configuration on Measurement	20
6.4. Operating Condition of EUT	20
6.5. Test Procedure	20
6.6. Test Result	21
7. POWER SPECTRAL DENSITY MEASUREMENT	28
7.1. Block Diagram of Test Setup.....	28
7.2. The Requirement For Section 15.247(e).....	28
7.3. EUT Configuration on Measurement	28
7.4. Operating Condition of EUT	28
7.5. Test Procedure	28
7.6. Test Result	29
8. BAND EDGE COMPLIANCE TEST	36
8.1. Block Diagram of Test Setup.....	36
8.2. The Requirement For Section 15.247(d)	36
8.3. EUT Configuration on Measurement	36
8.4. Operating Condition of EUT	36
8.5. Test Procedure	36
8.6. Test Result	37
9. RADIATED SPURIOUS EMISSION TEST	58
9.1. Block Diagram of Test Setup.....	58
9.2. The Limit For Section 15.247(d)	58
9.3. Restricted bands of operation	59
9.4. Configuration of EUT on Measurement	59

9.5.	Operating Condition of EUT	59
9.6.	Test Procedure	60
9.7.	The Field Strength of Radiation Emission Measurement Results	60
10.	CONDUCTED SPURIOUS EMISSION COMPLIANCE TEST	87
10.1.	Block Diagram of Test Setup.....	87
10.2.	The Requirement For Section 15.247(d)	87
10.3.	EUT Configuration on Measurement	87
10.4.	Operating Condition of EUT	87
10.5.	Test Procedure	88
10.6.	Test Result	88
11.	AC POWER LINE CONDUCTED EMISSION FOR FCC PART 15 SECTION 15.207(A)	101
11.1.	Block Diagram of Test Setup.....	101
11.2.	The Emission Limit	101
11.3.	Configuration of EUT on Measurement	102
11.4.	Operating Condition of EUT	102
11.5.	Test Procedure	102
11.6.	Power Line Conducted Emission Measurement Results	103
12.	ANTENNA REQUIREMENT.....	105
12.1.	The Requirement	105
12.2.	Antenna Construction	105

Test Report Certification

Applicant : EKEN (HK) Electronics Co., Ltd.
Manufacturer : EKEN (HK) Electronics Co., Ltd.
EUT Description : 7 INCH TABLET
(A) MODEL NO.: X70, GT70X , GC70XG ,K7A20-4
(B) SERIAL NO.: N/A
(C) POWER SUPPLY: DC 3.7V (Li-polymer battery) & DC 5V (Power by Adapter)

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247
ANSI C63.4: 2009

The EUT was tested according to DTS test procedure of April 09, 2013 KDB558074 D01 DTS Meas Guidance v03 for compliance to FCC 47CFR 15.247 requirements

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.247 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : July 17-23, 2013

Prepared by :



(Engineer)

Approved & Authorized Signer :



(Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	7 INCH TABLET
Model Number	:	X70, GT70X , GC70XG ,K7A20-4 (Note: These samples are same except for the model number is difference. So we prepare the X70 for FCC test.)
Frequency Range	:	802.11b/g/n(20MHz): 2412-2462MHz 802.11n(40MHz): 2422-2452MHz
Number of Channels	:	802.11b/g/n (20MHz):11 802.11n (40MHz): 7
Antenna Gain	:	0dBi
Power Supply	:	DC 3.7V (Li-polymer battery) & DC 5V (Power by adapter)
Adapter	:	Model number: HND050200U Input: AC 100-240V; 50/60Hz 0.35A Output: DC 5V/2.0A USB line: Non-shielded, Non-detachable, 1.5m
Data Rate	:	802.11b: 11, 5.5, 2, 1 Mbps 802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps 802.11n: up to 150Mbps
Applicant	:	EKEN (HK) Electronics Co., Ltd.
Address	:	Building 2F-2B, HuaFeng Science Park GongHe Road, XiXiang, Baoan District, ShenZhen, China
Manufacturer	:	EKEN (HK) Electronics Co., Ltd.
Address	:	Building 2F-2B, HuaFeng Science Park GongHe Road, XiXiang, Baoan District, ShenZhen, China
Date of sample received	:	July 16, 2013
Date of Test	:	July 17-23, 2013

1.2.Carrier Frequency of Channels

802.11b, 802.11g, 802.11n (20MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	11	2462
06	2437	---	---

802.11n (40MHz)

Channel	Frequency(MHz)	Channel	Frequency(MHz)
---	---	07	2442
---	---	08	2447
03	2422	09	2452
04	2427	---	---
05	2432	---	---
06	2437	---	---

1.3.Special Accessory and Auxiliary Equipment

n.a.

1.4.Description of Test Facility

EMC Lab	:	Accredited by TUV Rheinland Shenzhen
		Listed by FCC
		The Registration Number is 752051
		Listed by Industry Canada
		The Registration Number is 5077A-2
		Accredited by China National Accreditation Committee for Laboratories
		The Certificate Registration Number is L3193
Name of Firm	:	ACCURATE TECHNOLOGY CO. LTD
Site Location	:	F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

1.5.Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty
(9kHz-30MHz) = 3.08dB, k=2

Radiated emission expanded uncertainty
(30MHz-1000MHz) = 4.42dB, k=2

Radiated emission expanded uncertainty
(Above 1GHz) = 4.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 12, 2013	Jan. 11, 2014
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 12, 2013	Jan. 11, 2014
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 12, 2013	Jan. 11, 2014
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 12, 2013	Jan. 11, 2014
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 12, 2013	Jan. 11, 2014
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 12, 2013	Jan. 11, 2014
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 12, 2013	Jan. 11, 2014
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 12, 2013	Jan. 11, 2014
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 12, 2013	Jan. 11, 2014
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 12, 2013	Jan. 11, 2014
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 12, 2013	Jan. 11, 2014
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 12, 2013	Jan. 11, 2014

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode

The mode is used: **1.802.11b Transmitting mode**

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

2.802.11g Transmitting mode

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

3.802.11n (20MHz) Transmitting mode

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

4.802.11n (40MHz) Transmitting mode

Low Channel: 2422MHz

Middle Channel: 2437MHz

High Channel: 2452MHz

5. Charging

3.2.Configuration and peripherals




Figure 1 Setup: Transmitting mode




Figure 2 Setup: Charging mode

4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.247(a)(2)	6dB Bandwidth Test	Compliant
Section 15.247(e)	Power Spectral Density Test	Compliant
Section 15.247(b)(3)	Maximum Peak Output Power Test	Compliant
Section 15.247(d)	Band Edge Compliance Test	Compliant
Section 15.247(d) Section 15.209	Radiated Spurious Emission Test	Compliant
Section 15.247(d)	Conducted Spurious Emission Test	Compliant
Section 15.207	AC Power Line Conducted Emission Test	Compliant
Section 15.203	Antenna Requirement	Compliant

5. 6DB BANDWIDTH MEASUREMENT

5.1. Block Diagram of Test Setup



5.2. The Requirement For Section 15.247(a)(2)

Section 15.247(a)(2): Systems using digital modulation techniques may operate in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

5.3. EUT Configuration on Measurement

The equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.4. Operating Condition of EUT

5.4.1. Setup the EUT and simulator as shown as Section 5.1.

5.4.2. Turn on the power of all equipment.

5.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

5.5. Test Procedure

1. Set resolution bandwidth (RBW) = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.6. Test Result

The test was performed with 802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2412	8.08	> 0.5MHz
Middle	2437	8.04	> 0.5MHz
High	2462	8.08	> 0.5MHz

The test was performed with 802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2412	15.16	> 0.5MHz
Middle	2437	15.44	> 0.5MHz
High	2462	15.44	> 0.5MHz

The test was performed with 802.11n (Bandwidth: 20 MHz)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2412	16.08	> 0.5MHz
Middle	2437	16.08	> 0.5MHz
High	2462	16.36	> 0.5MHz

The test was performed with 802.11n (Bandwidth: 40 MHz)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)
Low	2422	36.44	> 0.5MHz
Middle	2437	36.48	> 0.5MHz
High	2452	36.40	> 0.5MHz

The spectrum analyzer plots are attached as below.


802.11b Channel Low 2412MHz




802.11b Channel Middle 2437MHz




802.11b Channel High 2462MHz




802.11g Channel Low 2412MHz




802.11g Channel Middle 2437MHz




802.11g Channel High 2462MHz




802.11n Channel Low 2412MHz (20MHz)




802.11n Channel Middle 2437MHz(20MHz)




802.11n Channel High 2462MHz(20MHz)




802.11n Channel Low 2422MHz (40MHz)



802.11n Channel Middle 2437MHz(40MHz)



802.11n Channel High 2452MHz(40MHz)



6. MAXIMUM PEAK OUTPUT POWER

6.1. Block Diagram of Test Setup



6.2. The Requirement For Section 15.247(b)(3)

Section 15.247(b)(3): For systems using digital modulation in the 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz bands: 1 Watt.

6.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

6.5. Test Procedure

6.5.1. The EUT was tested according to DTS test procedure of April 09, 2013 KDB558074 D01 DTS Meas Guidance v03 for compliance to FCC 47CFR 15.247 requirements.

6.5.2. The transmitter output was connected to the spectrum analyzer through a low loss cable.

6.5.3. Set RBW of spectrum analyzer to 1MHz and VBW to 3MHz.

6.5.4. Measurement the maximum peak output power.

6.6.Test Result

The test was performed with 802.11b				
Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2412	8.24	6.67	30 dBm / 1 W
Middle	2437	8.11	6.47	30 dBm / 1 W
High	2462	8.74	7.48	30 dBm / 1 W


The test was performed with 802.11g				
Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2412	7.84	6.08	30 dBm / 1 W
Middle	2437	7.32	5.40	30 dBm / 1 W
High	2462	6.58	4.55	30 dBm / 1 W

The test was performed with 802.11n (20MHz)				
Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2412	7.87	6.12	30 dBm / 1 W
Middle	2437	6.08	4.06	30 dBm / 1 W
High	2462	7.31	5.38	30 dBm / 1 W


The test was performed with 802.11n (40MHz)				
Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limits dBm / W
Low	2422	7.65	5.82	30 dBm / 1 W
Middle	2437	7.83	6.07	30 dBm / 1 W
High	2452	7.41	5.51	30 dBm / 1 W

The spectrum analyzer plots are attached as below.


802.11b Channel Low 2412MHz




802.11b Channel Middle 2437MHz




802.11b Channel High 2462MHz




802.11g Channel Low 2412MHz




802.11g Channel Middle 2437MHz




802.11g Channel High 2462MHz




802.11n Channel Low 2412MHz (20MHz)




802.11n Channel Middle 2437MHz (20MHz)




802.11n Channel High 2462MHz (20MHz)




802.11n Channel Low 2422MHz (40MHz)



802.11n Channel Middle 2437MHz (40MHz)



802.11n Channel High 2452MHz (40MHz)



7. POWER SPECTRAL DENSITY MEASUREMENT

7.1. Block Diagram of Test Setup



7.2. The Requirement For Section 15.247(e)

Section 15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.4. Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

7.5. Test Procedure

7.5.1. The transmitter output was connected to the spectrum analyzer through a low loss cable.

7.5.2. Measurement Procedure PKPSD:

This procedure must be used if maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit, and is optional if the maximum (average) conducted output power was used to demonstrate compliance.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.

4. Set the VBW $\geq 3 \times$ RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.5.3.Measurement the maximum power spectral density.

7.6.Test Result

The test was performed with 802.11b			
Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2412	-16.45	8 dBm
Middle	2437	-16.13	8 dBm
High	2462	-15.14	8 dBm


The test was performed with 802.11g			
Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2412	-19.38	8 dBm
Middle	2437	-19.05	8 dBm
High	2462	-18.27	8 dBm

The test was performed with 802.11n (20MHz)			
Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2412	-20.79	8 dBm
Middle	2437	-19.93	8 dBm
High	2462	-18.98	8 dBm


The test was performed with 802.11n (40MHz)			
Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limits (dBm)
Low	2422	-24.68	8 dBm
Middle	2437	-24.85	8 dBm
High	2452	-24.74	8 dBm

The spectrum analyzer plots are attached as below.


802.11b Channel Low 2412MHz




802.11b Channel Middle 2437MHz




802.11b Channel High 2462MHz




802.11g Channel Low 2412MHz




802.11g Channel Middle 2437MHz




802.11g Channel High 2462MHz




802.11n Channel Low 2412MHz (20MHz)




802.11n Channel Middle 2437MHz (20MHz)




802.11n Channel High 2462MHz(20MHz)




802.11n Channel Low 2422MHz (40MHz)



802.11n Channel Middle 2437MHz(40MHz)



802.11n Channel High 2452MHz(40MHz)



8. BAND EDGE COMPLIANCE TEST

8.1. Block Diagram of Test Setup



8.2. The Requirement For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

8.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

8.4. Operating Condition of EUT

8.4.1. Setup the EUT and simulator as shown as Section 8.1.

8.4.2. Turn on the power of all equipment.

8.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz MHz. We select 2412MHz, 2462MHz and 2422MHz, 2452MHz TX frequency to transmit.

8.5. Test Procedure

Conducted Band Edge:

8.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

8.5.2. Set RBW of spectrum analyzer to 100kHz and VBW to 300kHz.

Radiate Band Edge:

8.5.3. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.

8.5.4. The turntable was rotated for 360 degrees to determine the position of maximum emission level.

8.5.5. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

8.5.6. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

RBW=1MHz, VBW=1MHz

8.5.7. The band edges were measured and recorded.

8.6. Test Result

The test was performed with 802.11b

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2412	38.02	> 20dBc
2462	39.35	> 20dBc

The test was performed with 802.11g

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2412	36.95	> 20dBc
2462	37.35	> 20dBc


The test was performed with 802.11n (20MHz)

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2412	27.83	> 20dBc
2462	31.81	> 20dBc


The test was performed with 802.11n (40MHz)

Frequency (MHz)	Result of Band Edge (dBc)	Limit of Band Edge (dBc)
2422	26.96	> 20dBc
2452	26.87	> 20dBc


802.11b Channel Low 2412MHz




802.11b Channel High 2462MHz




802.11g Channel Low 2412MHz




802.11g Channel High 2462MHz




802.11n Channel Low 2412MHz (20MHz)




802.11n Channel High 2462MHz (20MHz)



802.11n Channel Low 2422MHz (40MHz)



802.11n Channel High 2452MHz (40MHz)



Radiated Band Edge Result

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

3. Display the measurement of peak values.



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Star_tmp #386

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: 7INCH TABLET

Mode: TX Channel 1(802.11b)

Model: X70

Manufacturer: EKEN

Polarization: Vertical

Power Source: AC 120V


Date: 13/07/18/

Time: 4/22/47

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	47.63	-7.81	39.82	74.00	-34.18	peak			
2	2310.000	39.00	-7.81	31.19	54.00	-22.81	AVG			
3	2376.130	50.43	-7.62	42.81	74.00	-31.19	peak			
4	2376.130	45.02	-7.62	37.40	54.00	-16.60	AVG			
5	2390.000	43.99	-7.53	36.46	74.00	-37.54	Peak			
6	2390.000	38.69	-7.53	31.16	54.00	-22.84	AVG			




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Star_tmp #387	Polarization: Horizontal
Standard: FCC 15C PK	Power Source: AC 120V
Test item: Radiation Test	Date: 13/07/18//
Temp.(C)/Hum.(%) 23 C / 49 %	Time: 4/24/26
EUT: 7INCH TABLET	Engineer Signature:
Mode: TX Channel 1(802.11b)	Distance: 3m
Model: X70	
Manufacturer: EKEN	

Note: Report No.:ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	48.76	-7.81	40.95	74.00	-33.05	peak			
2	2310.000	42.00	-7.81	34.19	54.00	-19.81	AVG			
3	2375.989	49.29	-7.62	41.67	74.00	-32.33	peak			
4	2375.989	43.85	-7.62	36.23	54.00	-17.77	AVG			
5	2390.000	45.67	-7.53	38.14	74.00	-35.86	peak			
6	2390.000	39.62	-7.53	32.09	54.00	-21.91	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Star_tmp #385

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: 7INCH TABLET

Mode: TX Channel 11(802.11b)

Model: X70

Manufacturer: EKEN

Polarization: Vertical

Power Source: AC 120V


Date: 13/07/18//

Time: 4/18/12

Engineer Signature:

Distance: 3m

Note: Report No.: ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	47.94	-7.37	40.57	74.00	-33.43	peak			
2	2483.500	41.42	-7.37	34.05	54.00	-19.95	AVG			
3	2488.774	49.33	-7.39	41.94	74.00	-32.06	peak			
4	2488.774	42.92	-7.39	35.53	54.00	-18.47	AVG			
5	2500.000	45.17	-7.40	37.77	74.00	-36.23	peak			
6	2500.000	39.32	-7.40	31.92	54.00	-22.08	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Star_tmp #384

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: 7INCH TABLET

Mode: TX Channel 11(802.11b)

Model: X70

Manufacturer: EKEN

Polarization: Horizontal

Power Source: AC 120V


Date: 13/07/18//

Time: 4/15/56

Engineer Signature:

Distance: 3m

Note: Report No.: ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	44.94	-7.37	37.57	74.00	-36.43	peak			
2	2483.500	38.91	-7.37	31.54	54.00	-22.46	AVG			
3	2490.993	48.91	-7.38	41.53	74.00	-32.47	peak			
4	2490.993	41.46	-7.38	34.08	54.00	-19.92	AVG			
5	2500.000	45.20	-7.40	37.80	74.00	-36.20	peak			
6	2500.000	39.33	-7.40	31.93	54.00	-22.07	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Star_tmp #380
Standard: FCC 15C PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 49 %
EUT: 7INCH TABLET
Mode: TX Channel 1(802.11g)
Model: X70
Manufacturer: EKEN

Polarization: Horizontal
Power Source: AC 120V
Date: 13/07/18//
Time: 4/01/53
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	44.75	-7.81	36.94	74.00	-37.06	peak			
2	2310.000	38.97	-7.81	31.16	54.00	-22.84	AVG			
3	2376.130	48.89	-7.62	41.27	74.00	-32.73	peak			
4	2376.130	42.61	-7.62	34.99	54.00	-19.01	AVG			
5	2390.000	45.46	-7.53	37.93	74.00	-36.07	peak			
6	2390.000	39.17	-7.53	31.64	54.00	-22.36	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Star_tmp #381

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: 7INCH TABLET

Mode: TX Channel 1(802.11g)

Model: X70

Manufacturer: EKEN

Polarization: Vertical

Power Source: AC 120V


Date: 13/07/18//

Time: 4/05/06

Engineer Signature:

Distance: 3m

Note: Report No.: ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	46.75	-7.81	38.94	74.00	-35.06	peak			
2	2310.000	41.69	-7.81	33.88	54.00	-20.12	AVG			
3	2375.849	52.68	-7.62	45.06	74.00	-28.94	peak			
4	2375.849	47.99	-7.62	40.37	54.00	-13.63	AVG			
5	2390.000	53.15	-7.53	45.62	74.00	-28.38	peak			
6	2390.000	47.98	-7.53	40.45	54.00	-13.55	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Star_tmp #382
Standard: FCC 15C PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 49 %
EUT: 7INCH TABLET
Mode: TX Channel 11(802.11g)
Model: X70
Manufacturer: EKEN

Polarization: Vertical
Power Source: AC 120V
Date: 13/07/18//
Time: 4/08/08
Engineer Signature:
Distance: 3m

Note: Report No.: ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	49.00	-7.37	41.63	74.00	-32.37	peak			
2	2483.500	43.97	-7.37	36.60	54.00	-17.40	AVG			
3	2490.993	47.76	-7.38	40.38	74.00	-33.62	peak			
4	2490.993	41.36	-7.38	33.98	54.00	-20.02	AVG			
5	2500.000	45.77	-7.40	38.37	74.00	-35.63	peak			
6	2500.000	40.00	-7.40	32.60	54.00	-21.40	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Star_tmp #383
Standard: FCC 15C PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 49 %
EUT: 7INCH TABLET
Mode: TX Channel 11(802.11g)
Model: X70
Manufacturer: EKEN

Polarization: Horizontal
Power Source: AC 120V
Date: 13/07/18//
Time: 4/12/59
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	44.98	-7.37	37.61	74.00	-36.39	peak			
2	2483.500	37.95	-7.37	30.58	54.00	-23.42	AVG			
3	2495.118	46.74	-7.39	39.35	74.00	-34.65	peak			
4	2495.118	40.02	-7.39	32.63	54.00	-21.37	AVG			
5	2500.000	44.90	-7.40	37.50	74.00	-36.50	peak			
6	2500.000	36.99	-7.40	29.59	54.00	-24.41	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Star_tmp #388

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: 7INCH TABLET

Mode: TX Channel 1(802.11n)

Model: X70

Manufacturer: EKEN

Polarization: Horizontal

Power Source: AC 120V


Date: 13/07/18//

Time: 4/27/12

Engineer Signature:

Distance: 3m

Note: Report No.: ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	45.84	-7.81	38.03	74.00	-35.97	peak			
2	2310.000	39.69	-7.81	31.88	54.00	-22.12	AVG			
3	2375.849	48.48	-7.62	40.86	74.00	-33.14	peak			
4	2375.849	42.71	-7.62	35.09	54.00	-18.91	AVG			
5	2390.000	47.35	-7.53	39.82	74.00	-34.18	peak			
6	2390.000	41.22	-7.53	33.69	54.00	-20.31	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Star_tmp #389

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: 7INCH TABLET

Mode: TX Channel 1(802.11n)

Model: X70

Manufacturer: EKEN

Polarization: Vertical

Power Source: AC 120V


Date: 13/07/18//

Time: 4/31/39

Engineer Signature:

Distance: 3m

Note: Report No.: ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	47.22	-7.81	39.41	74.00	-34.59	peak			
2	2310.000	41.66	-7.81	33.85	54.00	-20.15	AVG			
3	2376.130	53.41	-7.62	45.79	74.00	-28.21	peak			
4	2376.130	43.93	-7.62	36.31	54.00	-17.69	AVG			
5	2390.000	48.73	-7.53	41.20	74.00	-32.80	peak			
6	2390.000	42.02	-7.53	34.49	54.00	-19.51	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Star_tmp #390

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: 7INCH TABLET

Mode: TX Channel 11(802.11n)

Model: X70

Manufacturer: EKEN

Polarization: Vertical

Power Source: AC 120V


Date: 13/07/18//

Time: 4/33/30

Engineer Signature:

Distance: 3m

Note: Report No.:ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	48.47	-7.37	41.10	74.00	-32.90	peak			
2	2483.500	42.02	-7.37	34.65	54.00	-19.35	AVG			
3	2492.578	46.75	-7.39	39.36	74.00	-34.64	peak			
4	2492.578	40.00	-7.39	32.61	54.00	-21.39	AVG			
5	2500.000	43.62	-7.40	36.22	74.00	-37.78	peak			
6	2500.000	38.99	-7.40	31.59	54.00	-22.41	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Star_tmp #391

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: 7INCH TABLET

Mode: TX Channel 11(802.11n)

Model: X70

Manufacturer: EKEN

Polarization: Horizontal

Power Source: AC 120V


Date: 13/07/18//

Time: 4/36/42

Engineer Signature:

Distance: 3m

Note: Report No.: ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	45.35	-7.37	37.98	74.00	-36.02	peak			
2	2483.500	39.17	-7.37	31.80	54.00	-22.20	AVG			
3	2489.566	46.87	-7.39	39.48	74.00	-34.52	peak			
4	2489.566	40.02	-7.39	32.63	54.00	-21.37	AVG			
5	2500.000	43.69	-7.40	36.29	74.00	-37.71	peak			
6	2500.000	36.91	-7.40	29.51	54.00	-24.49	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Star_tmp #395
Standard: FCC 15C PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 49 %
EUT: 7INCH TABLET
Mode: TX Channel 3(802.11n)40MHz
Model: X70
Manufacturer: EKEN

Polarization: Horizontal
Power Source: AC 120V
Date: 13/07/18//
Time: 4/50/16
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	46.58	-7.81	38.77	74.00	-35.23	peak			
2	2310.000	40.03	-7.81	32.22	54.00	-21.78	AVG			
3	2376.235	51.90	-7.62	44.28	74.00	-29.72	peak			
4	2376.235	43.69	-7.62	36.07	54.00	-17.93	AVG			
5	2390.000	46.24	-7.53	38.71	74.00	-35.29	peak			
6	2390.000	40.33	-7.53	32.80	54.00	-21.20	AVG			


ACCURATE TECHNOLOGY CO., LTD.


 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 966 chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

 Job No.: Star_tmp #394
 Standard: FCC 15C PK
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 23 C / 49 %
 EUT: 7INCH TABLET
 Mode: TX Channel 3(802.11n)40MHz
 Model: X70
 Manufacturer: EKEN

 Polarization: Vertical
 Power Source: AC 120V
 Date: 13/07/18//
 Time: 4/46/04
 Engineer Signature:
 Distance: 3m

Note: Report No.: ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	46.60	-7.81	38.79	74.00	-35.21	peak			
2	2310.000	40.02	-7.81	32.21	54.00	-21.79	AVG			
3	2376.046	53.47	-7.62	45.85	74.00	-28.15	peak			
4	2376.046	48.02	-7.62	40.40	54.00	-13.60	AVG			
5	2390.000	54.18	-7.53	46.65	74.00	-27.35	peak			
6	2390.000	49.32	-7.53	41.79	54.00	-12.21	AVG			



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Star_tmp #393
Standard: FCC 15C PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 49 %
EUT: 7INCH TABLET
Mode: TX Channel 9(802.11n)40MHz
Model: X70
Manufacturer: EKEN

Polarization: Vertical
Power Source: AC 120V
Date: 13/07/18//
Time: 4/43/32
Engineer Signature:
Distance: 3m

Note: Report No.:ATE20131533



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	46.57	-7.37	39.20	74.00	-34.80	peak			
2	2483.500	40.08	-7.37	32.71	54.00	-21.29	AVG			
3	2493.631	47.82	-7.39	40.43	74.00	-33.57	peak			
4	2493.631	41.08	-7.39	33.69	54.00	-20.31	AVG			
5	2500.000	46.05	-7.40	38.65	74.00	-35.35	peak			
6	2500.000	39.62	-7.40	32.22	54.00	-21.78	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: Star_tmp #392

Standard: FCC 15C PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 49 %

EUT: 7INCH TABLET

Mode: TX Channel 9(802.11n)40MHz

Model: X70

Manufacturer: EKEN

Polarization: Horizontal

Power Source: AC 120V


Date: 13/07/18//

Time: 4/40/19

Engineer Signature:

Distance: 3m

Note: Report No.: ATE20131533




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	45.82	-7.37	38.45	74.00	-35.55	peak			
2	2483.500	39.64	-7.37	32.27	54.00	-21.73	AVG			
3	2487.116	47.91	-7.38	40.53	74.00	-33.47	peak			
4	2487.116	41.90	-7.38	34.52	54.00	-19.48	AVG			
5	2500.000	44.83	-7.40	37.43	74.00	-36.57	peak			
6	2500.000	38.97	-7.40	31.57	54.00	-22.43	AVG			

9. RADIATED SPURIOUS EMISSION TEST


9.1. Block Diagram of Test Setup

9.1.1. Block diagram of connection between the EUT and peripherals



Setup: Transmitting mode

9.1.2. Semi-Anechoic Chamber Test Setup Diagram



9.2. The Limit For Section 15.247(d)

Section 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the

transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

9.3.Restricted bands of operation

9.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

9.4.Configuration of EUT on Measurement

The equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

9.5.Operating Condition of EUT

9.5.1. Setup the EUT and simulator as shown as Section 9.1.

9.5.2. Turn on the power of all equipment.

9.5.3. Let the EUT work in TX modes measure it. The transmit frequency are 2412-2462 and 2422-2452MHz. We select 2412MHz, 2437MHz, 2462MHz and 2422MHz, 2437MHz, 2452MHz TX frequency to transmit.

9.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2009 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The worst-case data rate for this channel to be 1Mbps for 802.11b mode and 6Mbps for 802.11g mode and 150Mbps for 802.11n mode, based on previous with 802.11 WLAN product design architectures.

The bandwidth of test receiver is set at 9kHz in below 30MHz. and set at 120kHz in 30-1000MHz, and 1MHz in above 1000MHz.

The frequency range from 9kHz to 25GHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

The field strength is calculated by adding the antenna factor, and cable loss, and subtracting the amplifier gain from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

Where Corrected Factor = Antenna Factor + Cable Loss – Amplifier Gain

9.7. The Field Strength of Radiation Emission Measurement Results

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

2. *: Denotes restricted band of operation.

3. The fundamental radiated emissions were reduced by Band Reject Filter in the attached plots.

4. The EUT is tested radiation emission at each test mode(802.11 b/g/n) in three axes. The worst emissions are reported in all test mode and channels.

5. The 18-25GHz emissions are not reported, because the levels are too low against the limit.

Below 1G