


FREQUENCY STABILITY

Frequency stability versus temperature and line voltage was measured in a controlled environment. For these tests the exciter RF output was fed to a calibrated frequency measuring device that has better than a 1ppm accuracy. The test equipment configuration is shown below.



The variac was adjusted for nominal voltage and the frequency was recorded. Then the variac was adjusted to 85% and 115% of the nominal voltage and the frequency was recorded at each voltage level. The results are tabulated below.

Line Voltage (Volts)	Pilot Frequency (MHz)
103 (85%)	536.309471
121 (Nominal)	536.309482
139 (115%)	536.309475


For the temperature stability measurements the exciter was placed inside a Cincinnati Sub-Zero temperature chamber Model Z-32-2-2-H/WC equipped with a CSZ Dimension II temperature controller. The exciter was energized and the pilot frequency was measured on the Rhode and Schwarz test set. The temperature was then raised to +40 °C, allowed to stabilize for 15 minutes and then cycled to each colder temperature where it was allowed to stabilize for 10 minutes before recording the measured frequency and moving on to the next lower temperature.

Temperature °C	Time	Set Pilot Freq= 536.3094406	
		Pilot Freq (MHz)	Difference (Hz)
25	11:25	536.309515	74
40	11:46	536.309908	467
30	12:10	536.309688	247
20	12:30	536.309513	72
10	12:50	536.309574	133
0	13:10	536.309755	314

The recorded data indicates that the frequency stability requirements of FCC Rule 2.1055 were met.

CABINET RADIATION

The transmitter and test equipment were configured as shown below including the angles of measurement with respect to the transmitter cabinet. The photo on the subsequent page also shows the physical set-up of the test equipment and equipment under test. The transmitter was operating at 15W average power. The free space path loss, cable loss and antenna gain characteristics were obtained at the fundamental frequency and at each of the harmonics of the visual carrier frequency in order to accurately assess the level of the signal radiated from the cabinet. Radiation from the cabinet was measured at a distance of 12 feet in 4 different physical rotation angles: 0, 90, 180 and 270 degrees (0 degrees being the front of the cabinet). All spectral components above -85 dB power radiated from the cabinet were recorded. The values are tabulated in the table on the next page following the photo.



Physical Cabinet Radiation Test Configuration
Page 2

This photograph shows the actual laboratory environment in which the cabinet radiation tests were conducted. The log periodic antenna, cable and spectrum analyzer are shown in the foreground and the DTXPRO-10U is shown in the background. The transmitter was rotated 90 degrees for each of the measurement orientations.



As calculated from the spreadsheet data on the following page, the worst case measurement was -80.2 dBm at the second harmonic. (The photo above shows this particular measurement). The measurement tables for the remaining views of the transmitter are shown on the following pages.

Pineapple Technology Inc.																				
CABINET RADIATION TEST																				
TEST INPUTS			CONDITIONS & PARAMETERS																	
TEST DATE:	6/20/2011																			
TEST ENGINEER:	J. Collier																			
TRANSMITTER MODEL NO:	DTXPRO-10U																			
OPERATING POWER OUTPUT LEVEL	41.8 dBm		15	Power in Watts																
CENTER FREQUENCY	0.575 gHz		31	Channel																
ANTENNA MODEL NUMBER	ETS 3147 S/N 9112-1053																			
SPECTRUM ANALYZER MODEL	8595E																			
DISTANCE TO TRANSMITTER	4 METERS																			
(Power Levels were measured in 500kHz segments between lower freq edge and upper frequency edge. Center frequency of highest level in band segment is recorded below.)																				
FRONT VIEW																				
Harmonic	Center	SIGNAL	CABLE	ANTENNA	PATH	ADJ	MAXIMUM	STATUS	Lower	Upper										
	Frequency	LEVEL	LOSS dB	GAIN dB	LOSS dB	LEVEL	LEVEL	P=PASS	Frequency	Frequency										
	GHz	dBm	dB	dB	dB	dBm	dBm		Edge	Edge										
Fc*2	1.15	-80.6	0.7	6.5	45.76	-40.6733	-18.2	P	1.144	1.156										
Fc*3	1.725	-80.6	1.0	6.5	49.28	-36.8583	-18.2	P	1.716	1.734										
Fc*4	2.3	-80.1	1.3	4.3	51.78	-31.3662	-18.2	P	2.288	2.312										
Fc*5	2.875	-79.1	1.6	3.0	53.71	-26.8348	-18.2	P	2.86	2.89										
Fc*6	3.45	-81.0	1.8	4.4	55.30	-28.2579	-18.2	P	3.432	3.468										
Fc*7	4.025	-81.2	2.1	1.1	56.64	-23.5257	-18.2	P	4.004	4.046										
Fc*8	4.6	-80.2	2.4	-1.3	57.80	-18.6726	-18.2	P	4.576	4.624										
Fc*9	5.175	-81.2	2.7	1.9	58.82	-21.5563	-18.2	P	5.148	5.202										
Fc*10	5.75	-80.6	3.0	1.9	59.73	-19.7479	-18.2	P	5.72	5.78										
RIGHT VIEW																				
Harmonic	Center	SIGNAL	CABLE	ANTENNA	PATH	ADJ	MAXIMUM	STATUS	Lower	Upper										
	Frequency	LEVEL	LOSS dB	GAIN dB	LOSS dB	LEVEL	LEVEL		Frequency	Frequency										
	GHz	dBm	dB	dB	dB	dBm	dBm		Edge	Edge										
Fc*2	1.15	-80.5	0.7	6.5	45.76	-40.5733	-18.2	P	1.144	1.156										
Fc*3	1.725	-80.3	1.0	6.5	49.28	-36.5583	-18.2	P	1.716	1.734										
Fc*4	2.3	-79.8	1.3	4.3	51.78	-31.0662	-18.2	P	2.288	2.312										
Fc*5	2.875	-79.6	1.6	3.0	53.71	-27.3348	-18.2	P	2.86	2.89										
Fc*6	3.45	-81.1	1.8	4.4	55.30	-28.3579	-18.2	P	3.432	3.468										
Fc*7	4.025	-81.4	2.1	1.1	56.64	-23.7257	-18.2	P	4.004	4.046										
Fc*8	4.6	-81.2	2.4	-1.3	57.80	-19.6726	-18.2	P	4.576	4.624										
Fc*9	5.175	-80.8	2.7	1.9	58.82	-21.1563	-18.2	P	5.148	5.202										
Fc*10	5.75	-80.6	3.0	1.9	59.73	-19.7479	-18.2	P	5.72	5.75										

Test Equipment List

The following test equipment was used in the various test equipment configurations or to create calibration of equipment at various frequencies. All equipment was known to be in working order.

VENDOR	MODEL NUMBER	DESCRIPTION	SERIAL NUMBER
Agilent	N1996A	CSA Spectrum Analyzer	MY45371110
Com-Tech	DC2KC-1	Directional Coupler UHF 5kw RMS	044863
Mini-Circuits	NHP-1000	High Pass Filter	15542
Microwave Filter Company	R16560-25	DTV Band Stop Filter	D/C 0705-R1009
Agilent	E4418B	EPM Series Power Meter	MY40330293
Agilent	8481A	Power Sensor	1550A03679
Bird	8890-300	2500 Watt Dummy Load	4778
Rohde & Schwarz	EFA-53	TV Test Receiver	100041
ETS	3147	Log Periodic Antenna	9112-1053
Hewlett Packard	8596E	Spectrum Analyzer	3807A01244
Agilent	8753D	Network Analyzer	3410A04800