



WILSON ELECTRONICS, LLC
3301 E. Deseret Dr, St. George, UT 84790
T. 1 800 204 4104 F. 1 435 673 0899 E. info@weboost.com
www.wilsonelectronics.com

January 8, 2019

To: Whom it May Concern

Subject: Final Amplification Stage Voltage and Current

Please note that the maximum voltages and currents for the final amplification stages of the Model 460054 Signal Booster are:

Uplink Amplifier (698-716 MHz): 4.3 V, 0.5 A

Downlink Amplifier (728-746 MHz): 4.3 V, 0.5 A

Uplink Amplifier (777-787 MHz): 4.3 V, 0.5 A

Downlink Amplifier (746-756 MHz): 4.3 V, 0.5 A

Uplink Amplifier (824-849 MHz): 4.3 V, 0.5 A

Downlink Amplifier (869-894 MHz): 4.3 V, 0.5 A

Uplink Amplifier (1850-1915 MHz): 4.3 V, 0.5 A

Downlink Amplifier (1930-1995 MHz): 4.3 V, 0.5 A

Uplink Amplifier (1710-1755 MHz): 4.3 V, 0.5 A

Downlink Amplifier (2110-2155 MHz): 4.3 V, 0.5 A

Sincerely,

A handwritten signature in black ink that reads 'Erin Elder'.

Erin Elder

IP & Regulatory Compliance Engineer