

Minimum Safe Distance From Antennas

Based upon FCC OET Bulletin 65 and other FCC Sources

INPUT DATA

Frequency MHz	1930
Pout Watts	0.0160
Duty Cycle Percent	100.0%
Ant. Gain dBi	6.00
Coax Loss dB	0.00

RESULTS OF CALCULATIONS

Min. Distance Inches	0.89
Min. Distance Centimeters	2.25
ERP (Watts)	0.0388
EIRP (Watts)	0.0637


REFERENCE DATA

Antenna Gain (non-log)	3.98
Coax loss (non-log)	1.00
Calculated limit (mw/cm ²)	1.00
FCC Limit (mw/cm ²)	1.00

NOTES:

- (1) Valid only between 300 MHz - 100,000 MHz.
- (2) Calculations are sufficient for determining antenna safe distance for mobile antennas provided that calculated ERP < 1.5 watts for frequencies equal to or below 1.5 GHz, and calculated ERP < 3 watts for frequencies above 1.5 GHz.
- (3) Mobile antenna distances shall be no less than 8 inches.
- (4) There are no predefined ERP and distance limitations for fixed outside (building) antennas (see #5).
- (5) Indoor building antenna criteria is the same as the criteria for mobile antennas (see #2 & #3).
- (6) Mobile/portable stations are limited to 2 watts EIRP peak power in the 1900 MHz band (see 24.232[c]).

SUMMARY FOR PUBLICATION

For Amplifier Model Number:	271201
Frequency Band (MHz)	1900
Mobile or Building?	Mobile
Outside or Inside Antenna?	Inside
Antenna Type:	Any Antenna whose overall gain, including coax loss, is less than 6 dBi
Safe Distance (inches):	8
Signature:	
Date:	11/14/2008