

Minimum Safe Distance From Antennas

Based upon FCC OET Bulletin 65 and other FCC Sources

INPUT DATA

Frequency MHz	1930
Pout Watts	0.0250
Duty Cycle Percent	100.0%
Ant. Gain dBi	3.00
Coax Loss dB	0.00

RESULTS OF CALCULATIONS

Min. Distance Inches	0.78
Min. Distance Centimeters	1.99
ERP (Watts)	0.0304
EIRP (Watts)	0.0499


REFERENCE DATA

Antenna Gain (non-log)	2.00
Coax loss (non-log)	1.00
Calculated limit (mw/cm ²)	1.00
FCC Limit (mw/cm ²)	1.00

NOTES:

- (1) Valid only between 300 MHz - 100,000 MHz
- (2) Calculations are sufficient for determining antenna safe distance for mobile antennas provided that calculated ERP < 1.5 watts for frequencies equal to or below 1.5 GHz, and calculated ERP < 3 watts for frequencies above 1.5 GHz.
- (3) Mobile antenna distances shall be no less than 8 inches.
- (4) There are no predefined ERP and distance limitations for fixed outside (building) antennas (see #5).
- (5) Indoor building antenna criteria is the same as the criteria for mobile antennas (see #2 & #3).

SUMMARY FOR PUBLICATION

For Amplifier Model Number:	271230
Frequency Band (MHz)	1900
Mobile or Building?	Mobile
Outside or Inside Antenna?	Inside
Antenna Type:	Ultra-slim, Cradle Plus, or any antenna whose gain less coax loss does not exceed 3 dBi
Safe Distance (inches):	8
Signature:	
Date:	2/22/2008