



## Minimum Safe Distance From Antennas Based upon FCC OET Bulletin 65 and other FCC Sources

### INPUT DATA

Frequency MHz	1930
Pout Watts	0.0117
Duty Cycle Percent	100.0%
Ant. Gain dBi	15.00
Coax Loss dB	0.00

### RESULTS OF CALCULATIONS

Min. Distance Inches	2.14
Min. Distance Centimeters	5.44
ERP (Watts)	0.2264
EIRP (Watts)	0.3713


### REFERENCE DATA

Antenna Gain (non-log)	31.62
Coax loss (non-log)	1.00
Calculated limit (mw/cm <sup>2</sup> )	1.00
FCC Limit (mw/cm <sup>2</sup> )	1.00

### NOTES:

- (1) Valid only between 300 MHz - 100,000 MHz.
- (2) Calculations are sufficient for determining antenna safe distance for mobile antennas provided that calculated ERP < 1.5 watts for frequencies equal to or below 1.5 GHz, and calculated ERP < 3 watts for frequencies above 1.5 GHz.
- (3) Mobile antenna distances shall be no less than 8 inches.
- (4) There are no predefined ERP and distance limitations for fixed outside (building) antennas (see #5).
- (5) Indoor building antenna criteria is the same as the criteria for mobile antennas (see #2 & #3).
- (6) Mobile/portable stations are limited to 2 watts EIRP peak power in the 1900 MHz band (see 24.232[c]).

### SUMMARY FOR PUBLICATION

For Amplifier Model Number:	271247-50 & 271247-75
Frequency Band (MHz)	1900
Mobile or Fixed?	Fixed
Outside or Inside Antenna?	Inside
Antenna Type:	Any antenna with gain not exceeding 15 dBi
Safe Distance (inches):	8
Signature:	
Date:	1/16/2009