



849 NW State Road 45
Newberry, Fl 32669 USA
Phone: 888.472.2424 or 352.472.5500
Fax: 352.472.2030
Email: info@timcoengr.com
Website: www.timcoengr.com

PART 22, 24

AND RSS-131

CLASS II PERMISSIVE CHANGE TEST REPORT

Applicant	WILSON ELECTRONICS, INC.
Address	3301 E. DESERET DRIVE ST. GEORGE UTAH 84790 USA
FCC ID IC Model Number	PWO271265 4726A-217265 271265
Product Description	DUAL BAND IN-BUILDING AMPLIFIER
Date Sample Received	4/6/2011
Date Tested	4/11/2011
Tested By	Nam Nguyen
Approved By	Mario de Aranzeta
Report Number	683AUT11TestReport2.doc
Test Results	<input checked="" type="checkbox"/> PASS <input type="checkbox"/> FAIL

**THE ATTACHED REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL
WITHOUT THE WRITTEN APPROVAL OF TIMCO ENGINEERING, INC.**



Testing Certificate # 0955-01



TABLE OF CONTENTS

GENERAL REMARKS	3
REPORT SUMMARY	4
TEST ENVIRONMENT	4
TEST SETUP SUMMARY	4
DUT SPECIFICATION	5
TEST EQUIPMENT LIST	7
TEST PROCEDURES	8
TX RADIATED SPURIOUS EMISSIONS.....	9

APPLICANT: WILSON ELECTRONICS, INC.

FCC ID: PWO271265, IC: 4726A-271265

REPORT: Z:\W\WILSON_PWO\683AUT11\Extra683AUT11\683AUT11TestReport2.doc

Page 2 of 9

mdea 12.11.2007

GENERAL REMARKS

The attached report shall not be reproduced except in full without the written permission of Timco Engineering Inc.

The test results only relate to the item tested.

Summary

The device under test does:

- fulfill the general approval requirements as identified in this test report
- not fulfill the general approval requirements as identified in this test report

Attestations

This equipment has been tested in accordance with the standards identified in this test report. To the best of my knowledge and belief, these tests were performed using the measurement procedures described in this report.

All instrumentation and accessories used to test products for compliance to the indicated standards are calibrated regularly in accordance with ISO 17025: 2005 requirements.



Testing Certificate # 0955-01

I attest that the necessary measurements were made, under my supervision, at:

Timco Engineering Inc.
849 NW State Road 45
Newberry, Fl 32669



Authorized Signatory Name:

Mario de Aranzeta C.E.T.
Compliance Engineer/ Lab. Supervisor

Date: April 25th, 2011

APPLICANT: WILSON ELECTRONICS, INC.
FCC ID: PWO271265, IC: 4726A-271265
REPORT: Z:\W\WILSON_PWO\683AUT11\Extra683AUT11\683AUT11TestReport2.doc



REPORT SUMMARY

Applicable Rule(s)	ANSI C63.4: 2003, FCC PART 22, 24, and IC RSS-131
--------------------	---

TEST ENVIRONMENT

Test Facility	Timco Engineering, Inc. 849 NW State Road 45 Newberry, FL 32669 USA.
Test Condition in the laboratory	Temperature: 26°C Relative humidity: 50%

TEST SETUP SUMMARY

Test Setup Diagram/Description	The DUT was placed on the turntable per setup per ANSI C63.4: 2003. A test set up photo is provided for clarification.
Deviation from the standard/procedure	No deviation
Modification of DUT	No modification

APPLICANT: WILSON ELECTRONICS, INC.

FCC ID: PWO271265, IC: 4726A-271265

REPORT: Z:\W\WILSON_PWO\683AUT11\Extra683AUT11\683AUT11TestReport2.doc

Page 4 of 9

mdea 12.11.2007

DUT SPECIFICATION

DUT Description	DUAL BAND IN-BUILDING AMPLIFIER
FCC ID	PWO271265
IC	4726A-271265
DUT Power Source	<input checked="" type="checkbox"/> 110-120Vac/50- 60Hz
	<input type="checkbox"/> DC Power
	<input type="checkbox"/> Battery Operated Exclusively
Test Item	<input type="checkbox"/> Prototype
	<input checked="" type="checkbox"/> Pre-Production
	<input type="checkbox"/> Production
Type of Equipment	<input checked="" type="checkbox"/> Fixed
	<input type="checkbox"/> Mobile
	<input type="checkbox"/> Portable
Laboratory Test Conditions	Temperature: 26°C Humidity: 55%
Modifications to DUT:	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes (explanation below)

APPLICANT: WILSON ELECTRONICS, INC.

FCC ID: PWO271265, IC: 4726A-271265

REPORT: Z:\W\WILSON_PWO\683AUT11\Extra683AUT11\683AUT11TestReport2.doc

DUT EXTERNAL PHOTOS



APPLICANT: WILSON ELECTRONICS, INC.
FCC ID: PWO271265, IC: 4726A-271265
REPORT: Z:\W\WILSON_PWO\683AUT11\Extra683AUT11\683AUT11TestReport2.doc



TEST EQUIPMENT LIST

Device	Manufacturer	Model	Serial Number	Cal/Char Date	Due Date
3-Meter Semi-Anechoic Chamber	Panashield	N/A	N/A	Listed 3/10/10	3/10/12
AC Voltmeter	HP	400FL	2213A14499	CAL 3/23/09	3/23/12
Antenna: Dipole Kit	Electro-Metrics	TDA-30/1-4	153	CHAR 6/10/09	6/10/11
Frequency Counter	HP	5385A	3242A07460	CAL 5/26/09	5/26/11
Hygro-Thermometer	Extech	445703	0602	CAL 1/30/09	1/30/12
Modulation Analyzer	HP	8901A	3435A06868	CAL 5/26/09	5/26/11
Digital Multimeter	Fluke	FLUKE-77-3	79510405	CAL 5/18/09	5/18/11
Analyzer Tan Tower Preamplifier	HP	8449B-H02	3008A00372	CAL 11/21/09	11/21/11
Analyzer Tan Tower Quasi-Peak Adapter	HP	85650A	3303A01690	CAL 11/22/09	11/22/11
Analyzer Tan Tower RF Preselector	HP	85685A	3221A01400	CAL 11/21/09	11/21/11
Analyzer Tan Tower Spectrum Analyzer	HP	8566B Opt 462	3138A07786 3144A20661	CAL 11/24/09	11/24/11
Temperature Chamber	Tenney Engineering	TTRC	11717-7	CHAR 4/25/10	4/25/12

APPLICANT: WILSON ELECTRONICS, INC.

FCC ID: PWO271265, IC: 4726A-271265

REPORT: Z:\W\WILSON_PWO\683AUT11\Extra683AUT11\683AUT11TestReport2.doc

Page 7 of 9

mdea 12.11.2007



TEST PROCEDURES

Power line conducted Emission: The test procedure used was ANSI C63.4-2003. The spectrum was scanned from 0.15 to 30 MHz.

Radiation Interference: The test procedure used was ANSI C63.4-2003 using a spectrum analyzer with preselector. The resolution bandwidth used was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The video bandwidth was always greater than or equal to the RBW.

The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. The frequency was scanned from 30 MHz to 1.0 GHz. The DUT was measured in three (3) orthogonal planes when necessary.

Formula of Conversion Factors: The field strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB μ V) to the antenna correction factor supplied by the antenna manufacturer plus the coax loss. The antenna correction factors are stated in terms of dB. The gain of the preselector was accounted for in the spectrum analyzer meter reading.

Example:

Freq (MHz)	Meter Reading	+ ACF	+CL	= FS
33	20 dB μ V	+ 10.36 dB/m	+0.40 dB	=30.76 dB μ V/m @ 3m

APPLICANT: WILSON ELECTRONICS, INC.

FCC ID: PWO271265, IC: 4726A-271265

REPORT: Z:\W\WILSON_PWO\683AUT11\Extra683AUT11\683AUT11TestReport2.doc

Page 8 of 9

mdea 12.11.2007

TX RADIATED SPURIOUS EMISSIONS

Rule Parts. No.: FCC Pt 2.1053, IC RSS-131

Requirements: Emissions must be $43 + 10\log(P_o)$ dB below the mean power output of the transmitter:

$$43 + 10\log(1.00) = 43.0 \text{ dBc (Uplink)}$$

$$43 + 10\log(0.30) = 37.8 \text{ dBc (Downlink)}$$

Test Data:

Emission Frequency MHz	Ant. Polarity	dB Below Carrier (dBc)
836.50	0	0
1673.00	V	87.77
2509.50	H	70.85
3346.00	H	75.75
4182.50	V	84.23
5019.00	H/V	NF
5855.50	H/V	NF
6692.00	H/V	NF
7528.50	H/V	NF
8365.00	H/V	NF

Emission Frequency MHz	Ant. Polarity	dB Below Carrier (dBc)
1880.00	0	0
3760.00	H	85.17
5640.00	V	82.01
7520.00	V	84.67
9400.00	V	81.96
11280.00	H/V	NF
13160.00	H/V	NF
15040.00	H/V	NF
16920.00	H/V	NF
18800.00	H/V	NF

Emission Frequency MHz	Ant. Polarity	dB Below Carrier (dBc)
881.50	0	0
1763.00	H	82.87
2644.50	H	76.95
3526.00	V	71.65
4407.50	V	77.03
5289.00	H/V	NF
6170.50	H/V	NF
7052.00	H/V	NF
7933.50	H/V	NF
8815.00	H/V	NF

Emission Frequency MHz	Ant. Polarity	dB Below Carrier (dBc)
1960.00	0	0
3920.00	H	76.41
5880.00	V	71.61
7840.00	V	75.42
9800.00	V	72.92
11760.00	H/V	NF
13720.00	H/V	NF
15680.00	H/V	NF
17640.00	H/V	NF
19600.00	H/V	NF

APPLICANT: WILSON ELECTRONICS, INC.

FCC ID: PWO271265, IC: 4726A-271265

REPORT: Z:\W\WILSON_PWO\683AUT11\Extra683AUT11\683AUT11TestReport2.doc