



Minimum Safe Distance From Antennas Based upon FCC OET Bulletin 65 and other FCC Sources

INPUT DATA

Frequency MHz	824
Pout Watts	0.95500
Duty Cycle Percent	100.0%
Ant. Gain dBi	15.00
Cable and Connector Losses dB	0.00

RESULTS OF CALCULATIONS

Ant. Gain less Losses dBi	15.00
Min. Distance Inches	26.04
Min. Distance Centimeters	66.14
ERP (Watts)	18.4145
EIRP (Watts)	30.1998


REFERENCE DATA

Pout dBm	29.80
Antenna Gain (non-log)	31.62
Coax loss (non-log)	1.00
FCC Limit (mw/cm ²)	f/1500
Calculated limit (mw/cm ²)	0.55

NOTES:

- (1) Valid only between 300 MHz - 100,000 MHz.
- (2) Calculations are sufficient for determining antenna safe distance for mobile antennas and fixed inside antennas provided that calculated ERP < 1.5 watts for frequencies equal to or below 1.5 GHz, and calculated ERP < 3 watts for frequencies above 1.5 GHz.
- (3) Mobile antenna distances and fixed indoor antenna distances shall be no less than 8 inches.
- (4) There are no predefined ERP and distance limitations for fixed outside (building) antennas.
- (5) Mobile/portable stations are limited to 2 watts EIRP peak power in the 1900 MHz band per FCC rules §24.232(c).
- (6) Fixed/Mobile/Portable stations are limited to 1 watt EIRP in 1710-1755 MHz band per FCC rules §27.50(d)(4).

SUMMARY FOR PUBLICATION

For Amplifier Model Number:	277180
Frequency Band (MHz)	800 MHz
Mobile or Fixed?	Fixed
Outside or Inside Antenna?	Outside
Antenna Type:	Any antenna whose gain less cable and connector losses does not exceed 15 dBi.
Safe Distance (inches):	27 inches
Signature:	
Date:	December 21, 2011