



3301 E. Deseret Drive
St. George, Utah 84790
wilsonelectronics.com
cellular@wilsonelectronics.com

Phone 1-800-204-4104 Fax 1-435-656-2432

July 15, 2013

To: Whom it May Concern

Subject: Final Amplification Stage Voltage and Current

Please note that the maximum voltages and currents for the final amplification stages of the Model 460001 Signal Booster are:

Uplink Amplifier (704-716 MHz): 4.3 V, 0.5 A

Downlink Amplifier (734-746 MHz): 4.3 V, 0.5 A

Uplink Amplifier (777-787 MHz): 4.3 V, 0.5 A

Downlink Amplifier (746-756 MHz): 4.3 V, 0.5 A

Uplink Amplifier (824-849 MHz): 4.3 V, 0.5 A

Downlink Amplifier (869-894 MHz): 4.3 V, 0.5 A

Uplink Amplifier (1850-1915 MHz): 4.3 V, 0.5 A

Downlink Amplifier (1930-1995 MHz): 4.3 V, 0.5 A

Uplink Amplifier (1710-1755 MHz): 4.3 V, 0.5 A

Downlink Amplifier (2110-2155 MHz): 4.3 V, 0.5 A

A handwritten signature in black ink, appearing to read 'Patrick L. Cook', is written in a cursive style.

Patrick L. Cook
Senior Research and Development Engineer