



3301 E. Deseret Drive, St. George, UT 84790
www.wilsonelectronics.com • info@wilsonelectronics.com
phone 1-800-204-4104 • fax 1-435-656-2432

December 5, 2013

To: Whom it May Concern

Subject: Final Amplification Stage Voltage and Current

Please note that the maximum voltages and currents for the final amplification stages of the Model 460007 Signal Booster are:

Uplink Amplifier (698-716 MHz): 4.3 V, 0.5 A

Downlink Amplifier (728-746 MHz): 4.3 V, 0.5 A

Uplink Amplifier (777-787 MHz): 4.3 V, 0.5 A

Downlink Amplifier (746-756 MHz): 4.3 V, 0.5 A

Uplink Amplifier (824-849 MHz): 4.3 V, 0.5 A

Downlink Amplifier (869-894 MHz): 4.3 V, 0.5 A

Uplink Amplifier (1850-1910 MHz): 4.3 V, 0.5 A

Downlink Amplifier (1930-1990 MHz): 4.3 V, 0.5 A

Uplink Amplifier (1710-1755 MHz): 4.3 V, 0.5 A

Downlink Amplifier (2110-2155 MHz): 4.3 V, 0.5 A

A handwritten signature in black ink, appearing to read 'Patrick L. Cook', written in a cursive style.

Patrick L. Cook
Senior Research and Development Engineer