



Compliance Testing, LLC

Previously Flom Test Lab

EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268

fax: (480) 926-3598

<http://www.ComplianceTesting.com>

info@ComplianceTesting.com

Test Report

Prepared for: Wilson Electronics, Inc.

Model: 460027

Description: Quint Band Signal Booster

FCC ID: PWO460027

To

FCC Part 20

Date of Issue: February 17, 2015

On the behalf of the applicant: Wilson Electronics, Inc.
3301 E Deseret Drive
St. George, UT 84790

Attention of: Patrick Cook, Sr Research & Development Engineer
Ph: (435) 673-5021
E-Mail: pcook@infowest.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p14b0014

Mike Graffeo
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing.
All results contained herein relate only to the sample tested.



Test Report Revision History

| Revision | Date | Revised By | Reason for Revision |
|----------|-------------------|--------------|--|
| 1.0 | November 24, 2014 | Mike Graffeo | Original Document |
| 2.0 | February 11, 2015 | Mike Graffeo | Added EIRP results page 16, per new FCC Equipment Authorization requirements |
| 3.0 | February 17, 2015 | Mike Graffeo | Updated 869-894 antenna kit information |



Table of Contents

| <u>Description</u> | <u>Page</u> |
|--|--------------------|
| Standard Test Conditions and Engineering Practices | 5 |
| Test Result Summary | 7 |
| Authorized Frequency Band | 8 |
| Maximum Power and Gain | 14 |
| Intermodulation | 17 |
| Out-of-Band Emissions | 23 |
| Conducted Spurious Emissions | 57 |
| Noise Limits | 82 |
| Uplink Inactivity | 94 |
| Variable Gain | 98 |
| Occupied Bandwidth | 104 |
| Oscillation Detection | 135 |
| Radiated Spurious | 152 |
| Test Equipment Utilized | 155 |



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communiqué dated January 2009).

The tests results contained within this test report all fall within our scope of accreditation, unless noted below.

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A



Test and Measurement Data

Sub-part
2.1033(c)(14):

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Part 2, Subpart J and the following individual Parts: 20.21 in conjunction with latest version of KDB 935210.

Standard Test Conditions and Engineering Practices

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI/C63.4-2009, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104°F), unless the particular equipment requirements specified testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

| Environmental Conditions | | |
|--------------------------|--------------|-----------------|
| Temp (°C) | Humidity (%) | Pressure (mbar) |
| 24.9 – 31.0 | 33.5 – 63.0 | 985.5 - 943.0 |

Measurement results, unless otherwise noted, are worst-case measurements.

EUT Description

Model: 460027

Description: Quint Band Signal Booster

Firmware: N/A

Software: N/A

Additional Information:

The EUT is an In-Building, fixed install bi-directional amplifier for the boosting of cellular phone signals and data communication devices.

The following frequency bands and emission types are utilized.

| Frequency Band (MHz) | | | | | |
|------------------------|-----------|-----------|----------------------------------|-------------|-----------------------------|
| Uplink | 698 - 716 | 776 - 787 | 824 - 849 | 1850 - 1915 | 1710 – 1755 |
| Downlink | 728 - 746 | 746 - 757 | 869 - 894 | 1930 - 1995 | 2110 - 2155 |
| Modulation Type | LTE | | GSM, CDMA, EDGE, HSPA, EVDO, LTE | | CDMA, HSPA, LTE, EDGE, EVDO |

| Emission Designators | | | | | |
|----------------------|------|-----|------|------|-----|
| CDMA | HSPA | LTE | EVDO | EDGE | GSM |
| F9W | F9W | G7D | F9W | G7W | GXW |

The modulation types and emission designators listed in the tables represent the modulations that the cell phone providers use for each frequency band. GSM, CDMA, and WCDMA represent all the modulation types (phase and amplitude or a combination thereof) utilized within the industry. EDGE, HSPA, LTE etc. are all protocols or multiplexing techniques using the base modulations.

EUT Operation during Tests

The EUT was in a normal operating condition.



Accessories:

| Qty | Description | Manufacturer | Model | S/N |
|------------|----------------------|---------------------|--------------|------------|
| 1 | 50 to 75 ohm adaptor | MiniCircuits | SFMP-5075-3+ | N/A |
| 1 | Power Supply, 5V, 3A | Toshiba | PA1650-21 | N/A |

Cables: N/A

Modifications: N/A



Test Result Summary

| Specification | Test Name | Pass, Fail, N/A | Comments |
|---|------------------------------|-----------------|---|
| 20.21(e)(3) | Authorized Frequency Band | Pass | |
| 20.21(e)(8)(i)(B) 20.21(e)(8)(i)(C) 20.21(e)(8)(i)(D) | Maximum Power and Gain | Pass | |
| 20.21(e)(8)(i)(F) | Intermodulation | Pass | |
| 20.21(e)(8)(i)(E) | Out-of-Band Emissions | Pass | |
| 2.1051 22.917(a) 24.238((a) 27.53(c) 27.53(e) 27.53(f) 27.53(g) | Conducted Spurious Emissions | Pass | |
| 20.21(e)(8)(i)(A) | Noise Limits | Pass | |
| 20.21(e)(8)(i)(I) | Uplink Inactivity | Pass | |
| 20.21(e)(8)(i)(C)(1) 20.21(e)(8)(i)(H) Choose: 20.21(e)(8)(i)(C)(2)(i) (Fixed) | Variable Gain | Pass | |
| 2.1049 | Occupied Bandwidth | Pass | |
| 20.21(e)(8)(ii)(A) | Oscillation Detection | Pass | |
| 2.1053 | Radiated Spurious | Pass | |
| 20.21(e)(8)(i)(B) | Spectrum Block Filtering | N/A | This only applies to devices utilizing spectrum block filtering |



Authorized Frequency Band


Engineer: Mike Graffeo

Test Date: 11/19/14

Test Procedure

The EUT was connected to a spectrum analyzer through an attenuator with the losses being input into the spectrum analyzer as a combination of reference level offset and correction factor as needed to ensure accurate readings. A signal generator was utilized to produce a CW input signal tuned to the center channel of the operational band. The RF input level was increased to a point just prior to the AGC being in control of the power. The Signal generator was set to sweep across 2X the operational band of the EUT while the spectrum analyzer was set to MAX HOLD. Two markers were placed at the edges of the operational band and a third marker was placed at the highest point within the band no closer than 2.5 MHz from the band edge.


Test Setup






Uplink Test Results

698 - 716 MHz Band




776 - 787 MHz Band






824 - 849 MHz Band




1710 - 1755 MHz Band






1850 - 1915 MHz Band




Downlink Test Results

728 - 746 MHz Band






746 - 757 MHz Band




869 - 894 MHz Band






1930 - 1995 MHz Band



2110 - 2155 MHz Band





Maximum Power and Gain

Engineer: Mike Graffeo

Test Date: 11/19/14

Test Procedure


The EUT was connected to a spectrum analyzer through an attenuator with the losses being input into the spectrum analyzer as a combination of reference level offset and correction factor as needed to ensure accurate readings. The spectrum analyzer and signal generator were tuned to the frequency with the highest power level in the band, as determined by the Authorized Frequency Band test. The RF input level was increased to a point just prior to the AGC being in control of the power for both pulsed single time slot GSM modulation and 4.1 MHz AWGN modulation. The maximum power was measured and verified to meet the minimum and maximum levels allowed, with the maximum gain being computed from these values. The uplink and downlink gain under each condition were verified to be within 9 dB of each other.

For Fixed installations the following formula was used for calculating the gain limits.

$$\text{Gain Limit (dB)} = 6.5 \text{ dB} + 20\text{Log}(F_{\text{MHz}})$$

F_{MHz} is the uplink mid-band frequency with the downlink gain limit being equivalent to the paired Uplink band gain limit.

Test Setup



Uplink Power Test Results

| Frequency Band (MHz) | Input Level (dBm) | Output Power (dBm) | Lower Limit (dBm) | Upper Limit (dBm) | Result |
|----------------------------|-------------------|--------------------|-------------------|-------------------|--------|
| 698 - 716 MHz Pulsed GSM | -38.9 | 20.40 | 17 | 30 | Pass |
| 698 - 716 MHz AWGN | -41.1 | 17.23 | 17 | 30 | Pass |
| 776 - 787 MHz Pulsed GSM | -35.9 | 20.82 | 17 | 30 | Pass |
| 776 - 787 MHz AWGN | -37.5 | 20.09 | 17 | 30 | Pass |
| 824 - 849 MHz Pulsed GSM | -36.9 | 25.16 | 17 | 30 | Pass |
| 824 - 849 MHz AWGN | -35.2 | 23.88 | 17 | 30 | Pass |
| 1710 - 1755 MHz Pulsed GSM | -37.0 | 23.00 | 17 | 30 | Pass |
| 1710 - 1755 MHz AWGN | -39.0 | 19.87 | 17 | 30 | Pass |
| 1850 - 1915 MHz Pulsed GSM | -36.1 | 21.42 | 17 | 30 | Pass |
| 1850 - 1915 MHz AWGN | -37.3 | 18.75 | 17 | 30 | Pass |



Downlink Power Test Results

| Frequency Band (MHz) | Input Level (dBm) | Output Power (dBm) | Upper Limit (dBm) | Result |
|----------------------------|-------------------|--------------------|-------------------|--------|
| 728 - 746 MHz Pulsed GSM | -50.8 | 8.88 | 17 | Pass |
| 728 - 746 MHz AWGN | -48.9 | 11.57 | 17 | Pass |
| 746 - 757 MHz Pulsed GSM | -52.1 | 6.77 | 17 | Pass |
| 746 - 757 MHz AWGN | -49.8 | 10.41 | 17 | Pass |
| 869 - 894 MHz Pulsed GSM | -53.6 | 6.67 | 17 | Pass |
| 869 - 894 MHz AWGN | -51.7 | 9.39 | 17 | Pass |
| 1930 - 1995 MHz Pulsed GSM | -59.1 | 7.18 | 17 | Pass |
| 1930 - 1995 MHz AWGN | -55.1 | 9.47 | 17 | Pass |
| 2110 - 2155 MHz Pulsed GSM | -55.2 | 8.72 | 17 | Pass |
| 2110 - 2155 MHz AWGN | -53.1 | 11.31 | 17 | Pass |

Uplink and Downlink Gain Test Results

| Modulation | Uplink Frequency (MHz) | Downlink Frequency (MHz) | Uplink Gain (dB) | Uplink Limit (dB) | Downlink Gain (dB) | Downlink Limit (dB) | Delta (dB) | Limit (dB) | Margin (dB) |
|------------|------------------------|--------------------------|------------------|-------------------|--------------------|---------------------|------------|------------|-------------|
| Pulsed GSM | 706.63 | 743 | 59.30 | 63.5 | 59.7 | 63.5 | 0.38 | 9 | -8.62 |
| AWGN | 706.63 | 743 | 58.33 | 63.5 | 60.5 | 63.5 | 2.14 | 9 | -6.86 |
| Pulsed GSM | 777.8 | 748.5 | 56.72 | 64.4 | 58.9 | 64.4 | 2.15 | 9 | -6.85 |
| AWGN | 777.8 | 748.5 | 57.59 | 64.4 | 60.2 | 64.4 | 2.62 | 9 | -6.38 |
| Pulsed GSM | 832.75 | 878 | 62.06 | 64.9 | 60.3 | 64.9 | 1.79 | 9 | -7.21 |
| AWGN | 832.75 | 878 | 59.08 | 64.9 | 61.1 | 64.9 | 2.01 | 9 | -6.99 |
| Pulsed GSM | 1730.75 | 2114 | 60.00 | 71.3 | 63.9 | 71.3 | 3.92 | 9 | -5.08 |
| AWGN | 1730.75 | 2114 | 58.87 | 71.3 | 64.4 | 71.3 | 5.54 | 9 | -3.46 |
| Pulsed GSM | 1890.3 | 1938.4 | 57.52 | 72 | 66.3 | 72 | 8.76 | 9 | -0.24 |
| AWGN | 1890.3 | 1938.4 | 56.05 | 72 | 64.6 | 72 | 8.52 | 9 | -0.48 |



EIRP Uplink Power Calculations

| Frequency Band (MHz) | Antenna Kit | EIRP (Watts) | Limit (Watts) | Result |
|----------------------|---------------|--------------|---------------|--------|
| 698 - 716 | 314411-40075 | 0.3090 | 1.0 | Pass |
| 776 - 787 | 314411-40075 | 0.3177 | 1.0 | Pass |
| 824 - 849 | 311129-400100 | 1.0000 | 1.0 | Pass |
| 1710 - 1755 | 314453-40075 | 0.5741 | 1.0 | Pass |
| 1850 - 1915 | 3144473-0640 | 0.4130 | 1.0 | Pass |

EIRP Downlink Power Calculations

| Frequency Band (MHz) | Antenna Kit | EIRP (Watts) | Limit (Watts) | Result |
|----------------------|-------------|--------------|---------------|--------|
| 728 - 746 | 309900-50N | 0.0374 | 1.0 | Pass |
| 746 - 757 | 309900-50N | 0.0286 | 1.0 | Pass |
| 869 - 894 | 311115-1150 | 0.0353 | 1.0 | Pass |
| 1930 - 1995 | 309900-50N | 0.0405 | 1.0 | Pass |
| 2110 - 2155 | 309900-50N | 0.0302 | 1.0 | Pass |



Intermodulation


Engineer: Mike Graffeo

Test Date: 11/18/14

Test Procedure

The EUT was connected to a spectrum analyzer through an attenuator. Two signal generators were utilized to produce two CW signals 600 kHz apart and centered in the operational band. Attenuator and cable insertion loss correction factors were input to either the signal generator or the spectrum analyzer as required to ensure that accurate measurements were recorded. The input power was set at the maximum allowable power and the RMS intermodulation products were measured to ensure they were less than -19 dBm in a 3 kHz RBW. The uplink and downlink intermodulation products were plotted, with the levels being listed in the summary tables.

Test Setup



Uplink Test Results

| Frequency Band (MHz) | Intermodulation Level (dBm) | Limit (dBm) | Result |
|----------------------|-----------------------------|-------------|--------|
| 698 - 716 MHz | -20.63 | -19 | Pass |
| 776 - 787 MHz | -20.70 | -19 | Pass |
| 824 - 849 MHz | -20.67 | -19 | Pass |
| 1710 - 1755 MHz | -21.39 | -19 | Pass |
| 1850 - 1915 MHz | -23.37 | -19 | Pass |


Downlink Test Results

| Frequency Band (MHz) | Intermodulation Level (dBm) | Limit (dBm) | Result |
|----------------------|-----------------------------|-------------|--------|
| 728 - 746 MHz | -37.01 | -19 | Pass |
| 746 - 757 MHz | -40.53 | -19 | Pass |
| 869 - 894 MHz | -38.50 | -19 | Pass |
| 1930 - 1995 MHz | -37.94 | -19 | Pass |
| 2110 - 2155 MHz | -30.24 | -19 | Pass |




Uplink Test Results

698 - 716 MHz Band




776 - 787 MHz Band






824 - 849 MHz Band




1710 - 1755 MHz Band






1850 - 1915 MHz Band




Downlink Test Results

728 - 746 MHz Band






746 - 757 MHz Band




869 - 894 MHz Band






1930 - 1995 MHz Band



2110 - 2155 MHz Band





Out-of-Band Emissions

Engineer: Mike Graffeo

Test Date: 11/20/14

Test Procedure

The EUT was connected to a spectrum analyzer through an attenuator with the losses being input into the spectrum analyzer as a combination of reference level offset and correction factor in order to ensure accurate readings. A signal generator was utilized to produce the following signals: GSM, CDMA, and WCDMA. The signal generator was tuned to the lowest allowable upper and lower channel within the EUT operational band for each respective modulation type. The RF input level was increased to a point just prior to the AGC being in control of the power. For each modulation type the Out of Band Emissions were measured to ensure they met the limits.

The following formula was used for calculating the limits:

$$\text{Limit} = P1 - 6 - (43 + 10\text{Log}(P2)) = -19\text{dBm}$$

P1 = power in dBm

P2 = power in Watts

Test Setup





GSM Uplink Test Results

| Frequency Band (MHz) | Band Edge | Measured Level (dBm) | Limit (dBm) | Result |
|----------------------|-----------|----------------------|-------------|--------|
| 698 - 716 | Lower | -28.23 | -19 | Pass |
| 698 - 716 | Upper | -32.76 | -19 | Pass |
| 776 - 787 | Lower | -27.12 | -19 | Pass |
| 776 - 787 | Upper | -28.15 | -19 | Pass |
| 824 - 849 | Lower | -33.23 | -19 | Pass |
| 824 - 849 | Upper | -30.80 | -19 | Pass |
| 1710 - 1755 | Lower | -36.24 | -19 | Pass |
| 1710 - 1755 | Upper | -37.47 | -19 | Pass |
| 1850 - 1915 | Lower | -37.20 | -19 | Pass |
| 1850 - 1915 | Upper | -41.57 | -19 | Pass |

CDMA Uplink Test Results

| Frequency Band (MHz) | Band Edge | Measured Level (dBm) | Limit (dBm) | Result |
|----------------------|-----------|----------------------|-------------|--------|
| 698 - 716 | Lower | -48.36 | -19 | Pass |
| 698 - 716 | Upper | -55.82 | -19 | Pass |
| 776 - 787 | Lower | -38.15 | -19 | Pass |
| 776 - 787 | Upper | -44.56 | -19 | Pass |
| 824 - 849 | Lower | -30.24 | -19 | Pass |
| 824 - 849 | Upper | -35.96 | -19 | Pass |
| 1710 - 1755 | Lower | -41.85 | -19 | Pass |
| 1710 - 1755 | Upper | -41.56 | -19 | Pass |
| 1850 - 1915 | Lower | -43.66 | -19 | Pass |
| 1850 - 1915 | Upper | -48.29 | -19 | Pass |



WCDMA Uplink Test Results

| Frequency Band (MHz) | Band Edge | Measured Level (dBm) | Limit (dBm) | Result |
|----------------------|-----------|----------------------|-------------|--------|
| 698 - 716 | Lower | -54.48 | -19 | Pass |
| 698 - 716 | Upper | -55.96 | -19 | Pass |
| 776 - 787 | Lower | -40.91 | -19 | Pass |
| 776 - 787 | Upper | -47.81 | -19 | Pass |
| 824 - 849 | Lower | -32.56 | -19 | Pass |
| 824 - 849 | Upper | -29.63 | -19 | Pass |
| 1710 - 1755 | Lower | -37.87 | -19 | Pass |
| 1710 - 1755 | Upper | -37.56 | -19 | Pass |
| 1850 - 1915 | Lower | -40.46 | -19 | Pass |
| 1850 - 1915 | Upper | -44.89 | -19 | Pass |

GSM Downlink Test Results

| Frequency Band (MHz) | Band Edge | Measured Level (dBm) | Limit (dBm) | Result |
|----------------------|-----------|----------------------|-------------|--------|
| 728 - 746 | Lower | -39.36 | -19 | Pass |
| 728 - 746 | Upper | -33.74 | -19 | Pass |
| 746 - 757 | Lower | -32.97 | -19 | Pass |
| 746 - 757 | Upper | -43.05 | -19 | Pass |
| 869 - 894 | Lower | -44.72 | -19 | Pass |
| 869 - 894 | Upper | -47.92 | -19 | Pass |
| 1930 - 1995 | Lower | -47.85 | -19 | Pass |
| 1930 - 1995 | Upper | -50.44 | -19 | Pass |
| 2110 - 2155 | Lower | -44.72 | -19 | Pass |
| 2110 - 2155 | Upper | -45.80 | -19 | Pass |



CDMA Downlink Test Results

| Frequency Band (MHz) | Band Edge | Measured Level (dBm) | Limit (dBm) | Result |
|----------------------|-----------|----------------------|-------------|--------|
| 728 - 746 | Lower | -55.24 | -19 | Pass |
| 728 - 746 | Upper | -54.78 | -19 | Pass |
| 746 - 757 | Lower | -54.57 | -19 | Pass |
| 746 - 757 | Upper | -56.46 | -19 | Pass |
| 869 - 894 | Lower | -52.50 | -19 | Pass |
| 869 - 894 | Upper | -51.86 | -19 | Pass |
| 1930 - 1995 | Lower | -55.13 | -19 | Pass |
| 1930 - 1995 | Upper | -53.96 | -19 | Pass |
| 2110 - 2155 | Lower | -48.99 | -19 | Pass |
| 2110 - 2155 | Upper | -50.20 | -19 | Pass |

WCDMA Downlink Test Results


| Frequency Band (MHz) | Band Edge | Measured Level (dBm) | Limit (dBm) | Result |
|----------------------|-----------|----------------------|-------------|--------|
| 728 - 746 | Lower | -55.29 | -19 | Pass |
| 728 - 746 | Upper | -55.03 | -19 | Pass |
| 746 - 757 | Lower | -54.22 | -19 | Pass |
| 746 - 757 | Upper | -55.60 | -19 | Pass |
| 869 - 894 | Lower | -46.92 | -19 | Pass |
| 869 - 894 | Upper | -46.73 | -19 | Pass |
| 1930 - 1995 | Lower | -48.13 | -19 | Pass |
| 1930 - 1995 | Upper | -48.06 | -19 | Pass |
| 2110 - 2155 | Lower | -44.79 | -19 | Pass |
| 2110 - 2155 | Upper | -44.27 | -19 | Pass |




GSM Uplink Test Plots

698 - 716 MHz Band

Lower Band Edge




Upper Band Edge






776 - 787 MHz Band

Lower Band Edge




Upper Band Edge






824 - 849 MHz Band

Lower Band Edge




Upper Band Edge






1710 - 1755 MHz Band

Lower Band Edge




Upper Band Edge






1850 - 1915 MHz Band

Lower Band Edge



Upper Band Edge







CDMA Uplink Test Plots

698 - 716 MHz Band

Lower Band Edge




Upper Band Edge






776 - 787 MHz Band

Lower Band Edge




Upper Band Edge






824 - 849 MHz Band

Lower Band Edge




Upper Band Edge






1710 - 1755 MHz Band

Lower Band Edge




Upper Band Edge






1850 - 1915 MHz Band

Lower Band Edge




Upper Band Edge






WCDMA Uplink Test Plots 698 - 716 MHz Band Lower Band Edge




Upper Band Edge






776 - 787 MHz Band

Lower Band Edge




Upper Band Edge






824 - 849 MHz Band

Lower Band Edge




Upper Band Edge






1710 - 1755 MHz Band

Lower Band Edge




Upper Band Edge






1850 - 1915 MHz Band

Lower Band Edge




Upper Band Edge






GSM Downlink Test Plots 728 - 746 MHz Band Lower Band Edge




Upper Band Edge






746 - 757 MHz Band

Lower Band Edge




Upper Band Edge






869 - 894 MHz Band

Lower Band Edge




Upper Band Edge






1930 - 1995 MHz Band

Lower Band Edge




Upper Band Edge






2110 - 2155 MHz Band

Lower Band Edge



Upper Band Edge







CDMA Downlink Test Plots

728 - 746 MHz Band

Lower Band Edge




Upper Band Edge






746 - 757 MHz Band

Lower Band Edge




Upper Band Edge






869 - 894 MHz Band

Lower Band Edge




Upper Band Edge






1930 - 1995 MHz Band

Lower Band Edge




Upper Band Edge






2110 - 2155 MHz Band

Lower Band Edge



Upper Band Edge







WCDMA Downlink Test Plots

728 - 746 MHz Band

Lower Band Edge




Upper Band Edge






746 - 757 MHz Band

Lower Band Edge




Upper Band Edge






869 - 894 MHz Band

Lower Band Edge




Upper Band Edge






1930 - 1995 MHz Band

Lower Band Edge




Upper Band Edge






2110 - 2155 MHz Band

Lower Band Edge



Upper Band Edge





Conducted Spurious Emissions

Engineer: Mike Graffeo

Test Date: 11/20/14

Test Procedure

The EUT was connected to a spectrum analyzer through an attenuator, with the losses being input into the spectrum analyzer as a combination of reference level offset and correction factor as needed to ensure accurate readings. A signal generator was utilized to produce a 4.1 MHz AWGN signal operating at the maximum allowable power. The conducted spurious emissions from 9 kHz to 10 times the highest tunable frequency for each operational band were measured (excluding the band defined by the Out of band emissions test). The emissions were plotted and the highest level was recorded in the summary table.


The following formulas are used for calculating the limits.

Conducted Spurious Emissions Limit = $P1 - (43 + 10\text{Log}(P2)) = -13 \text{ dBm}$

P1 = power in dBm

P2 = power in Watts

Test Setup



Uplink Test Results

| Frequency Band (MHz) | Measured Frequency (MHz) | Measured Level (dBm) | Limit (dBm) | Result |
|----------------------|--------------------------|----------------------|-------------|--------|
| 698 - 716 | 1894.6 | -33.77 | -13 | Pass |
| 776 - 787 | 787.1 | -21.95 | -13 | Pass |
| 824 - 849 | 1729.6 | -32.36 | -13 | Pass |
| 1710 - 1755 | 3465.2 | -39.61 | -13 | Pass |
| 1850 - 1915 | 3764.7 | -28.92 | -13 | Pass |

Downlink Test Results

| Frequency Band (MHz) | Measured Frequency (MHz) | Measured Level (dBm) | Limit (dBm) | Result |
|----------------------|--------------------------|----------------------|-------------|--------|
| 728 - 746 | 1950.2 | -33.51 | -13 | Pass |
| 746 - 757 | 1980.6 | -33.25 | -13 | Pass |
| 869 - 894 | 1973.4 | -32.33 | -13 | Pass |
| 1930 - 1995 | 2148.5 | -34.76 | -13 | Pass |
| 2110 - 2155 | 1950.6 | -33.06 | -13 | Pass |



For the 746 – 758 downlink and 776 – 788 Uplink bands of operation, the following additional spurious emissions requirements apply.

FCC 27.53(c)

For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;

The test is performed using a 10 kHz RBW. Since the limit is referenced to a 6.25 kHz BW, the following correction factor is applied to the measured data.

BW correction Factor = $10 \log B1/B2$

BW correction Factor = $10 \log 6.25 / 10 = - 2.0$ dB

Final Value (dBm) = conducted measurement + BW correction factor

776 – 787 MHz Uplink Band

| Spurious Frequency Range (MHz) | Measured Frequency (MHz) | Measured Value (dBm) | Bandwidth Correction Factor (dB) | Final Value (dBm) | Limit (dBm) | Margin (dB) |
|--------------------------------|--------------------------|----------------------|----------------------------------|-------------------|-------------|-------------|
| 763 – 775 | 774.61 | -54.1 | -2.0 | -56.14 | -46 | -10.14 |
| 793 – 805 | 793.17 | -75.6 | -2.0 | -77.64 | -46 | -31.64 |

746 - 757 MHz Downlink Band

| Spurious Frequency Range (MHz) | Measured Frequency (MHz) | Measured Value (dBm) | Bandwidth Correction Factor (dB) | Final Value (dBm) | Limit (dBm) | Margin (dB) |
|--------------------------------|--------------------------|----------------------|----------------------------------|-------------------|-------------|-------------|
| 763 – 775 | 763.09 | -84 | -2.0 | -86.04 | -46 | -40.04 |
| 793 – 805 | 798.08 | -83.99 | -2.0 | -86.03 | -46 | -40.03 |



FCC 27.53(f)

For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

Since the limit is referenced to EIRP, the final data is computed using the Conducted Spurious Emission data and adding the BW correction factor plus the final gain/loss data from the antenna kitting information supplied by the manufacturer.

For the Narrowband measurement, the test is performed using a 10 kHz RBW. Since the limit is referenced to a 700 Hz BW, the following correction factor is applied to the measured data.

$$\text{BW correction Factor} = 10\text{Log } B1/B2$$

$$\text{BW correction Factor} = 10\text{Log } 700 / 10000 = -11.55 \text{ dB}$$

$$\text{Final Value (dBm)} = \text{conducted measurement} + \text{BW correction factor} + \text{final gain/loss from Antenna Kitting document}$$

The Limit for discreet (narrowband) emissions is -80dBW (-50 dBm) in 700 MHz BW.

The Limit for (wideband Emissions) is -70 dBW (-40 dBm) in a 1 MHz BW.

776 – 787 MHz Uplink Band

| Spurious Frequency Range (MHz) | Measured Frequency (MHz) | Measured Value (dBm) | Bandwidth Correction Factor (dB) | Gain/Loss from Antenna Kitting Information (dB) | Final Value (dBm) | Limit (dBm) | Margin (dB) |
|--------------------------------|--------------------------|----------------------|----------------------------------|---|-------------------|-------------|-------------|
| 1559 – 1610 (Wideband) | 1563.4 | -53.16 | 0 | 2.13 | -51.03 | -40 | -11.03 |
| 1559 – 1610 (Narrowband) | 1562.3 | -77.5 | -11.55 | 2.13 | -86.92 | -50 | -36.92 |



746 - 757 MHz Downlink Band

| Spurious Frequency Range (MHz) | Measured Frequency (MHz) | Measured Value (dBm) | Bandwidth Correction Factor (dB) | Gain/Loss from Antenna Kitting information (dB) | Final Value (dBm) | Limit (dBm) | Margin (dB) |
|--------------------------------|--------------------------|----------------------|----------------------------------|---|-------------------|-------------|-------------|
| 1559 – 1610 (Wideband) | 1593.1 | -58.83 | 0 | 2.13 | -56.70 | -40 | -16.70 |
| 1559 – 1610 (Narrowband) | 1597.1 | -80.95 | -11.55 | 2.13 | -90.37 | -50 | -40.37 |





Uplink Test Plots

698 - 716 MHz Band







776 - 787 MHz Band







824 - 849 MHz Band







1710 - 1755 MHz Band






1710 - 1755 MHz Band (cont)







1710 - 1755 MHz Band (cont)







1850 - 1915 MHz Band






1850 - 1915 MHz Band (cont)







1850 - 1915 MHz Band (cont)







Downlink Test Plots

728 - 746 MHz Band







746 - 757 MHz Band







869 - 894 MHz Band







1930 - 1995 MHz Band






1930 - 1995 MHz Band (cont)







1930 - 1995 MHz Band (cont)







2110 - 2155 MHz Band






2110 - 2155 MHz Band (cont)






2110 - 2155 MHz Band (cont)






776 – 787 MHz Uplink Test Plots for the

763 - 775 MHz Frequency Range




793 - 805 MHz Frequency Range






776 – 787 MHz Uplink Test Plots for the

1559 - 1610 MHz Frequency Range (Wideband)




1559 - 1610 MHz Frequency Range (Narrowband)






746 – 757 MHz Downlink Test Plots for the

763 - 775 MHz Frequency Range




793 - 805 MHz Frequency Range






746 – 757 MHz Downlink Test Plots for the

1559 - 1610 MHz Frequency Range (Wideband)



1559 - 1610 MHz Frequency Range (Narrowband)





Noise Limits

Engineer: Mike Graffeo

Test Date: 11/19/14

Test Procedure

The EUT was connected to a spectrum analyzer through an attenuator with the losses being input into the spectrum analyzer as a combination of reference level offset and correction factor as necessary to ensure that accurate readings were obtained. A series of three tests were performed: the maximum uplink noise, the variable noise for the uplink in the presence of a downlink signal, and the variable uplink noise timing. The detailed procedures from KDB 935210 D03 Wideband Consumer Signal Booster Measurement Guidance DR04-41516c were followed.

The following formulas are used for calculating the limits. Note – Downlink noise power limit is calculated with the center frequency of the associated uplink band.

Noise Power = $-102.5 + \text{LOG}_{10}(\text{Band Center Frequency}) * 20$


Variable Noise = $-103 \text{ dBm/MHz-RSSI}$

Test Setup

Maximum Noise Power



Variable Uplink Noise Power and Timing





Maximum Uplink Noise Test Results

| Frequency Band (MHz) | Measured Noise (dBm) | Limit (dBm) | Margin (dB) | Result |
|----------------------|----------------------|-------------|-------------|--------|
| 698 - 716 | -49.05 | -45.5 | -3.5 | Pass |
| 776 - 787 | -45.7 | -44.6 | -1.1 | Pass |
| 824 - 849 | -47.09 | -44.1 | -3.0 | Pass |
| 1710 - 1755 | -38.87 | -37.7 | -1.1 | Pass |
| 1850 - 1915 | -40.16 | -37.0 | -3.2 | Pass |

Maximum Downlink Noise Test Results

| Frequency Band (MHz) | Measured Noise (dBm) | Limit (dBm) | Margin (dB) | Result |
|----------------------|----------------------|-------------|-------------|--------|
| 728 - 746 | -47.89 | -45.5 | -2.4 | Pass |
| 746 - 757 | -48.16 | -44.6 | -3.5 | Pass |
| 869 - 894 | -44.33 | -44.1 | -0.3 | Pass |
| 1930 - 1995 | -38.87 | -37.0 | -1.9 | Pass |
| 2110 - 2155 | -40.56 | -37.7 | -2.8 | Pass |

Uplink Noise Timing Test Results

| Frequency Band (MHz) | Measured Timing (ms) | Limit (ms) | Result |
|----------------------|----------------------|------------|--------|
| 698 - 716 | 38.91 | 3000 | Pass |
| 776 - 787 | 334.60 | 3000 | Pass |
| 824 - 849 | 365.70 | 3000 | Pass |
| 1710 - 1755 | 303.50 | 3000 | Pass |
| 1850 - 1915 | 108.50 | 3000 | Pass |



Variable Uplink Noise Limit Test Results

698 - 716 MHz

| RSSI (dBm) | Noise Limit (dBm) | Measured Noise (dBm) | Margin (dB) |
|-------------------|--------------------------|-----------------------------|--------------------|
| -56.0 | -47.0 | -57.7 | -10.7 |
| -57.0 | -46.0 | -56.6 | -10.6 |
| -67.0 | -45.5 | -50.1 | -4.6 |
| -66.0 | -45.5 | -50.1 | -4.6 |
| -65.0 | -45.5 | -50.1 | -4.6 |
| -64.0 | -45.5 | -50.1 | -4.6 |

776 - 787 MHz

| RSSI (dBm) | Noise Limit (dBm) | Measured Noise (dBm) | Margin (dB) |
|-------------------|--------------------------|-----------------------------|--------------------|
| -47.0 | -56.0 | -62.2 | -6.2 |
| -46.0 | -57.0 | -63.2 | -6.2 |
| -71.0 | -44.6 | -45.5 | -0.9 |
| -70.0 | -44.6 | -45.5 | -0.9 |
| -69.0 | -44.6 | -45.5 | -0.9 |
| -68.0 | -44.6 | -45.5 | -0.9 |

824 - 849 MHz

| RSSI (dBm) | Noise Limit (dBm) | Measured Noise (dBm) | Margin (dB) |
|-------------------|--------------------------|-----------------------------|--------------------|
| -41.0 | -62.0 | -71.7 | -9.7 |
| -40.0 | -63.0 | -71.71 | -8.7 |
| -69.0 | -44.05 | -47.2 | -3.1 |
| -68.0 | -44.05 | -47.2 | -3.1 |
| -67.0 | -44.05 | -47.2 | -3.1 |
| -66.0 | -44.05 | -47.2 | -3.1 |

1710 - 1755 MHz

| RSSI (dBm) | Noise Limit (dBm) | Measured Noise (dBm) | Margin (dB) |
|-------------------|--------------------------|-----------------------------|--------------------|
| -71.0 | -37.7 | -43.2 | -5.5 |
| -70.0 | -37.7 | -43.2 | -5.5 |
| -69.0 | -37.7 | -43.2 | -5.5 |
| -68.0 | -37.7 | -43.2 | -5.5 |
| -44.0 | -59.0 | -61.1 | -2.1 |
| -43.0 | -60.0 | -61.1 | -1.1 |


1850 - 1915 MHz

| RSSI (dBm) | Noise Limit (dBm) | Measured Noise (dBm) | Margin (dB) |
|-------------------|--------------------------|-----------------------------|--------------------|
| -59.0 | -44.0 | -53.2 | -9.2 |
| -58.0 | -45.0 | -54.2 | -9.2 |
| -73.0 | -37.0 | -42.4 | -5.4 |
| -72.0 | -37.0 | -42.4 | -5.4 |
| -71.0 | -37.0 | -42.4 | -5.4 |
| -70.0 | -37.0 | -42.4 | -5.4 |




Maximum Uplink Noise Test Plots

698 - 716 MHz Band




776 - 787 MHz Band






824 - 849 MHz Band




1710 - 1755 MHz Band






1850 - 1915 MHz Band






Maximum Downlink Noise Test Plots

728 - 746 MHz Band






746 - 757 MHz Band




869 - 894 MHz Band






1930 - 1995 MHz Band




2110 - 2155 MHz Band






Uplink Noise Timing Test Plots

698 - 716 MHz Band




776 - 787 MHz Band






824 - 849 MHz Band




1710 - 1755 MHz Band





1850 - 1915 MHz Band





Uplink Inactivity


Engineer: Mike Graffeo

Test Date: 11/19/14

Test Procedure

The EUT was connected directly to a spectrum analyzer set to operate in the center of the EUT operational uplink and downlink bands. The span was set to 0 Hz with a sweep time of 330 seconds and MAX HOLD operation. The EUT was powered on and the time for the uplink to return to an inactive state was measured using the DELTA MARKER method to ensure that it was less than 300 seconds. The noise level after the return to an inactive state was less than -70 dBm/MHz

Test Setup




Uplink Test Results

| Frequency Band (MHz) | Measured Time (Seconds) | Limit (Seconds) | Result |
|----------------------|-------------------------|-----------------|--------|
| 698 - 716 | 279.8 | 300 | Pass |
| 776 - 787 | 280.5 | 300 | Pass |
| 824 - 849 | 280.5 | 300 | Pass |
| 1710 - 1755 | 279.0 | 300 | Pass |
| 1850 - 1915 | 279.8 | 300 | Pass |




Uplink Inactivity Test Results

698 - 716 MHz




776 - 787 MHz






824 - 849 MHz




1710 - 1755 MHz





1850 - 1915 MHz





Variable Gain

Engineer: Mike Graffeo

Test Date: 11/19/14

Test Procedure

The EUT was connected to a spectrum analyzer through an attenuator with the losses being input into the spectrum analyzer as a combination of reference level offset and correction factor in order to ensure accurate readings were obtained. The uplink gain in the presence of a downlink signal was measured for each operational uplink band using the detailed procedures from KDB 935210 D03 Wideband Consumer Signal Booster Measurement Guidance DR04-41516.


The following formula is used for calculating the limits:

$$\text{Variable Gain} = -34 \text{ dB} - \text{RSSI} + \text{MSCL}$$

$$\text{Fixed booster maximum gain} = 6.5 \text{ dB} + 20 * \text{LOG}_{10}(\text{mid-band of uplink band})$$

Downlink fixed booster maximum gain is identical to the corresponding fixed booster maximum gain for uplink.

Test Setup





Uplink Test Results

698 - 716 MHz

| RSSI (dBm) | MSCL (dB) | Gain Limit (dBm) | P(in) (dBm) | P(out) (dBm) | Gain (dB) | Margin (dB) |
|------------|-----------|------------------|-------------|--------------|-----------|-------------|
| -46.0 | 35.61 | 47.6 | -46.1 | -1.0 | 45.1 | -2.5 |
| -45.0 | 35.61 | 46.6 | -46.1 | -2.0 | 44.1 | -2.5 |
| -70.0 | 35.61 | 63.5 | -46.1 | 16.0 | 62.1 | -1.4 |
| -69.0 | 35.61 | 63.5 | -46.1 | 16.0 | 62.1 | -1.4 |
| -68.0 | 35.61 | 63.5 | -46.1 | 16.0 | 62.1 | -1.4 |
| -67.0 | 35.61 | 63.5 | -46.1 | 16.0 | 62.1 | -1.4 |

776 - 787 MHz

| RSSI (dBm) | MSCL (dB) | Gain Limit (dBm) | P(in) (dBm) | P(out) (dBm) | Gain (dB) | Margin (dB) |
|------------|-----------|------------------|-------------|--------------|-----------|-------------|
| -65.0 | 36.44 | 64.4 | -42.5 | 16.4 | 58.9 | -5.5 |
| -64.0 | 36.44 | 64.4 | -42.5 | 16.4 | 58.9 | -5.5 |
| -63.0 | 36.44 | 64.4 | -42.5 | 16.4 | 58.9 | -5.5 |
| -62.0 | 36.44 | 64.4 | -42.5 | 16.4 | 58.9 | -5.5 |
| -48.0 | 36.44 | 50.4 | -42.5 | 3.2 | 45.7 | -4.7 |
| -47.0 | 36.44 | 49.4 | -42.5 | 2.2 | 44.7 | -4.7 |

824 - 849 MHz

| RSSI (dBm) | MSCL (dB) | Gain Limit (dBm) | P(in) (dBm) | P(out) (dBm) | Gain (dB) | Margin (dB) |
|------------|-----------|------------------|-------------|--------------|-----------|-------------|
| -47.0 | 37.04 | 50.0 | -40.2 | 2.2 | 42.4 | -7.6 |
| -46.0 | 37.04 | 49.0 | -40.2 | 1.2 | 41.4 | -7.6 |
| -70.0 | 37.04 | 64.9 | -40.2 | 23.0 | 63.2 | -1.7 |
| -69.0 | 37.04 | 64.9 | -40.2 | 23.0 | 63.2 | -1.7 |
| -68.0 | 37.04 | 64.9 | -40.2 | 23.0 | 63.2 | -1.7 |
| -67.0 | 37.04 | 64.9 | -40.2 | 23.0 | 63.2 | -1.7 |

1710 - 1755 MHz

| RSSI (dBm) | MSCL (dB) | Gain Limit (dBm) | P(in) (dBm) | P(out) (dBm) | Gain (dB) | Margin (dB) |
|------------|-----------|------------------|-------------|--------------|-----------|-------------|
| -69.0 | 40.39 | 71.3 | -44.0 | 18.3 | 62.3 | -9.0 |
| -68.0 | 40.39 | 71.3 | -44.0 | 18.3 | 62.3 | -9.0 |
| -67.0 | 40.39 | 71.3 | -44.0 | 18.3 | 62.3 | -9.0 |
| -66.0 | 40.39 | 71.3 | -44.0 | 18.3 | 62.3 | -9.0 |
| -57.0 | 40.39 | 63.4 | -44.0 | 11.8 | 55.8 | -7.6 |
| -56.0 | 40.39 | 62.4 | -44.0 | 10.8 | 54.8 | -7.6 |

1850 - 1915 MHz

| RSSI (dBm) | MSCL (dB) | Gain Limit (dBm) | P(in) (dBm) | P(out) (dBm) | Gain (dB) | Margin (dB) |
|------------|-----------|------------------|-------------|--------------|-----------|-------------|
| -71.0 | 38.72 | 72.0 | -42.3 | 19.2 | 61.5 | -10.5 |
| -70.0 | 38.72 | 72.0 | -42.3 | 19.2 | 61.5 | -10.5 |
| -69.0 | 38.72 | 72.0 | -42.3 | 19.2 | 61.5 | -10.5 |
| -68.0 | 38.72 | 72.0 | -42.3 | 19.2 | 61.5 | -10.5 |
| -51.0 | 38.72 | 55.7 | -42.3 | 4.8 | 47.1 | -8.6 |
| -50.0 | 38.72 | 54.7 | -42.3 | 3.8 | 46.1 | -8.6 |



Uplink Gain Timing Test Results

| Frequency Band (MHz) | Measured Timing (milliseconds) | Limit (milliseconds) | Result |
|----------------------|--------------------------------|----------------------|--------|
| 704 - 716 | 15.56 | 3000.0 | Pass |
| 776 - 787 | 389.10 | 3000.0 | Pass |
| 824 - 849 | 404.60 | 3000.0 | Pass |
| 1710 - 1755 | 46.69 | 3000.0 | Pass |
| 1850 - 1915 | 116.70 | 3000.0 | Pass |




Uplink Gain Timing 704 - 716 MHz Band

Agilent 16:24:56 Nov 19, 2014

L

Mkr1 Δ 15.56 ms
-14.44 dB




Uplink Gain Timing 776 - 787 MHz Band

Agilent 16:29:42 Nov 19, 2014

L

Mkr1 Δ 389.1 ms
-13.4 dB






Uplink Gain Timing 824 - 849 MHz Band

Agilent 16:31:30 Nov 19, 2014

L

Mkr1 Δ 404.6 ms
-20.19 dB




Uplink Gain Timing 1710 - 1755 MHz Band

Agilent 16:33:53 Nov 19, 2014

L

Mkr1 Δ 46.69 ms
-19.38 dB






Uplink Gain Timing 1850 - 1915 MHz Band

Agilent 16:35:27 Nov 19, 2014

L

Mkr1 Δ 116.7 ms
-20.4 dB





Occupied Bandwidth


Engineer: Mike Graffeo

Test Date: 11/20/14

Test Procedure

The EUT was connected to a spectrum analyzer through an attenuator with the losses being input into the spectrum analyzer as a combination of reference level offset and correction factor as required to ensure that accurate readings were obtained. A signal generator was utilized to produce the following signals: GSM, CDMA, and WCDMA. The signal generator was tuned to the center channel of each of the EUT operational uplink and downlink bands with the RF level set at a point just prior to the AGC being in control of the power. For each modulation type, the input and output signal was measured and plotted to ensure that the signals were similar.

Test Setup







GSM Uplink Test Plots

698 - 716 MHz Band

Input




Output






776 - 787 MHz Band

Input




Output






824 - 849 MHz Band

Input




Output






1710 - 1755 MHz Band

Input




Output






1850 - 1915 MHz Band

Input



Output







GSM Downlink Test Plots

728 - 746 MHz Band

Input




Output






746 - 757 MHz Band

Input




Output






869 - 894 MHz Band

Input




Output






1930 - 1995 MHz Band

Input




Output






2110 - 2155 MHz Band

Input



Output







CDMA Uplink Test Plots

698 - 716 MHz Band

Input




Output






776 - 787 MHz Band

Input




Output






824 - 849 MHz Band

Input




Output






1710 - 1755 MHz Band

Input




Output






1850 - 1915 MHz Band

Input



Output







CDMA Downlink Test Plots

728 - 746 MHz Band

Input




Output






746 - 757 MHz Band

Input




Output






869 - 894 MHz Band

Input




Output






1930 - 1995 MHz Band

Input




Output






2110 - 2155 MHz Band

Input



Output







WCDMA Uplink Test Plots

698 - 716 MHz Band

Input




Output






776 - 787 MHz Band

Input




Output






824 - 849 MHz Band

Input




Output






1710 - 1755 MHz Band

Input




Output






1850 - 1915 MHz Band

Input



Output







WCDMA Downlink Test Plots

728 - 746 MHz Band

Input




Output






746 - 757 MHz Band

Input




Output






869 - 894 MHz Band

Input




Output






1930 - 1995 MHz Band

Input




Output






2110 - 2155 MHz Band

Input



Output





Oscillation Detection


Engineer: Mike Graffeo

Test Date: 11/20/14

Test Procedure

The EUT was connected to a spectrum analyzer set for 0 Hz operation. The EUT uplink and downlink were fed back upon each other through a selectable band pass filter and variable attenuator. The EUT uplink and downlink were tested to ensure that the presence of oscillation was detected and that the EUT output turned off within 300 mS for the Uplink and 1 second for the Downlink and remained off for 1 minute. A EUT with test software was utilized to ensure that the EUT only had a maximum of 5 attempts at restart from oscillation before permanently shutting off.

Test Setup



Uplink Detection Time Test Results

| Frequency Band (MHz) | Measured Time (mS) | Limit (mS) | Result |
|----------------------|--------------------|------------|--------|
| 698 - 716 | 111.6 | 300 | Pass |
| 776 - 787 | 79.2 | 300 | Pass |
| 824 - 849 | 82.8 | 300 | Pass |
| 1710 - 1755 | 34.2 | 300 | Pass |
| 1850 - 1915 | 104.2 | 300 | Pass |

Downlink Detection Time Test Results

| Frequency Band (MHz) | Measured Time (mS) | Limit (mS) | Result |
|----------------------|--------------------|------------|--------|
| 728 - 746 | 38.7 | 1000 | Pass |
| 746 - 757 | 108.0 | 1000 | Pass |
| 869 - 894 | 51.3 | 1000 | Pass |
| 1930 - 1995 | 87.3 | 1000 | Pass |
| 2110 - 2155 | 86.4 | 1000 | Pass |



Uplink Restart Time Test Results

| Frequency Band (MHz) | Measured Time (S) | Limit (S) | Result |
|----------------------|-------------------|-----------|--------|
| 698 - 716 | shut off | ≥60 | Pass |
| 776 - 787 | shut off | ≥60 | Pass |
| 824 - 849 | shut off | ≥60 | Pass |
| 1710 - 1755 | shut off | ≥60 | Pass |
| 1850 - 1915 | shut off | ≥60 | Pass |

Downlink Restart Time Test Results

| Frequency Band (MHz) | Measured Time (S) | Limit (S) | Result |
|----------------------|-------------------|-----------|--------|
| 728 - 746 | shut off | ≥60 | Pass |
| 746 - 757 | shut off | ≥60 | Pass |
| 869 - 894 | shut off | ≥60 | Pass |
| 1930 - 1995 | shut off | ≥60 | Pass |
| 2110 - 2155 | shut off | ≥60 | Pass |

Uplink Restart Count Test Results

| Frequency Band (MHz) | Restarts | Limit | Result |
|----------------------|----------|-------|--------|
| 698 - 716 | shut off | ≤5 | Pass |
| 776 - 787 | shut off | ≤5 | Pass |
| 824 - 849 | shut off | ≤5 | Pass |
| 1710 - 1755 | shut off | ≤5 | Pass |
| 1850 - 1915 | shut off | ≤5 | Pass |


Downlink Restart Count Test Results

| Frequency Band (MHz) | Restarts | Limit | Result |
|----------------------|----------|-------|--------|
| 728 - 746 | shut off | ≤5 | Pass |
| 746 - 757 | shut off | ≤5 | Pass |
| 869 - 894 | shut off | ≤5 | Pass |
| 1930 - 1995 | shut off | ≤5 | Pass |
| 2110 - 2155 | shut off | ≤5 | Pass |




Uplink Detection Time Test Results

698 - 716 MHz Band




776 - 787 MHz Band






824 - 849 MHz Band




1710 - 1755 MHz Band






1850 - 1915 MHz Band




Uplink Restart Time Test Results

698 - 716 MHz Band






776 - 787 MHz Band




824 - 849 MHz Band






1710 - 1755 MHz Band




1850 - 1915 MHz Band






Uplink Restart Count Test Results

698 - 716 MHz Band




776 - 787 MHz Band






824 - 849 MHz Band




1710 - 1755 MHz Band






1850 - 1915 MHz Band




Downlink Detection Time Test Results

728 - 746 MHz Band






746 - 757 MHz Band




869 - 894 MHz Band






1930 - 1995 MHz Band




2110 - 2155 MHz Band






Downlink Restart Time Test Results

728 - 746 MHz Band




746 - 757 MHz Band






869 - 894 MHz Band




1930 - 1995 MHz Band






2110 - 2155 MHz Band




Downlink Restart Count Test Results

728 - 746 MHz Band






746 - 757 MHz Band




869 - 894 MHz Band






1930 - 1995 MHz Band



2110 - 2155 MHz Band





Radiated Spurious

Engineer: Mike Graffeo

Test Date: 11/21/14

Test Procedure

The EUT was tested in a semi-anechoic chamber with the turntable set 3m from the receiving antenna. A spectrum analyzer was used to verify that the EUT met the requirements for Radiated Emissions. The EUT was tested by rotating it 360 degrees with the antenna in both the vertical and horizontal orientation while raised from 1 to 4 meters to ensure that the signal levels were maximized. All cable and antenna correction factors were input into the spectrum analyzer ensuring an accurate measurement in ERP/EIRP with the resultant power in dBm. A signal generator was used to provide a CW signal centered in each operational uplink and downlink band. The EUT output was terminated into a 50 Ohm non-radiating load.


The following formula was used for calculating the limits:

$$\text{Radiated Spurious Emissions Limit} = P1 - (43 + 10\text{Log}(P2)) = -13\text{dBm}$$

P1 = power in dBm

P2 = power in Watts

Test Setup





Uplink Test Results

698 - 716 MHz Band 707 MHz Tuned Frequency

| Measured Frequency (MHz) | Measured Level (dBm) | Limit (dBm) | Result |
|--------------------------|----------------------|-------------|--------|
| 1414 | -56.18 | -13 | Pass |
| 2121 | -51.65 | -13 | Pass |
| 2828 | -45.26 | -13 | Pass |

776 - 787 MHz Band 781.5 MHz Tuned Frequency

| Measured Frequency (MHz) | Measured Level (dBm) | Limit (dBm) | Result |
|--------------------------|----------------------|-------------|--------|
| 1563 | -64.32 | -13 | Pass |
| 2344.5 | -62.44 | -13 | Pass |
| 3126 | -45.81 | -13 | Pass |

824 - 849 MHz Band 836.5 MHz Tuned Frequency

| Measured Frequency (MHz) | Measured Level (dBm) | Limit (dBm) | Result |
|--------------------------|----------------------|-------------|--------|
| 1673 | -66.69 | -13 | Pass |
| 2509.5 | -61.88 | -13 | Pass |
| 3346 | -43.84 | -13 | Pass |

1710 - 1755 MHz Band 1732.5 MHz Tuned Frequency

| Measured Frequency (MHz) | Measured Level (dBm) | Limit (dBm) | Result |
|--------------------------|----------------------|-------------|--------|
| 3465 | -61.44 | -13 | Pass |
| 5197.5 | -42.16 | -13 | Pass |
| 6930 | -46.21 | -13 | Pass |

1850 - 1915 MHz Band 1882.5 MHz Tuned Frequency

| Measured Frequency (MHz) | Measured Level (dBm) | Limit (dBm) | Result |
|--------------------------|----------------------|-------------|--------|
| 3765 | -46.73 | -13 | Pass |
| 5647.5 | -40.57 | -13 | Pass |
| 7530 | -29.65 | -13 | Pass |



Downlink Test Results

728 - 746 MHz Band 737 MHz Tuned Frequency

| Measured Frequency (MHz) | Measured Level (dBm) | Limit (dBm) | Result |
|--------------------------|----------------------|-------------|--------|
| 1474 | -70.08 | -13 | Pass |
| 2211 | -64.6 | -13 | Pass |
| 2948 | -56.77 | -13 | Pass |

746 - 757 MHz Band 751.5 MHz Tuned Frequency

| Measured Frequency (MHz) | Measured Level (dBm) | Limit (dBm) | Result |
|--------------------------|----------------------|-------------|--------|
| 1503 | -66.83 | -13 | Pass |
| 2254.5 | -61.71 | -13 | Pass |
| 3006 | -46.7 | -13 | Pass |

869 - 894 MHz Band 881.5 MHz Tuned Frequency

| Measured Frequency (MHz) | Measured Level (dBm) | Limit (dBm) | Result |
|--------------------------|----------------------|-------------|--------|
| 1763 | -61.07 | -13 | Pass |
| 2644.5 | -60.31 | -13 | Pass |
| 3526 | -42.28 | -13 | Pass |

1930 - 1995 MHz Band 1962.5 MHz Tuned Frequency

| Measured Frequency (MHz) | Measured Level (dBm) | Limit (dBm) | Result |
|--------------------------|----------------------|-------------|--------|
| 3925 | -44.59 | -13 | Pass |
| 5887.5 | -39.59 | -13 | Pass |
| 7850 | -27.61 | -13 | Pass |

2110 - 2155 MHz Band 2132.5 MHz Tuned Frequency

| Measured Frequency (MHz) | Measured Level (dBm) | Limit (dBm) | Result |
|--------------------------|----------------------|-------------|--------|
| 4265 | -37.94 | -13 | Pass |
| 6397.5 | -36.67 | -13 | Pass |
| 8530 | -29.36 | -13 | Pass |

No other emissions were detected. All emissions were lower than -13 dBm.
All emissions were system noise floor.



Test Equipment Utilized

| Description | Manufacturer | Model # | CT Asset # | Last Cal Date | Cal Due Date |
|-------------------------|-----------------|-------------|------------|---------------------|--------------|
| Horn Antenna, Amplified | ARA | DRG-118/A | i00271 | 5/8/14 | 5/8/16 |
| Bi-Log Antenna | Schaffner | CBL 6111D | i00349 | 10/8/13 | 10/8/15 |
| Humidity / Temp Meter | Newport | IBTHX-W-5 | i00282 | 3/24/14 | 3/24/15 |
| Voltmeter | Fluke | 75III | i00320 | 3/24/14 | 3/24/15 |
| EMI Analyzer | Agilent | E7405A | i00379 | 1/14/14 | 1/14/15 |
| Spectrum Analyzer * | Tektronix | RSA5126A | i00424 | 9/22/13 | 9/22/14 |
| Non-radiating load | Termaline | 8201 | i00334 | Verified on: 9/1/14 | |
| Signal Generator | Rohde & Schwarz | SMU200A | i00405 | 12/11/13 | 12/11/14 |
| RF Directional Coupler | Meca | CS06-1.500V | i00412 | Verified on: 9/1/14 | |

In addition to the above listed equipment standard RF connectors and cables were utilized in the testing of the described equipment. Prior to testing these components were tested to verify proper operation.

* Lab Manager has approved a 60 day extension on this piece of equipment

END OF TEST REPORT