

Mobile Station Coupling Losses (MSCL)

September 30, 2020
FCCID: PWO460065

The following formulas were used to calculate MSCL with a 2 m path loss and a 45 degree polarity mismatch between the inside antenna and the mobile device for EUT model 460065 signal booster:

$$\text{MSCL (dB)} = \text{Path Loss (dB)} + \text{Polarity Loss (dB)} - G_t - G_r$$


$$\text{Path Loss (dB)} = 20 \log(d) + 20 \log(f) - 27.55$$

f = frequency MHz

d = Distance from transmitter to receiver antenna (meters)

$$\text{Polarity Loss (dB)} = 20 \log\left(\frac{E_1}{E_2}\right)$$

$$\text{Polarity Loss} = 20 \log\left(\frac{E_1}{E_1 \sin(\tau)}\right), \quad \tau = 45^\circ$$



E₁ = Maximum possible magnitude of the Electric Field from Mobile Device

E₂ = Magnitude of the electric field from the Mobile Device with a 45° polarity mismatch

$$E_2 = E_1 \sin(\tau)$$

G_t = UE Transmitter Antenna Gain

G_r = Signal Booster Server Antenna Gain

Path Loss Evaluation

$$\text{Path Loss (dB)} = 20 \log(d) + 20 \log(f) - 27.55$$

f = frequency in MHz

d = Distance from transmitter to receiver antenna (meters)

Frequency Range (MHz)	f (MHz)	d (m)	Constant (dB)	Path Loss (dB)
698-716	707	2	27.55	35.4
776-787	781.5	2	27.55	36.3



WILSON ELECTRONICS, LLC
3301 E. Deseret Dr, St. George, UT 84790
T. 1 800 204 4104 F. 1 435 673 0899 E. info@weboost.com
www.weboost.com www.wilsonpro.com

Polarity Loss Evaluation

$$\text{Polarity Loss (dB)} = 20 \log\left(\frac{E_1}{E_2}\right)$$

$$\text{Polarity Loss (dB)} = 20 \log\left(\frac{E_1}{E_1 \sin(\tau)}\right), \quad \tau = 45^\circ$$

E_1 = Maximum possible magnitude of the Electric Field from Mobile Device

E_2 = Magnitude of the electric field from the Mobile Device with a 45° polarity mismatch

$$E_2 = E_1 \sin(\tau)$$

$$\text{Polarity Loss} = 20 \log\left(\frac{1}{\sin\left(\frac{\pi}{180}\right)}\right) = \mathbf{3.01 \ dB}$$

UE Transmitter Antenna Gain Evaluation

$$G_t = \text{UE Transmitter Antenna Gain} = \mathbf{0 \ dBi}$$

Signal Booster Server Antenna Gain Evaluation

Component	Type	Product Number	Gain (dBi) / Loss (dB)	
			B12 700 MHz	B13 700 MHz
Server Cable	N/A	N/A	0	0
Server Antenna	Omni	311236	2	2.2
		311159	2	1.9

Minimum MSCL Evaluation

Maximum antenna gain and minimum coax loss was selected to calculate “worst case” limit for MSCL

	B12 700 MHz	B13 700 MHz
Path Loss (dB)	35.4	36.3
Polarity Loss (dB)	3.01	3.01
UE Antenna Gain (dBi)	0	0
Server Antenna Gain (dBi)	2	2.2
Server Coax Loss (dB)	0	0
Minimum MSCL (dB)	36.41	37.11

END OF REPORT