



Test Report

Test Report No.:	KTI01E-F0936		
Registration No.:	99058		
Applicant:	GEOVISION INC.		
Applicant Address:	4F-1, No.298, Ruei-Guang Road, Nei-Hu, Taipei114 Taiwan, R.O.C.		
Product:	Capture Card		
FCC ID:	PWQGV-600	Model No.	GV-600
Receipt No.:	KTI20010816	Date of receipt:	Aug, 16, 2001
Date of Issue:	Aug, 23, 2001		
Testing location	Korea Technology Institute Co., Ltd. 51-19, Sanglim3-Ri, Docheok-Myeun, Gwangju-Shi, Gyeongki-Do, Korea		
Test Standards:	ANSI. C63.4 : 1992		
Rule Parts:	FCC Part 15, Subpart B		
Equipment Class:	JBP		
Test Result:	The above mentioned product has been tested and passed.		
Prepare by: J. H. Lee	Tested by: S. B. Kim/ Engineer	Approved by: G. C. Min/ President	
Signature Date	Signature Date	Signature	Date
Other Aspects :			
Abbreviations :	OK, Pass=passed Fail=failed N/A=not applicable		

- ♣ This test report is not permitted to copy partly without our permission.
- ♣ This test result is dependent on only equipment to be used.
- ♣ This test result is based on a single evaluation of one sample of the above mentioned.
- ♣ This test report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S Government.
- ♣ We certify this test report has been based on the measurement standards that is traceable to the national or international standards.



Contents

	Contents	2
	List of Tables	2
	List of Figures	2
	List of Photographs	3
1.	General	3
2.	Test Site	3
	2.1 Location	4
	2.2 List of Test and Measurement Instruments	4
	2.3 Test Data	4
	2.4 Test Environment	5
3.	Description of the tested samples	5
	3.1 Rating and Physical characteristics	5
	3.2 Submitted documents	6
4.	Measurement conditions	6
	4.1 Modes of operation	6
	4.2 Additional equipments	6
	4.3 Uncertainty	6
	4.4 Test Setup	7
5.	Emission Test	8
	5.1 Conducted Emissions	8
	5.2 Radiated Emissions	9
6.	Photographs of the Test Set-up	11
Annex1	Label	13
Annex2	Photographs of EUT	14~16

List of Tables

Table 1	List of test and measurement equipment	4
Table 2	Test Data. Radiated Emissions	10

List of Photographs

Photograph 1	Setup for Conducted Emissions	11
Photograph 2	Setup for Radiated Emissions	12



1. General

This equipment has been shown to be capable of compliance with the applicable technical standards and was tested in accordance with the measurement procedures as indicated in this report.

We attest to the accuracy of data. All measurements reported herein were performed by Korea Technology Institute Co., LTD. And were made under Chief Engineer's supervision. We assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

2. Test Site

Korea Technology Institute Co., LTD

2.1 Location

51-19, Sanglim3-Ri, Docheok-Myeun, Gwangju-Shi, Gyeongki-Do, Korea

The Test Site is in compliance with ANSI C63.4/1992 for measurement of radio Interference.



2.2 List of Test and Measurement Instruments

Table 1 : List of Test and Measurement Equipment

• Conducted Emissions

Kind of Equipment Type S/N Calibrated until
Spectrum Analyzer R3261C 61720427 11.2001
Field Strength Meter ESPC 832827/011 4.2002
LISN ESH3-Z5 8254601019 5.2002
LISN KNW407 8-1097-7 11.2001
Pulse limiter ESH3Z2 357.8810.52 11.2001
Conducted Cable N/A N/A 11.2001

• Radiated Emissions

Kind of Equipment Type S/N Calibrated until
Field Strength Meter ESPC 832827/011 11.2001
Spectrum Analyzer R3261C 61720427 11.2001
Pre Amplifier 8447D 2944A06874 11.2001



3. Description of the tested samples

The EUT is Capture Card.

3.1 Rating and Physical Characteristics

Interface

PCI connector, BNC×4, 5pin port×4, 40pin port, reset port×2

Resolution

640×480, 320×240, 160×120

Video Mode

YUV 4:2:2, RGB 24bit

Video Channel

Full 16 channels

Frame Rate

Max. 30FPS

Brightness

Adjustable

Hue

Adjustable

Saturation

Adjustable

Supplied Accessory

5pin connector, 40pin connector

3.2 Submitted Documents

User's Guide
Block Diagram



4. Measurement Conditions

Testing Input Voltage: AC 220V.

4.1 Modes of Operation

The EUT was in the following operation mode during all testing;

4.2 Additional Equipment

DEVICE TYPE

Manufacturer

M/N

S/N

FCC ID

PC
 COMPAQ COMPUTER CORPORATION
 Deskpro EXM
 6F13JC8JN619
 -

Monitor
 Samsung Electronics
 750S
 P223HVAR502035
 -

Keyboard
 COMPAQ COMPUTER CORPORATION
 KB-9963
 B26960GBUKKOWW
 -

Mouse
 logitech
 M-S48a
 None
 JNZ201213

Mouse
 SEJIN ELECTRON INC.
 SMB-400
 0CIM004047
 GJJS965M3

Printer
 Hewlett Packard
 C4569A
 SG78M1H0CF
 -


Camera1
 N/A
 N/A
 N/A
 -

Camera2
 N/A
 N/A
 N/A
 -

Camera3
 N/A
 N/A
 N/A



4.4 Test setup





5. EMISSION Test

5.1 Conducted Emissions

Result : **Pass**

The line-conducted facility is located inside a 2.3M x 3.5M x 5.5M shielded closure.

The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 605-05.

A 1m x 1.5m wooden table 80cm. High is placed 80cm away from the vertical wall and 1.5m away from the side wall of the shielded room. R&S Model ESH3-Z5(10kHz-30MHz)

50ohm/50 uH line-Impedance Stabilization Networks(LISN) are bonded to the shielded room.

The EUT is powered from the R&S LISN and the support equipment is powered from the Kyoritsu LISN. Power to the LISN are filtered by a high-current high-insertion loss shield enclosures power line filters(100dB 14kHz-1Ghz).

The purpose of the filter is to attenuate ambient signal interference and this filter is also bonded to the shielded enclosure.

All electrical cables are shielded by braided tinned copper zipper tubing with inner diameter of 1/2".

If the EUT is a DC-Powered device, power will be derived from the source power supply it normally will be powered from and this supply lines will be connected to the Kyoritsu LISN.

All interconnecting cables more than 1 meter were shortened by non-inductive bundling (serpentine fashion) to a 1-meter length.

Sufficient time for the EUT, Support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer to determine the frequency producing the maximum EME from the EUT.

The spectrum was scanned from 450kHz to 30MHz with 100sec. sweep time.

The frequency producing the maximum level was reexamined using EMI field Intensity meter (ESPC). The detector function was set to CISPR Q.P. mode.

The bandwidth of the receiver was set to 10kHz. The EUT, support equipment, and interconnecting each emission was maximized by: switching power lines; varying the mode of operation or resolution; clock or data exchange speed; if applicable; whichever determined the worst-case emission.

Photographs of the worst-case emission can be seen in photograph of conducted test.

Each EME reported was calibrated using self-calibrating mode.



Figure 1 : Spectral Diagram, LINE – PE