

Date: ESPOO 14.09.2005Page: 1 (18)Appendices –Number:
No. 1 / 1**51750**

Date of handing in: 05.09.2005

Tested by:



Timo Hietala, Test Engineer

Reviewed by:



Jyrki Leino, Market Access Manager

SORT OF EQUIPMENT:

Triple band (EGSM 900, GSM 1800/1900) mobile phone

MARKETING NAME:

Siemens CC75

TYPE:

Siemens CC75

MANUFACTURER:

Siemens

CLIENT:

Elcoteq Design Center Oy

ADDRESS:

Joensuunkatu 13, FI-24100 SALO

TELEPHONE:

+358 10 41 311

TEST LABORATORY:

Nemko Oy

FCC REG. NO.

91087 August 24, 2004

IC FILE NO.

IC 4627 July 2, 2003**SUMMARY:**

In regard to the performed tests the equipment under test fulfils the requirements defined in the test specifications, see page 2 for details

The test results are valid for the tested unit only. Without a written permission of Nemko Oy it is allowed to copy this report as a whole, but not partially.

Summary of performed tests and test results

<i>Section in CFR 47</i>	<i>Section in RSS-133</i>		<i>Result</i>
24.232, (b)	6.2	Radiated RF output	PASS
2.1049, (h)	5.6	99% occupied bandwidth	X
24.238 (a)	6.3	Band-edge compliance	PASS
24.238 (a), 2.1053	6.3	Spurious radiated emissions	PASS
24.235, 2.1055 (a)(1)(b)	7	Frequency stability, temperature variation	PASS
24.235, 2.1055 (d)(1)(2)	7	Frequency stability, voltage variation	PASS

Explanations:

PASS The EUT passed that particular test.

FAIL The EUT failed that particular test.

X The measurement was done, but there is no applicable performance criteria.

Contents

Summary of performed tests and test results	2
1. EUT and Accessory Information	4
1.1 EUT description	4
1.2 EUT and accessories.....	4
2. Standards and measurement methods.....	5
3. Test results.....	5
3.1 Radiated RF output power.....	5
3.1.1 Test method and limit	5
3.1.2 Limit	6
3.1.3 EUT operation mode.....	6
3.1.4 Test results	6
3.2 99% occupied bandwidth.....	7
3.2.1 Test method and limit	7
3.2.2 Limit	7
3.2.3 EUT operation mode.....	8
3.2.4 Test results	8
3.3 Band-edge compliance.....	9
3.3.1 Test method and limit	9
3.3.2 Limit	9
3.3.3 EUT operation mode.....	10
3.3.4 Test results	10
3.4 Spurious radiated emission	12
3.4.1 Test method and limit	12
3.4.2 Limit	12
3.4.3 EUT operation mode.....	13
3.4.4 Test results	13
3.5 Frequency stability, temperature variation.....	14
3.5.1 Test method and limit	14
3.5.2 Limit	14
3.5.3 EUT operation mode.....	15
3.5.4 Test results	15
3.6 Frequency stability, voltage variation	16
3.6.1 Test method and limit	16
3.6.2 Limit	16
3.6.3 EUT operation mode.....	16
3.6.4 Test results	16
4. List of test equipment.....	17
5. Photographs.....	18

1. EUT and Accessory Information

1.1 EUT description

The EUT is a triple band (EGSM-900, GSM-1800/1900) mobile phone, it is also a GPRS class 10 transceiver.

1.2 EUT and accessories

	<i>unit</i>	<i>type</i>	<i>S/N</i>
<i>EUT1</i>	Mobile phone	Siemens CC75	357182000003199 HW: PWB4 SW: 2.0
<i>EUT2</i>	Mobile phone	Siemens CC75	357182000001771 HW: PWB4 SW: 2.0
<i>EUT3</i>	Mobile phone	Siemens CC75	357182000000062 HW: PWB4 SW: 2.0
<i>Accessories</i>	Battery, EUT 1	V30145-K1310-X373	VAC5A050809
<i>Accessories</i>	Battery, EUT 3	V30145-K1310-X373	VAC5A050603
<i>Accessories</i>	Dummy Battery, EUT 2	Special made	--

2. Standards and measurement methods

The tests were performed in guidance of the CFR 47 part 24, part 2, ANSI/TIA/EIA-603-A and RSS-133 Issue 3 June 2005.

3. Test results


3.1 Radiated RF output power

The test was performed as a compliance test. The test parameters concerned were as follows:

<i>EUT</i>	EUT1
<i>Site name</i>	Nemko Oy / Perkaa
<i>Section in CFR 47</i>	§ 24.232 (b)
<i>Section in RSS-133</i>	6.2
<i>Date of testing</i>	13.09.2005
<i>Test equipment</i>	350, 42, 525, 89, 351, 545
<i>Test conditions</i>	22 °C, 40 % RH
<i>Test result</i>	PASS

3.1.1 Test method and limit

The test was performed inside an anechoic shielded room. For the duration of the test the EUT was placed on a non-conductive support 0.8 m high standing on the turntable. In the corner of the chamber there was a communication antenna, which was connected to the BS simulator located outside the room. The radiated power from the EUT was measured with an antenna fixed to an antenna tower. The measured signal was routed from the measuring antenna to the spectrum analyzer. The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.



- a) The maximum power level was searched at each frequency by rotating the turntable and adjusting the measuring antenna polarization. This level (P_{EUT}) was recorded. The measurements were performed the EUT at all three orthogonal planes
- b) The EUT was replaced with a substituting antenna.
- c) The substituting antenna was fed with the power (P_{Gen}) giving a convenient reading on the spectrum analyzer. That reading (P_{Subst}) on spectrum analyzer was recorded.

The formula below was used to calculate the EIRP of the EUT.

$$P_{EIRP[dBm]} = P_{Measured[dB]} - P_{Subst[dB]} - L_{Cable[dB]} + G_{Antenna[dBi]} + P_{Gen[dBm]}$$

Where

$P_{Measured[dBm]}$ measured power level from the EUT

$P_{Subst[dBm]}$ measured emission level from substitutive antenna

$L_{Cable[dB]}$ loss of the cable between substitutive antenna and signal generator

$G_{Antenna[dBi]}$ gain of the substitutive antenna

$P_{Gen[dBm]}$ signal generator power fed to the substitutive antenna

3.1.2 Limit

Power level	EIRP power (dBm)	EIRP power (W)
0	≤ 33	≤ 2

3.1.3 EUT operation mode

EUT operation mode	GSM 1900, TX ON, 1 time slot transmission, audio PRBS 2E9-1 modulation, GMSK modulation
EUT channel	512, 661, 810
EUT power level	0 (+ 30 dBm)

3.1.4 Test results

EUT Channel	$P_{Measured}$ [dBm]	P_{Gen} [dBm]	P_{Subst} [dBm]	L_{Cable} [dBm]	$G_{Antenna}$ [dBd]	EIRP [dBm]	EIRP [W]
512	-7,1	0	-33,2	1,8	6,3	30,6	1,147
661	-7,8	0	-33,2	1,8	6,4	30,0	1,006
810	-8,9	0	-33,1	1,8	6,4	28,9	0,768


3.2 99% occupied bandwidth

The test was performed as a compliance test. The test parameters concerned were as follows:

<i>EUT</i>	EUT2
<i>Site name</i>	Nemko Oy / Perkkaa
<i>Section in CFR 47</i>	§ 2.1049, (h)
<i>Section in RSS-133</i>	5.6
<i>Date of testing</i>	06.09.2005
<i>Test equipment</i>	42, 519, 545, X2
<i>Test conditions</i>	22 °C, 40 % RH
<i>Test result</i>	PASS

3.2.1 Test method and limit

The test was performed inside a shielded room. The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.



3.2.2 Limit

<i>Power level</i>	<i>99% occupied bandwidth</i>
0	--


3.2.3 EUT operation mode

EUT operation mode	GSM 1900, TX ON, 1 time slot transmission, audio PRBS 2E9-1 modulation, GMSK modulation
EUT channel	661
EUT power level	0 (+ 30 dBm)

3.2.4 Test results

Channel	99% occupied bandwidth kHz
661	242,02

The 99% occupied bandwidth was calculated from the trace data of the spectrum analyzer.



Spectrum analyzer plot channel 661, GMSK modulation


3.3 Band-edge compliance

The test was performed as a compliance test. The test parameters concerned were as follows:

<i>EUT</i>	EUT2
<i>Site name</i>	Nemko Oy / Perkkaa
<i>Section in CFR 47</i>	§ 24.238 (a)
<i>Section in RSS-133</i>	6.3
<i>Date of testing</i>	06.09.2005
<i>Test equipment</i>	42, 519, 545,X2
<i>Test conditions</i>	22 °C, 40 % RH
<i>Test result</i>	PASS

3.3.1 Test method and limit

The test was performed inside a shielded room. The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.



3.3.2 Limit

<i>Frequency MHz</i>	<i>Band-edge compliance dBm</i>
< 1850 or 1910 <	≤ -13


3.3.3 EUT operation mode

<i>EUT operation mode</i>	<i>GSM 1900, TX ON, 1 time slot transmission, audio PRBS 2E9-1 modulation, GMSK modulation</i>
<i>EUT channel</i>	512, 810
<i>EUT power level</i>	0 (+ 30 dBm)

3.3.4 Test results


The line in the spectrum analyzer plot is the -13 dBm limit line. The band edge is at the middle of the screen. The results were corrected with combined attenuation of the cables, attenuator and power divider set as "offset" in the spectrum analyzer.

<i>Channel</i>	<i>Band-edge compliance MHz / dBm</i>	<i>Limit Frequency MHz / dBm</i>
512	1849,980 / -18,1	< 1850 or 1910 < / ≤ -13



Spectrum analyzer plot channel 512, GMSK modulation

Channel	Band-edge compliance MHz / dBm	Limit Frequency MHz / dBm
810	1910,026 / -17,7	< 1850 or 1910 < / ≤ -13



Spectrum analyzer plot channel 810, GMSK modulation

3.4 Spurious radiated emission

<i>EUT</i>	EUT3
<i>Site name</i>	Nemko Oy / Perkkaa
<i>Section in CFR 47</i>	§ 24.238 (a), § 2.1053
<i>Section in RSS-133</i>	6.3
<i>Date of testing</i>	05.09.2005
<i>Test equipment</i>	42, 525, 564, 184, 542, 545, 550, 552,350
<i>Test conditions</i>	22 °C, 40 % RH
<i>Test Result</i>	PASS

3.4.1 Test method and limit

The test was performed inside an anechoic shielded room. For the duration of the test the EUT was placed on a non-conductive support 0.8 m high standing on the turntable. In the corner of the chamber there was a communication antenna, which was connected to the BS simulator located outside the room. The radiated power from the EUT was measured with an antenna fixed to a antenna tower. The measured signal was routed from the measuring antenna to the spectrum analyzer. The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.

a) The maximum power level was searched at each frequency by rotating the turntable and adjusting the measuring antenna polarization. This level (P_{EUT}) was recorded. The measurements were performed the EUT at all three orthogonal planes

b) The EUT was replaced with a substituting antenna.

c) The substituting antenna was fed with the power (P_{Gen}) giving a convenient reading on the spectrum analyzer. That reading (P_{Subst}) on spectrum analyzer was recorded.

3.4.2 Limit

<i>Frequency MHz</i>	<i>Level dBm</i>
30 - 19100	- 13

3.4.3 EUT operation mode

<i>EUT operation mode</i>	<i>GSM 1900, TX ON, 1 time slot transmission, audio PRBS 2E9-1 modulation, GMSK modulation</i>
<i>EUT channel</i>	661
<i>EUT power level</i>	0 (+ 30 dBm)

3.4.4 Test results

The formula below was used to calculate the EIRP of the spurious emissions. If there were no emissions closer than 20 dB below the limit line, then the emission levels were measured at the transmitter's harmonics.

$$P_{Emission[dbm]} = P_{Measured[dB]} - P_{Subst[dB]} - L_{Cable[dB]} + G_{Antenna[dBi]} + P_{Gen[dBm]}$$

Where

$P_{Measured[dBm]}$ measured emission level

$P_{Subst[dBm]}$ measured emission level from substitutive antenna

$L_{Cable[dB]}$ loss of the cable between substitutive antenna and signal generator

$G_{Antenna[dBi]}$ gain of the substitutive antenna

$P_{Gen[dBm]}$ signal generator power fed to the substitutive antenna

Calculation example:

$$P_{3760[dbm]} = -49,0_{Measured[dB]} - (-34,2)_{Subst[dB]} - 2,6_{Cable[dB]} + 9,5_{Antenna[dBi]} + (-30)_{Gen[dBm]}$$

$$= -37,9_{dBm}$$

TX GSM 1900 (ch 661)

<i>Frequency MHz</i>	<i>Result dBm</i>	<i>Limit dBm</i>	<i>Margin dB</i>
3760,0	-37,9	-13,0	24,9
5640,0	-40,9	-13,0	27,9
7520,0	-33,1	-13,0	20,1
9400,0	-35,4	-13,0	22,4
11280,0	-39,6	-13,0	26,6

3.5 Frequency stability, temperature variation


The test was performed as a compliance test. The test parameters concerned were as follows:

<i>EUT</i>	EUT2
<i>Site name</i>	Nemko Oy / Perkkää
<i>Section in CFR 47</i>	24.235, 2.1055 (a)(1)(b)
<i>Section in RSS-133</i>	7
<i>Date of testing</i>	6 and 7.09.2005
<i>Test equipment</i>	545, 157
<i>Test conditions</i>	22 °C, 40 % RH
<i>Test result</i>	PASS

3.5.1 Test method and limit

For the duration of the test the EUT was placed inside a temperature chamber. The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.

- The climate chamber temperature was set to the minimum value and the temperature was allowed to stabilize.
- The EUT was placed in the chamber
- The EUT was set in idle mode for 60 minutes.
- The EUT was set to transmit.
- The transmit frequency error was measured immediately
- The steps c - e were repeated for each temperature



3.5.2 Limit

<i>Frequency error ppm</i>
± 2,5

3.5.3 EUT operation mode

<i>EUT operation mode</i>	<i>GSM 1900, TX ON, 1 time slot transmission, audio PRBS 2E9-1 modulation, GMSK modulation</i>
<i>EUT channel</i>	661
<i>EUT power level</i>	0 (+ 30 dBm)

3.5.4 Test results

<i>Temperature [°C]</i>	<i>Deviation [Hz]</i>	<i>Deviation [ppm]</i>
-30	101	0,054
-20	96	0,051
-10	86	0,046
0	74	0,039
10	64	0,034
20	64	0,034
30	62	0,033
40	62	0,033
50	61	0,032

Frequency deviation, temperature variation

3.6 Frequency stability, voltage variation


The test was performed as a compliance test. The test parameters concerned were as follows:

<i>EUT</i>	EUT2
<i>Site name</i>	Nemko Oy / Perkkaa
<i>Section in CFR 47</i>	24.235, 2.1055 (d)(1)(2)
<i>Section in RSS-133</i>	7
<i>Date of testing</i>	06.09.2005
<i>Test equipment</i>	545, 316
<i>Test conditions</i>	22 °C, 40 % RH
<i>Test result</i>	PASS

3.6.1 Test method and limit

The BS simulator was used to set the TX channel and power level and modulate the TX signal with different bit patterns.

The EUT battery was replaced with an adjustable power supply. The frequency stability was measured at maximum voltage, at nominal voltage and at battery cut-off point.



3.6.2 Limit

<i>Frequency error</i>	<i>ppm</i>
± 2,5	

3.6.3 EUT operation mode

<i>EUT operation mode</i>	GSM 1900, TX ON, 1 time slot transmission, audio PRBS 2E9-1 modulation, GMSK modulation
<i>EUT channel</i>	661
<i>EUT power level</i>	0 (+ 30 dBm)

3.6.4 Test results

<i>Battery level</i>	<i>Voltage [V]</i>	<i>Deviation [Hz]</i>	<i>Deviation [ppm]</i>
<i>Max.</i>	4,1	64	0,034
<i>Nominal</i>	3,7	63	0,034
<i>Cut off-point</i>	3,2	52	0,028

Frequency deviation, voltage variation

4. List of test equipment

Each active test equipment is calibrated once a year, antennas every 18 months and other passive equipment every 24 months.

Nr.	Equipment	Type	Manufacturer	Serial number
42	Spectrum analyzer	8566B	Hewlett Packard	2637A04102
76	Power supply	B32-30R	Oltronix	537
316	Power supply	HP 6032A	Hewlett Packard	2517A-00654
157	Temp. test chamber	VMT 04/240	Vötsch	31884
184	Temp. & humidity meter	H MI 32	Vaisala	63837
89	Antenna	3147	EMCO	9202-1078
319	Antenna	CBL6112	Chase	2018
348	Shielded room	RFSD-100	Euroshield Oy	1320
350	Semianechoic shielded room	RFD-F-100	Euroshield Oy	1327
351	RF generator	SMT 06	Rohde & Schwarz	845715/001
519	RF High-Power Attenuator	765-20	Narda	
525	Double-Ridged Horn	3115	Emco	6691
542	Double-Ridged Horn	3115	Emco	00023905
544	RF-amplifier	ZFL-2000VH2	Mini-Circuits	D01080
564	RF-amplifier	CA018-4010	CIAO Wireless	101
545	GSM MS Test System	CMU	Rohde & Schwarz	836536/049
552	Highpass Filter	WHK2.3/18G-10SS	Wainwright Instruments	1
550	Notch Filter	WRCD1800/2000-0.2/40-5SSSD	Wainwright Instruments	1
X1	RF-Generator	8341B	Hewlett Packard	2802A01090
X2	Power splitter	1870A	Weinschel	1798

5. Photographs

See "51750_test_setup_photographs"