

ALS BETRIEBSGEHEIMNIS ANVERTRAUT, ALLE RECHTE VORBEHALTEN. PROPRIETARY DATA, COMPANY CONFIDENTIAL. ALL RIGHTS RESERVED.

White label with black lettering

1) 2) 11) 12) 3)

SIEMENS A65 Made xx XXXXXX

S30880-SXXXXX-XXXXX-1 YY

5) 6) **CE 0682** FCC ID: P W X A 65 4)

IC: 267 E-A 65 13)

XXXXXXXX SSSSSS C 7)

8)

Barcode:

Typ 128, table C and B

Characteristic:

IMEI-No. has 15 digits
Digit 1-14 is generated as Barcode with table C.
Digit 15 is printed with table B.

Ink ribbon: TTR-Band Ricoh 110-A

Font: Title blocks concentric

1) Corporate logo: 1.5 SN 86324
2) Product name: Internal font D, size 4
3) Made xx XXXXXX: Internal font B, size 3 / Depending on production location
4) Code of date: Internal font D, size 4
e.g. F3 — March
L — 1995
5) Code number: Internal font D, size 3
6) CE- identification: Height: 5 mm

7) Barcode IMEI-No.: Code: 128 Size: 2 Ratio: 3.0 Height: 3 mm
8) IMEI-No. (plain writing): Internal font D, size 4, space between TAC, FAC, serial no. and 15.digit
10) Document for IMEI-No. allocation: DIS 59809
Valid is the highest level in the system
Corresponding to the number of the transceiver unit part list
For production in Germany
For production out of Germany – for details please see lettering plan of retail box label
font: B3

11) Code number:
12) "Made in Germany"
"Made in XXXXXX"
13) Canada IC and US FCC

CHECK DIGIT
15. digit

Current serial number (6 digits)

Assigned by PICS 10)

Final-Assembly Code: 10)
FAC

Typ-Approval Code: 10)
TAC

			Date	04.03.05	Approval label A65-B6E/IMEI-Label/ STD Z30880-Z9999-Z85-* LETTERING PLAN	Page 1 From 1
			Name	Li Gang		
				MP PD LPD BJ		
1		04.03.05	Li G			
Version		Date	Token	SIEMENS AG	DIS 142987	

A24850-V1-A4-2

VORSTD.DOC

Siemens Communications, Inc.



A65 IMEI LABEL and LABEL LOCATION