
Appendix for the Report

Dosimetric Assessment of the Siemens AX75 (FCC ID: PWX-AX75)

According to the FCC Requirements

SAR Distribution Plots

May 20, 2005
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
Siemens Information & Communication Mobile LLC
16475 West Bernado Drive, Suite 400
CA 92127 San Diego

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written
approval of the testing laboratory.

Table of Contents

1	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD, WITHOUT CAMERA.....	3
2	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD, WITH CAMERA.	7
3	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WORN (GAP = 15 MM)	11
4	SAR Z-AXIS SCANS (VALIDATION)	14
5	SAR Z-AXIS SCANS (MEASUREMENTS).....	15

1 SAR Distribution Plots, PCS 1900 head, without camera

Test Laboratory: IMST GmbH, DASY Yellow (II); File Name: [090yplm_1.da4](#)

DUT: Siemens; Type: AX75 ; Serial: 004400009038090

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.4$ mho/m; $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn631; Calibrated: 23.07.2004

- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.342 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm; Reference

Value = 15.5 V/m; Power Drift = 0.198 dB

Peak SAR (extrapolated) = 0.504 W/kg

SAR(1 g) = 0.326 mW/g; SAR(10 g) = 0.194 mW/g

Maximum value of SAR (measured) = 0.369 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm; Reference

Value = 15.5 V/m; Power Drift = 0.198 dB

Peak SAR (extrapolated) = 0.239 W/kg

SAR(1 g) = 0.203 mW/g; SAR(10 g) = 0.136 mW/g

Maximum value of SAR (measured) = 0.220 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 2: Measurement grid: dx=5mm, dy=5mm, dz=5mm; Reference

Value = 15.5 V/m; Power Drift = 0.198 dB

Peak SAR (extrapolated) = 0.426 W/kg

SAR(1 g) = 0.288 mW/g; SAR(10 g) = 0.168 mW/g

Maximum value of SAR (measured) = 0.322 mW/g




Fig. 1: SAR distribution for PCS 1900, channel 661, cheek position, left side of head (05.13.2005; Ambient Temperature: 21.1° C; Liquid Temperature: 20.6° C).

Test Laboratory: IMST GmbH, DASY Yellow (II); **File Name:** [090yplm 2.da4](#)

DUT: Siemens; **Type:** AX75 ; **Serial:** 004400009038090

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.4$ mho/m; $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2004
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.444 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.1 V/m; Power Drift = 0.011 dB

Peak SAR (extrapolated) = 0.588 W/kg

SAR(1 g) = 0.415 mW/g; SAR(10 g) = 0.234 mW/g

Maximum value of SAR (measured) = 0.467 mW/g




Fig. 2: SAR distribution for PCS 1900, channel 661, tilted position, left side of head (05.13.2005; Ambient Temperature: 21.1° C; Liquid Temperature: 20.6° C).

Test Laboratory: IMST GmbH, DASY Yellow (II); **File Name:** [090yprm_1.da4](#)

DUT: Siemens; **Type:** AX75 ; **Serial:** 004400009038090

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.4$ mho/m; $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn631; Calibrated: 23.07.2004

- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.267 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.5 V/m; Power Drift = 0.067 dB

Peak SAR (extrapolated) = 0.404 W/kg

SAR(1 g) = 0.261 mW/g; SAR(10 g) = 0.175 mW/g

Maximum value of SAR (measured) = 0.286 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.5 V/m; Power Drift = 0.067 dB

Peak SAR (extrapolated) = 0.376 W/kg

SAR(1 g) = 0.242 mW/g; SAR(10 g) = 0.147 mW/g

Maximum value of SAR (measured) = 0.272 mW/g




Fig. 3: SAR distribution for PCS 1900, channel 661, cheek position, right side of head (05.13.2005; Ambient Temperature: 21.1° C; Liquid Temperature: 20.6° C).

Test Laboratory: IMST GmbH, DASY Yellow (II); **File Name:** [090yprm_2.da4](#)

DUT: Siemens; **Type:** AX75 ; **Serial:** 004400009038090

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.4$ mho/m; $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn631; Calibrated: 23.07.2004

- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.373 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.0 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.580 W/kg

SAR(1 g) = 0.382 mW/g; SAR(10 g) = 0.225 mW/g

Maximum value of SAR (measured) = 0.425 mW/g




Fig. 4: SAR distribution for PCS 1900, channel 661, tilted position, right side of head (05.13.2005; Ambient Temperature: 21.2° C; Liquid Temperature: 20.6° C).

2 SAR Distribution Plots, PCS 1900 head, with camera.

Test Laboratory: IMST GmbH, DASY Yellow (II); File Name: [090yplm_1_cam.da4](#)

DUT: Siemens; Type: AX75 ; Serial: 004400009038090

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.4$ mho/m; $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn631; Calibrated: 23.07.2004

- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Cheek Left/Area Scan (6x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.292 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.9 V/m; Power Drift = 0.064 dB

Peak SAR (extrapolated) = 1.17 W/kg

SAR(1 g) = 0.313 mW/g; SAR(10 g) = 0.165 mW/g

Maximum value of SAR (measured) = 0.359 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.9 V/m; Power Drift = 0.064 dB

Peak SAR (extrapolated) = 0.516 W/kg

SAR(1 g) = 0.313 mW/g; SAR(10 g) = 0.182 mW/g

Maximum value of SAR (measured) = 0.350 mW/g




Fig. 5: SAR distribution for PCS 1900, channel 661, cheek position, left side of head (05.13.2005; Ambient Temperature: 21.3° C; Liquid Temperature: 20.6° C).

Test Laboratory: IMST GmbH, DASY Yellow (II); **File Name:** [090yplm_2_cam.da4](#)

DUT: Siemens; **Type:** AX75 ; **Serial:** 004400009038090

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.4$ mho/m; $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2004
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Left/Area Scan (6x15x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.354 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.9 V/m; Power Drift = 0.101 dB

Peak SAR (extrapolated) = 0.486 W/kg

SAR(1 g) = 0.325 mW/g; SAR(10 g) = 0.182 mW/g

Maximum value of SAR (measured) = 0.367 mW/g




Fig. 6: SAR distribution for PCS 1900, channel 661, tilted position, left side of head (05.13.2005; Ambient Temperature: 21.3° C; Liquid Temperature: 20.7° C).

Test Laboratory: IMST GmbH, DASY Yellow (II); **File Name:** [090yprm_1_cam.da4](#)

DUT: Siemens; **Type:** AX75 ; **Serial:** 004400009038090

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.4$ mho/m; $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn631; Calibrated: 23.07.2004

- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Cheek Right/Area Scan (6x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.281 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.3 V/m; Power Drift = 0.054 dB

Peak SAR (extrapolated) = 0.477 W/kg

SAR(1 g) = 0.311 mW/g; SAR(10 g) = 0.180 mW/g

Maximum value of SAR (measured) = 0.353 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.3 V/m; Power Drift = 0.054 dB

Peak SAR (extrapolated) = 0.329 W/kg

SAR(1 g) = 0.207 mW/g; SAR(10 g) = 0.130 mW/g

Maximum value of SAR (measured) = 0.231 mW/g




Fig. 7: SAR distribution for PCS 1900, channel 661, cheek position, right side of head (05.13.2005; Ambient Temperature: 21.3° C; Liquid Temperature: 20.7° C).

Test Laboratory: IMST GmbH, DASY Yellow (II); **File Name:** [090yprm 2 cam.da4](#)

DUT: Siemens; **Type:** AX75 ; **Serial:** 004400009038090

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.4$ mho/m; $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2004
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Right/Area Scan (6x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.257 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.8 V/m; Power Drift = 0.198 dB

Peak SAR (extrapolated) = 0.459 W/kg

SAR(1 g) = 0.275 mW/g; SAR(10 g) = 0.147 mW/g

Maximum value of SAR (measured) = 0.318 mW/g




Fig. 8: SAR distribution for PCS 1900, channel 661, tilted position, right side of head (05.13.2005; Ambient Temperature: 21.1° C; Liquid Temperature: 20.7° C).

3 SAR Distribution Plots, PCS 1900 Body worn (gap = 15 mm)

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [090bphm_1_15mm.da4](#)

DUT: Siemens; Type: AX75 ; Serial: 004400009038090

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.58$ mho/m; $\epsilon_r = 55$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.52, 4.52, 4.52); Calibrated: 13.01.2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 17.03.2005

- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.271 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.3 V/m; Power Drift = 0.020 dB

Peak SAR (extrapolated) = 0.412 W/kg

SAR(1 g) = 0.275 mW/g; SAR(10 g) = 0.175 mW/g

Maximum value of SAR (measured) = 0.296 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.3 V/m; Power Drift = 0.020 dB

Peak SAR (extrapolated) = 0.362 W/kg

SAR(1 g) = 0.220 mW/g; SAR(10 g) = 0.131 mW/g

Maximum value of SAR (measured) = 0.242 mW/g




Fig. 9: SAR distribution for PCS 1900, channel 661, antenna towards the phantom, GSM without accessory, (05.20.2005; Ambient Temperature: 21.3° C; Liquid Temperature: 20.7° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [090bphm 2 15mm.da4](#)

DUT: Siemens; **Type:** AX75 ; **Serial:** 004400009038090

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.58$ mho/m; $\epsilon_r = 55$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.52, 4.52, 4.52); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.248 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.4 V/m; Power Drift = 0.044 dB

Peak SAR (extrapolated) = 0.382 W/kg

SAR(1 g) = 0.256 mW/g; SAR(10 g) = 0.162 mW/g

Maximum value of SAR (measured) = 0.276 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.4 V/m; Power Drift = 0.044 dB

Peak SAR (extrapolated) = 0.366 W/kg

SAR(1 g) = 0.223 mW/g; SAR(10 g) = 0.133 mW/g

Maximum value of SAR (measured) = 0.246 mW/g




Fig. 10: SAR distribution for PCS 1900, channel 661, antenna towards the phantom, GSM with headset, (05.20.2005; Ambient Temperature: 21.4° C; Liquid Temperature: 20.7° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [090bphm 3 15mm.da4](#)

DUT: Siemens; **Type:** AX75 ; **Serial:** 004400009038090

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.58$ mho/m; $\epsilon_r = 55$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.52, 4.52, 4.52); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.236 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.2 V/m; Power Drift = 0.036 dB

Peak SAR (extrapolated) = 0.409 W/kg

SAR(1 g) = 0.249 mW/g; SAR(10 g) = 0.151 mW/g

Maximum value of SAR (measured) = 0.274 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.2 V/m; Power Drift = 0.036 dB

Peak SAR (extrapolated) = 0.272 W/kg

SAR(1 g) = 0.181 mW/g; SAR(10 g) = 0.117 mW/g

Maximum value of SAR (measured) = 0.194 mW/g




Fig. 11: SAR distribution for PCS 1900, channel 661, antenna towards the phantom, GSM with data cable, (05.20.2005; Ambient Temperature: 21.4° C; Liquid Temperature: 20.6° C).

4 SAR z-axis scans (Validation)




Fig. 12: SAR versus liquid depth, 1900 MHz, head (05.13.2005; Ambient Temperature: 21.1° C; Liquid Temperature : 20.6° C).




Fig. 13: SAR versus liquid depth, 1900 MHz, body (05.20.2005; Ambient Temperature: 21.3° C; Liquid Temperature : 20.7° C).

5 SAR z-axis scans (Measurements)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 14: SAR versus liquid depth, head: PCS 1900, channel 661, tilted position, left side of head without flash, with headset (05.13.2005, Ambient Temperature: 21.1 °C; Liquid Temperature : 20.6° C).




Fig. 15: SAR versus liquid depth, body: PCS 1900, channel 661, antenna towards the phantom, GSM without accessory, (05.20.2005; Ambient Temperature: 21.3 °C; Liquid Temperature : 20.7° C).