
Appendix for the Report

Dosimetric Assessment of the Siemens C60 (FCC ID: PWX-C60) According to the FCC Requirements

SAR Distribution Plots

July 30, 2003
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
Siemens Information & Communication Mobile LLC
16475 West Bernado Drive, Suite 400
San Diego CA 92127

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written
approval of the testing laboratory.

Table of Contents

1	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD WITHOUT QUICKPIC CAMERA.....	3
2	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD WITH QUICKPIC CAMERA	7
3	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WITH HEADSET.....	11
4	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WITH DATACABLE.....	12
5	SAR DISTRIBUTION PLOTS, PCS 1900 BODY, C60.....	13
6	SAR Z-AXIS SCANS (VALIDATION).....	14
7	SAR Z-AXIS SCANS (MEASUREMENTS).....	16

1 SAR Distribution Plots, PCS 1900 Head without QuickPic Camera

Test Laboratory: IMST; File Name: [c60plm_1.da4](#)

DUT: Siemens; Type: C60; Serial: 004999002488244

Program: Measurement

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: Head 1900 MHz ($\sigma = 1.39$ mho/m, $\epsilon_r = 38.9$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.2, 5.2, 5.2); Calibrated: 21.03.2003
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.05.2003
- Phantom: SAM TP:1176; Type: SAM 4.0; Serial: 1176
- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 115

cheek left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 15.2 V/m

Power Drift = 0.06 dB

Maximum value of SAR = 0.304 mW/g

cheek left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.454 W/kg

SAR(1 g) = 0.307 mW/g; SAR(10 g) = 0.189 mW/g

Reference Value = 15.2 V/m

Power Drift = 0.06 dB

Maximum value of SAR = 0.333 mW/g




Fig. 1: SAR distribution for PCS 1900, channel 661, cheek position, left side of head. (28.07.2003; Liquid Temperature: 20.9° C; Ambient Temperature : 21.6° C).

Test Laboratory: IMST; File Name: [c60plm_2.da4](#)

DUT: Siemens; Type: C60; Serial: 004999002488244

Program: Measurement

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: Head 1900 MHz ($\sigma = 1.39$ mho/m, $\epsilon_r = 38.9$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.2, 5.2, 5.2); Calibrated: 21.03.2003

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 05.05.2003

- Phantom: SAM TP:1176; Type: SAM 4.0; Serial: 1176

- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 115

tilted left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 15.2 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.295 mW/g

tilted left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.408 W/kg

SAR(1 g) = 0.282 mW/g; SAR(10 g) = 0.172 mW/g

Reference Value = 15.2 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.308 mW/g




Fig. 2: SAR distribution for PCS 1900, channel 661, tilted position, left side of head. (28.07.2003; Liquid Temperature: 20.9° C; Ambient Temperature : 21.6°C).

Test Laboratory: IMST; File Name: [c60prm_1.da4](#)

DUT: Siemens; Type: C60; Serial: 004999002488244

Program: Measurement

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: Head 1900 MHz ($\sigma = 1.39$ mho/m, $\epsilon_r = 38.9$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.2, 5.2, 5.2); Calibrated: 21.03.2003

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 05.05.2003

- Phantom: SAM TP:1176; Type: SAM 4.0; Serial: 1176

- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 115

cheek right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 15.4 V/m

Power Drift = 0.04 dB

Maximum value of SAR = 0.435 mW/g

cheek right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.708 W/kg

SAR(1 g) = 0.448 mW/g; SAR(10 g) = 0.26 mW/g

Reference Value = 15.4 V/m

Power Drift = 0.04 dB

Maximum value of SAR = 0.492 mW/g




Fig. 3: SAR distribution for PCS 1900, channel 661, cheek position, right side of head. (28.07.2003; Liquid Temperature: 20.9° C; Ambient Temperature : 21.7 C).

Test Laboratory: IMST; File Name: [c60prm_2.da4](#)

DUT: Siemens; Type: C60; Serial: 004999002488244

Program: Measurement

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: Head 1900 MHz ($\sigma = 1.39$ mho/m, $\epsilon_r = 38.9$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.2, 5.2, 5.2); Calibrated: 21.03.2003

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 05.05.2003

- Phantom: SAM TP:1176; Type: SAM 4.0; Serial: 1176

- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 115

tilted right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 14.5 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.361 mW/g

tilted right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.583 W/kg

SAR(1 g) = 0.358 mW/g; SAR(10 g) = 0.208 mW/g

Reference Value = 14.5 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.388 mW/g




Fig. 4: SAR distribution for PCS 1900, channel 661, tilted position, right side of head. (28.07.2003; Liquid Temperature: 20.9° C; Ambient Temperature : 21.7 C).

2 SAR Distribution Plots, PCS 1900 Head with QuickPic Camera

Test Laboratory: IMST; File Name: [c6qplm_1.da4](#)

DUT: Siemens; Type: C60 QuickPic; Serial: 004999002488244

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: Head 1900 MHz ($\sigma = 1.39$ mho/m, $\epsilon_r = 38.9$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.2, 5.2, 5.2); Calibrated: 21.03.2003

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 05.05.2003

- Phantom: SAM TP:1176; Type: SAM 4.0; Serial: 1176

- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 115

cheek left/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 12.7 V/m

Power Drift = 0.2 dB

Maximum value of SAR = 0.237 mW/g

cheek left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.352 W/kg

SAR(1 g) = 0.238 mW/g; SAR(10 g) = 0.147 mW/g

Reference Value = 12.7 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.254 mW/g

cheek left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.241 W/kg

SAR(1 g) = 0.166 mW/g; SAR(10 g) = 0.101 mW/g

Reference Value = 12.7 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.185 mW/g




Fig. 5: SAR distribution for PCS 1900, channel 661, cheek position, left side of head. (28.07.2003; Liquid Temperature: 20.9° C; Ambient Temperature : 22.2° C).

Test Laboratory: IMST; File Name: [c6qplm_2.da4](#)

DUT: Siemens; Type: C60 QuickPic; Serial: 004999002488244

Program: Measurement

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: Head 1900 MHz ($\sigma = 1.39$ mho/m, $\epsilon_r = 38.9$, $\rho = 1000$ kg/m³)

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.2, 5.2, 5.2); Calibrated: 21.03.2003

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 05.05.2003

- Phantom: SAM TP:1176; Type: SAM 4.0; Serial: 1176

- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 115

tilted left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 12.3 V/m

Power Drift = 0.03 dB

Maximum value of SAR = 0.23 mW/g

tilted left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.376 W/kg

SAR(1 g) = 0.233 mW/g; SAR(10 g) = 0.138 mW/g

Reference Value = 12.3 V/m

Power Drift = 0.03 dB

Maximum value of SAR = 0.251 mW/g




Fig. 6: SAR distribution for PCS 1900, channel 661, tilted position, left side of head. (28.07.2003; Liquid Temperature: 20.9° C; Ambient Temperature : 22.2 C).

Test Laboratory: IMST; File Name: [c6qprm_1.da4](#)

DUT: Siemens; Type: C60 QuickPic; Serial: 004999002488244

Program: Measurement

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: Head 1900 MHz ($\sigma = 1.39$ mho/m, $\epsilon_r = 38.9$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.2, 5.2, 5.2); Calibrated: 21.03.2003

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 05.05.2003

- Phantom: SAM TP:1176; Type: SAM 4.0; Serial: 1176

- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 115

cheek right/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 11.4 V/m

Power Drift = 0.09 dB

Maximum value of SAR = 0.304 mW/g

cheek right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.606 W/kg

SAR(1 g) = 0.339 mW/g; SAR(10 g) = 0.194 mW/g

Reference Value = 11.4 V/m

Power Drift = 0.09 dB

Maximum value of SAR = 0.355 mW/g




Fig. 7: SAR distribution for PCS 1900, channel 661, cheek position, right side of head. (28.07.2003; Liquid Temperature: 22.2° C; Ambient Temperature : 20.9 C).

Test Laboratory: IMST; File Name: [c6qprm_2.da4](#)

DUT: Siemens; Type: C60 QuickPic; Serial: 004999002488244

Program: Measurement

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: Head 1900 MHz ($\sigma = 1.39$ mho/m, $\epsilon_r = 38.9$, $\rho = 1000$ kg/m³)

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(5.2, 5.2, 5.2); Calibrated: 21.03.2003

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 05.05.2003

- Phantom: SAM TP:1176; Type: SAM 4.0; Serial: 1176

- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 115

tilted right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 11.2 V/m

Power Drift = 0.06 dB

Maximum value of SAR = 0.33 mW/g

tilted right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.513 W/kg

SAR(1 g) = 0.315 mW/g; SAR(10 g) = 0.181 mW/g

Reference Value = 11.2 V/m

Power Drift = 0.06 dB

Maximum value of SAR = 0.344 mW/g




Fig. 8: SAR distribution for PCS 1900, channel 661, tilted position, right side of head. (28.07.2003; Liquid Temperature: 20.9° C; Ambient Temperature : 22.2 C).

3 SAR Distribution Plots, PCS 1900 Body with headset

Test Laboratory: IMST; File Name: [c60phm_3.da4](#)

DUT: Siemens; Type: C60 Body; Serial: 004999002488244

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: Body1900 MHz ($\sigma = 1.48$ mho/m, $\epsilon_r = 51.6$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.8, 4.8, 4.8); Calibrated: 21.03.2003

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 05.05.2003

- Phantom: SAM TP:1176;

- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 115

Unnamed procedure/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 10.1 V/m

Power Drift = 0.08 dB

Maximum value of SAR = 0.282 mW/g

Unnamed procedure/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.441 W/kg

SAR(1 g) = 0.285 mW/g; SAR(10 g) = 0.18 mW/g

Reference Value = 10.1 V/m

Power Drift = 0.08 dB

Maximum value of SAR = 0.305 mW/g

Unnamed procedure/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.304 W/kg

SAR(1 g) = 0.199 mW/g; SAR(10 g) = 0.13 mW/g

Reference Value = 10.1 V/m

Power Drift = 0.08 dB

Maximum value of SAR = 0.211 mW/g




Fig. 9: SAR distribution for PCS 1900, channel 661, body worn configuration, display away from phantom, with headset (29.07.2003; Liquid Temperature: 20.3° C; Ambient Temperature : 21.2° C).

4 SAR Distribution Plots, PCS 1900 Body with datacable

Test Laboratory: IMST; File Name: [c60phm_2.da4](#)

DUT: Siemens; Type: C60 Body; Serial: 004999002488244

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: Body1900 MHz ($\sigma = 1.48$ mho/m, $\epsilon_r = 51.6$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.8, 4.8, 4.8); Calibrated: 21.03.2003

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 05.05.2003

- Phantom: SAM TP:1176;

- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 115

Unnamed procedure/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 11.7 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.211 mW/g

Unnamed procedure/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.3 W/kg

SAR(1 g) = 0.207 mW/g; SAR(10 g) = 0.134 mW/g

Reference Value = 11.7 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.221 mW/g

Unnamed procedure/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.299 W/kg

SAR(1 g) = 0.199 mW/g; SAR(10 g) = 0.126 mW/g

Reference Value = 11.7 V/m

Power Drift = 0.1 dB

Maximum value of SAR = 0.212 mW/g




Fig. 10: SAR distribution for PCS 1900, channel 661, body worn configuration, display away from phantom, with datacable (29.07.2003; Liquid Temperature: 20.3° C; Ambient Temperature : 21.2° C).

5 SAR Distribution Plots, PCS 1900 Body, C60

Test Laboratory: IMST; File Name: [c60phm_1.da4](#)

DUT: Siemens; Type: C60 Body; Serial: 004999002488244

Program: Unnamed Program

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8

Medium: Body1900 MHz ($\sigma = 1.48$ mho/m, $\epsilon_r = 51.6$, $\rho = 1000$ kg/m³)

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1669; ConvF(4.8, 4.8, 4.8); Calibrated: 21.03.2003

- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 05.05.2003

- Phantom: SAM TP:1176;

- Measurement SW: DASY4, V4.1 Build 47; Postprocessing SW: SEMCAD, V1.6 Build 115

Unnamed procedure/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 9.84 V/m

Power Drift = 0.01 dB

Maximum value of SAR = 0.297 mW/g

Unnamed procedure/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Peak SAR (extrapolated) = 0.462 W/kg

SAR(1 g) = 0.308 mW/g; SAR(10 g) = 0.195 mW/g

Reference Value = 9.84 V/m

Power Drift = 0.01 dB

Maximum value of SAR = 0.328 mW/g




Fig. 11: SAR distribution for PCS 1900, channel 661, body worn configuration, display away from phantom, C60 (29.07.2003; Liquid Temperature: 20.3° C; Ambient Temperature : 21.1° C).

6 SAR z-axis scans (Validation)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 12: SAR versus liquid depth, 1900 MHz, head (28.07.2003; Liquid Temperature: 20.9° C; Ambient Temperature : 21.6° C).




Fig. 13: SAR versus liquid depth, 1900 MHz, body (29.07.2003; Liquid Temperature: 20.3° C; Ambient Temperature : 21.1° C).

7 SAR z-axis scans (Measurements)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 14: SAR versus liquid depth, head: without QuickPic camera , PCS 1900, channel 661, cheek position, right side of head. (28.07.2003, Liquid Temperature: 20.9° C; Ambient Temperature : 21.7° C).




Fig. 15: SAR versus liquid depth: PCS 1900, channel 661, body worn configuration, display away from phantom (29.07.2003, Liquid Temperature: 20.3° C; Ambient Temperature : 21.1° C).