
Appendix for the Report

Dosimetric Assessment of the Siemens C75 (FCC ID: PWX-C75)

According to the FCC Requirements

SAR Distribution Plots

June 06, 2005
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
Siemens Information & Communication Mobile LLC
16745 West Bernado Drive, Suite 400
San Diego, CA 92127

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written
approval of the testing laboratory.

Table of Contents

1	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD, WITHOUT FLASH	3
2	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD, WITH FLASH.....	7
3	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WORN (GAP = 20 MM)	11
4	SAR Z-AXIS SCANS (VALIDATION)	14
5	SAR Z-AXIS SCANS (MEASUREMENTS).....	15

1 SAR Distribution Plots, PCS 1900 head, without flash

Test Laboratory: IMST GmbH, DASY Yellow (II); File Name: [802yplm_1.da4](#)

DUT: Siemens; Type: Aries; Serial: 004400011069802

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2004
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.528 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.8 V/m; Power Drift = 0.112 dB

Peak SAR (extrapolated) = 0.852 W/kg

SAR(1 g) = 0.513 mW/g; SAR(10 g) = 0.299 mW/g

Maximum value of SAR (measured) = 0.571 mW/g




Fig. 1: SAR distribution for PCS 1900, channel 661, cheek position, left side of head (05.24.2005; Ambient Temperature: 21.8° C; Liquid Temperature: 21.1° C).

Test Laboratory: IMST GmbH, DASY Yellow (II); **File Name:** [802yp1m_2.da4](#)

DUT: Siemens; **Type:** Aries; **Serial:** 004400011069802

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2004
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.601 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.2 V/m; Power Drift = 0.160 dB

Peak SAR (extrapolated) = 1.01 W/kg

SAR(1 g) = 0.575 mW/g; SAR(10 g) = 0.320 mW/g

Maximum value of SAR (measured) = 0.642 mW/g




Fig. 2: SAR distribution for PCS 1900, channel 661, tilted position, left side of head (05.24.2005; Ambient Temperature: 21.8° C; Liquid Temperature : 21.1° C).

Test Laboratory: IMST GmbH, DASY Yellow (II); **File Name:** [802yprm_1.da4](#)

DUT: Siemens; **Type:** Aries; **Serial:** 004400011069802

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2004
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Cheek Right/Area Scan (6x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.377 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 16.9 V/m; Power Drift = 0.147 dB

Peak SAR (extrapolated) = 0.725 W/kg

SAR(1 g) = 0.394 mW/g; SAR(10 g) = 0.243 mW/g

Maximum value of SAR (measured) = 0.420 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 16.9 V/m; Power Drift = 0.147 dB

Peak SAR (extrapolated) = 0.436 W/kg

SAR(1 g) = 0.296 mW/g; SAR(10 g) = 0.203 mW/g

Maximum value of SAR (measured) = 0.344 mW/g




Fig. 3: SAR distribution for PCS 1900, channel 661, cheek position, right side of head (05.24.2005; Ambient Temperature: 21.9° C; Liquid Temperature : 21.1° C).

Test Laboratory: IMST GmbH, DASY Yellow (II); **File Name:** [802yprm 2.da4](#)

DUT: Siemens; **Type:** Aries; **Serial:** 004400011069802

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn631; Calibrated: 23.07.2004

- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.482 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.4 V/m; Power Drift = 0.162 dB

Peak SAR (extrapolated) = 0.935 W/kg

SAR(1 g) = 0.526 mW/g; SAR(10 g) = 0.302 mW/g

Maximum value of SAR (measured) = 0.577 mW/g




Fig. 4: SAR distribution for PCS 1900, channel 661, tilted position, right side of head (05.24.2005; Ambient Temperature: 21.9° C; Liquid Temperature : 21.1° C).

2 SAR Distribution Plots, PCS 1900 head, with flash

Test Laboratory: IMST GmbH, DASY Yellow (II); File Name: [802yplm_1_flash.da4](#)

DUT: Siemens; Type: Aries; Serial: 004400011069802

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2004
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 145

Cheek Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.490 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.1 V/m; Power Drift = 0.104 dB

Peak SAR (extrapolated) = 0.902 W/kg

SAR(1 g) = 0.473 mW/g; SAR(10 g) = 0.264 mW/g

Maximum value of SAR (measured) = 0.524 mW/g




Fig. 5: SAR distribution for PCS 1900, channel 661, cheek position, left side of head (05.24.2005; Ambient Temperature: 21.6° C; Liquid Temperature : 21.0° C).

Test Laboratory: IMST GmbH, DASY Yellow (II); **File Name:** [802yp1m 2 flash.da4](#)

DUT: Siemens; **Type:** Aries; **Serial:** 004400011069802

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2004
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Left/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.532 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.9 V/m; Power Drift = 0.103 dB

Peak SAR (extrapolated) = 1.00 W/kg

SAR(1 g) = 0.515 mW/g; SAR(10 g) = 0.283 mW/g

Maximum value of SAR (measured) = 0.585 mW/g




Fig. 6: SAR distribution for PCS 1900, channel 661, tilted position, left side of head (05.24.2005; Ambient Temperature: 21.6° C; Liquid Temperature : 21.0° C).

Test Laboratory: IMST GmbH, DASY Yellow (II); **File Name:** [802yprm_1_flash.da4](#)

DUT: Siemens; **Type:** Aries; **Serial:** 004400011069802

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2004
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Cheek Right/Area Scan (6x11x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.392 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 16.8 V/m; Power Drift = 0.177 dB

Peak SAR (extrapolated) = 0.631 W/kg

SAR(1 g) = 0.377 mW/g; SAR(10 g) = 0.246 mW/g

Maximum value of SAR (measured) = 0.403 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 16.8 V/m; Power Drift = 0.177 dB

Peak SAR (extrapolated) = 0.481 W/kg

SAR(1 g) = 0.341 mW/g; SAR(10 g) = 0.235 mW/g

Maximum value of SAR (measured) = 0.383 mW/g




Fig. 7: SAR distribution for PCS 1900, channel 661, cheek position, right side of head (05.24.2005; Ambient Temperature: 21.5° C; Liquid Temperature : 21.0° C).

Test Laboratory: IMST GmbH, DASY Yellow (II); **File Name:** [802yprm 2 flash.da4](#)

DUT: Siemens; **Type:** Aries; **Serial:** 004400011069802

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 40.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.19, 8.19, 8.19); Calibrated: 27.08.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2004
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Right/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.439 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.7 V/m; Power Drift = 0.054 dB

Peak SAR (extrapolated) = 0.840 W/kg

SAR(1 g) = 0.509 mW/g; SAR(10 g) = 0.301 mW/g

Maximum value of SAR (measured) = 0.554 mW/g




Fig. 8: SAR distribution for PCS 1900, channel 661, tilted position, right side of head (05.24.2005; Ambient Temperature: 21.5 °C; Liquid Temperature : 21.0° C)

3 SAR Distribution Plots, PCS 1900 Body worn (gap = 20 mm)

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [802bphm_1_GSM_wdh.da4](#)

DUT: Siemens; Type: Aries; Serial: 004400011069802

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.56$ mho/m; $\epsilon_r = 54.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.52, 4.52, 4.52); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.472 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.84 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.724 W/kg

SAR(1 g) = 0.443 mW/g; SAR(10 g) = 0.256 mW/g

Maximum value of SAR (measured) = 0.489 mW/g




Fig. 9: SAR distribution for PCS 1900, channel 661, antenna towards the phantom, GSM, (06.03.2005; Ambient Temperature: 22.5° C; Liquid Temperature : 21.6° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [802bphm 2 GSM WDH.da4](#)

DUT: Siemens; **Type:** Aries; **Serial:** 004400011069802

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.56$ mho/m; $\epsilon_r = 54.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.52, 4.52, 4.52); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.466 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.50 V/m; Power Drift = 0.068 dB

Peak SAR (extrapolated) = 0.723 W/kg

SAR(1 g) = 0.444 mW/g; SAR(10 g) = 0.258 mW/g

Maximum value of SAR (measured) = 0.487 mW/g




Fig. 10: SAR distribution for PCS 1900, channel 661, antenna towards the phantom, GSM with headset, (06.03.2005; Ambient Temperature: 22.5° C; Liquid Temperature : 21.6° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [802bphm 4 GPRS WDH.da4](#)

DUT: Siemens; **Type:** Aries; **Serial:** 004400011069802

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.56$ mho/m; $\epsilon_r = 54.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.52, 4.52, 4.52); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.740 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = 0.150 dB

Peak SAR (extrapolated) = 1.27 W/kg

SAR(1 g) = 0.777 mW/g; SAR(10 g) = 0.456 mW/g

Maximum value of SAR (measured) = 0.852 mW/g




Fig. 11: SAR distribution for PCS 1900, channel 661, antenna towards the phantom, GPRS Class 10 with data cable (03.06.2005; Ambient Temperature: 22.5° C; Liquid Temperature : 21.6° C).

4 SAR z-axis scans (Validation)




Fig. 12: SAR versus liquid depth, 1900 MHz, head (24.05.2005; Ambient Temperature: 21.8° C; Liquid Temperature : 21.1° C).




Fig. 13: SAR versus liquid depth, 1900 MHz, body (03.06.2005; Ambient Temperature: 22.5° C; Liquid Temperature : 21.6° C).

5 SAR z-axis scans (Measurements)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 14: SAR versus liquid depth, head: PCS 1900, channel 661, tilted position, left side of head without flash (24.05.2005, Ambient Temperature: 21.8° C; Liquid Temperature : 21.1° C).




Fig. 15: SAR versus liquid depth, body: PCS 1900, channel 661, antenna towards the phantom, GPRS Class 10 with data cable, (03.06.2005; Ambient Temperature: 22.5° C; Liquid Temperature : 21.6° C).