
Appendix for the Report

Dosimetric Assessment of the BenQ Siemens C81 (FCC ID: PWX-C81)

According to the FCC Requirements

SAR Distribution Plots

March 31, 2006
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
BenQ Denmark asp
Siemens Kaj 1
DK-9400 Norresundby

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written
approval of the testing laboratory.

Table of Contents

1	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD	3
2	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD, WORST CASE WITH BT ACTIVATED.....	7
3	SAR DISTRIBUTION PLOTS, PCS 1900 BODY, GSM MODE.....	8
4	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WITH DATA CABLE, GPRS MODE	11
5	SAR Z-AXIS SCANS (VALIDATION)	12
6	SAR Z-AXIS SCANS (MEASUREMENTS).....	13

1 SAR Distribution Plots, PCS 1900 Head

Test Laboratory: Imst GmbH; File Name: [561yplm_1.da4](#)

DUT: BenQ; Type: C81; Serial: 004401490002561

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 38.9$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.25, 8.25, 8.25); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.03.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.417 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.5 V/m; Power Drift = 0.003 dB

Peak SAR (extrapolated) = 0.818 W/kg

SAR(1 g) = 0.427 mW/g; SAR(10 g) = 0.226 mW/g

Maximum value of SAR (measured) = 0.476 mW/g




Fig. 1: SAR distribution for PCS 1900, channel 661, cheek position, left side of head (March 28, 2006; Ambient Temperature: 22.3° C; Liquid Temperature : 21.5° C).

Test Laboratory: Imst GmbH; File Name: [561yplm 2.da4](#)

DUT: BenQ; Type: C81; Serial: 004401490002561

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 38.9$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.25, 8.25, 8.25); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.03.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

Tilted Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.407 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.5 V/m; Power Drift = -0.026 dB

Peak SAR (extrapolated) = 0.679 W/kg

SAR(1 g) = 0.362 mW/g; SAR(10 g) = 0.191 mW/g

Maximum value of SAR (measured) = 0.404 mW/g




Fig. 2: SAR distribution for PCS 1900, channel 661, tilted position, left side of head (March 28, 2006; Ambient Temperature: 22.2°C; Liquid Temperature: 21.4°C).

Test Laboratory: Imst GmbH; File Name: [561yprm_1.da4](#)

DUT: BenQ; Type: C81; Serial: 004401490002561

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 38.9$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.25, 8.25, 8.25); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.03.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

Cheek Right/Area Scan (6x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.237 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 11.6 V/m; Power Drift = -0.011 dB

Peak SAR (extrapolated) = 0.432 W/kg

SAR(1 g) = 0.248 mW/g; SAR(10 g) = 0.141 mW/g

Maximum value of SAR (measured) = 0.272 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 11.6 V/m; Power Drift = -0.011 dB

Peak SAR (extrapolated) = 0.323 W/kg

SAR(1 g) = 0.178 mW/g; SAR(10 g) = 0.100 mW/g

Maximum value of SAR (measured) = 0.198 mW/g




Fig. 3: SAR distribution for PCS 1900, channel 661, cheek position, right side of head (March 28, 2006; Ambient Temperature: 22.3° C; Liquid Temperature : 21.5° C).

Test Laboratory: Imst GmbH; File Name: [561yprm_2.da4](#)

DUT: BenQ; Type: C81; Serial: 004401490002561

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 38.9$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.25, 8.25, 8.25); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.03.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.275 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.3 V/m; Power Drift = -0.016 dB

Peak SAR (extrapolated) = 0.463 W/kg

SAR(1 g) = 0.269 mW/g; SAR(10 g) = 0.150 mW/g

Maximum value of SAR (measured) = 0.293 mW/g




Fig. 4: SAR distribution for PCS 1900, channel 661, tilted position, right side of head (March 28, 2006; Ambient Temperature: 22.4 °C; Liquid Temperature : 21.6° C)

2 SAR Distribution Plots, PCS 1900 Head, worst case with BT activated

Test Laboratory: Imst GmbH; File Name: [561yplm_1_BT.da4](#)

DUT: BenQ; Type: C81; Serial: 004401490002561

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.44$ mho/m; $\epsilon_r = 38.9$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.25, 8.25, 8.25); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.03.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.470 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.5 V/m; Power Drift = 0.086 dB

Peak SAR (extrapolated) = 0.865 W/kg

SAR(1 g) = 0.443 mW/g; SAR(10 g) = 0.233 mW/g

Maximum value of SAR (measured) = 0.495 mW/g




Fig. 5: SAR distribution for PCS 1900, channel 661, cheek position, left side of head (March 28, 2006; Ambient Temperature: 22.3° C; Liquid Temperature : 21.5° C).

3 SAR Distribution Plots, PCS 1900 Body, GSM mode

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [561bphm_4_ohne_15mm.da4](#)

DUT: BenQ; Type: C81; Serial: 004401490002561

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 52.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.47, 4.47, 4.47); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.334 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.34 V/m; Power Drift = 0.047 dB

Peak SAR (extrapolated) = 0.517 W/kg

SAR(1 g) = 0.315 mW/g; SAR(10 g) = 0.184 mW/g

Maximum value of SAR (measured) = 0.345 mW/g




Fig. 6: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, without accessory with 15 mm distance (March 30, 2006; Ambient Temperature: 22.1° C; Liquid Temperature: 21.3° C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [561bphm_6_BT_15mm.da4](#)

DUT: BenQ; Type: C81; Serial: 004401490002561

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 52.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.47, 4.47, 4.47); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

Body Worn/Area Scan (7x11x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.304 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.94 V/m; Power Drift = 0.091 dB

Peak SAR (extrapolated) = 0.464 W/kg

SAR(1 g) = 0.288 mW/g; SAR(10 g) = 0.169 mW/g

Maximum value of SAR (measured) = 0.316 mW/g




Fig. 7: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, without accessory and BT activated (March 30, 2006; Ambient Temperature: 22.1° C; Liquid Temperature: 21.3° C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [561bphm 5 headset 15mm.da4](#)

DUT: BenQ; Type: C81; Serial: 004401490002561

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 52.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.47, 4.47, 4.47); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

Body Worn/Area Scan (7x11x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.327 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 8.18 V/m; Power Drift = 0.063 dB

Peak SAR (extrapolated) = 0.496 W/kg

SAR(1 g) = 0.309 mW/g; SAR(10 g) = 0.182 mW/g

Maximum value of SAR (measured) = 0.336 mW/g




Fig. 8: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, with headset (March 30, 2006; Ambient Temperature: 22.0° C; Liquid Temperature: 21.2° C).

4 SAR Distribution Plots, PCS 1900 Body with data cable, GPRS mode

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: 561bphm_8_data_20mm.da4

DUT: BenQ; Type: C81; Serial: 004401490002561

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.54$ mho/m; $\epsilon_r = 52.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.47, 4.47, 4.47); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.356 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.64 V/m; Power Drift = -0.020 dB

Peak SAR (extrapolated) = 0.544 W/kg

SAR(1 g) = 0.339 mW/g; SAR(10 g) = 0.205 mW/g

Maximum value of SAR (measured) = 0.373 mW/g




Fig. 9: SAR distribution for GPRS 1900 (Class 10), channel 661, body worn configuration, antenna towards the phantom, with data and 20 mm distance (March 30, 2006; Ambient Temperature: 22.0° C; Liquid Temperature: 21.2°C).

5 SAR z-axis scans (Validation)




Fig. 10: SAR versus liquid depth, 1900 MHz, head (March 28, 2006; Ambient Temperature: 21.8° C; Liquid Temperature : 20.9° C).




Fig. 11: SAR versus liquid depth, 1900 MHz, body (March 30, 2006; Ambient Temperature: 21.9° C; Liquid Temperature : 20.5° C).

6 SAR z-axis scans (Measurements)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 12: SAR versus liquid depth, head: PCS 1900, channel 661, cheek position, left side of head with BT activated (March 28, 2006; Ambient Temperature: 22.3° C; Liquid Temperature : 21.5° C).




Fig. 13: SAR versus liquid depth, body: GPRS 1900 (Class 10), channel 661, data cable and 20 mm distance (March 30, 2006; Ambient Temperature: 22.0° C; Liquid Temperature: 21.2° C).