
Appendix for the Report

Dosimetric Assessment of the Siemens CF110 (FCC ID: PWX-CF110)

According to the FCC Requirements

SAR Distribution Plots

August 23, 2005
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
Siemens Communication Inc.
16475 West Bernado Drive, Suite 400
San Diego CA 92127

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written
approval of the testing laboratory.

Table of Contents

1	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD SLIDER UP	3
2	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD SLIDER DOWN	7
3	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WITHOUT ACCESSORY	11
4	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WITH HEADSET	17
5	SAR DISTRIBUTION PLOTS, PCS 1900 BODY, GPRS CLASS 8 WITH DATCABLE	23
6	SAR Z-AXIS SCANS (VALIDATION)	29
7	SAR Z-AXIS SCANS (MEASUREMENTS)	30

1 SAR Distribution Plots, PCS 1900 Head slider up

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [058bplm_1\(Slider up\).da4](#)

DUT: Siemens Flamingo (Slider up); Type: CF110; Serial: 004400013590058

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(5.11, 5.11, 5.11); Calibrated: 13.01.2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 17.03.2005

- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Cheek Left/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.247 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.8 V/m; Power Drift = 0.039 dB

Peak SAR (extrapolated) = 0.409 W/kg

SAR(1 g) = 0.249 mW/g; SAR(10 g) = 0.140 mW/g

Maximum value of SAR (measured) = 0.282 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.8 V/m; Power Drift = 0.039 dB

Peak SAR (extrapolated) = 0.325 W/kg

SAR(1 g) = 0.189 mW/g; SAR(10 g) = 0.113 mW/g

Maximum value of SAR (measured) = 0.229 mW/g




Fig. 1: SAR distribution for PCS 1900, channel 661, cheek position, left side of head (August 08, 2005; Ambient Temperature: 21.7° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bplm_2\(Slider up\).da4](#)

DUT: Siemens Flamingo (Slider up); **Type:** CF110; **Serial:** 004400013590058

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(5.11, 5.11, 5.11); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Left/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.232 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.9 V/m; Power Drift = -0.080 dB

Peak SAR (extrapolated) = 0.441 W/kg

SAR(1 g) = 0.268 mW/g; SAR(10 g) = 0.146 mW/g

Maximum value of SAR (measured) = 0.307 mW/g




Fig. 2: SAR distribution for PCS 1900, channel 661, tilted position, left side of head (August 08, 2005; Ambient Temperature: 21.7° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bprm_1\(Slider up\).da4](#)

DUT: Siemens Flamingo (Slider up); **Type:** CF110; **Serial:** 004400013590058
Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3
 Medium parameters used: $f = 1880$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.6$; $\rho = 1000$ kg/m³
 Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(5.11, 5.11, 5.11); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Cheek Right/Area Scan (6x9x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.281 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 11.5 V/m; Power Drift = -0.105 dB

Peak SAR (extrapolated) = 0.514 W/kg

SAR(1 g) = 0.317 mW/g; SAR(10 g) = 0.173 mW/g

Maximum value of SAR (measured) = 0.350 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 11.5 V/m; Power Drift = -0.105 dB

Peak SAR (extrapolated) = 0.248 W/kg

SAR(1 g) = 0.177 mW/g; SAR(10 g) = 0.104 mW/g

Maximum value of SAR (measured) = 0.200 mW/g




Fig. 3: SAR distribution for PCS 1900, channel 661, cheek position, right side of head (August 08, 2005; Ambient Temperature: 21.7° C; Liquid Temperature : 20.2° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bprm_2\(Slider up\).da4](#)

DUT: Siemens Flamingo (Slider up); **Type:** CF110; **Serial:** 004400013590058

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(5.11, 5.11, 5.11); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Right/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.333 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.4 V/m; Power Drift = 0.019 dB

Peak SAR (extrapolated) = 0.536 W/kg

SAR(1 g) = 0.331 mW/g; SAR(10 g) = 0.181 mW/g

Maximum value of SAR (measured) = 0.365 mW/g




Fig. 4: SAR distribution for PCS 1900, channel 661, tilted position, right side of head (August 08, 2005; Ambient Temperature: 21.7 °C; Liquid Temperature : 20.2° C)

2 SAR Distribution Plots, PCS 1900 Head slider down

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [058bplm_1_slider_down.da4](#)

DUT: Siemens Flamingo (Slider Down); Type: CF110; Serial: 004400013590058

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(5.11, 5.11, 5.11); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.293 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.3 V/m; Power Drift = -0.169 dB

Peak SAR (extrapolated) = 0.405 W/kg

SAR(1 g) = 0.254 mW/g; SAR(10 g) = 0.145 mW/g

Maximum value of SAR (measured) = 0.278 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.3 V/m; Power Drift = -0.169 dB

Peak SAR (extrapolated) = 0.326 W/kg

SAR(1 g) = 0.209 mW/g; SAR(10 g) = 0.124 mW/g

Maximum value of SAR (measured) = 0.226 mW/g




Fig. 5: SAR distribution for PCS 1900, channel 661, cheek position, left side of head (August 08, 2005; Ambient Temperature: 21.8° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bplm 2 slider down.da4](#)

DUT: Siemens Flamingo (Slider Down); **Type:** CF110; **Serial:** 004400013590058

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1747.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(5.36, 5.36, 5.36); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Left/Area Scan (6x9x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.257 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.4 V/m; Power Drift = -0.023 dB

Peak SAR (extrapolated) = 0.426 W/kg

SAR(1 g) = 0.261 mW/g; SAR(10 g) = 0.144 mW/g

Maximum value of SAR (measured) = 0.295 mW/g




Fig. 6: SAR distribution for PCS 1900, channel 661, tilted position, left side of head (August 08, 2005; Ambient Temperature: 21.8° C; Liquid Temperature : 20.2° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bprm_1_slider_down.da4](#)

DUT: Siemens Flamingo (Slider Down); **Type:** CF110; **Serial:** 004400013590058

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(5.11, 5.11, 5.11); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Cheek Right/Area Scan (6x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.319 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 12.4 V/m; Power Drift = 0.135 dB

Peak SAR (extrapolated) = 0.534 W/kg

SAR(1 g) = 0.329 mW/g; SAR(10 g) = 0.181 mW/g

Maximum value of SAR (measured) = 0.365 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 12.4 V/m; Power Drift = 0.135 dB

Peak SAR (extrapolated) = 0.284 W/kg

SAR(1 g) = 0.202 mW/g; SAR(10 g) = 0.120 mW/g

Maximum value of SAR (measured) = 0.225 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 2: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 12.4 V/m; Power Drift = 0.135 dB

Peak SAR (extrapolated) = 0.375 W/kg

SAR(1 g) = 0.207 mW/g; SAR(10 g) = 0.122 mW/g

Maximum value of SAR (measured) = 0.257 mW/g




Fig. 7: SAR distribution for PCS 1900, channel 661, cheek position, right side of head (August 08, 2005; Ambient Temperature: 21.8° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bprm 2 slider down.da4](#)

DUT: Siemens Flamingo (Slider Down); **Type:** CF110; **Serial:** 004400013590058

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1747.6 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(5.36, 5.36, 5.36); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 17.03.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Tilted Right/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.370 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.4 V/m; Power Drift = 0.026 dB

Peak SAR (extrapolated) = 0.559 W/kg

SAR(1 g) = 0.344 mW/g; SAR(10 g) = 0.188 mW/g

Maximum value of SAR (measured) = 0.379 mW/g




Fig. 8: SAR distribution for PCS 1900, channel 661, tilted position, right side of head (August 08, 2005; Ambient Temperature: 21.7 °C; Liquid Temperature : 20.2° C)

3 SAR Distribution Plots, PCS 1900 Body without accessory

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [058bphm_3_su_ohne_15mm.da4](#)

DUT: Siemens Flamingo (Slider Up); Type: CF110; Serial: 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.834 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 9.89 V/m; Power Drift = 0.086 dB

Peak SAR (extrapolated) = 1.51 W/kg

SAR(1 g) = 0.909 mW/g; SAR(10 g) = 0.494 mW/g

Maximum value of SAR (measured) = 1.02 mW/g




Fig. 9: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, slider up, without accessory, 15 mm distance (August 19, 2005; Ambient Temperature: 22.0° C; Liquid Temperature: 21.2° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphm 3 sd ohne 15mm.da4](#)

DUT: Siemens Flamingo (Slider Down); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 1.09 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 10.9 V/m; Power Drift = 0.038 dB

Peak SAR (extrapolated) = 1.66 W/kg

SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.557 mW/g

Maximum value of SAR (measured) = 1.16 mW/g




Fig. 10: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, slider down, without accessory, 15 mm distance (August 19, 2005; Ambient Temperature: 22.1° C; Liquid Temperature: 21.1° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphl 3 su ohne 15mm.da4](#)

DUT: Siemens Flamingo (Slider Up); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.26 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.3 V/m; Power Drift = -0.111 dB

Peak SAR (extrapolated) = 1.90 W/kg

SAR(1 g) = 1.15 mW/g; SAR(10 g) = 0.622 mW/g

Maximum value of SAR (measured) = 1.28 mW/g




Fig. 11: SAR distribution for PCS 1900, channel 512, body worn configuration, antenna towards the phantom, slider up, without accessory, 15 mm distance (August 19, 2005; Ambient Temperature: 22.2° C; Liquid Temperature: 21.2° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphh 3 su ohne 15mm.da4](#)

DUT: Siemens Flamingo (Slider Up); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1909.8$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.608 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.6 V/m; Power Drift = 0.015 dB

Peak SAR (extrapolated) = 0.996 W/kg

SAR(1 g) = 0.576 mW/g; SAR(10 g) = 0.311 mW/g

Maximum value of SAR (measured) = 0.647 mW/g




Fig. 12: SAR distribution for PCS 1900, channel 810, body worn configuration, antenna towards the phantom, slider up, without accessory, 15 mm distance (August 19, 2005; Ambient Temperature: 22.3° C; Liquid Temperature: 21.2° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphl 3 sd ohne 15mm.da4](#)

DUT: Siemens Flamingo (Slider Down); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.27 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.54 V/m; Power Drift = -0.080 dB

Peak SAR (extrapolated) = 1.85 W/kg

SAR(1 g) = 1.14 mW/g; SAR(10 g) = 0.621 mW/g

Maximum value of SAR (measured) = 1.29 mW/g

Fig. 13: SAR distribution for PCS 1900, channel 512, body worn configuration, antenna towards the phantom, slider down, without accessory, 15 mm distance (August 19, 2005; Ambient Temperature: 22.1° C; Liquid Temperature: 21.3° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphh 3 sd ohne 15mm.da4](#)

DUT: Siemens Flamingo (Slider Down); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1909.8$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.696 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.80 V/m; Power Drift = 0.100 dB

Peak SAR (extrapolated) = 1.06 W/kg

SAR(1 g) = 0.633 mW/g; SAR(10 g) = 0.343 mW/g

Maximum value of SAR (measured) = 0.711 mW/g




Fig. 14: SAR distribution for PCS 1900, channel 810, body worn configuration, antenna towards the phantom, slider down, without accessory, 15 mm distance (August 19, 2005; Ambient Temperature: 22.2° C; Liquid Temperature: 21.3° C).

4 SAR Distribution Plots, PCS 1900 Body with headset

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [058bphm_3_su_headset_15mm.da4](#)

DUT: Siemens Flamingo (Slider Up); Type: CF110; Serial: 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.831 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.8 V/m; Power Drift = 0.134 dB

Peak SAR (extrapolated) = 1.57 W/kg

SAR(1 g) = 0.927 mW/g; SAR(10 g) = 0.499 mW/g

Maximum value of SAR (measured) = 1.05 mW/g




Fig. 15: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, slider up, with headset, 15 mm distance (August 19, 2005; Ambient Temperature: 22.0° C; Liquid Temperature: 21.3° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphm 3 sd headset 15mm.da4](#)

DUT: Siemens Flamingo (Slider Down); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.14 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.7 V/m; Power Drift = -0.187 dB

Peak SAR (extrapolated) = 1.72 W/kg

SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.556 mW/g

Maximum value of SAR (measured) = 1.15 mW/g




Fig. 16: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, slider down, with headset, 15 mm distance (August 19, 2005; Ambient Temperature: 22.1° C; Liquid Temperature: 21.1° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphl 3 su headset 15mm.da4](#)

DUT: Siemens Flamingo (Slider Up); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.19 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.7 V/m; Power Drift = -0.026 dB

Peak SAR (extrapolated) = 1.75 W/kg

SAR(1 g) = 1.08 mW/g; SAR(10 g) = 0.589 mW/g

Maximum value of SAR (measured) = 1.23 mW/g




Fig. 17: SAR distribution for PCS 1900, channel 512, body worn configuration, antenna towards the phantom, slider up, with headset, 15 mm distance (August 19, 2005; Ambient Temperature: 22.3° C; Liquid Temperature: 21.2° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphh_3_su_headset_15mm.da4](#)

DUT: Siemens Flamingo (Slider Up); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1909.8$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.595 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.4 V/m; Power Drift = 0.047 dB

Peak SAR (extrapolated) = 0.920 W/kg

SAR(1 g) = 0.537 mW/g; SAR(10 g) = 0.289 mW/g

Maximum value of SAR (measured) = 0.603 mW/g




Fig. 18: SAR distribution for PCS 1900, channel 810, body worn configuration, antenna towards the phantom, slider up, with headset, 15 mm distance (August 19, 2005; Ambient Temperature: 22.3° C; Liquid Temperature: 21.2° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphl 3 sd headset 15mm.da4](#)

DUT: Siemens Flamingo (Slider Down); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.22 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.47 V/m; Power Drift = -0.011 dB

Peak SAR (extrapolated) = 1.76 W/kg

SAR(1 g) = 1.1 mW/g; SAR(10 g) = 0.599 mW/g




Fig. 19: SAR distribution for PCS 1900, channel 512, body worn configuration, antenna towards the phantom, slider down, with headset, 15 mm distance (August 19, 2005; Ambient Temperature: 22.2° C; Liquid Temperature: 21.2° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphh 3 sd headset 15mm.da4](#)

DUT: Siemens Flamingo (Slider Down); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1909.8$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.660 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.25 V/m; Power Drift = 0.2 dB

Peak SAR (extrapolated) = 1.03 W/kg

SAR(1 g) = 0.617 mW/g; SAR(10 g) = 0.334 mW/g

Maximum value of SAR (measured) = 0.687 mW/g




Fig. 20: SAR distribution for PCS 1900, channel 810, body worn configuration, antenna towards the phantom, slider down, with headset, 15 mm distance (August 19, 2005; Ambient Temperature: 22.2° C; Liquid Temperature: 21.2° C).

5 SAR Distribution Plots, PCS 1900 Body, GPRS Class 8 with datcable

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [058bphm_3_su_data_15mm.da4](#)

DUT: Siemens Flamingo (Slider Up); Type: CF110; Serial: 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn631; Calibrated: 07.07.2005

- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176

- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.899 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 20.6 V/m; Power Drift = 0.091 dB

Peak SAR (extrapolated) = 1.70 W/kg

SAR(1 g) = 1.000 mW/g; SAR(10 g) = 0.537 mW/g

Maximum value of SAR (measured) = 1.13 mW/g




Fig. 21: SAR distribution for GPRS 1900, channel 661, body worn configuration, antenna towards the phantom, slider up, with data cable, 15 mm distance (August 19, 2005; Ambient Temperature: 22.1° C; Liquid Temperature: 21.3° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphm 3 sd data 15mm.da4](#)

DUT: Siemens Flamingo (Slider Down); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.15 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.5 V/m; Power Drift = 0.2 dB

Peak SAR (extrapolated) = 1.74 W/kg

SAR(1 g) = 1.05 mW/g; SAR(10 g) = 0.567 mW/g

Maximum value of SAR (measured) = 1.17 mW/g




Fig. 22: SAR distribution for GPRS 1900, channel 661, body worn configuration, antenna towards the phantom, slider down, with data cable, 15 mm distance (August 19, 2005; Ambient Temperature: 22.0° C; Liquid Temperature: 21.2° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphl 3 su data 15mm.da4](#)

DUT: Siemens Flamingo (Slider Up); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.26 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 13.5 V/m; Power Drift = -0.019 dB

Peak SAR (extrapolated) = 1.83 W/kg

SAR(1 g) = 1.11 mW/g; SAR(10 g) = 0.603 mW/g




Fig. 23: SAR distribution for GPRS 1900, channel 512, body worn configuration, antenna towards the phantom, slider up, with data cable, 15 mm distance (August 19, 2005; Ambient Temperature: 22.2° C; Liquid Temperature: 21.2° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphh 3 su data 15mm.da4](#)

DUT: Siemens Flamingo (Slider Up); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1909.8$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.611 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.0 V/m; Power Drift = 0.032 dB

Peak SAR (extrapolated) = 0.952 W/kg

SAR(1 g) = 0.550 mW/g; SAR(10 g) = 0.297 mW/g

Maximum value of SAR (measured) = 0.618 mW/g




Fig. 24: SAR distribution for GPRS 1900, channel 810, body worn configuration, antenna towards the phantom, slider up, with data cable, 15 mm distance (August 19, 2005; Ambient Temperature: 22.1° C; Liquid Temperature: 21.2° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphl_3_sd_data_15mm.da4](#)

DUT: Siemens Flamingo (Slider Down); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1850.2 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.17 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.29 V/m; Power Drift = -0.097 dB

Peak SAR (extrapolated) = 1.72 W/kg

SAR(1 g) = 1.05 mW/g; SAR(10 g) = 0.575 mW/g

Maximum value of SAR (measured) = 1.19 mW/g




Fig. 25: SAR distribution for GPRS 1900, channel 512, body worn configuration, antenna towards the phantom, slider down, with data cable, 15 mm distance (August 19, 2005; Ambient Temperature: 22.2° C; Liquid Temperature: 21.2° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [058bphh 3 sd data 15mm.da4](#)

DUT: Siemens Flamingo (Slider Down); **Type:** CF110; **Serial:** 004400013590058

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1909.8$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(4.69, 4.69, 4.69); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

Body Worn/Area Scan (7x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.663 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.5 V/m; Power Drift = 0.040 dB

Peak SAR (extrapolated) = 1.04 W/kg

SAR(1 g) = 0.620 mW/g; SAR(10 g) = 0.340 mW/g

Maximum value of SAR (measured) = 0.689 mW/g




Fig. 26: SAR distribution for GPRS 1900, channel 810, body worn configuration, antenna towards the phantom, slider down, with data cable, 15 mm distance (August 19, 2005; Ambient Temperature: 22.2° C; Liquid Temperature: 21.2° C).

6 SAR z-axis scans (Validation)




Fig. 27: SAR versus liquid depth, 1900 MHz, head (August 08, 2005; Ambient Temperature: 22.0° C; Liquid Temperature : 21.0° C).




Fig. 28: SAR versus liquid depth, 1900 MHz, body (August 19, 2005; Ambient Temperature: 22.0° C; Liquid Temperature : 21.0° C).

7 SAR z-axis scans (Measurements)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 29: SAR versus liquid depth, head: PCS 1900, channel 661, tilted position, right side of head, slider down (August 08, 2005; Ambient Temperature: 21.7° C; Liquid Temperature : 20.2° C).




Fig. 30: SAR versus liquid depth, body: PCS 1900, channel 512, body worn configuration, antenna towards the phantom, slider up, without accessory, 15 mm distance (August 19, 2005; Ambient Temperature: 22.2° C; Liquid Temperature: 21.2° C).