
Appendix for the Report

Dosimetric Assessment of the Siemens CX70E (FCC ID: PWX-CX70E) According to the FCC Requirements

SAR Distribution Plots

September 23, 2004
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
Siemens Information & Communication Mobile LLC
16475 West Bernado Drive, Suite 400
San Diego CA 92127

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written
approval of the testing laboratory.

Table of Contents

1	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD WITHOUT FLASH.....	3
2	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD WITH FLASH	11
3	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WITH HEADSET (GAP = 22 MM).....	19
4	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WITH DATA CABLE (GAP = 22 MM).....	21
5	SAR DISTRIBUTION PLOTS, PCS 1900 BODY PTT MODE (GAP = 25 MM).....	23
6	SAR Z-AXIS SCANS (VALIDATION)	25
7	SAR Z-AXIS SCANS (MEASUREMENTS)	27

1 SAR Distribution Plots, PCS 1900 Head without Flash

Test Laboratory: IMST GmbH; File Name: [ARCplm_1.da4](#)

DUT: Siemens; Type: CX 70E; Serial: 004999003278248

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19 V/m; Power Drift = 0.035 dB

Maximum value of SAR (measured) = 0.599 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19 V/m; Power Drift = 0.035 dB

Maximum value of SAR (measured) = 0.627 mW/g

Peak SAR (extrapolated) = 0.953 W/kg

SAR(1 g) = 0.578 mW/g; SAR(10 g) = 0.333 mW/g




Fig. 1: SAR distribution for PCS 1900, channel 661, cheek position, left side of head, ARC. (16.09.2004; Ambient Temperature: 20.7° C; Liquid Temperature: 20.0° C).

Test Laboratory: IMST GmbH; **File Name:** [ARCplm_2.da4](#)

DUT: Siemens; **Type:** CX 70E; **Serial:** 004999003278248

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 23 V/m; Power Drift = -0.059 dB

Maximum value of SAR (measured) = 0.688 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 23 V/m; Power Drift = -0.059 dB

Maximum value of SAR (measured) = 0.737 mW/g

Peak SAR (extrapolated) = 1.11 W/kg

SAR(1 g) = 0.666 mW/g; SAR(10 g) = 0.380 mW/g




Fig. 2: SAR distribution for PCS 1900, channel 661, tilted position, left side of head, ARC. (16.09.2004; Ambient Temperature: 20.8° C; Liquid Temperature: 20.1° C).

Test Laboratory: IMST GmbH; File Name: [ARCprm_1.da4](#)

DUT: Siemens; Type: CX 70E; Serial: 004999003278248

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.8 V/m; Power Drift = -0.029 dB

Maximum value of SAR (measured) = 0.455 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.8 V/m; Power Drift = -0.029 dB

Maximum value of SAR (measured) = 0.496 mW/g

Peak SAR (extrapolated) = 0.683 W/kg

SAR(1 g) = 0.453 mW/g; SAR(10 g) = 0.276 mW/g




Fig. 3: SAR distribution for PCS 1900, channel 661, cheek position, right side of head, ARC. (16.09.2004; Ambient Temperature: 20.6° C; Liquid Temperature: 20.0° C).

Test Laboratory: IMST GmbH; **File Name:** [ARCprm 2.da4](#)

DUT: Siemens; **Type:** CX 70E; **Serial:** 004999003278248

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Reference Value = 20.9 V/m; Power Drift = 0.040 dB

Maximum value of SAR (measured) = 0.486 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 20.9 V/m; Power Drift = 0.040 dB

Maximum value of SAR (measured) = 0.589 mW/g

Peak SAR (extrapolated) = 0.816 W/kg

SAR(1 g) = 0.531 mW/g; SAR(10 g) = 0.310 mW/g




Fig. 4: SAR distribution for PCS 1900, channel 661, tilted position, right side of head, ARC. (16.09.2004; Ambient Temperature: 20.8° C; Liquid Temperature: 20.0° C).

Test Laboratory: IMST GmbH; File Name: [Actplm_1.da4](#)

DUT: Siemens; Type: CX 70E; Serial: 004999003278248

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.4 V/m; Power Drift = -0.035 dB

Maximum value of SAR (measured) = 0.579 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.4 V/m; Power Drift = -0.035 dB

Maximum value of SAR (measured) = 0.594 mW/g

Peak SAR (extrapolated) = 0.889 W/kg

SAR(1 g) = 0.550 mW/g; SAR(10 g) = 0.320 mW/g




Fig. 5: SAR distribution for PCS 1900, channel 661, cheek position, left side of head, Active. (16.09.2004; Ambient Temperature: 20.6° C; Liquid Temperature: 20.0° C).

Test Laboratory: IMST GmbH; **File Name:** [Actplm 2.da4](#)

DUT: Siemens; **Type:** CX 70E; **Serial:** 004999003278248

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 123

Tilted Left/Area Scan (6x12x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.608 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 21.1 V/m; Power Drift = -0.050 dB

Peak SAR (extrapolated) = 0.933 W/kg

SAR(1 g) = 0.581 mW/g; SAR(10 g) = 0.332 mW/g

Maximum value of SAR (measured) = 0.634 mW/g




Fig. 6: SAR distribution for PCS 1900, channel 661, tilted position, left side of head, Active. (16.09.2004; Ambient Temperature: 20.7° C; Liquid Temperature: 19.9° C).

Test Laboratory: IMST GmbH; **File Name:** [Actprm_1.da4](#)

DUT: Siemens; **Type:** CX 70E; **Serial:** 004999003278248

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.6 V/m; Power Drift = -0.031 dB

Maximum value of SAR (measured) = 0.472 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.6 V/m; Power Drift = -0.031 dB

Maximum value of SAR (measured) = 0.525 mW/g

Peak SAR (extrapolated) = 0.725 W/kg

SAR(1 g) = 0.478 mW/g; SAR(10 g) = 0.290 mW/g




Fig. 7: SAR distribution for PCS 1900, channel 661, cheek position, right side of head, Active. (16.09.2004; Ambient Temperature: 20.8° C; Liquid Temperature: 19.9° C).

Test Laboratory: IMST GmbH; **File Name:** [Actprm_2.da4](#)

DUT: Siemens; **Type:** CX 70E; **Serial:** 004999003278248

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x12x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Reference Value = 20.2 V/m; Power Drift = 0.009 dB

Maximum value of SAR (measured) = 0.453 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 20.2 V/m; Power Drift = 0.009 dB

Maximum value of SAR (measured) = 0.511 mW/g

Peak SAR (extrapolated) = 0.723 W/kg

SAR(1 g) = 0.466 mW/g; SAR(10 g) = 0.274 mW/g




Fig. 8: SAR distribution for PCS 1900, channel 661, tilted position, right side of head, Active. (16.09.2004; Ambient Temperature: 20.8° C; Liquid Temperature: 20.0° C).

2 SAR Distribution Plots, PCS 1900 Head with Flash

Test Laboratory: IMST GmbH; File Name: [ARCP1m_1_flash.da4](#)

DUT: Siemens; Type: CX 70E ARC. + Flash; Serial: 004999003278248

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x13x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.2 V/m; Power Drift = -0.074 dB

Maximum value of SAR (measured) = 0.536 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.2 V/m; Power Drift = -0.074 dB

Maximum value of SAR (measured) = 0.568 mW/g

Peak SAR (extrapolated) = 0.845 W/kg

SAR(1 g) = 0.515 mW/g; SAR(10 g) = 0.300 mW/g




Fig. 9: SAR distribution for PCS 1900, channel 661, cheek position, left side of head, ARC. (16.09.2004; Ambient Temperature: 21.3° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH; **File Name:** [ARCplm_2_flash.da4](#)

DUT: Siemens; **Type:** CX 70E ARC. + Flash; **Serial:** 004999003278248

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Reference Value = 20 V/m; Power Drift = -0.129 dB

Maximum value of SAR (measured) = 0.522 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 20 V/m; Power Drift = -0.129 dB

Maximum value of SAR (measured) = 0.619 mW/g

Peak SAR (extrapolated) = 0.930 W/kg

SAR(1 g) = 0.551 mW/g; SAR(10 g) = 0.312 mW/g




Fig. 10: SAR distribution for PCS 1900, channel 661, tilted position, left side of head, ARC. (16.09.2004; Ambient Temperature: 21.2° C; Liquid Temperature : 20.0° C).

Test Laboratory: IMST GmbH; **File Name:** [ARCprm_1_flash.da4](#)

DUT: Siemens; **Type:** CX 70E ARC. + Flash; **Serial:** 004999003278248

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3a

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x13x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.3 V/m; Power Drift = -0.122 dB

Maximum value of SAR (measured) = 0.396 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.3 V/m; Power Drift = -0.122 dB

Maximum value of SAR (measured) = 0.466 mW/g

Peak SAR (extrapolated) = 0.655 W/kg

SAR(1 g) = 0.430 mW/g; SAR(10 g) = 0.264 mW/g




Fig. 11: SAR distribution for PCS 1900, channel 661, cheek position, right side of head, ARC. (16.09.2004; Ambient Temperature: 21.1° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH; File Name: [ARCprm_2_flash.da4](#)

DUT: Siemens; Type: CX 70E ARC. + Flash; Serial: 004999003278248

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x13x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 19.2 V/m; Power Drift = -0.066 dB

Maximum value of SAR (measured) = 0.405 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 19.2 V/m; Power Drift = -0.066 dB

Maximum value of SAR (measured) = 0.486 mW/g

Peak SAR (extrapolated) = 0.700 W/kg

SAR(1 g) = 0.441 mW/g; SAR(10 g) = 0.259 mW/g




Fig. 12: SAR distribution for PCS 1900, channel 661, tilted position, right side of head, ARC. (16.09.2004; Ambient Temperature: 21.3° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH; **File Name:** [Actplm_1_flash.da4](#)

DUT: Siemens; **Type:** CX 70E + flash; **Serial:** 004999003278248

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Left/Area Scan (6x13x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 16.3 V/m; Power Drift = -0.034 dB

Maximum value of SAR (measured) = 0.477 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.3 V/m; Power Drift = -0.034 dB

Maximum value of SAR (measured) = 0.538 mW/g

Peak SAR (extrapolated) = 0.779 W/kg

SAR(1 g) = 0.486 mW/g; SAR(10 g) = 0.282 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.3 V/m; Power Drift = -0.034 dB

Maximum value of SAR (measured) = 0.374 mW/g

Peak SAR (extrapolated) = 0.501 W/kg

SAR(1 g) = 0.349 mW/g; SAR(10 g) = 0.228 mW/g




Fig. 13: SAR distribution for PCS 1900, channel 661, cheek position, left side of head, Active. (16.09.2004; Ambient Temperature: 21.3° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH; **File Name:** [Actplm_2_flash.da4](#)

DUT: Siemens; **Type:** CX 70E + flash; **Serial:** 004999003278248

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Left/Area Scan (6x13x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 17.9 V/m; Power Drift = -0.005 dB

Maximum value of SAR (measured) = 0.506 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 17.9 V/m; Power Drift = -0.005 dB

Maximum value of SAR (measured) = 0.574 mW/g

Peak SAR (extrapolated) = 0.842 W/kg

SAR(1 g) = 0.515 mW/g; SAR(10 g) = 0.295 mW/g




Fig. 14: SAR distribution for PCS 1900, channel 661, tilted position, left side of head Active. (16.09.2004; Ambient Temperature: 21.3° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH; **File Name:** [Actprm_1_flash.da4](#)

DUT: Siemens; **Type:** CX 70E + flash; **Serial:** 004999003278248

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004

- Sensor-Surface: 4mm (Mechanical Surface Detection)

Sensor-Surface: 4mm (Mechanical And Optical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 05.08.2004

- Phantom: SAM Glycol; Type: Speag; Serial: 1176

- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Cheek Right/Area Scan (6x13x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Reference Value = 18.1 V/m; Power Drift = -0.079 dB

Maximum value of SAR (measured) = 0.379 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 18.1 V/m; Power Drift = -0.079 dB

Maximum value of SAR (measured) = 0.433 mW/g

Peak SAR (extrapolated) = 0.611 W/kg

SAR(1 g) = 0.399 mW/g; SAR(10 g) = 0.245 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 18.1 V/m; Power Drift = -0.079 dB

Maximum value of SAR (measured) = 0.350 mW/g

Peak SAR (extrapolated) = 0.441 W/kg

SAR(1 g) = 0.327 mW/g; SAR(10 g) = 0.212 mW/g




Fig. 15: SAR distribution for PCS 1900, channel 661, cheek position, right side of head Active. (16.09.2004; Ambient Temperature: 21.3° C; Liquid Temperature : 20.1° C).

Test Laboratory: IMST GmbH; File Name: [Actprm 2 flash.da4](#)

DUT: Siemens; Type: CX 70 + Flash; Serial: 004999003279147

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(5.19, 5.19, 5.19); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Tilted Right/Area Scan (6x13x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 18.7 V/m; Power Drift = -0.036 dB

Maximum value of SAR (measured) = 0.395 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 18.7 V/m; Power Drift = -0.036 dB

Maximum value of SAR (measured) = 0.447 mW/g

Peak SAR (extrapolated) = 0.646 W/kg

SAR(1 g) = 0.407 mW/g; SAR(10 g) = 0.240 mW/g




Fig. 16: SAR distribution for PCS 1900, channel 661, tilted position, right side of head Active. (16.09.2004; Ambient Temperature: 21.3° C; Liquid Temperature : 20.1° C).

3 SAR Distribution Plots, PCS 1900 Body with headset (gap = 22 mm)

Test Laboratory: IMST GmbH; File Name: [ARCphm_1.da4](#)

DUT: Siemens; Type: CX 70E; Serial: 004999003278248

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.55$; mho/m, $\epsilon_r = 51.9$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.57, 4.57, 4.57); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 5.62 V/m; Power Drift = 0.105 dB

Maximum value of SAR (measured) = 0.298 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.62 V/m; Power Drift = 0.105 dB

Maximum value of SAR (measured) = 0.300 mW/g

Peak SAR (extrapolated) = 0.431 W/kg

SAR(1 g) = 0.276 mW/g; SAR(10 g) = 0.166 mW/g




Fig. 17: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, ARC cover with headset GSM mode 1 TX (13.09.2004; Ambient Temperature: 21.7° C; Liquid Temperature : 20.7° C).

Test Laboratory: IMST GmbH; **File Name:** [Actphm_1.da4](#)

DUT: Siemens; **Type:** CX 70E; **Serial:** 004999003278248

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.55$; mho/m, $\epsilon_r = 51.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.57, 4.57, 4.57); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 5.83 V/m; Power Drift = 0.040 dB

Maximum value of SAR (measured) = 0.158 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.83 V/m; Power Drift = 0.040 dB

Maximum value of SAR (measured) = 0.162 mW/g

Peak SAR (extrapolated) = 0.235 W/kg

SAR(1 g) = 0.150 mW/g; SAR(10 g) = 0.0925 mW/g




Fig. 18: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, Active cover with headset, GSM mode 1 TX (13.09.2004; Ambient Temperature: 21.8° C; Liquid Temperature : 20.7° C).

4 SAR Distribution Plots, PCS 1900 Body with data cable (gap = 22 mm)

Test Laboratory: IMST GmbH; File Name: [ARCphm_2.da4](#)

DUT: Siemens; Type: CX 70E; Serial: 004999003278248

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.55$; mho/m, $\epsilon_r = 51.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.57, 4.57, 4.57); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 8.7 V/m; Power Drift = -0.192 dB

Maximum value of SAR (measured) = 0.697 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.7 V/m; Power Drift = -0.192 dB

Maximum value of SAR (measured) = 0.702 mW/g

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.641 mW/g; SAR(10 g) = 0.377 mW/g




Fig. 19: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, ARC cover with data cable, GPRS mode2 TX (13.09.2004; Ambient Temperature: 21.7° C; Liquid Temperature : 20.7° C).

Test Laboratory: IMST GmbH; **File Name:** [Actphm_2.da4](#)

DUT: Siemens; **Type:** CX 70E; **Serial:** 004999003278248

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.55$; mho/m, $\epsilon_r = 51.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.57, 4.57, 4.57); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 9.18 V/m; Power Drift = -0.104 dB

Maximum value of SAR (measured) = 0.289 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.18 V/m; Power Drift = -0.104 dB

Maximum value of SAR (measured) = 0.310 mW/g

Peak SAR (extrapolated) = 0.458 W/kg

SAR(1 g) = 0.286 mW/g; SAR(10 g) = 0.176 mW/g




Fig. 20: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, Active cover with data cable, GPRS mode 2 TX (13.09.2004; Ambient Temperature: 21.8° C; Liquid Temperature : 20.7° C).

5 SAR Distribution Plots, PCS 1900 Body PTT mode (gap = 25 mm)

Test Laboratory: IMST GmbH; File Name: [ARCphm_3.da4](#)

DUT: Siemens; Type: CX 70E; Serial: 004999003278248

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.55$; mho/m, $\epsilon_r = 51.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.57, 4.57, 4.57); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 6.93 V/m; Power Drift = 0.073 dB

Maximum value of SAR (measured) = 0.149 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.93 V/m; Power Drift = 0.073 dB

Maximum value of SAR (measured) = 0.155 mW/g

Peak SAR (extrapolated) = 0.214 W/kg

SAR(1 g) = 0.144 mW/g; SAR(10 g) = 0.094 mW/g




Fig. 21: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the ground, ARC cover in PTT mode, 2 TX (13.09.2004; Ambient Temperature: 21.7° C; Liquid Temperature : 20.7° C).

Test Laboratory: IMST GmbH; **File Name:** [Actphm_3.da4](#)

DUT: Siemens; **Type:** CX 70E; **Serial:** 004999003278248

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.55$; mho/m, $\epsilon_r = 51.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1579; ConvF(4.57, 4.57, 4.57); Calibrated: 01.09.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.2 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 112

Body Worn/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Reference Value = 7.73 V/m; Power Drift = -0.073 dB

Maximum value of SAR (measured) = 0.135 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.73 V/m; Power Drift = -0.073 dB

Maximum value of SAR (measured) = 0.145 mW/g

Peak SAR (extrapolated) = 0.200 W/kg

SAR(1 g) = 0.135 mW/g; SAR(10 g) = 0.087 mW/g




Fig. 22: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, Active cover in PTT mode, 2 TX (13.09.2004; Ambient Temperature: 21.8° C; Liquid Temperature : 20.7° C).

6 SAR z-axis scans (Validation)




Fig. 23: SAR versus liquid depth, 1900 MHz, head (16.09.2004; Ambient Temperature: 20.6° C; Liquid Temperature : 19.9° C).




Fig. 24: SAR versus liquid depth, 1900 MHz, body (13.09.2004; Ambient Temperature: 20.9° C; Liquid Temperature : 20.4° C).

7 SAR z-axis scans (Measurements)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 25: SAR versus liquid depth, head: with flash, PCS 1900, channel 661, tilted position, left side of head with ARC cover. (16.09.2004, Ambient Temperature: 20.8° C; Liquid Temperature : 20.1° C).




Fig. 26: SAR versus liquid depth: PCS 1900 body, channel 661, body worn configuration, antenna towards the phantom, data cable, 2 TX with ARC cover (13.09.2004, Ambient Temperature: 21.7° C; Liquid Temperature : 20.7° C).