
Appendix for the Report

Dosimetric Assessment of the BenQ Siemens E71 (FCC ID: PWX-E71)

According to the FCC Requirements

SAR Distribution Plots

July 24, 2006
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
BenQ Mobile GmbH & Co OHG
Haidenauplatz 1
D-81667 München

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written
approval of the testing laboratory.

Table of Contents

1	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD	3
2	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WORN CONFIGURATION.....	8
3	SAR Z-AXIS SCANS (VALIDATION)	12
4	SAR Z-AXIS SCANS (MEASUREMENTS).....	13

1 SAR Distribution Plots, PCS 1900 Head

Test Laboratory: Imst GmbH, DASY Yellow (II); File Name: [742yplm_1.da4](#)

DUT: BenQ Siemenes ; Type: E71; Serial: 004401490055742

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.99, 4.99, 4.99); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 11.07.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.399 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.0 V/m; Power Drift = -0.122 dB

Peak SAR (extrapolated) = 0.681 W/kg

SAR(1 g) = 0.403 mW/g; SAR(10 g) = 0.237 mW/g

Maximum value of SAR (measured) = 0.442 mW/g




Fig. 1: SAR distribution for PCS 1900, channel 661, cheek position, left side of head (July 18, 2006; Ambient Temperature: 22.3° C; Liquid Temperature : 21.5° C).

Test Laboratory: Imst GmbH, DASY Yellow (II); **File Name:** [742yplm 2.da4](#)

DUT: BenQ Siemenes ; **Type:** E71; **Serial:** 004401490055742

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.99, 4.99, 4.99); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 11.07.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Tilted Left/Area Scan (7x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.351 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.5 V/m; Power Drift = 0.017 dB

Peak SAR (extrapolated) = 0.542 W/kg

SAR(1 g) = 0.339 mW/g; SAR(10 g) = 0.191 mW/g

Maximum value of SAR (measured) = 0.379 mW/g




Fig. 2: SAR distribution for PCS 1900, channel 661, tilted position, left side of head (July 18, 2006; Ambient Temperature: 22.3° C; Liquid Temperature : 21.5° C).

Test Laboratory: Imst GmbH, DASY Yellow (II); **File Name:** [742yprm_1.da4](#)

DUT: BenQ Siemenes ; **Type:** E71; **Serial:** 004401490055742

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.99, 4.99, 4.99); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 11.07.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Cheek Right/Area Scan (6x10x1): Measurement grid: $dx=15$ mm, $dy=15$ mm

Maximum value of SAR (measured) = 0.285 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 14.9 V/m; Power Drift = 0.047 dB

Peak SAR (extrapolated) = 0.434 W/kg

SAR(1 g) = 0.290 mW/g; SAR(10 g) = 0.173 mW/g

Maximum value of SAR (measured) = 0.318 mW/g




Fig. 3: SAR distribution for PCS 1900, channel 661, cheek position, right side of head (July 18, 2006; Ambient Temperature: 22.3° C; Liquid Temperature : 21.5° C).

Test Laboratory: Imst GmbH, DASY Yellow (II); **File Name:** [742yprm 2.da4](#)

DUT: BenQ Siemenes ; **Type:** E71; **Serial:** 004401490055742

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.99, 4.99, 4.99); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 11.07.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Tilted Right/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.290 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.1 V/m; Power Drift = 0.007 dB

Peak SAR (extrapolated) = 0.417 W/kg

SAR(1 g) = 0.269 mW/g; SAR(10 g) = 0.154 mW/g

Maximum value of SAR (measured) = 0.298 mW/g




Fig. 4: SAR distribution for PCS 1900, channel 661, tilted position, right side of head (July 18, 2006; Ambient Temperature: 22.3 °C; Liquid Temperature : 21.5° C)

Test Laboratory: Imst GmbH, DASY Yellow (II); **File Name:** [742yplm_1_BT.da4](#)

DUT: BenQ Siemenes ; **Type:** E71; **Serial:** 004401490055742

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 39.7$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.99, 4.99, 4.99); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 11.07.2006
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Cheek Left/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.413 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.4 V/m; Power Drift = -0.136 dB

Peak SAR (extrapolated) = 0.696 W/kg

SAR(1 g) = 0.406 mW/g; SAR(10 g) = 0.239 mW/g

Maximum value of SAR (measured) = 0.445 mW/g




Fig. 5: SAR distribution for PCS 1900 at worst case position with Bluetooth activated, channel 661, cheek position, left side of head (July 18, 2006; Ambient Temperature: 22.3 °C; Liquid Temperature : 21.5° C)

2 SAR Distribution Plots, PCS 1900 Body worn configuration

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [742bphm_5_ohne_20mm.da4](#)

DUT: BenQ Siemenes ; Type: E71; Serial: 004401490055742

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 51.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.84, 7.84, 7.84); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.03.2006
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body Worn/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.185 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.26 V/m; Power Drift = -0.173 dB

Peak SAR (extrapolated) = 0.305 W/kg

SAR(1 g) = 0.192 mW/g; SAR(10 g) = 0.115 mW/g

Maximum value of SAR (measured) = 0.208 mW/g




Fig. 6: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, without accessory, with 20 mm distance (July 18, 2006; Ambient Temperature: 22.1° C; Liquid Temperature: 21.4° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [742bphm 6 headset 20mm.da4](#)

DUT: BenQ Siemenes ; **Type:** E71; **Serial:** 004401490055742

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 51.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.84, 7.84, 7.84); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.03.2006
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body Worn/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.187 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.93 V/m; Power Drift = -0.133 dB

Peak SAR (extrapolated) = 0.308 W/kg

SAR(1 g) = 0.194 mW/g; SAR(10 g) = 0.116 mW/g

Maximum value of SAR (measured) = 0.210 mW/g




Fig. 7: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, with headset, with 20 mm distance (July 18, 2006; Ambient Temperature: 22.1° C; Liquid Temperature: 21.4° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [742bphm 7 BT 20mm.da4](#)

DUT: BenQ Siemenes ; **Type:** E71; **Serial:** 004401490055742

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 51.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.84, 7.84, 7.84); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.03.2006
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body Worn/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.194 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.06 V/m; Power Drift = 0.094 dB

Peak SAR (extrapolated) = 0.306 W/kg

SAR(1 g) = 0.190 mW/g; SAR(10 g) = 0.113 mW/g

Maximum value of SAR (measured) = 0.207 mW/g




Fig. 8: SAR distribution for GSM 1900, channel 661, body worn configuration, antenna towards the phantom, without accessory with Bluetooth activated, with 20 mm distance (July 18, 2006; Ambient Temperature: 22.1° C; Liquid Temperature: 21.4° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [742bphm 8 data 20mm.da4](#)

DUT: BenQ Siemenes ; **Type:** E71; **Serial:** 004401490055742

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 51.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.84, 7.84, 7.84); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 09.03.2006
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body Worn/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.383 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.78 V/m; Power Drift = -0.019 dB

Peak SAR (extrapolated) = 0.638 W/kg

SAR(1 g) = 0.402 mW/g; SAR(10 g) = 0.243 mW/g

Maximum value of SAR (measured) = 0.434 mW/g




Fig. 9: SAR distribution for GPRS 1900, channel 661, body worn configuration, antenna towards the phantom, with data cable, with 20 mm distance (July 18, 2006; Ambient Temperature: 22.1° C; Liquid Temperature: 21.4° C).

3 SAR z-axis scans (Validation)




Fig. 10: SAR versus liquid depth, 1900 MHz, head (July 18, 2006; Ambient Temperature: 22.1° C; Liquid Temperature : 21.3° C).




Fig. 11: SAR versus liquid depth, 1900 MHz, body (July 18, 2006; Ambient Temperature: 22.3° C; Liquid Temperature : 21.6° C).

4 SAR z-axis scans (Measurements)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 12: SAR versus liquid depth, head: PCS 1900, channel 661, cheek position, left side of head, with Bluetooth activated (July 18, 2006; Ambient Temperature: 22.3° C; Liquid Temperature : 21.5° C).




Fig. 13: SAR versus liquid depth, body: GPRS 1900, channel 661, data cable, with 20 mm distance (July 18, 2006; Ambient Temperature: 22.1° C; Liquid Temperature: 21.4° C).