
Appendix for the Report

Dosimetric Assessment of the BenQ Siemens EL71 (FCC ID: PWX-EL71)

According to the FCC Requirements

SAR Distribution Plots

March 13, 2006
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
BenQ Denmark Aps
Siemens Kaj 1
DK-9400 Norresundby

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written
approval of the testing laboratory.

Table of Contents

1	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD, SLIDER UP.....	3
2	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD, SLIDER DOWN.....	7
3	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD, SLIDER DOWN, BT ACTIVATED	11
4	SAR DISTRIBUTION PLOTS, PCS 1900 BODY	12
5	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WITH FCL 170 CARRY CASE.....	16
6	SAR Z-AXIS SCANS (VALIDATION)	18
7	SAR Z-AXIS SCANS (MEASUREMENTS).....	19

1 SAR Distribution Plots, PCS 1900 Head, slider up

Test Laboratory: Imst GmbH; File Name: [865yplm_1_su.da4](#)

DUT: BenQ; Type: EL71; Serial: 004400016196865

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.25, 8.25, 8.25); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn909; Calibrated: 20.10.2005
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.404 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.58 V/m; Power Drift = -0.104 dB

Peak SAR (extrapolated) = 0.680 W/kg

SAR(1 g) = 0.409 mW/g; SAR(10 g) = 0.230 mW/g

Maximum value of SAR (measured) = 0.450 mW/g




Fig. 1: SAR distribution for PCS 1900, channel 661, cheek position, left side of head (March 07, 2006; Ambient Temperature: 22.0° C; Liquid Temperature: 21.0° C).

Test Laboratory: Imst GmbH; **File Name:** [865yplm 2 su.da4](#)

DUT: BenQ; **Type:** EL71; **Serial:** 004400016196865

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.25, 8.25, 8.25); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn909; Calibrated: 20.10.2005
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Tilted Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.187 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.50 V/m; Power Drift = -0.001 dB

Peak SAR (extrapolated) = 0.275 W/kg

SAR(1 g) = 0.175 mW/g; SAR(10 g) = 0.108 mW/g

Maximum value of SAR (measured) = 0.188 mW/g




Fig. 2: SAR distribution for PCS 1900, channel 661, tilted position, left side of head (March 07, 2006; Ambient Temperature: 22.0°C; Liquid Temperature: 21.0°C).

Test Laboratory: Imst GmbH; File Name: [865yprm_1_su.da4](#)

DUT: BenQ; Type: EL71; Serial: 004400016196865

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.25, 8.25, 8.25); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn909; Calibrated: 20.10.2005
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.276 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.02 V/m; Power Drift = 0.120 dB

Peak SAR (extrapolated) = 0.427 W/kg

SAR(1 g) = 0.267 mW/g; SAR(10 g) = 0.158 mW/g

Maximum value of SAR (measured) = 0.295 mW/g




Fig. 3: SAR distribution for PCS 1900, channel 661, cheek position, right side of head (March 07, 2006; Ambient Temperature: 22.1°C; Liquid Temperature: 21.0°C).

Test Laboratory: Imst GmbH; **File Name:** [865yprm 2 su.da4](#)

DUT: BenQ; **Type:** EL71; **Serial:** 004400016196865

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.25, 8.25, 8.25); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn909; Calibrated: 20.10.2005
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.206 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.23 V/m; Power Drift = -0.050 dB

Peak SAR (extrapolated) = 0.380 W/kg

SAR(1 g) = 0.231 mW/g; SAR(10 g) = 0.134 mW/g

Maximum value of SAR (measured) = 0.253 mW/g




Fig. 4: SAR distribution for PCS 1900, channel 661, tilted position, right side of head (March 07, 2006; Ambient Temperature: 22.1°C; Liquid Temperature: 21.1°C)

2 SAR Distribution Plots, PCS 1900 Head, slider down

Test Laboratory: Imst GmbH; File Name: [865yplm_1_sd.da4](#)

DUT: BenQ; Type: EL71; Serial: 004400016196865

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.25, 8.25, 8.25); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn909; Calibrated: 20.10.2005
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Cheek Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.405 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.29 V/m; Power Drift = 0.056 dB

Peak SAR (extrapolated) = 0.676 W/kg

SAR(1 g) = 0.372 mW/g; SAR(10 g) = 0.212 mW/g

Maximum value of SAR (measured) = 0.417 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.29 V/m; Power Drift = 0.056 dB

Peak SAR (extrapolated) = 0.658 W/kg

SAR(1 g) = 0.394 mW/g; SAR(10 g) = 0.233 mW/g

Maximum value of SAR (measured) = 0.427 mW/g




Fig. 5: SAR distribution for PCS 1900, channel 661, cheek position, left side of head (March 07, 2006; Ambient Temperature: 22.1° C; Liquid Temperature : 21.1° C).

Test Laboratory: Imst GmbH; File Name: [865yplm 2 sd.da4](#)

DUT: BenQ; Type: EL71; Serial: 004400016196865

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.25, 8.25, 8.25); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn909; Calibrated: 20.10.2005
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Tilted Left/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.216 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 12.0 V/m; Power Drift = -0.060 dB

Peak SAR (extrapolated) = 0.338 W/kg

SAR(1 g) = 0.215 mW/g; SAR(10 g) = 0.128 mW/g

Maximum value of SAR (measured) = 0.235 mW/g




Fig. 6: SAR distribution for PCS 1900, channel 661, tilted position, left side of head (March 07, 2006; Ambient Temperature: 22.1°C; Liquid Temperature: 21.1°C).

Test Laboratory: Imst GmbH; **File Name:** [865yprm_1_sd.da4](#)

DUT: BenQ; **Type:** EL71; **Serial:** 004400016196865

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.25, 8.25, 8.25); Calibrated: 23.09.2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn909; Calibrated: 20.10.2005

- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340

- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.398 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.20 V/m; Power Drift = -0.008 dB

Peak SAR (extrapolated) = 0.749 W/kg

SAR(1 g) = 0.412 mW/g; SAR(10 g) = 0.228 mW/g

Maximum value of SAR (measured) = 0.444 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.20 V/m; Power Drift = -0.008 dB

Peak SAR (extrapolated) = 0.416 W/kg

SAR(1 g) = 0.269 mW/g; SAR(10 g) = 0.171 mW/g

Maximum value of SAR (measured) = 0.310 mW/g




Fig. 7: SAR distribution for PCS 1900, channel 661, cheek position, right side of head (March 07, 2006; Ambient Temperature: 22.1°C; Liquid Temperature: 21.1°C).

Test Laboratory: Imst GmbH; File Name: [865yprm 2 sd.da4](#)

DUT: BenQ; Type: EL71; Serial: 004400016196865

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.25, 8.25, 8.25); Calibrated: 23.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn909; Calibrated: 20.10.2005
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Tilted Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.218 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.92 V/m; Power Drift = -0.057 dB

Peak SAR (extrapolated) = 0.389 W/kg

SAR(1 g) = 0.241 mW/g; SAR(10 g) = 0.141 mW/g

Maximum value of SAR (measured) = 0.266 mW/g




Fig. 8: SAR distribution for PCS 1900, channel 661, tilted position, right side of head (March 07, 2006; Ambient Temperature: 22.1°C; Liquid Temperature: 21.1°C)

3 SAR Distribution Plots, PCS 1900 Head, slider down, BT activated

Test Laboratory: Imst GmbH; File Name: [865yprm_1_BT_sd.da4](#)

DUT: BenQ; Type: EL71; Serial: 004400016196865

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.41$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(8.25, 8.25, 8.25); Calibrated: 23.09.2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE4 Sn909; Calibrated: 20.10.2005

- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340

- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Cheek Right/Area Scan (6x10x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.382 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.32 V/m; Power Drift = 0.093 dB

Peak SAR (extrapolated) = 0.731 W/kg

SAR(1 g) = 0.401 mW/g; SAR(10 g) = 0.220 mW/g

Maximum value of SAR (measured) = 0.436 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.32 V/m; Power Drift = 0.093 dB

Peak SAR (extrapolated) = 0.359 W/kg

SAR(1 g) = 0.251 mW/g; SAR(10 g) = 0.161 mW/g

Maximum value of SAR (measured) = 0.269 mW/g




Fig. 9: SAR distribution for PCS 1900, channel 661, cheek position, right side of head (March 07, 2006; Ambient Temperature: 22.1°C; Liquid Temperature: 21.1°C).

4 SAR Distribution Plots, PCS 1900 Body

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [865bphm_4_ohne_15mm.da4](#)

DUT: BenQ; Type: EL71; Serial: 004400016196865

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ mho/m; $\epsilon_r = 51.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.47, 4.47, 4.47); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.213 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.5 V/m; Power Drift = -0.191 dB

Peak SAR (extrapolated) = 0.315 W/kg

SAR(1 g) = 0.203 mW/g; SAR(10 g) = 0.131 mW/g

Maximum value of SAR (measured) = 0.217 mW/g




Fig. 10: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, without accessory 15 mm distance (March 10, 2006; Ambient Temperature: 22.1° C; Liquid Temperature: 21.3° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [865bphm 5 headset 15mm.da4](#)

DUT: BenQ; **Type:** EL71; **Serial:** 004400016196865

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ mho/m; $\epsilon_r = 51.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.47, 4.47, 4.47); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.221 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.9 V/m; Power Drift = -0.028 dB

Peak SAR (extrapolated) = 0.383 W/kg

SAR(1 g) = 0.210 mW/g; SAR(10 g) = 0.120 mW/g

Maximum value of SAR (measured) = 0.227 mW/g




Fig. 11: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, with headset, with 15 mm distance (March 10, 2006; Ambient Temperature: 22.1° C; Liquid Temperature: 21.3° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [865bphm 6 data 15mm.da4](#)

DUT: BenQ; **Type:** EL71; **Serial:** 004400016196865

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ mho/m; $\epsilon_r = 51.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.47, 4.47, 4.47); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.338 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.3 V/m; Power Drift = -0.163 dB

Peak SAR (extrapolated) = 0.581 W/kg

SAR(1 g) = 0.333 mW/g; SAR(10 g) = 0.196 mW/g

Maximum value of SAR (measured) = 0.361 mW/g




Fig. 12: SAR distribution for GPRS 1900 (Class10), channel 661, body worn configuration, antenna towards the phantom, with data cable, with 15 mm distance (March 10, 2006; Ambient Temperature: 22.0° C; Liquid Temperature: 21.2° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [865bphm 11 ohne 15mm BT.da4](#)

DUT: BenQ; **Type:** EL71; **Serial:** 004400016196865

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ mho/m; $\epsilon_r = 51.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.47, 4.47, 4.47); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.337 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 14.2 V/m; Power Drift = -0.060 dB

Peak SAR (extrapolated) = 0.588 W/kg

SAR(1 g) = 0.325 mW/g; SAR(10 g) = 0.192 mW/g

Maximum value of SAR (measured) = 0.352 mW/g




Fig. 13: SAR distribution for GPRS 1900 (Class 10), channel 661, body worn configuration, antenna towards the phantom, with Bluetooth activated, with 15 mm distance (March 10, 2006; Ambient Temperature: 22.0° C; Liquid Temperature: 21.2° C).

5 SAR Distribution Plots, PCS 1900 Body with FCL 170 carry case

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [865bphm_15_FCL170_BT_1_wdh.da4](#)

DUT: BenQ; Type: EL71; Serial: 004400016196865

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ mho/m; $\epsilon_r = 51.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.47, 4.47, 4.47); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.203 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 10.8 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 0.348 W/kg

SAR(1 g) = 0.193 mW/g; SAR(10 g) = 0.108 mW/g

Maximum value of SAR (measured) = 0.210 mW/g




Fig. 14: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, with Bluetooth activated 15 mm distance (March 10, 2006; Ambient Temperature: 22.0° C; Liquid Temperature: 21.2° C).

Test Laboratory: IMST GmbH, DASY Blue (I); **File Name:** [865bphm 15 FCL170 BT 2 wdh.da4](#)

DUT: BenQ; **Type:** EL71; **Serial:** 004400016196865

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.57$ mho/m; $\epsilon_r = 51.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.47, 4.47, 4.47); Calibrated: 15.02.2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 07.07.2005
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.6 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 159

Body Worn/Area Scan (7x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.421 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 15.5 V/m; Power Drift = -0.017 dB

Peak SAR (extrapolated) = 0.706 W/kg

SAR(1 g) = 0.389 mW/g; SAR(10 g) = 0.216 mW/g

Maximum value of SAR (measured) = 0.425 mW/g




Fig. 15: SAR distribution for GPRS 1900 (Class 10), channel 661, body worn configuration, antenna towards the phantom, with Bluetooth activated, with 15 mm distance (March 10, 2006; Ambient Temperature: 22.0° C; Liquid Temperature: 21.2° C).

6 SAR z-axis scans (Validation)




Fig. 16: SAR versus liquid depth, 1900 MHz, head (March 07, 2006; Ambient Temperature: 22.0° C; Liquid Temperature : 21.0° C).




Fig. 17: SAR versus liquid depth, 1900 MHz, body (March 10, 2006; Ambient Temperature: 22.0° C; Liquid Temperature : 21.0° C).

7 SAR z-axis scans (Measurements)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 18: SAR versus liquid depth, head: PCS 1900, channel 661, cheek position, right side of head, slider down (March 07, 2006; Ambient Temperature: 22.1° C; Liquid Temperature : 21.1° C).




Fig. 19: SAR versus liquid depth, body: GPRS 1900 (Class 10), channel 661, body worn configuration, antenna towards the phantom, with data cable, with 15 mm distance (March 10, 2006; Ambient Temperature: 22.0° C; Liquid Temperature: 21.2° C).