
Appendix for the Report

Dosimetric Assessment of the Siemens SP65 (FCC ID: PWX-SP65)

According to the FCC Requirements

SAR Distribution Plots

February 08, 2005
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
Siemens Information & Communication Mobile LLC
16475 West Bernado Dirve, Suite 400
CA 92127 San Diego

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written
approval of the testing laboratory.

Table of Contents

1	SAR DISTRIBUTION PLOTS, PCS 1900 HEAD	3
2	SAR DISTRIBUTION PLOTS, PCS 1900 BODY WITH HEADSET IN GSM MODE	8
3	SAR DISTRIBUTION PLOTS, GPRS 1900 (CLASS 10).....	9
4	SAR Z-AXIS SCANS (VALIDATION)	11
5	SAR Z-AXIS SCANS (MEASUREMENTS).....	12

1 SAR Distribution Plots, PCS 1900 head

Test Laboratory: IMST GmbH; File Name: [730bplm_1.da4](#); DUT: Siemens; Type: SP65; Serial: 353910009449730

Program Name: Cheek Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.43$; mho/m, $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(5.28, 5.28, 5.28); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.3 Build 16; Postprocessing SW: SEMCAD, V1.8 Build 127

Cheek Left/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.359 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.8 V/m; Power Drift = 0.113 dB

Peak SAR (extrapolated) = 0.610 W/kg

SAR(1 g) = 0.351 mW/g; SAR(10 g) = 0.200 mW/g

Maximum value of SAR (measured) = 0.398 mW/g

Cheek Left/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 27.8 V/m; Power Drift = 0.113 dB

Peak SAR (extrapolated) = 0.431 W/kg

SAR(1 g) = 0.279 mW/g; SAR(10 g) = 0.179 mW/g

Maximum value of SAR (measured) = 0.302 mW/g




Fig. 1: SAR distribution for PCS 1900, channel 661, cheek position, left side of head (31.01.2005; Ambient Temperature: 21.8° C; Liquid Temperature: 20.9° C).

Test Laboratory: IMST GmbH; File Name: [730bplm 2.da4](#)

DUT: Siemens; Type: SP65; Serial: 353910009449730

Program Name: Tilted Left

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.43$; mho/m, $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(5.28, 5.28, 5.28); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.3 Build 16; Postprocessing SW: SEMCAD, V1.8 Build 127

Tilted Left/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.331 mW/g

Tilted Left/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 30.1 V/m; Power Drift = 0.035 dB

Peak SAR (extrapolated) = 0.508 W/kg

SAR(1 g) = 0.309 mW/g; SAR(10 g) = 0.177 mW/g

Maximum value of SAR (measured) = 0.334 mW/g




Fig. 2: SAR distribution for PCS 1900, channel 661, tilted position, left side of head (31.01.2005; Ambient Temperature: 21.8° C; Liquid Temperature : 20.9° C).

Test Laboratory: IMST GmbH; **File Name:** [730bprm_1.da4](#)

DUT: Siemens; **Type:** SP65; **Serial:** 353910009449730

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.43$; mho/m, $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(5.28, 5.28, 5.28); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.3 Build 16; Postprocessing SW: SEMCAD, V1.8 Build 127

Cheek Right/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.366 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.7 V/m; Power Drift = -0.105 dB

Peak SAR (extrapolated) = 0.556 W/kg

SAR(1 g) = 0.318 mW/g; SAR(10 g) = 0.175 mW/g

Maximum value of SAR (measured) = 0.362 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 24.7 V/m; Power Drift = -0.105 dB

Peak SAR (extrapolated) = 0.718 W/kg

SAR(1 g) = 0.389 mW/g; SAR(10 g) = 0.184 mW/g

Maximum value of SAR (measured) = 0.456 mW/g




Fig. 3: SAR distribution for PCS 1900, channel 661, cheek position, right side of head (31.01.2005; Ambient Temperature: 21.9° C; Liquid Temperature : 20.9° C).

Test Laboratory: IMST GmbH; File Name: [730bprm 2.da4](#)

DUT: Siemens; Type: SP65; Serial: 353910009449730

Program Name: Tilted Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.43$; mho/m, $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(5.28, 5.28, 5.28); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.3 Build 16; Postprocessing SW: SEMCAD, V1.8 Build 127

Tilted Right/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.218 mW/g

Tilted Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 27 V/m; Power Drift = 0.048 dB

Peak SAR (extrapolated) = 0.348 W/kg

SAR(1 g) = 0.223 mW/g; SAR(10 g) = 0.127 mW/g

Maximum value of SAR (measured) = 0.248 mW/g




Fig. 4: SAR distribution for PCS 1900, channel 661, tilted position, right side of head (31.01.2005; Ambient Temperature: 22.1° C; Liquid Temperature : 21.0° C).

Test Laboratory: IMST GmbH; **File Name:** [730bprm_1_BT.da4](#)

DUT: Siemens; **Type:** SP65; **Serial:** 353910009449730

Program Name: Cheek Right

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.43$; mho/m, $\epsilon_r = 40.5$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1579; ConvF(5.28, 5.28, 5.28); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn335; Calibrated: 05.08.2004
- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176
- Measurement SW: DASY4, V4.3 Build 16; Postprocessing SW: SEMCAD, V1.8 Build 130

Cheek Right/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.370 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.32 V/m; Power Drift = -0.032 dB

Peak SAR (extrapolated) = 0.581 W/kg

SAR(1 g) = 0.332 mW/g; SAR(10 g) = 0.180 mW/g

Maximum value of SAR (measured) = 0.376 mW/g

Cheek Right/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 9.32 V/m; Power Drift = -0.032 dB

Peak SAR (extrapolated) = 0.854 W/kg

SAR(1 g) = 0.452 mW/g; SAR(10 g) = 0.209 mW/g

Maximum value of SAR (measured) = 0.540 mW/g




Fig. 5: SAR distribution for PCS 1900, worst case with Bluetooth, channel 661, cheek position, right side of head (31.01.2005; Ambient Temperature: 22.0° C; Liquid Temperature : 21.0° C).

2 SAR Distribution Plots, PCS 1900 Body with headset in GSM mode

Test Laboratory: IMST GmbH; File Name: [730yphm_1.da4](#)

DUT: Siemens; Type: SP65; Serial: 353910009449730

Program Name: Body Worn

Communication System: GSM 1900; Frequency: 1880 MHz; Duty Cycle: 1:8.3

Medium parameters used: $\sigma = 1.57$; mho/m, $\epsilon_r = 54.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.52, 4.52, 4.52); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2004
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body Worn/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.102 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.5 V/m; Power Drift = 0.083 dB

Peak SAR (extrapolated) = 0.148 W/kg

SAR(1 g) = 0.103 mW/g; SAR(10 g) = 0.067 mW/g

Maximum value of SAR (measured) = 0.110 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.5 V/m; Power Drift = 0.083 dB

Peak SAR (extrapolated) = 0.146 W/kg

SAR(1 g) = 0.099 mW/g; SAR(10 g) = 0.062 mW/g

Maximum value of SAR (measured) = 0.108 mW/g




Fig. 6: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, with headset, gap = 22mm (02.02.2005; Ambient Temperature: 21.8° C; Liquid Temperature : 20.9° C).

3 SAR Distribution Plots, GPRS 1900 (Class 10)

Test Laboratory: IMST GmbH; File Name: [730yphm_3.da4](#)

DUT: Siemens; Type: SP65; Serial: 353910009449730

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.57$; mho/m, $\epsilon_r = 54.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.52, 4.52, 4.52); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2004
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body Worn/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.230 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.7 V/m; Power Drift = 0.116 dB

Peak SAR (extrapolated) = 0.334 W/kg

SAR(1 g) = 0.227 mW/g; SAR(10 g) = 0.147 mW/g

Maximum value of SAR (measured) = 0.243 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.7 V/m; Power Drift = 0.116 dB

Peak SAR (extrapolated) = 0.323 W/kg

SAR(1 g) = 0.220 mW/g; SAR(10 g) = 0.143 mW/g

Maximum value of SAR (measured) = 0.236 mW/g




Fig. 7: SAR distribution for PCS 1900, worst case with Bluetooth channel 661, body worn configuration, antenna towards the phantom, GPRS 1900 (Class 10), Gap = 22mm (02.02.2005; Ambient Temperature: 21.9° C; Liquid Temperature : 20.9° C).

Test Laboratory: IMST GmbH; File Name: [730yphm_5.da4](#)

DUT: Siemens; Type: SP65; Serial: 353910009449730

Program Name: Body Worn

Communication System: GPRS 1900; Frequency: 1880 MHz; Duty Cycle: 1:4

Medium parameters used: $\sigma = 1.57$; mho/m, $\epsilon_r = 54.4$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6R - SN1669; ConvF(4.52, 4.52, 4.52); Calibrated: 13.01.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn631; Calibrated: 23.07.2004
- Phantom: SAM Glycol 1340; Type: QD 000 P40 CB; Serial: TP-1340
- Measurement SW: DASY4, V4.3 Build 22; Postprocessing SW: SEMCAD, V1.8 Build 127

Body Worn/Area Scan (6x11x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.227 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.4 V/m; Power Drift = 0.034 dB

Peak SAR (extrapolated) = 0.329 W/kg

SAR(1 g) = 0.225 mW/g; SAR(10 g) = 0.146 mW/g

Maximum value of SAR (measured) = 0.242 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.4 V/m; Power Drift = 0.034 dB

Peak SAR (extrapolated) = 0.320 W/kg

SAR(1 g) = 0.217 mW/g; SAR(10 g) = 0.140 mW/g

Maximum value of SAR (measured) = 0.233 mW/g




Fig. 8: SAR distribution for PCS 1900, channel 661, body worn configuration, antenna towards the phantom, GPRS 1900 (Class 10), Gap = 22mm (02.02.2005; Ambient Temperature: 22.0° C; Liquid Temperature : 20.9° C).

4 SAR z-axis scans (Validation)




Fig. 9: SAR versus liquid depth, 1900 MHz, head (31.01.2005; Ambient Temperature: 21.8° C; Liquid Temperature : 20.9° C).




Fig. 10: SAR versus liquid depth, 1900 MHz, body (02.02.2005; Ambient Temperature: 21.9° C; Liquid Temperature : 21.1° C).

5 SAR z-axis scans (Measurements)

The following pictures show the plots of SAR versus liquid depth for the worst case values.




Fig. 11: SAR versus liquid depth, head: PCS 1900, channel 661, tilted position, right side of head with Bluetooth (31.01.2005, Ambient Temperature: 22.0° C; Liquid Temperature : 21.0° C).




Fig. 12: SAR versus liquid depth: PCS 1900, channel 661, body worn configuration, antenna towards the phantom, GPRS 1900 (Class10) with Bluetooth (02.02.2005, Ambient Temperature: 21.9° C; Liquid Temperature: 20.9° C).