

Test Report

Conducted Output power GSM 900 / 1800 / 1900

Report No:
Issue date: Sep 14th, 2005

Test Sites: COM MD PD ST2 BEJ
Development Center BEJ

Phone: +86 10 64721888
Fax: +86 10 64720276

Wang Tao
RF Test Engineer, System Test

Wang Tao
Sep 23 2005

Contents

1 Objective and Method3

2 Results.....3

2.1 GSM 8503

2.2 GSM 18003

2.3 GSM 19003

3 Minutes of Test4

3.1 Description of device under test4

3.2 Measurement Set-up4

4 Calibration Certificate5

1 Objective and Method

FCC approval for mobile phones requires reporting output power at RF output terminal pursuant to title 47 CFR part 2.1046. SIEMENS devices use special test fixtures with 50 Ohm connection suitable for such measurements. Using a special adapter and connecting the phone to an appropriate load in terms of the input port of the measurement equipment used, we hereby report the values for highest power setting.

2 Results

2.1 GSM 900

Device	Average Power during burst at connector		
	Ch. 128 824.2 MHz	Ch. 190 836.6 MHz	Ch. 251 893.8 MHz
004400015459371	32.3	31.8	31.8
004400015459157	32.3	31.7	31.6
004400015459348	32.4	31.8	31.7

Table 1: Results of power measurements at connector in the GSM 900 Band

2.2 GSM 1800

Device	Average Power during burst at connector		
	Ch. 512 1710.2 MHz	Ch. 698 1747.4 MHz	Ch. 885 1784.8 MHz
004400015459371	29.2	29.7	29.6
004400015459157	29.0	29.5	29.5
004400015459348	29.2	29.6	29.6

Table 2: Results of power measurements at connector in the GSM 1800 Band

2.3 GSM 1900

Device	Average Power during burst at connector		
	Ch. 512 1850.2 MHz	Ch. 661 1880.0 MHz	Ch. 810 1909.8 MHz
004400015459371	29.8	29.4	29.2
004400015459157	29.7	29.3	29.0
004400015459348	29.8	29.4	29.2


Table 3: Results of power measurements at connector in the GSM 1900 Band

3 Minutes of Test

3.1 Description of device under test

Mobile Phone:	Siemens A70
Frequency Range GSM 900:	880 – 915 MHz
Frequency Range GSM 1800:	1710 – 1785 MHz
Frequency Range GSM 1900:	1850 – 1990 MHz
Siemens Part Number:	S30880-Q2710-****_*

3.2 Measurement Set-up



Base Station Simulator:	CMU 200
Serial Number:	106703
Software Version:	Base 3.61 / GSM 3.62

Figure 1: Block Diagram of set-up for conducted power measurement




Figure 2: Set-up for conducted power measurement

4 Calibration Certificate


ROHDE & SCHWARZ

Messgerätebau GmbH

Kalibrierschein
Calibration Certificate
Nummer 20-145110

Number
Gegenstand
Item CMU200 UNIV.RADIOCOMM.

Hersteller
Manufacturer ROHDE & SCHWARZ

Typ
Type CMU200

Material Nr.
Material No. 1100.0008K02

Serial Nr.
Serial No. 106703

Auftraggeber
Customer
Bestellung Nr.
Order No.
Ort u. Datum d. Kalibrierung
Place and date of calibration Memmingen, 2004-12-16

Umfang der Kalibrierung
Scope of calibration Standard Calibration

Eingangsprüfung
Performance on receipt
Kalibrierergebnis
Result of calibration Measurement results within specifications

Umfang des Kalibrierscheins
Extent of the certificate 2 pages incl. this

Dieser Kalibrierschein dokumentiert, daß der genannte Gegenstand nach festgelegten Vorgaben geprüft und gemessen wurde. Die Meßwerte lagen im Regelfall mit einer Wahrscheinlichkeit von annähernd 95 % im zugeordneten Werteintervall (Erweiterte Meßunsicherheit mit $k = 2$).

Die Kalibrierung erfolgte mit Meßmitteln und Normen, die direkt oder indirekt durch Ableitung mittels anerkannter Kalibriertechniken rückgeführt sind auf Normale der PTB/DKD oder anderer nationaler/internationaler Standards zur Darstellung der physikalischen Einheiten in Übereinstimmung mit dem Internationalen Einheitensystem (SI). Wenn keine Normale existieren, erfolgt die Rückführung auf Bezugsnormale der R&S-Laboratorien.

Grundsätze und Verfahren der Kalibrierung entsprechen IEC/ISO 17025. Das Bestätigungssystem für die verwendeten Meßmittel entspricht DIN ISO 10012-1.

Das angewandte Qualitätsmanagement-System ist zertifiziert nach DIN EN ISO 9001.

Dieser Kalibrierschein darf nur vollständig und unverändert weiterverbreitet werden. Kalibrierscheine ohne Signifizierungen sind ungültig.

Für die Einhaltung einer angemessenen Frist zur Wiederholung der Kalibrierung ist der Benutzer verantwortlich.

This calibration certificate documents, that the named item is tested and measured against defined specifications.


Measurement results are located usually in the corresponding interval with a probability of approx. 95 % (coverage factor $k = 2$).

Calibration is performed with test equipment and standards directly or indirectly traceable by means of approved calibration techniques to the PTB/DKD or other national/international standards, which realize the physical units of measurement according to the International System of Units (SI). In all cases where no national standards are available, measurements are referenced to standards of the R&S laboratories.

Principles and methods of calibration correspond with IEC/ISO 17025. The metrological confirmation system for the measuring equipment used is in compliance with DIN ISO 10012-1. The applied quality system is certified to DIN EN ISO 9001.

This calibration certificate may not be reproduced other than in full. Calibration certificates without signatures are not valid.

The user is obliged to have the item recalibrated at appropriate intervals.


Ausstellungsdatum
Date of issue

2004-12-16

Laborleitung
Head of laboratory

 Stegmüller

Bearbeiter
Person responsible

 Alexander Bohl

Page 1/2

Rohde & Schwarz Messgerätebau GmbH · Postfach 1652 D-87696 Memmingen · Riedbachstraße 58 D-87700 Memmingen
 Telefon national: 08331/108-0; international: 0049 8331/108-0; Fax: 08331/108-124
 Geschäftsführer: Dipl.-Ing. Dipl.-Wirtsch.-Ing. Friedrich Schwarz · Aufsichtsratsvorsitzender: Ing. (grad) Heinz Ewald
 Sitz der Gesellschaft: München · Registeramt: Amtsgericht München HRB 1059