


# TEST REPORT



<b>Applicant</b>	JADA TOYS CO., LTD
<b>Address</b>	UNIT 315-318, TOWER A, NEW MANDARIN PLAZA, 14 SCIENCE MUSEUM ROAD, TST EASR, KOWLOON, HONGKONG

<b>Manufacturer or Supplier</b>	JADA TOYS CO., LTD	
<b>Address</b>	UNIT 315-318, TOWER A, NEW MANDARIN PLAZA, 14 SCIENCE MUSEUM ROAD, TST EASR, KOWLOON, HONGKONG	
<b>Product</b>	18" Buster The Dog	
<b>Brand Name</b>	N/A	
<b>Model</b>	84085	
<b>Additional Model &amp; Model Difference</b>	N/A	
<b>Date of tests</b>	Mar. 15~ 21, 2012	

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

**FCC Part 15, Subpart C (Section 15.227)**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Tested by Madison Luo Project Engineer / EMC Department	Approved by Sam Tung Manager / EMC Department
	
Date: Mar. 22, 2012	

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

## Table of Contents

RELEASE CONTROL RECORD .....	3
1 SUMMARY OF TEST RESULTS .....	4
1.1 MEASUREMENT UNCERTAINTY .....	5
2 GENERAL INFORMATION .....	6
2.1 GENERAL DESCRIPTION OF EUT .....	6
2.2 DESCRIPTION OF TEST MODES .....	7
2.3 DESCRIPTION OF SUPPORT UNITS .....	7
3 EMISSION TEST .....	8
3.1 CONDUCTED EMISSION MEASUREMENT .....	8
3.2 RADIATED EMISSION MEASUREMENT .....	8
3.2.1 TEST INSTRUMENTS .....	9
3.2.2 TEST PROCEDURE .....	10
3.2.3 DEVIATION FROM TEST STANDARD .....	11
3.2.4 TEST SETUP .....	11
3.2.5 EUT OPERATING CONDITIONS .....	11
3.2.6 TEST RESULTS .....	12
3.3 26DB BANDWIDTH OF FUNDAMENTAL EMISSION .....	14
3.3.1 LIMITS FOR 26DB BANDWIDTH OF FUNDAMENTAL EMISSION: .....	14
3.3.2 TEST INSTRUMENTS .....	14
3.3.3 TEST PROCEDURE .....	14
3.3.4 TEST RESULTS .....	15
3.4 DUTY CYCLE CORRECTION DURING 100MSEC: .....	16
3.4.1 TEST RESULTS .....	17
4 PHOTOGRAPHS OF TEST CONFIGURATION .....	18
5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	18



Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
Original release	N/A	Mar. 22, 2012



BUREAU  
VERITAS

Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Item	Result	Remark
15.207	Conducted Emission Test	N/A	-
15.209	Radiated Emission Test (30MHz ~ 1GHz)	PASS	Meets Class B Limit Minimum passing margin is -9.71 dB at 54.25 MHz
15.227	26dB Bandwidth	PASS	-
	Duty Cycle	PASS	-

**Note:** 1. The maximum emission levels were compared with the requirements in section 15.209, 15.227 of FCC Part 15 regulation.



**BUREAU  
VERITAS**

**Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007**

## 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

MEASUREMENT	FREQUENCY	UNCERTAINTY
Radiated emissions	30MHz ~ 1GHz	+/- 3.58 dB



**BUREAU  
VERITAS**

Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	18" Buster The Dog
<b>MODEL NO.</b>	84085
<b>POWER SUPPLY</b>	DC 9V Battery
<b>DATA CABLE SUPPLIED</b>	N/A
<b>OPERATING FREQUENCY</b>	27.145MHz

#### NOTE:

1. The EUT is a wireless remote.
2. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



**BUREAU  
VERITAS**

Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

## 2.2 DESCRIPTION OF TEST MODES


The EUT was tested under the following modes, the final worst mode were marked in boldface and recorded in this report.

<b>TXMode</b>
---------------

## 2.3 DESCRIPTION OF SUPPORT UNITS

N/A.

### TEST CONFIGURATION





**BUREAU  
VERITAS**

Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

### 3 EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

The EUT'S power provide by battery. no data about this item test.

#### 3.2 RADIATED EMISSION MEASUREMENT

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.227]:

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Peak] [ $\mu\text{V}/\text{m}$ ]	Field Strength of Fundamental Emission [Average] [ $\mu\text{V}/\text{m}$ ]
26.96 – 27.28	100,000 (100 dB $\mu\text{V}/\text{m}$ )	10,000 (80 dB $\mu\text{V}/\text{m}$ )

Limits for Radiated Emissions [FCC 47 CFR 15.209]:

Frequency Range [MHz]	Quasi-Peak Limits [ $\mu\text{V}/\text{m}$ ]
1.705-30	300
30-88	100
88-216	150
216-960	200
Above960	500

Note: (1) The lower limit shall apply at the transition frequencies.

(2) Emission level (dB $\mu\text{V}/\text{m}$ ) = 20 log Emission level ( $\mu\text{V}/\text{m}$ ).

(3) All emanation from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.





BUREAU  
VERITAS

Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

### 3.2.1 TEST INSTRUMENTS

#### Frequency Range 30MHz~1GHz

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pectrum Analyzer	Agilent	E4446A	MY46180622	Apr. 25,11	Apr. 25,12
EMI Test Receiver	Rohde&Schwarz	ESVD	847398/003	May 25,11	May 25,12
Bilog Antenna	Teseq	CBL 6111D	27089	Jul. 24,11	Jul. 24,12
10m Semi-anechoic Chamber	CHANGLING	21.4m*12.1m* 8.8m	NSEMC006	May 2,11	May 2,12
Pre-Amplifier (20MHz-3GHz)	EMCI	EMC 330	980095	Nov. 7,11	Nov. 7,12
Test Software	ADT	ADT_Radiated _V7.6.15	N/A	N/A	N/A

- NOTE:** 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA and NIM/CHINA.  
2. The test was performed in 10m Chamber.



Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

### 3.2.2 TEST PROCEDURE

The basic test procedure was in accordance with ANSI C63.4 (section 12).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meters Semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using new battery. The turntable was rotated to maximize the emission level.
- g. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.

#### NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
4. Margin value = Emission level – Limit value.
5. Fundamental AV value =PK value +duty cycle.



BUREAU VERITAS


Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

### 3.2.3 DEVIATION FROM TEST STANDARD


No deviation

### 3.2.4 TEST SETUP

Below 30MHz



About 30MHz~1GHz



### 3.2.5 EUT OPERATING CONDITIONS

- Turned on the power of all equipment.
- EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



BUREAU  
VERITAS

Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

### 3.2.6 TEST RESULT OF FUNDAMENTAL

#### Detection mode: Peak

Frequency (MHz)	antenna orientation (H/V) and table degree	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
27.145	V°/90°	18.73	69.01	100	-30.99

#### Detection mode: # Average

Frequency (MHz)	antenna orientation (H/V) and table degree	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
27.145	V°/90°	18.73	**63.59	80	-16.41

# For pulse modulated devices and using measuring equipment employing a peak detection mode, properly adjusted for such factor as pulse desensitisation.

\*\*Duty Cycle Correction =  $20\text{Log}(0.536) = -5.42\text{dB}$

Note: Field Strength includes Antenna Factor and Cable Loss.



BUREAU  
VERITAS

Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

### 3.2.7 TEST RESULTS OF OTHER

<b>TEST MODE</b>	TX Mode	<b>FREQUENCY RANGE</b>	30-1000MHz
<b>INPUT POWER</b>	DC 9V Battery	<b>DETECTOR FUNCTION &amp; RESOLUTION BANDWIDTH</b>	Quasi-Peak, 120kHz
<b>ENVIRONMENTAL CONDITIONS</b>	23 deg. C, 55% RH,	<b>TESTED BY:</b> Madison	

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	54.25	24.08	40.00	-15.92	194	357	14.67	9.41
2	135.08	21.26	43.50	-22.24	115	279	8.53	12.73
3	270.88	27.29	46.00	-18.71	145	309	12.26	15.03
4	298.37	22.76	46.00	-23.24	131	295	7.74	15.02
5	380.82	23.05	46.00	-22.95	198	262	5.94	17.11
6	830.25	29.80	46.00	-16.20	179	242	3.80	26.00

**REMARKS:** The emission levels of other frequencies were very low against the limit.

<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (cm)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	<b>54.25</b>	<b>30.29</b>	<b>40.00</b>	<b>-9.71</b>	<b>100</b>	<b>120</b>	<b>20.88</b>	<b>9.41</b>
2	81.73	19.07	40.00	-20.93	110	125	10.34	8.73
3	109.22	20.17	43.50	-23.33	132	128	8.14	12.03
4	135.08	23.54	43.50	-19.96	106	112	10.81	12.73
5	380.82	21.52	46.00	-24.48	120	55	4.41	17.11
6	406.68	22.36	46.00	-23.64	100	88	4.21	18.15

**REMARKS:** The emission levels of other frequencies were very low against the limit.

Bureau Veritas Shenzhen Co., Ltd.  
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie  
Town, Dongguan City,  
Guangdong 523942, China

Tel: +86 769 8593 5656  
Fax: +86 769 8593 1080  
Email: [customerservice.dg@cn.bureauveritas.com](mailto:customerservice.dg@cn.bureauveritas.com)



BUREAU  
VERITAS

Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

### 3.3 26DB BANDWIDTH OF FUNDAMENTAL EMISSION

#### 3.3.1 LIMITS FOR 26DB BANDWIDTH OF FUNDAMENTAL EMISSION:

FREQUENCY (MHz)	26dB Bandwidth	Limits
	[KHz]	[MHz]
27.145	52kHz	within 26.96 – 27.28

#### 3.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Pectrum Analyzer Agilent	E4446A	MY46180622	Apr. 25,11	Apr. 25,12

**NOTE:** 1. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA and NIM/CHINA.  
2. The test was performed in RF Room.

#### 3.3.3 TEST PROCEDURE

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.




BUREAU VERITAS

Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

### 3.3.4 TEST RESULTS

Test Result of 26dB Bandwidth of Fundamental Emission: PASS





BUREAU  
VERITAS

Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

### 3.4 DUTY CYCLE CORRECTION DURING 100MSEC:

Each function key sends a different series of characters, but each packet period(19.95msec) never exceeds a series of 4 long (1.5msec) pulses and 40 short(0.5msec).

Assuming any combination of short or long pulses may be obtained due to encoding the worst case transmit duty cycle would be considered  $(4 \times 1.5\text{msec}) + (40 \times 0.5\text{msec})$  per  $48.53\text{msec} = 53.6\%$  duty cycle. Figure A and E show the characteristics of the pulse train for one of these functions.

Remarks:

Duty Cycle Correction =  $20\text{Log}(0.536) = -5.42\text{dB}$

The following figures [Figure A to Figure B] show the characteristics of the pulse train for one of these functions.





BUREAU VERITAS

Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

### 3.4.1 TEST RESULTS

Figure A





Figure B





Test Report No.: FC120315N007  
FCC ID: PWYJT27TX99007

#### 4 PHOTOGRAPHS OF TEST CONFIGURATION

Please see test setup photo file.

#### 5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---