

Report No. : AF013017-001 Date : 2005 June 16

Application No.: LF209305(8)

Applicant : Jada Toys Co. Ltd

Unit 901, 9/F., Energy Plaza, 92 Granville Road, TST East, Kowloon, Hong Kong.

Sample Description : One(1) submitted sample stated to be 1:6 Dub City RC car of Model No. 83008

Rating : 9.6V rechargeable battery
No. of submitted sample : Two (2) piece(s)***

Date Received : 2005 May 26

Test Period : 2005 May 26 – 2005 June 06

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – July 2004

ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15

Subpart B.

For and on behalf of CMA Testing and Certification Laboratories

Authorized Signature : Page 1 of 11

Damy Chui

EMC Engineer - EL. Division



Report No. : AF013017-001 Date : 2005 June 16

Table of Contents

1	Gen	eral Information	3
	1.1	General Description	
	1.2	Location of the test site	
	1.3	List of measuring equipment.	5
2	Des	cription of the radiated emission test	
	2.1	Test Procedure	6
	2.2	Test Result	6
	2.3	Radiated Emission Measurement Data	7
3	Des	cription of the Line-conducted Test	8
	3.1	Test Procedure	8
	3.2	Test Result	8
	3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Pho	tograph	9
	4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	9
	4.2	Photographs of the External and Internal Configurations of the EUT	9
5	Supp	plementary document	10
	5.1	Bandwidth	
	5.2	Duty Cycle	10
6	App	endices	11



Date: 2005 June 16 Report No. AF013017-001

1 **General Information**

General Description 1.1

The equipment under test (EUT) is a superregenerative for 1:6 Dub City RC car. Operating at 49.860MHz which is controlled by LRC circuit. The EUT is powered by a 9.6V rechargeable battery. When it switchs on, it will receive a different radio signal from the transmitter continuously.

The brief circuit description is listed as follows:

- Q1 and associated circuit act as superregenerative receiver.
- IC1 and associated circuit act as remote control decoder.
- IC2 and associated circuit act as single channel voice IC.
- IC3 and associated circuit act as low voltage audio power amplifier. Q9-Q14 and associated circuit act as current driver of the left and right motors.
- Q22-Q25, RL1-RL4 and associated circuit act as current driver of the forward and backward motors.



Report No. : AF013017-001 Date : 2005 June 16

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at :

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.



Report No. : AF013017-001 Date : 2005 June 16

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S43284
Broadband Antenna	Schaffner	CBL6112B	2692	CA3025
Signal Generator	IFR	2023B	202302/938	S43098
LISN	R&S	ESH3-Z5	100038	S43377
LISN	R&S	ESH3-Z5	100010	S43101
Pulse Limiter	R&S	ESH3-Z2	100001	S43325
Biconical Antenna	R&S	HK116	837414/004	2GB05000535-0001
Loop Antenna	EMCO	6502	00056620	49906



Report No. : AF013017-001 Date : 2005 June 16

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 - 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

A signal generator was used to radiate an unmodulated continuous wave (CW) signal to the EUT (superregenerative receiver) at its operating frequency in order to "cohere" the characteristic broadband emissions from the receiver.

2.2 Test Result

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR qusai-peak detector.

It was found that the EUT meet the FCC requirement.



Report No. : AF013017-001 Date : 2005 June 16

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart B

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBµV/m)	Antenna and Cable factor (dB)	Field Strength (dBµV/m)	Limit at 3m (dBμV/m)	Margin (dB)
49.973	V	19.2	10.3	29.5	40.0	-10.5
50.073	V	21.4	8.1	29.5	40.0	-10.5
50.193	V	20.7	8.1	28.8	40.0	-11.2
52.648	V	13.2	8.1	21.3	40.0	-18.7
99.839	V	12.6	9.2	21.8	43.5	-21.7
99.952	V	12.0	9.2	21.2	43.5	-22.3
100.055	V	10.7	11.0	21.7	43.5	-21.8
104.716	V	11.0	11.0	22.0	43.5	-21.5
140.781	V	7.5	11.9	19.4	43.5	-24.1
149.708	V	7.7	11.9	19.6	43.5	-23.9



Report No. : AF013017-001 Date : 2005 June 16

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



Report No. : AF013017-001 Date : 2005 June 16

- 4 Photograph
- 4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho9.jpg.



Report No. : AF013017-001 Date : 2005 June 16

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

N/A

5.2 Duty Cycle

N/A



Report No. : AF013017-001 Date : 2005 June 16

6 Appendices

A 1	Photos of the set-up of Radiated Emissions	1 page
A2	Photos of External Configurations	1 page
A3	Photos of Internal Configurations	5 pages
A4	ID Label/Location	1 page
A5	Block Diagram	1 page
A6	Schematics	1 page
A7	User Manual	2 pages
A8	Operation Description	1 page

***** End of Report *****