



## TEST REPORT

Report No. : AJ025765-001 Date : 2007 November 01

Application No. : LJ220521(1)

Applicant : JADA TOYS CO., LTD.  
UNIT 901, 9/F., ENERGY PLAZA,  
92 GRANVILLE ROAD,  
T.S.T. EAST, KLN.,  
HONG KONG.

Sample Description : One(1) submitted sample(s) stated to be 1:16 RC Rollers RC Car and  
1:16 Big Time Muscle RC Car of Model No. 83007 and 83015  
Radio Frequency : 49.860MHz Receiver  
Rating : 6 x 1.5V AA size batteries  
No. of submitted sample : Two(2) set(s) \*\*\*

Date Received : 2007 August 23

Test Period : 2007 August 26 – 2007 September 11

Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-05 Edition)  
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15  
Subpart B.

Remark : All Two models are the same in circuitry and components; and therefore model  
83007 was chosen to be the representative of the test sample.

*For and on behalf of*  
CMA Industrial Development Foundation Limited

Authorized Signature : \_\_\_\_\_

Danny Chui  
Deputy Manager - EL. Division

FCC ID: PWYJT49RX89002

Page 1 of 11



## **TEST REPORT**

Report No. : AJ025765-001

Date : 2007 November 01

### **Table of Contents**

1	General Information .....	3
1.1	General Description.....	3
1.2	Location of the test site .....	4
1.3	List of measuring equipment .....	5
2	Description of the radiated emission test .....	6
2.1	Test Procedure .....	6
2.2	Test Result.....	6
3	Description of the Line-conducted Test.....	8
3.1	Test Procedure .....	8
3.2	Test Result.....	8
3.3	Graph and Table of Conducted Emission Measurement Data .....	8
4	Photograph .....	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission.....	9
4.2	Photographs of the External and Internal Configurations of the EUT .....	9
5	Supplementary document.....	10
5.1	Bandwidth.....	10
5.2	Duty cycle.....	10
5.3	Transmission time .....	10
5.4	Power Spectral Density.....	10
6	Appendices.....	11



## **TEST REPORT**

Report No. : AJ025765-001

Date : 2007 November 01

### **1 General Information**

#### **1.1 General Description**

The equipment under test (EUT) is a receiver for 1:16 RC Rollers RC Car. It operates at 49.860MHz and the oscillation of radio control is generated by LRC circuit. The EUT is powered by 6 x 1.5V AA size batteries. When it switched on and received radio control signal, it will be running to corresponding direction.

The brief circuit description is listed as follows:

- Q1 and associated circuit act as RF receiver.
- IC1 and associated circuit act as decoder.
- Q2 ~ Q7, Q14 ~ Q17 and associated circuit act as M2 motor controller.
- Q8 ~ Q13 and associated circuit act as M1 motor controller.



## **TEST REPORT**

Report No. : AJ025765-001

Date : 2007 November 01

### **1.2 Location of the test site**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.



## TEST REPORT

Report No. : AJ025765-001

Date : 2007 November 01

### 1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.
EMI Test Receiver	R&S	ESCI	100152
Bilog Antenna	Schaffner	CBL6112B	2718
Signal Generator	IFR	2023B	202302/938



## **TEST REPORT**

Report No. : AJ025765-001

Date : 2007 November 01

### **2 Description of the radiated emission test**

#### **2.1 Test Procedure**

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

A signal generator was used to radiate an unmodulated continuous wave (CW) signal to the EUT (superregenerative receiver) at its operating frequency in order to “cohere” the characteristic broadband emissions from the receiver.

#### **2.2 Test Result**

All operation modes had been tested.

The emissions from 30MHz to 1000MHz were investigated. The highest emissions were presented in next page.

Emissions with more than 20dB below the limit were not reported in next page.

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasi-peak detector below 1000MHz and average detector for frequencies above 1000MHz.

It was found that the EUT meet the FCC requirement.



## **TEST REPORT**

Report No. : AJ025765-001

Date : 2007 November 01

### **2.3 Radiated Emission Measurement Data**

#### **Radiated emission**

**pursuant to**

**the requirement of FCC Part 15 subpart B**

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB $\mu$ V/m)	Antenna and Cable factor (dB)	Field Strength (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
49.520	V	14.6	10.6	25.2	40.0	-14.8
49.740	V	14.0	10.6	24.6	40.0	-15.4
50.280	V	15.4	8.4	23.8	40.0	-16.2
52.080	V	14.3	8.4	22.7	40.0	-17.3
96.620	V	9.4	9.5	18.9	43.5	-24.6
97.546	V	9.9	9.5	19.4	43.5	-24.1
148.171	H	9.1	12.0	21.1	43.5	-22.4
251.200	H	8.1	13.9	22.0	46.0	-24.0



## **TEST REPORT**

Report No. : AJ025765-001

Date : 2007 November 01

### **3 Description of the Line-conducted Test**

#### **3.1 Test Procedure**

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

#### **3.2 Test Result**

No measurement is required as the EUT is a battery-operated product.

#### **3.3 Graph and Table of Conducted Emission Measurement Data**

Not Applicable





## **TEST REPORT**

Report No. : AJ025765-001

Date : 2007 November 01

### **4 Photograph**

#### **4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission**

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

#### **4.2 Photographs of the External and Internal Configurations of the EUT**

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho2.jpg.



## TEST REPORT

Report No. : AJ025765-001

Date : 2007 November 01

### 5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

#### 5.1 Bandwidth

N/A

#### 5.2 Duty cycle

N/A

#### 5.3 Transmission time

N/A

#### 5.4 Power Spectral Density

N/A



## **TEST REPORT**

Report No. : AJ025765-001

Date : 2007 November 01

### **6 Appendices**

A1.	Photos of the set-up of Radiated Emission	1	page
A2.	Photos of External Configurations	1	page
A3.	Photos of Internal Configurations	1	page
A4.	ID Label / Location	1	page
A5.	Block Diagram	1	page
A6.	Schematic Diagram	1	page
A7.	User Manual	2	pages
A8.	Operation Description	1	page

\*\*\*\*\* End of Report \*\*\*\*\*