

Report No. : AF024200-001 Date : 2005 October 25

Application No. : LF215944(3)

Applicant : Jada Toys Co. Ltd

Unit 901, 9/F., Energy Plaza, 92 Granville Road, TST East, Kowloon, Hong Kong.

Sample Description : One(1) submitted sample(s) stated to be:

1:16 Dub City Big Time Muscle R/C Car of Model No. 83015

Rating : 1 x 9V size battery No. of submitted sample : Two (2) piece(s)

Date Received : 2005 September 29

Test Period : 2005 September 29 – 2005 October 25

Test Requested : FCC Part 15 Certification.

Test Method : FCC Rules and Regulations Part 15 – July 2004

ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15

Subpart C.

For and on behalf of

CMA Testing and Certification Laboratories

Authorized Signature:

Danny Chui

EMC Engineer - EL. Division



Report No. : AF024200-001 Date : 2005 October 25

## **Table of Contents**

1	Gen	General Information					
	1.1	General Description					
	1.2	Location of the test site					
	1.3	List of measuring equipment					
2	Desc	cription of the radiated emission test					
	2.1	Test Procedure	6				
	2.2	Test Result	6				
	2.3	Radiated Emission Measurement Data	7				
3	Desc	cription of the Line-conducted Test	8				
	3.1	Test Procedure	8				
	3.2	Test Result	8				
	3.3	Graph and Table of Conducted Emission Measurement Data	8				
4	Phot	ograph	9				
	4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	9				
	4.2	Photographs of the External and Internal Configurations of the EUT	9				
5	Supp	plementary document	10				
	5.1	Bandwidth	10				
	5.2	Duty cycle	10				
	5.3	Transmission time	10				
6	App	endices	11				



Report No. : AF024200-001 Date : 2005 October 25

Test Result :

### 1 General Information

## 1.1 General Description

The equipment under test (EUT) is a transmitter for 1:16 Dub City Big Time Muscle R/C Car. Operating at 49.860MHz which is controlled by a crystal. The EUT is powered by a 9V size battery. There are two control sticks in front of the EUT. When it turns on, it will transmit different radio signal to the receiver.

The brief circuit description is listed as follows:

- Y1, Q1 and associated circuit act as oscillator.
- Q2 and associated circuit act as RF amplifier.
- U3 and associated circuit act as encoder.
- C34, L4, C10 and associated circuit act as low pass fitter.



Report No. : AF024200-001 Date : 2005 October 25

Test Result :

### 1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. A shielded room is located at:

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.



Report No. : AF024200-001 Date : 2005 October 25

Test Result :

## 1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.
EMI Test Receiver	R&S	ESCS30	100001	S43284
Broadband Antenna	Schaffner	CBL6112B	2692	CA3025
Signal Generator	IFR	2023B	202302/938	S43098
LISN	R&S	ESH3-Z5	100038	S43377
LISN	R&S	ESH3-Z5	100010	S43101
Pulse Limiter	R&S	ESH3-Z2	100001	S43325
Biconical Antenna	R&S	HK116	837414/004	2GB05000535-0001
Loop Antenna	EMCO	6502	00056620	49906



Report No. : AF024200-001 Date : 2005 October 25

Test Result:

### 2 Description of the radiated emission test

#### 2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 - 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

### 2.2 Test Result

Peak Detector data was measured unless otherwise stated.

\* Emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.



Report No. : AF024200-001 Date : 2005 October 25

Test Result :

### 2.3 Radiated Emission Measurement Data

#### **Radiated emission**

### pursuant to

# the requirement of FCC Part 15 subpart C

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBµV/m)	Antenna and Cable factor (dB)	Average Factor (dB)	Field Strength (dBµV/m)	Limit at 3m (dBµV/m)	Margin (dB)
49.860	V	70.5	10.3	-4.5	76.3	80.0	-3.7
99.728	V	24.5	9.2	-	33.7	43.5	-9.8
149.584	V	16.8	11.9	-	28.7	43.5	-14.8
199.460	Н	20.5	9.2	-	29.7	43.5	-13.8
* 249.304	Н	16.7	9.7	-	26.4	46.0	-19.6
299.172	Н	12.9	13.9	-	26.8	46.0	-19.2
349.020	Н	10.3	14.9	-	25.2	46.0	-20.8
398.868	Н	12.4	14.9	-	27.3	46.0	-18.7
448.764	Н	8.3	17.7	-	26.0	46.0	-20.0
498.624	Н	9.0	17.7	-	26.7	46.0	-19.3



Report No. : AF024200-001 Date : 2005 October 25

Test Result :

# 3 Description of the Line-conducted Test

### 3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. The EUT was setup as described in the procedures, and both lines were measured.

### 3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

## 3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



Report No. : AF024200-001 Date : 2005 October 25

Test Result :

4 Photograph

### 4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

## 4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho3.jpg.



Report No. : AF024200-001 Date : 2005 October 25

Test Result :

## 5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

### 5.1 Bandwidth

The plot on saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. The field strength of any emission appearing between the band edges and up to 10 kHz above and below the band edges (49.81 and 49.91 MHz) is at least 26dB below the carrier level. It meets the requirement of Section 15.235(b).

## 5.2 Duty cycle

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 18.15ms

Effective period of the cycle = (1.5 ms x 4) + (0.48 ms x 10)

= 10.8 ms

Duty Cycle = 10.8 ms / 18.15 ms

= 0.595

Therefore, the average factor is found by  $20 \log_{10} 0.595 = -4.5 dB$ 

### **5.3** Transmission time

N/A



Report No. : AF024200-001 Date : 2005 October 25

## 6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1	page
A2.	Photos of External Configurations	1	page
A3.	Photos of Internal Configurations	2	pages
A4.	ID Label/Location	1	page
A5.	Bandwidth Plot	1	page
A6.	Average Factor	2	pages
A7.	Block Diagram	1	page
A8.	Schematics	1	page
A9.	User Manual	2	pages
A10.	Operation Description	1	page

\*\*\*\*\* End of Report \*\*\*\*\*