



**SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch**

Application No.: GZEM1803001216CR

Page: 1 of 3

FCC ID: PX8RX-4122-A

**RF Exposure Compliance Requirement**

**1. Standard requirement**

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

**(a) Limits for Occupational / Controlled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm <sup>2</sup> )	Averaging Times  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100000			5	6

**(b) Limits for General Population / Uncontrolled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm <sup>2</sup> )	Averaging Times  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/500	30
1500-100000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density



**SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch**

Application No.: GZEM1803001216CR

Page: 2 of 3

FCC ID: PX8RX-4122-A

**2. MPE Calculation Method**

$$S \text{ (mW/cm}^2\text{)} = P * G / 4\pi * R^2$$

S= Power Density (mW/cm<sup>2</sup>)

P=Peak RF conducted output Power (mW)

G=EUT Antenna numeric gain (numeric)

R= Separation distance between radiator and human body (cm);

$$R = \sqrt{(P * G) / 4\pi * S}$$

From the maximum EUT RF output power, as well as the gain of the used antenna, according to the RF power density limit above, the minimum distance between the antenna and human body will be calculated.

**3. Calculated Result**

3.1 For downlink: 450MHz to 509MHz

Frequency (MHz) F	Maximum Antenna Gain (dBi)	Maximum Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Minimum Distance to human body (cm)
<b>For C4FM mode</b>						
450.00625	12.5	17.8	36.0	3981.072	1.500	61.329
481	12.5	17.8	36.0	3981.072	1.603	59.320
508.99735	12.5	17.8	36.0	3981.072	1.697	57.666
<b>For FM(6.25k) mode</b>						
450.003125	12.5	17.8	36.0	3981.072	1.500	61.329
481	12.5	17.8	36.0	3981.072	1.603	59.320
508.996875	12.5	17.8	36.0	3981.072	1.697	57.666
<b>For FM(12.5k) mode</b>						
450.00625	12.5	17.8	36.0	3981.072	1.500	61.329
481	12.5	17.8	36.0	3981.072	1.603	59.320
508.99375	12.5	17.8	36.0	3981.072	1.697	57.666
<b>For FM(25k) mode</b>						
450.0125	12.5	17.8	36.0	3981.072	1.500	61.329
481	12.5	17.8	36.0	3981.072	1.603	59.320
508.9875	12.5	17.8	36.0	3981.072	1.697	57.666

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



**SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch**

Application No.: GZEM1803001216CR

Page: 3 of 3

FCC ID: PX8RX-4122-A

3.2 For uplink: 455MHz to 512MHz

Frequency (MHz) F	Maximum Antenna Gain (dBi)	Maximum Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Minimum Distance to human body (cm)
<b>For C4FM mode</b>						
455.00625	12.5	17.8	27.0	501.187	1.517	21.640
484	12.5	17.8	27.0	501.187	1.613	20.982
511.99735	12.5	17.8	27.0	501.187	1.707	20.401
<b>For FM(6.25k) mode</b>						
455.003125	12.5	17.8	27.0	501.187	1.517	22.660
484	12.5	17.8	27.0	501.187	1.613	21.971
511.996875	12.5	17.8	27.0	501.187	1.707	20.876
<b>For FM(12.5k) mode</b>						
455.00625	12.5	17.8	27.0	501.187	1.517	21.640
484	12.5	17.8	27.0	501.187	1.613	20.982
511.99375	12.5	17.8	27.0	501.187	1.707	20.401
<b>For FM(25k) mode</b>						
455.0125	12.5	17.8	27.0	501.187	1.517	21.640
484	12.5	17.8	27.0	501.187	1.613	20.982
511.9875	12.5	17.8	27.0	501.187	1.707	20.401

**Conclusion:**

So the recommend use distance away from EUT external antenna is larger than 61.329 centimeter(cm).