



**SGS-CSTC Standards Technical Services Co., Ltd.  
Guangzhou Branch**

Application No.: GZEM1803001395CR

Page: 1 of 3

FCC ID: PX8COMFLEX-6900

**RF Exposure Compliance Requirement**

**1. Standard requirement**

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

**(a) Limits for Occupational / Controlled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm <sup>2</sup> )	Averaging Times  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100000			5	6

**(b) Limits for General Population / Uncontrolled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm <sup>2</sup> )	Averaging Times  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/500	30
1500-100000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density



**2. MPE Calculation Method**

$$S \text{ (mW/cm}^2\text{)} = P * G / 4\pi * R^2$$

S= Power Density (mW/cm<sup>2</sup>)

P=Peak RF conducted output Power (mW)

G=EUT Antenna numeric gain (numeric)

R= Separation distance between radiator and human body (cm);

$$R = \sqrt{(P * G) / 4\pi * S}$$

From the maximum EUT RF output power, as well as the gain of the used antenna, according to the RF power density limit above, the minimum distance between the antenna and human body will be calculated.

**3. Calculated Result**

3.1 For downlink: 2350MHz to 2360MHz

Max composite out power:

LTE(5M Modulation)

Frequency (MHz) F	Maximum Antenna Gain (dBi)	Maximum Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Minimum Distance to human body (cm)
Lowest	12.5	17.8	50.0	100000	5	237.63
Middle	12.5	17.8	50.0	100000	5	237.63
Highest	12.5	17.8	50.0	100000	5	237.63

LTE(10M Modulation)

Frequency (MHz) F	Maximum Antenna Gain (dBi)	Maximum Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Minimum Distance to human body (cm)
Middle	12.5	17.8	50.0	100000	5	237.63



**SGS-CSTC Standards Technical Services Co., Ltd.**  
**Guangzhou Branch**

Application No.: GZEM1803001395CR

Page: 3 of 3

FCC ID: PX8COMFLEX-6900

3.3 For downlink: 2496MHz to 2690MHz:

5M Modulation:

Frequency (MHz) F	Maximum Antenna Gain (dBi)	Maximum Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Minimum Distance to human body (cm)
Lowest	12.5	17.8	50.0	100000	5	237.63
Middle	12.5	17.8	50.0	100000	5	237.63
Highest	12.5	17.8	50.0	100000	5	237.63

20M Modulation:

Frequency (MHz) F	Maximum Antenna Gain (dBi)	Maximum Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Minimum Distance to human body (cm)
Lowest	12.5	17.8	50.0	100000	5	237.63
Middle	12.5	17.8	50.0	100000	5	237.63
Highest	12.5	17.8	50.0	100000	5	237.63

Note: 50 dBm is the total power of both output ports 2 X 47dBm,

**Conclusion:**

So the recommend use distance away from EUT external antenna is larger than 2.3763 meter.