

**RF Exposure Compliance Requirement****1. Standard requirement**

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times $ E ^2, H ^2$ or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm ²)	Averaging Times $ E ^2, H ^2$ or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/500	30
1500-100000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

**2. MPE Calculation Method**

$$S \text{ (mW/cm}^2\text{)} = P * G / 4\pi * R^2$$

S= Power Density (mW/cm²)

P=Peak RF conducted output Power (mW)

G=EUT Antenna numeric gain (numeric)

R= Separation distance between radiator and human body (cm);

$$R = \sqrt{(P * G) / 4\pi * S}$$

From the maximum EUT RF output power, as well as the gain of the used antenna, according to the RF power density limit above, the minimum distance between the antenna and human body will be calculated.

3. Calculated Result

3.1 For downlink: 862MHz to 869MHz

1) CDMA::

Frequency (MHz) F	Maximum Antenna Gain (dBi)	Maximum Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Limit of Power Density (S) (mW/cm ²)	Minimum Distance to human body (cm)
Lowest	10	10	32.8	1905.461	1.726	29.65
Middle	10	10	32.7	1862.087	1.731	29.27
Highest	10	10	32.6	1819.701	1.736	29.26

2) LTE:

Frequency (MHz) F	Maximum Antenna Gain (dBi)	Maximum Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Limit of Power Density (S) (mW/cm ²)	Minimum Distance to human body (cm)
Lowest	10	10	32.8	1905.461	1.730	29.61
Middle	10	10	32.6	1819.701	1.731	28.93
Highest	10	10	32.8	1905.461	1.732	28.89



SGS-CSTC Standards Technical Services Co., Ltd.

Application No.: GZEM170800480703

Page: 3 of 3

FCC ID: PX8MBDA-80

3.5 For downlink: 817MHz to 824MHz:

1) CDMA::

Frequency (MHz) F	Maximum Antenna Gain (dBi)	Maximum Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Limit of Power Density (S) (mW/cm ²)	Minimum Distance to human body (cm)
Lowest	10	10	17.2	52.481	1.636	5.05
Middle	10	10	17.6	57.544	1.641	5.28
Highest	10	10	17.4	54.954	1.646	5.16

2) LTE:

Frequency (MHz) F	Maximum Antenna Gain (dBi)	Maximum Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Limit of Power Density (S) (mW/cm ²)	Minimum Distance to human body (cm)
Lowest	10	10	17.0	50.119	1.640	4.93
Middle	10	10	16.9	48.978	1.641	4.87
Highest	10	10	17.0	50.119	1.642	4.93

Conclusion:

So the recommend use distance away from EUT external antenna is larger than 0.2965 meter.