

1. GENERAL INFORMATION

1.1. EUT Description

Product Name : Access Point
Trade Name : WINMATE
FCC ID. : PX91200
Model No. : WN1200

Frequency Range : 2412MHz to 2462MHz

Channel Number : 11

Chip Rate : 1Mbps, 2Mbps, 5.5Mbps, 11Mbps Type of Modulation : Direct Sequence Spread Spectrum

Antenna type : Soldered on PCB

Operator Selection of

: By software

Operating Frequency

WN10A-050

Power Adapter : Cable Out: Non-shielded, 1.8m

Frequency of Each Channel:

Channel Frequency Channel Frequency Channel Frequency Channel 1: 2412 MHz Channel 2: 2417 MHz Channel 3: 2422 MHz Channel 4: 2427 MHz Channel 5: Channel 6: 2432 MHz 2437 MHz Channel 7: 2442 MHz Channel 8. 2447 MHz Channel 9. 2452 MHz

Channel 10: 2457 MHz Channel 11: 2462 MHz

Note:

- 1. This device is a 2.4GHz Access Point included a 2.4GHz receiving function, a 2.4GHz transmitting function for the desktop/ laptop computers. Direct Sequence device with 11 channels.
- 2. Regards to the frequency band operation; two rate that were included the lowest \cdot middle and highest frequency of channel were selected to perform the test, then shown on this report.
- 3. These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15 Subpart C Paragraph 15.247 for spread spectrum devices.
- 4. This device is a composite device in accordance with Part 15 regulations. The function receiving was measured and made a test report that the report number is 023L104F under Declaration of Conformity.

1.2. Operational Description

EUT is an USB interface 2.4GHz wireless LAN with 11 channels. This device provided four kind of transmitting speed 1,2,5.5 and 11Mbps. The device of RF carrier is DQPSK, DB PSK and CCK.

The device adapts direct sequence spread spectrum modulation. The soldered on PCB antenna printed on PCB provides diversity function to improve the receiving function. Data can be transmitted by the radio signal connect to the Internet or Local network.

Page: 5 of 42 Version:1.0