

FCC TEST REPORT FCC 47 CFR Part 15C Industry Canada RSS-247 Frequency hopping systems operating within the 2400 – 2483.5 MHz band	
Report Reference No.	G0M-1505-4755-TFC247BT-V01
Testing Laboratory	Eurofins Product Service GmbH
Address.....	Storkower Str. 38c 15526 Reichenwalde Germany
Accreditation	<div style="display: flex; justify-content: center; align-items: center;">   </div> <p style="text-align: center; margin-top: 5px;"> A2LA Accredited Testing Laboratory, Certificate No.: 1983.01 FCC Filed Test Laboratory, Reg.-No.: 96970 IC OATS Filing assigned code: 3470A </p>
Applicant's name	Spectralink Europe ApS
Address.....	Langmarksvej 34 8700 Horsens DENMARK
Test specification:	
Standard	47 CFR Part 15C RSS-247, Issue 1, 2015-05 RSS-Gen, Issue 4, 2014-11 ANSI C63.10:2013 ANSI C63.4:2014
Test scope.....	complete Radio compliance test
Equipment under test (EUT):	
Product description	DECT handset 7742
Model No.	K023a
Additional Model(s)	DECT handset 7642 (K23b)
Brand Name(s)	Spectralink
Hardware version	PCS 04
Firmware / Software version	PCS 15J_
	FCC-ID: PXA-K023A IC: 4604A-K023A
Test result	Passed

Possible test case verdicts:

- neither assessed nor tested: N/N
- required by standard but not appl. to test object.....: N/A
- required by standard but not tested.....: N/T
- not required by standard for the test object: N/R
- test object does meet the requirement.....: P (Pass)
- test object does not meet the requirement.....: F (Fail)

Testing:

Test Lab Temperature.....: 20 – 23 °C

Test Lab Humidity: 32 – 38 %

Date of receipt of test item: 2015-06-01

Date (s) of performance of tests: 2011-06-05

Compiled by: Wilfried Treffke

Tested by (+ signature).....: Wilfried Treffke
(Responsible for Test)

Approved by (+ signature): Christian Weber
(Head of Lab)

Date of issue: 2015-08-03

Total number of pages: 73

W. Treffke

C. Weber

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

Additional comments:**Declaration of changes due to variant creation.**

Applicant: Spectralink Europe ApS
Project No(s): G0M-1505-4752, G0M-1505-4755
EUT (Product): Spectralink 7742 (K023a), Spectralink 7642 (K023b)

The difference between 7742 and 7642 is the keyboard type with corresponding plastic.
7742 use Foil-keyboard with ESD protection circuit.
7642 use Key-buttons with keyfoil.
All other components and firmware are the same.

Date: 2015-06-11


Henrik Birch Rasmussen

Spectralink Europe Aps.
Langmarksvej 34
8700 Horsens
Denmark

spectralink.com | 2560 55th Street | Boulder, CO 80301 | +1 800-775-5330

Note:

The test for all radiated spurious emission was performed on the fully version 7742 (K023a)

Version History

Version	Issue Date	Remarks	Revised by
01	2015-08-03	Initial Release	

REPORT INDEX

1	EQUIPMENT (TEST ITEM) DESCRIPTION	6
1.1	Photos – Equipment External	8
1.2	Photos – Equipment internal	15
1.3	Photos – Test setup	18
1.4	Supporting Equipment Used During Testing	19
1.5	Test Modes	20
1.6	Test Equipment Used During Testing	21
1.7	Sample emission level calculation	22
2	RESULT SUMMARY	23
3	TEST CONDITIONS AND RESULTS	24
3.1	Test Conditions and Results – Occupied Bandwidth	24
3.2	Test Conditions and Results – AC power line conducted emissions	25
3.3	Test Conditions and Results – Transmitter radiated emissions	28
3.4	Test Conditions and Results – Receiver radiated emissions	30


1 Equipment (Test item) Description

Description	DECT handset 7742	
Model	K023a	
Additional Model(s)	DECT handset 7642 (K23b)	
Brand Name(s)	Spectralink	
Serial number	None	
Hardware version	PCS 04	
Software / Firmware version	PCS 15J_	
FCC-ID	PXA-K023A	
IC	4604A-K023A	
Equipment type	End product	
Radio type	Transceiver	
Radio technology	Bluetooth	
Operating frequency range	2402 - 2480 MHz	
Assigned frequency band	2400 - 2483.5 MHz	
Main test frequencies	F _{LOW}	2402 MHz
	F _{MID}	2441 MHz
	F _{HIGH}	2480 MHz
Spreading	FHSS	
Modulations	GFSK	
Number of channels	79 hopping channels at all	
Channel spacing	1 MHz	
Number of antennas	1	
Radio module	Type	TI Bluetooth HCI module
	Model	CC2564MODN
	Manufacturer	Texas Instrument Inc.
	HW Version	V3.32
	SW Version	7.16
	FCC-ID	Z64-2564N
	IC	4511-2564N
Antenna	Type	integrated
	Model	47948
	Manufacturer	MOLEX
	Gain	-1 (manufacturer declaration)
Manufacturer	Spectralink Europe ApS Langmarksvej 34 8700 Horsens DENMARK	

Power supply	V _{NOM}	3.7 VDC (lithium battery)
	V _{MIN}	N/R
	V _{MIN}	N/R
AC/DC-Adaptor	Model	UE08WCP-060100SPA
	Vendor	Fuhua
	Input	110 - 240 VAC
	Output	6,0V 1,0A


1.1 Photos – Equipment External







AE1: Charger, single 84642493, TOP



AE1: Charger, single 84642493, CONNECTOR



AE1: Charger, single 84642493, LABEL



AE2: Charger, USB 84642494, TOP



AE2: Charger, USB 84642494, CONNECTORS





AE2: Charger, USB 84642494, LABEL




AE3: Power adaptor




1.2 Photos – Equipment internal




EUT 7742 PCB BOTTOM




VARIANT 7642 OPEN





VARIANT 7642 PCB TOP



VARIANT 7642 PCB BOTTOM



1.3 Photos – Test setup



1.4 Supporting Equipment Used During Testing

Product Type*	Device	Manufacturer	Model No.	Comments
SIM	Communication tester	Rohde & Schwarz	CBT	BT signalling
AE1	Charger, single	Spectralink	84642493	
AE2	Charger, single, USB	Spectralink	84642494	
AE3	Power adaptor	Fuhua	UE08WCP-060100SPA	

***Note:** Use the following abbreviations:

AE : Auxiliary/Associated Equipment, or

SIM : Simulator (Not Subjected to Test)

CABL : Connecting cables

1.5 Test Modes

Mode #	Description	
DH5-Sngl	General conditions:	EUT powered by laboratory power supply.
	Radio conditions:	Mode = standalone transmit Spreading = Hopping stopped (single hopping channel) Modulation = GFSK Packet type = DH5 Data rate = 1 Mbps Duty cycle = 77 % Power level = Maximum
Receive	General conditions:	EUT powered by laboratory power supply.
	Radio conditions:	Mode = standalone receive Spreading = Hopping
AC-Powerline	General conditions:	EUT powered by commercial AC/DC-Adapter
	Radio conditions:	Mode = standalone transmit Spreading = Hopping Power level = Maximum

1.6 Test Equipment Used During Testing

Measurement Software			
Description	Manufacturer	Name	Version
EMC Test Software	Dare Instruments	Radimation	2014.1.15

Occupied Bandwidth					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSP 30	EF00312	2015-02	2016-02

Radiated spurious emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Semi-anechoic chamber	Frankonia	AC 1	EF00062	-	-
Spectrum Analyzer	R&S	FSIQ26	EF00242	2015-04	2016-04
Biconical Antenna	R&S	HK 116	EF00012	2013-02	2016-02
LPD Antenna	R&S	HL 223	EF00187	2014-03	2017-03
LPD Antenna	R&S	HL 025	EF00327	2013-02	2016-02

AC powerline conducted emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
AMN	R&S	ESH2-Z5	EF00182	2014-11	2016-11
AMN	R&S	ESH3-Z5	EF00036	2014-12	2016-12
EMI Test Receiver	R&S	ESCS 30	EF00295	2014-10	2015-10

1.7 Sample emission level calculation

The following is a description of terms and a sample calculation, as appears in the radiated emissions data table. The numbers used in the calculation are for example only. There is no direct correlation to the specific data taken for the product described in this document:

Reading:

This is the reading obtained on the spectrum analyzer in dB μ V. Any external preamplifiers used are taken into account through internal analyzer settings.

A.F.:

This is the antenna factor for the receiving antenna. It is a conversion factor, which converts electric fields strengths to voltages, which can be measured directly on the spectrum analyzer. It is treated as a loss in dB. Cable losses have been included with the A.F. to simplify the calculations. The antenna factor is used in calculations as follows:

$$\text{Reading on Analyzer (dB}\mu\text{V)} + \text{A.F. (dB)} = \text{Net field strength (dB}\mu\text{V/m)}$$

Net:

This is the net field strength measurement (as shown above).

Limit:

This is the FCC Class B radiated emission limit (in units of dB μ V/m). The FCC limits are given in units of μ V/m. The following formula is used to convert the units of μ V/m to dB μ V/m:

$$\text{Limit (dB}\mu\text{V/m)} = 20 \cdot \log(\mu\text{V/m})$$

Margin:

This is the margin of compliance below the FCC limit. The units are given in dB. A negative margin indicates the emission was below the limit. A positive margin indicates that the emission exceeds the limit.

Example only:


$$\begin{array}{rclcl} \text{Reading} & + & \text{AF} & = & \text{Net Reading} & : & \text{Net reading - FCC limit} & = & \text{Margin} \\ 21.5 \text{ dB}\mu\text{V} & + & 26 \text{ dB} & = & 47.5 \text{ dB}\mu\text{V/m} & : & 47.5 \text{ dB}\mu\text{V/m} - 57.0 \text{ dB}\mu\text{V/m} & = & -9.5 \text{ dB} \end{array}$$

2 Result Summary

FCC 47 CFR Part 15C, IC RSS-247				
Product Specific Standard Section	Requirement – Test	Reference Method	Result	Remarks
RSS-Gen 6.6	Occupied Bandwidth	ANSI C63.10	N/R	Informational only
FCC § 15.247(a)(1) IC RSS-247 § 5.1	20 dB Bandwidth	ANSI C63.10	N/R	Note1
FCC § 15.247(a)(1)(iii) IC RSS-247 § 5.1	Number of hopping frequencies	ANSI C63.10	N/R	Note1
FCC § 15.247(a)(1) IC RSS-247 § 5.1	Frequency hopping channel separation	ANSI C63.10	N/R	Note1
FCC § 15.247(a)(1)(iii) IC RSS-247 § 5.1	Time of occupancy (Dwell time)	ANSI C63.10	N/R	Note1
FCC § 15.247(b)(1) IC RSS-247 § 5.4	Maximum peak conducted power	ANSI C63.10	N/R	Note1
47 CFR 15.207 IC RSS-247 § 3.1	AC power line conducted emissions	ANSI C63.4	PASS	
FCC § 15.247(d) IC RSS-247 § 5.5	Band edge compliance	ANSI C63.10	N/R	Note1
FCC § 15.247(d) IC RSS-247 § 5.5	Conducted spurious emissions	ANSI C63.10	N/R	Note1
FCC § 15.247(d) FCC § 15.209 IC RSS-247 § 5.5	Transmitter radiated spurious emissions	ANSI C63.10	PASS	
IC RSS-247 § 3.1	Receiver radiated spurious emissions	ANSI C63.10	PASS	
Remarks: Note1: see report FR3D0402AD Rev.01 for conducted measurement results				

3 Test Conditions and Results

3.1 Test Conditions and Results – Occupied Bandwidth

Occupied Bandwidth acc. IC RSS-Gen		Verdict: PASS	
Test according to measurement reference	Reference Method		
	ANSI C63.10		
Test frequency range	Tested frequencies		
	$F_{LOW} / F_{MID} / F_{HIGH}$		
Limits			
None (Informational only)			
Test setup			
 <pre> graph LR SA[Spectrum Analyzer] --- EUT[EUT] </pre>			
Test procedure			
<ol style="list-style-type: none"> 1. EUT set to test mode (Communication tester is used if needed) 2. Span set to at least twice the emission spectrum 3. Resolution bandwidth set to 1 % of span 4. Occupied Bandwidth (99 %) measurement with spectrum analyzer built in measurement function 			
Test results			
Channel	Frequency [MHz]	Mode	Occupied Bandwidth [kHz]
F_{LOW}	2402	DH5-Sngl	845
F_{MID}	2441	DH5-Sngl	884
F_{HIGH}	2480	DH5-Sngl	861
Comments:			

3.2 Test Conditions and Results – AC power line conducted emissions


Power line conducted emissions acc. FCC 47 CFR 15.207 / IC RSS-Gen		Verdict: PASS		
Test according referenced standards	Reference Method			
	ANSI C63.4			
Fully configured sample scanned over the following frequency range	Frequency range			
	0.15 MHz to 30 MHz			
Points of Application	Application Interface			
AC Mains	LISN			
EUT test mode	AC-Powerline			
Limits and results				
Frequency [MHz]	Quasi-Peak [dB μ V]	Result	Average [dB μ V]	Result
0.15 to 5	66 to 56*	PASS	56 to 46*	PASS
0.5 to 5	56	PASS	46	PASS
5 to 30	60	PASS	50	PASS
Comments: * Limit decreases linearly with the logarithm of the frequency.				

Conducted Emissions
EMI voltage test in the ac-mains according to FCC 15B

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742/7642
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Klein
 Test Conditions: Tnom: 23°C, Unom: 120 VAC
 LISN: ESH2-Z5 L
 Mode: 7742, charging in cradle, DECT link to Base/Companion,
 BT Classic to Headset
 Test Date: Montag, 1. Juni 2015
 Note:

Index 2


 Frequency
586,5 kHz


Frequency	Average	Average Limit	Average Difference	Average Status
586,5 kHz	27,03 dBµV	46 dBµV	-18,97 dB	Pass

Conducted Emissions
EMI voltage test in the ac-mains according to FCC 15B


Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742/7642
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Klein
 Test Conditions: Tnom: 23°C, Unom: 120 VAC
 LISN: ESH2-Z5 N
 Mode: 7742, charging in cradle, DECT link to Base/Companion,
 BT Classic to Headset
 Test Date: Montag, 1. Juni 2015
 Note:

Index 3




3.3 Test Conditions and Results – Transmitter radiated emissions

Transmitter radiated emissions acc. FCC 47 CFR 15.247 / IC RSS-247				Verdict: PASS	
Test according referenced standards	Reference Method				
	FCC 15.247(d) / IC RSS-247 5.5				
Test according to measurement reference	Reference Method				
	ANSI C63.10				
Test frequency range	Tested frequencies				
	30 MHz – 10 th Harmonic				
Limits					
Frequency range [MHz]	Detector	Limit [μ V/m]	Limit [dB μ V/m]	Limit Distance [m]	
30 – 88	Quasi-Peak	100	40	3	
88 – 216	Quasi-Peak	150	43.5	3	
216 – 960	Quasi-Peak	200	46	3	
960 – 1000	Quasi-Peak	500	54	3	
> 1000	Average	500	54	3	
<p>Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).</p> <p>When average radiated emission measurements are specified, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.</p>					
Test setup					
 <p>The diagram illustrates the test setup within a Semi-anechoic Chamber. A Ground Plane is at the base. The Equipment Under Test (EUT) is placed on a Turn table. A probe is positioned to measure emissions from the EUT. The probe is connected to an Amplifier Matrix, which is then connected to a Measurement Receiver.</p>					

Test procedure									
<ol style="list-style-type: none"> 1. EUT set to test mode (Communication tester is used if needed) 2. Span it set according to measurement range 3. Resolution bandwidth below 1 GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1 MHz with peak/average detector is used above 1 GHz 4. Markers are set to peak emission levels within restricted bands 									
Test results – Internal Antenna									
Channel	Frequency [MHz]	Mode	Emission [MHz]	Level [dB μ V/m]	Det.	Pol.	Limit [dB μ V/m]	Limit dist. [m]*	Margin [dB]
F _{LOW}	2402	DH5-Sngl	4804	55.13	pk	hor	74.00	1	-18.87
F _{LOW}	2402	DH5-Sngl	4804	52.79	avg	hor	54.00	1	-01.21
F _{LOW}	2402	DH5-Sngl	4804	54.35	pk	ver	74.00	1	-19.65
F _{LOW}	2402	DH5-Sngl	4804	52.40	avg	ver	54.00	1	-01.60
F _{MID}	2441	DH5-Sngl	2330	51.52	pk	hor	74.00	3	-22.48
F _{MID}	2441	DH5-Sngl	4880	50.59	pk	hor	74.00	1	-23.41
F _{MID}	2441	DH5-Sngl	4880	48.05	pk	ver	74.00	1	-25.95
F _{HIGH}	2480	DH5-Sngl	2483.5	52.42	pk	hor	74.00	3	-21.58
F _{HIGH}	2480	DH5-Sngl	2483.5	42.32	RMS	hor	54.00	3	-11.68
F _{HIGH}	2480	DH5-Sngl	2483.5	51.11	pk	ver	74.00	3	-22.89
F _{HIGH}	2480	DH5-Sngl	2483.5	40.38	RMS	ver	54.00	3	-13.62
F _{HIGH}	2480	DH5-Sngl	4960	54.46	pk	hor	74.00	1	-19.54
F _{HIGH}	2480	DH5-Sngl	4960	52.78	avg	hor	54.00	1	-01.22
F _{HIGH}	2480	DH5-Sngl	4960	49.89	pk	ver	74.00	1	-24.11
F _{HIGH}	2480	DH5-Sngl	4960	47.77	avg	ver	54.00	1	-06.23
Comments: * Physical distance between EUT and measurement antenna.									

3.4 Test Conditions and Results – Receiver radiated emissions

Receiver radiated emissions acc. IC RSS-247			Verdict: PASS	
Test according referenced standards	Reference Method			
	IC RSS-247 3.1			
Test according to measurement reference	Reference Method			
	ANSI C63.10			
Test frequency range	Tested frequencies			
	30 MHz – 5 th Harmonic			
EUT test mode	Receive			
Limits				
Frequency range [MHz]	Detector	Limit [μ V/m]	Limit [dB μ V/m]	Limit Distance [m]
30 – 88	Quasi-Peak	100	40	3
88 – 216	Quasi-Peak	150	43.5	3
216 – 960	Quasi-Peak	200	46	3
960 – 1000	Quasi-Peak	500	54	3
> 1000	Average	500	54	3
Test setup				
				

Test procedure

1. EUT set to receive mode (Communication tester is used if needed)
2. Span it set according to measurement range
3. Resolution bandwidth below 1 GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1 MHz with peak/average detector is used above 1 GHz
4. Markers are set to peak emission levels

Test results

Channel	Frequency [MHz]	Emission [MHz]	Emission Level [dB μ V/m]	Polarisation	Det.	Limit [dB μ V/m]	Margin [dB μ V/m]
F _{MID}	2402–2480	910.4	20.38	hor	pk	46.00	-25.62 dB
F _{MID}	2402–2480	7808	48.70	ver	pk	53.98	-5.28 dB
F _{MID}	2402–2480	9467	42.34	hor	pk	53.98	-11.64 dB
F _{MID}	2402–2480	12260	42.91	ver	pk	53.98	-11.07 dB

Comments:


ANNEX A Transmitter radiated spurious emissions

Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Rohde & Schwarz HK 116, Horizontal
Measurement distance:	3 m
Mode:	TX; #A01, DH5; 2402 MHz
Test Date:	2015-06-04
Note:	

Index 29




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3 m
Mode:	TX; #A01, DH5; 2402 MHz
Test Date:	2015-06-04
Note:	

Index 30




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Rohde & Schwarz HL 223, Horizontal
Measurement distance:	3 m
Mode:	TX; #A01, DH5; 2402 MHz
Test Date:	2015-06-04
Note:	

Index 31




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Rohde & Schwarz HL 223, Vertical
Measurement distance:	3 m
Mode:	TX; #A01, DH5; 2402 MHz
Test Date:	2015-06-04
Note:	

Index 32




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 120 VAC
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; #A01, DH5; 2402 MHz
 Test Date: 2015-06-04
 Note:

Index 33




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 120 VAC
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; #A01, DH5; 2402 MHz
 Test Date: 2015-06-04
 Note:

Index 38




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2402 MHz
Test Date:	2015-06-04
Note:	lower bandedge

Index 34




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2402 MHz
Test Date:	2015-06-04
Note:	lower bandedge

Index 39




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 120 VAC
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 1 m converted to 3m
 Mode: TX; #A01, DH5; 2402 MHz
 Test Date: 2015-06-04
 Note:

Index 35



Frequency	Peak	Peak Limit	Peak Difference	Status
4.804 GHz	55.13 dBµV/m	74 dBµV/m	-18.87 dB	Pass
Frequency	Average	Average Limit	Average Difference	Average Status
4.804 GHz	52.79 dBµV/m	54 dBµV/m	-1.21 dB	Pass

Test Report No.: G0M-1505-4755-TFC247BT-V01


 Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 120 VAC
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 1 m converted to 3m
 Mode: TX; #A01, DH5; 2402 MHz
 Test Date: 2015-06-04
 Note:

Index 40



Frequency	Peak	Peak Limit	Peak Difference	Status
4.804 GHz	54.35 dBµV/m	74 dBµV/m	-19.65 dB	Pass
Frequency	Average	Average Limit	Average Difference	Average Status
4.804 GHz	52.4 dBµV/m	54 dBµV/m	-1.6 dB	Pass

Test Report No.: G0M-1505-4755-TFC247BT-V01


 Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2402 MHz
Test Date:	2015-06-04
Note:	

Index 36




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2402 MHz
Test Date:	2015-06-04
Note:	

Index 41




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2402 MHz
Test Date:	2015-06-04
Note:	

Index 37




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2402 MHz
Test Date:	2015-06-04
Note:	

Index 42




Spurious emissions according to FCC Part 15b

Project number: GOM-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 120 VAC
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; #A01, DH5; 2441 MHz
 Test Date: 2015-06-04
 Note:

Index 43




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.33 GHz	51.52 dBµV/m	74 dBµV/m	-22.48 dB	Pass

Spurious emissions according to FCC Part 15b

Project number: GOM-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 120 VAC
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; #A01, DH5; 2441 MHz
 Test Date: 2015-06-05
 Note:

Index 48




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 120 VAC
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 1 m converted to 3m
 Mode: TX; #A01, DH5; 2441 MHz
 Test Date: 2015-06-04
 Note:

Index 44



Frequency	Peak	Peak Limit	Peak Difference	Status
4.88 GHz	50.59 dBµV/m	74 dBµV/m	-23.41 dB	Pass

Test Report No.: G0M-1505-4755-TFC247BT-V01


 Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 120 VAC
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 1 m converted to 3m
 Mode: TX; #A01, DH5; 2441 MHz
 Test Date: 2015-06-05
 Note:

Index 49



Frequency	Peak	Peak Limit	Peak Difference	Status
4.88 GHz	48.05 dBµV/m	74 dBµV/m	-25.95 dB	Pass

Test Report No.: G0M-1505-4755-TFC247BT-V01


 Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2441 MHz
Test Date:	2015-06-04
Note:	

Index 45




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2441 MHz
Test Date:	2015-06-05
Note:	

Index 50




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2441 MHz
Test Date:	2015-06-04
Note:	

Index 46




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2441 MHz
Test Date:	2015-06-05
Note:	

Index 51




Spurious emissions according to FCC Part 15b

Project number: GOM-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 120 VAC
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 3 m
 Mode: TX; #A01, DH5; 2480 MHz
 Test Date: 2015-06-05
 Note:

Index 52




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 120 VAC
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: TX; #A01, DH5; 2480 MHz
 Test Date: 2015-06-05
 Note:

Index 57




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 120 VAC
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 1 m converted to 3m
 Mode: TX; #A01, DH5; 2480 MHz
 Test Date: 2015-06-05
 Note: upper bandedge

Index 53



Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.4835 GHz	52.42 dBµV/m	74 dBµV/m	-21.58 dB	Pass
Frequency	RMS	RMS Limit	RMS Difference	RMS Status
2.4835 GHz	42.32 dBµV/m	54 dBµV/m	-11.68 dB	Pass

Test Report No.: G0M-1505-4755-TFC247BT-V01


 Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2480 MHz
Test Date:	2015-06-05
Note:	upper bandedge

Index 58




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
2.4835 GHz	51.11 dBµV/m	74 dBµV/m	-22.89 dB	Pass
Frequency	RMS	RMS Limit	RMS Difference	RMS Status
2.4835 GHz	40.38 dBµV/m	54 dBµV/m	-13.62 dB	Pass

Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 120 VAC
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 1 m converted to 3m
 Mode: TX; #A01, DH5; 2480 MHz
 Test Date: 2015-06-05
 Note:

Index 54



Frequency	Peak	Peak Limit	Peak Difference	Status
4.96 GHz	54.46 dBµV/m	74 dBµV/m	-19.54 dB	Pass
Frequency	Average	Average Limit	Average Difference	Average Status
4.96 GHz	52.78 dBµV/m	54 dBµV/m	-1.22 dB	Pass

Test Report No.: G0M-1505-4755-TFC247BT-V01


 Eurofins Product Service GmbH
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 120 VAC
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 1 m converted to 3m
 Mode: TX; #A01, DH5; 2480 MHz
 Test Date: 2015-06-05
 Note:

Index 59




Frequency	Peak	Peak Limit	Peak Difference	Status
4.96 GHz	49.89 dBµV/m	74 dBµV/m	-24.11 dB	Pass
Frequency	Average	Average Limit	Average Difference	Average Status
4.96 GHz	47.77 dBµV/m	54 dBµV/m	-6.23 dB	Pass

Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2480 MHz
Test Date:	2015-06-05
Note:	

Index 55




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2480 MHz
Test Date:	2015-06-05
Note:	

Index 60




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Rohde & Schwarz HL 025, Horizontal
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2480 MHz
Test Date:	2015-06-05
Note:	

Index 56




Spurious emissions according to FCC Part 15b

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 120 VAC
Antenna:	Rohde & Schwarz HL 025, Vertical
Measurement distance:	1 m converted to 3m
Mode:	TX; #A01, DH5; 2480 MHz
Test Date:	2015-06-05
Note:	

Index 61




ANNEX B Receiver radiated spurious emissions

Spurious emissions according to RSS-GEN

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC lithium battery
 Antenna: Rohde & Schwarz HK 116, Horizontal
 Measurement distance: 3 m
 Mode: RX; #A01, BT; scan mode
 Test Date: 2015-06-05
 Note:

Index 97




Spurious emissions according to RSS-GEN

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 3.7 V DC lithium battery
Antenna:	Rohde & Schwarz HK 116, Vertical
Measurement distance:	3 m
Mode:	RX; #A01, BT; scan mode
Test Date:	2015-06-05
Note:	

Index 98




Spurious emissions according to RSS-GEN

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC lithium battery
 Antenna: Rohde & Schwarz HL 223, Horizontal
 Measurement distance: 3 m
 Mode: RX; #A01, BT; scan mode
 Test Date: 2015-06-05
 Note:

Index 99




Frequency	Peak	Peak Limit	Peak Difference	Status
910.4 MHz	20.38 dBµV/m	46 dBµV/m	-25.62 dB	Pass

Spurious emissions according to RSS-GEN

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 3.7 V DC lithium battery
Antenna:	Rohde & Schwarz HL 223, Vertical
Measurement distance:	3 m
Mode:	RX; #A01, BT; scan mode
Test Date:	2015-06-05
Note:	

Index 100




Spurious emissions according to RSS-GEN

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 3.7 V DC lithium battery
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	3 m
Mode:	RX; #A01, BT; scan mode
Test Date:	2015-06-05
Note:	

Index 91




Spurious emissions according to RSS-GEN

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 3.7 V DC lithium battery
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	3 m
Mode:	RX; #A01, BT; scan mode
Test Date:	2015-06-05
Note:	

Index 94




Spurious emissions according to RSS-GEN

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 3.7 V DC lithium battery
Antenna:	Schwarzbeck BBHA 9120D, Horizontal
Measurement distance:	3 m
Mode:	RX; #A01, BT; scan mode
Test Date:	2015-06-05
Note:	

Index 92




Spurious emissions according to RSS-GEN

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC lithium battery
 Antenna: Schwarzbeck BBHA 9120D, Vertical
 Measurement distance: 3 m
 Mode: RX; #A01, BT; scan mode
 Test Date: 2015-06-05
 Note:

Index 95




Frequency	Peak	Peak Limit	Peak Difference	Peak Status
7.808 GHz	48.7 dBµV/m	53.98 dBµV/m	-5.28 dB	Pass

Spurious emissions according to RSS-GEN

Project number: G0M-1505-4755

Applicant: Spectralink Europe ApS
 EUT Name: DECT handset 7742
 Model: K023a
 Test Site: Eurofins Product Service GmbH
 Operator: Mr. Treffke
 Test Conditions: Tnom: 24°C, Vnom: 3.7 V DC lithium battery
 Antenna: Schwarzbeck BBHA 9120D, Horizontal
 Measurement distance: 1 m converted to 3m
 Mode: RX; #A01, BT; scan mode
 Test Date: 2015-06-05
 Note:

Index 93




Frequency	Peak	Peak Limit	Peak Difference	Status
9.467 GHz	42.34 dBµV/m	53.98 dBµV/m	-11.64 dB	Pass

Spurious emissions according to RSS-GEN

Project number: G0M-1505-4755

Applicant:	Spectralink Europe ApS
EUT Name:	DECT handset 7742
Model:	K023a
Test Site:	Eurofins Product Service GmbH
Operator:	Mr. Treffke
Test Conditions:	Tnom: 24°C, Vnom: 3.7 V DC lithium battery
Antenna:	Schwarzbeck BBHA 9120D, Vertical
Measurement distance:	1 m converted to 3m
Mode:	RX; #A01, BT; scan mode
Test Date:	2015-06-05
Note:	

Index 96



Frequency	Peak	Peak Limit	Peak Difference	Status
12.26 GHz	42.91 dBµV/m	53.98 dBµV/m	-11.07 dB	Pass