

**TCB****GRANT OF EQUIPMENT  
AUTHORIZATION****TCB**

Certification  
 Issued Under the Authority of the  
 Federal Communications Commission  
 By:

ACB, Inc.  
 6731 Whittier Avenue Suite C110  
 McLean, VA 22101

Date of Grant: 06/11/2020  
 Application Dated: 05/21/2020

MobileHelp, LLC  
 5050 Conference Way N,  
 Suite 125  
 Boca Raton, FL 33431

Attention: Robert Flippo , President

**NOT TRANSFERABLE**

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: PXT-20205EG91NA  
 Name of Grantee: MobileHelp, LLC  
 Equipment Class: PCS Licensed Transmitter  
 Notes: LTE Module  
 Modular Type: Single Modular

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
BC	22H	826.4 - 846.6	0.205	0.0068 PM	4M14F9W
BC	22H	824.7 - 848.3	0.265	0.01387 PM	1M12G7D
BC	22H	824.7 - 848.3	0.256	0.00574 PM	2M75W7D
BC	22H	824.7 - 848.3	0.261	0.01387 PM	9M02G7D
BC	22H	824.7 - 848.3	0.253	0.00574 PM	9M02W7D
BC	24E	1852.4 - 1907.6	0.218	0.00323 PM	4M14F9W
BC	24E	1850.7 - 1909.3	0.278	0.00211 PM	9M05G7D
BC	24E	1850.7 - 1909.3	0.259	0.00258 PM	9M02W7D
BC	24E	1850.7 - 1909.3	0.275	0.00211 PM	17M9G7D
BC	24E	1850.7 - 1909.3	0.256	0.00258 PM	17M9W7D
BC	27	1712.4 - 1752.6	0.228	0.00135 PM	4M13F9W
BC	27	1710.7 - 1754.3	0.27	0.00264 PM	9M02G7D
BC	27	1710.7 - 1754.3	0.236	0.00241 PM	9M06W7D
BC	27	1710.7 - 1754.3	0.267	0.00264 PM	17M9G7D
BC	27	1710.7 - 1754.3	0.233	0.00241 PM	17M9W7D
BC	27	699.7 - 715.3	0.265	0.00416 PM	2M74G7D
BC	27	699.7 - 715.3	0.242	0.00758 PM	1M12W7D
BC	27	699.7 - 715.3	0.263	0.00416 PM	9M03G7D
BC	27	699.7 - 715.3	0.233	0.00758 PM	9M02W7D
BC	27	779.5 - 784.5	0.248	0.01015 PM	4M53G7D
BC	27	779.5 - 784.5	0.205	0.0117 PM	4M53W7D
BC	27	779.5 - 784.5	0.238	0.01015 PM	9M04G7D
BC	27	779.5 - 784.5	0.21	0.0117 PM	9M05W7D

Modular Approval. Power output listed is conducted. This grant is valid only when the module is sold to OEM integrators and must be installed by the OEM or OEM integrators. The antennas used for this transmitter as shown in this filing must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. Maximum antenna gain (including cable loss) must not exceed 4dBi for WCDMA and LTE. End-users may not be provided with the module installation instructions. OEM integrators and end-users must be provided with transmitter operating conditions for satisfying RF exposure compliance. This module can only be used with a host antenna circuit trace layout design in strict compliance with the OEM instructions provided.

BC: The output power is continuously variable from the value listed in this entry to 5%-10% of the value listed.