

# FCC TEST REPORT

according to

## FCC Rules and Regulations

### Part 15 Subpart C

Applicant	Netgear Inc.
Address	4500 Great America Parkway Santa Clara California 95054 USA
Equipment	11g 8 port wireless VPN router
Model No.	FVG318
FCC ID	PY305200007
Trade Name	Netgear

Laboratory Accreditation



1332

- The test result refers exclusively to the test presented test model / sample.,
- Without written approval of **Exclusive Certification Corp.** the test report shall not be reproduced except in full.
- The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

## Contents

<b>1. Report of Measurements and Examinations</b> .....	<b>5</b>
1.1 List of Measurements and Examinations.....	5
<b>2. Test Configuration of Equipment under Test</b> .....	<b>6</b>
2.1 Feature of Equipment under Test.....	6
2.2 RF Module Specifications .....	6
2.3 Test Mode and Test Software.....	7
2.4 Description of Test System.....	7
2.5 Connection Diagram of Test System.....	8
2.6 General Information of Test.....	9
2.7 History of this test report .....	9
<b>3. Antenna Requirements</b> .....	<b>10</b>
3.1 Standard Applicable .....	10
3.2 Antenna Construction and Directional Gain.....	10
<b>4. Test of Conducted Emission</b> .....	<b>11</b>
4.1 Test Limit.....	11
4.2 Test Procedures.....	11
4.3 Typical Test Setup .....	12
4.4 Measurement equipment .....	12
4.5 Test Result and Data.....	13
<b>5. Test of Radiated Emission</b> .....	<b>33</b>
5.1 Test Limit.....	33
5.2 Test Procedures.....	33
5.3 Typical Test Setup .....	33
5.4 Measurement equipment .....	33
5.5 Test Result and Data.....	33
<b>6. 6dB Bandwidth Measurement Data</b> .....	<b>33</b>
6.1 Test Limit .....	33
6.2 Test Procedures .....	33
6.3 Test Setup Layout .....	33
6.4 Measurement equipment .....	33
6.5 Test Result and Data.....	33
<b>7. Maximum Peak Output Power</b> .....	<b>33</b>
7.1 Test Limit .....	33
7.2 Test Procedures .....	33
7.3 Test Setup Layout .....	33
7.4 List of Measuring Equipment Used.....	33
7.5 Test Result and Data.....	33
<b>8. Band Edges Measurement</b> .....	<b>33</b>
8.1 Test Limit .....	33
8.2 Test Procedure : .....	33
8.3 Test Setup Layout .....	33
8.4 List of Measuring Equipment Used.....	33
8.5 Test Result and Data.....	33
8.6 Restrict band emission Measurement Data.....	33
<b>9. Power Spectral Density</b> .....	<b>33</b>
9.1 Test Limit .....	33

9.2	Test Procedures .....	33
9.3	Test Setup Layout : .....	33
9.4	List of Measuring Equipment Used .....	33
9.5	Test Result and Data .....	33
<b>10.</b>	<b>Restricted Bands of Operation .....</b>	<b>33</b>
10.1	Labeling Requirement .....	33
<b>Appendix A.</b>	<b>Photographs of EUT .....</b>	<b>A1 ~ A9</b>

# CERTIFICATE OF COMPLIANCE

according to

## FCC Rules and Regulations

### Part 15 Subpart C

Applicant	Netgear Inc.
Address	4500 Great America Parkway Santa Clara California 95054 USA
Equipment	11g 8 port wireless VPN router
Model No.	FVG318
FCC ID	PY305200007

#### I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4**. The equipment was **passed** the test performed according to **FCC Rules and Regulations Part 15 Subpart C (2003)**. The test was carried out on Aug 26, 2005 at *Exclusive Certification Corp.*

Signature

  
Anson Chou / Manager

## 1. Report of Measurements and Examinations

### 1.1 List of Measurements and Examinations

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	Pass
15.207	. Conducted Emission	Pass
15.209	. Radiated Emission	Pass
15.247(a)(2)	. 6dB Bandwidth	Pass
15.247(b)	. Maximum Peak Output Power	Pass
15.247(c)	. 100kHz Bandwidth of Frequency Band Edges	Pass
15.247(d)	. Power Spectral Density	Pass
1.1307 1.1310 2.1091 2.1093	. RF Exposure Compliance	Pass

Test engineer: \_\_\_\_\_

*Jerry*

## 2. Test Configuration of Equipment under Test

### 2.1 Feature of Equipment under Test

- 802.11g and 802.11b standards-based wireless networking
- Wireless Multimedia (WMM) support
- Easy, Web-based setup for installation and management.
- Front panel LEDs for easy monitoring of status and activity.
- Content filtering and site blocking security
- Built-in eight-port 10/100 Mbps switch
- Ethernet connection to a WAN device, such as a cable modem or DSL modem
- Extensive protocol support
- Flash memory for upgrade

### 2.2 RF Module Specifications

Test Name	Criteria	Unit
• Output Power @11M	17.5	dBm
• Output Power @5.5M	17.5	dBm
• Output Power @2M	17.5	dBm
• Output Power @1M	17.5	dBm
• Output Power @54M	15 +/- 1.5	dBm
• Output Power @36M	15 +/- 1.5	dBm
• Output Power @24M	15 +/- 1.5	dBm
• Output Power @12M	15 +/- 1.5	dBm
• Output Power @6M	15 +/-1.5	dBm
• Sensertivity @ 11M	<-88	dBm
• Sensertivity @ 5.5M	<-90	dBm
• Sensertivity @ 2M	<-91	dBm
• Sensertivity @1M	<-93	dBm
• Sensertivity @ 54M	<-73	dBm
• Sensertivity @ 48M	<-75	dBm
• Sensertivity @ 36M	<-77	dBm
• Sensertivity @ 24M	<-79	dBm
• Sensertivity @ 12M	<-85	dBm
• Sensertivity @ 6M	<-86	dBm

## 2.3 Test Mode and Test Software

The following test mode and test software was performed for conduction and radiation test:

- 802.11b (CH LO: 2412MHz) • 802.11b (CH MID: 2437MHz) • 802.11b (CH HI: 2462MHz)
- 802.11g (CH LO: 2412MHz) • 802.11g (CH MID: 2437MHz) • 802.11g (CH HI: 2462MHz)
- 802.11 super g (CH MID: 2437MHz)
- An executive programs, "ART.exe" Application under WIN XP.

The test mode include two kind of adapter:

- Adapter model 1 : DSA-0131F-12
- Adapter model 2 : ADS18B-W


## 2.4 Description of Test System

Device	Manufacturer	Model No.	Description
PC	IBM	IGV	Power Cable, Unshielding 1.8 m
Monitor	SlimAGE	510A	Power Cable, Adapter Unshielding 1.8 m Data Cable, VGA shielding 1.35 m
Keyboard	IBM	KB-0225	Data Cable, PS2 shielding 1.85 m
Mouse	IBM	MO28VO	Data Cable, USB shielding 1.85 m
Modem	ACEXX	DM-1414	Power Cable, Adapter Unshielding 1.8 m Data Cable, RS232 shielding 1.35 m
Printer	HP	Desk Jet400	Power Cable, Adapter Unshielding 1.8 m Data Cable, PRINT shielding 1.6 m
Notebook (Remote site)	IBM	R40(2723-BV1)	Power Cable, Adapter Unshielding 1.8 m

Use Cable:

Cable	Description
RJ 45*7	Unshielding, 1.5m
RJ 45*1	Unshielding, 1 m
RJ 45*1	Unshielding, 3m

## 2.5 Connection Diagram of Test System



1. The RJ 45 cable is connected form remote workstation to the EUT.
2. The RJ 45 cable is connected from PC to the EUT.
3. The I/O cable is connected from PC to the Modem.
4. The I/O cable is connected from PC to the Printer.
5. The I/O cable is connected from PC to the Monitor.
6. The I/O cable is connected from PC to the Mouse.
7. The I/O cable is connected from PC to the Keyboard.
8. These cables are floating.

## 2.6 General Information of Test

Test Site:	Exclusive Certification Corp. 4F-2, No. 28, Lane 78, Xing-Ai Rd. Nei-hu, Taipei City 114 Taiwan R.O.C.
Test Site Location (OATS1-SD):	No.68-1, Shihbachongsi, shihding Township, Taipei County 223, Taiwan, R.O.C.
Test Voltage:	AC 120V/ 60Hz
Test in Compliance with:	ANSI C63.4-2003 FCC Part 15 Subpart C
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 24620MHz
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.

## 2.7 History of this test report

ORIGINAL.

### 3. Antenna Requirements

#### 3.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

#### 3.2 Antenna Construction and Directional Gain

Antenna type: Reverse SMA connector, dipole Antenna.

Antenna Gain: 5 dBi.

## 4. Test of Conducted Emission

### 4.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 115 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2003 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


Frequency (MHz)	Quasi Peak (dB $\mu$ V)	Average (dB $\mu$ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

\*Decreases with the logarithm of the frequency.

### 4.2 Test Procedures

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connecting to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 micro-henry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

### 4.3 Typical Test Setup



### 4.4 Measurement equipment


Instrument/Ancillary	Type	Manufacturer	Next Cal. Dat
Receiver	SCR3501	Schaffner	2005/11/03
LISN	NNB-2/16Z	MESS TEC	2006/03/30
LISN	NNB-2/16Z	ROLF HEINE	2006/05/01

### 4.5 Test Result and Data

The test mode include two kind of adapter:

Test Adapter 1 : DSA-0131F-12

EUT	: FVG318	Pol/Phase	: NEUTRAL
Power	: AC 120V	Temperature	: 25 °C
Test Mode	: 802.11b CH1	Humidity	: 70 %
Memo	: DSA-0131F-12		




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	21.91	0.32	22.23	55.99	-33.76	AVERAGE
0.15	39.46	0.32	39.78	65.99	-26.20	QP
0.27	39.05	0.34	39.39	60.99	-21.60	QP
0.27	21.81	0.34	22.15	50.99	-28.84	AVERAGE
0.40	35.64	0.50	36.14	57.76	-21.62	QP
0.40	31.08	0.50	31.58	47.76	-16.18	AVERAGE
0.53	32.35	0.50	32.85	56.00	-23.15	QP
0.53	27.34	0.50	27.84	46.00	-18.16	AVERAGE
0.81	30.41	0.50	30.91	56.00	-25.09	QP
0.81	14.24	0.50	14.74	46.00	-31.26	AVERAGE
2.82	31.99	0.60	32.59	56.00	-23.41	QP
2.82	29.00	0.60	29.60	46.00	-16.40	AVERAGE
23.13	44.12	0.80	44.92	60.00	-15.08	QP
23.13	39.57	0.80	40.37	50.00	-9.63	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11b CH1  
 Memo : DSA-0131F-12

Pol/Phase : LINE  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	36.23	0.38	36.61	65.87	-29.26	QP
0.15	24.45	0.38	24.83	55.87	-31.04	AVERAGE
0.26	38.47	0.41	38.88	61.50	-22.62	QP
0.26	20.98	0.41	21.39	51.50	-30.11	AVERAGE
0.41	36.58	0.60	37.18	57.74	-20.56	QP
0.41	31.50	0.60	32.10	47.74	-15.64	AVERAGE
0.53	36.27	0.57	36.84	56.00	-19.16	QP
0.53	29.29	0.57	29.86	46.00	-16.14	AVERAGE
0.71	21.95	0.54	22.49	46.00	-23.51	AVERAGE
0.71	31.76	0.54	32.30	56.00	-23.70	QP
23.13	43.77	0.73	44.50	60.00	-15.50	QP
23.13	39.18	0.73	39.91	50.00	-10.09	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11b CH6  
 Memo : DSA-0131F-12

Pol/Phase : NEUTRAL  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	21.99	0.32	22.31	55.99	-33.68	AVERAGE
0.15	39.55	0.32	39.87	65.99	-26.11	QP
0.27	39.16	0.34	39.50	60.99	-21.49	QP
0.27	21.90	0.34	22.24	50.99	-28.75	AVERAGE
0.40	35.54	0.50	36.04	57.76	-21.72	QP
0.40	31.00	0.50	31.50	47.76	-16.26	AVERAGE
0.53	32.26	0.50	32.76	56.00	-23.24	QP
0.53	27.50	0.50	28.00	46.00	-18.00	AVERAGE
0.81	30.39	0.50	30.89	56.00	-25.11	QP
0.81	14.24	0.50	14.74	46.00	-31.26	AVERAGE
2.82	31.87	0.60	32.47	56.00	-23.53	QP
2.82	28.77	0.60	29.37	46.00	-16.63	AVERAGE
23.13	44.12	0.80	44.92	60.00	-15.08	QP
23.13	39.57	0.80	40.37	50.00	-9.63	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11b CH6  
 Memo : DSA-0131F-12

Pol/Phase : LINE  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	36.36	0.38	36.74	65.87	-29.13	QP
0.15	24.52	0.38	24.90	55.87	-30.97	AVERAGE
0.26	38.33	0.41	38.74	61.50	-22.76	QP
0.26	20.88	0.41	21.29	51.50	-30.21	AVERAGE
0.41	36.42	0.60	37.02	57.74	-20.72	QP
0.41	31.39	0.60	31.99	47.74	-15.75	AVERAGE
0.53	36.23	0.57	36.80	56.00	-19.20	QP
0.53	29.39	0.57	29.96	46.00	-16.04	AVERAGE
0.71	21.90	0.54	22.44	46.00	-23.56	AVERAGE
0.71	31.76	0.54	32.30	56.00	-23.70	QP
23.13	43.70	0.73	44.43	60.00	-15.57	QP
23.13	39.14	0.73	39.87	50.00	-10.13	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11b CH11  
 Memo : DSA-0131F-12

Pol/Phase : NEUTRAL  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	21.86	0.32	22.18	55.99	-33.81	AVERAGE
0.15	39.50	0.32	39.82	65.99	-26.16	QP
0.27	39.10	0.34	39.44	60.99	-21.55	QP
0.27	21.80	0.34	22.14	50.99	-28.85	AVERAGE
0.40	35.50	0.50	36.00	57.76	-21.76	QP
0.40	31.30	0.50	31.80	47.76	-15.96	AVERAGE
0.53	32.26	0.50	32.76	56.00	-23.24	QP
0.53	27.50	0.50	28.00	46.00	-18.00	AVERAGE
0.81	30.39	0.50	30.89	56.00	-25.11	QP
0.81	14.24	0.50	14.74	46.00	-31.26	AVERAGE
2.82	31.80	0.60	32.40	56.00	-23.60	QP
2.82	28.77	0.60	29.37	46.00	-16.63	AVERAGE
23.13	44.45	0.80	45.25	60.00	-14.75	QP
23.13	39.80	0.80	40.60	50.00	-9.40	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11b CH11  
 Memo : DSA-0131F-12

Pol/Phase : LINE  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	36.30	0.38	36.68	65.87	-29.19	QP
0.15	24.47	0.38	24.85	55.87	-31.02	AVERAGE
0.26	38.40	0.41	38.81	61.50	-22.69	QP
0.26	20.93	0.41	21.34	51.50	-30.16	AVERAGE
0.41	36.50	0.60	37.10	57.74	-20.64	QP
0.41	31.44	0.60	32.04	47.74	-15.70	AVERAGE
0.53	36.26	0.57	36.83	56.00	-19.17	QP
0.53	29.39	0.57	29.96	46.00	-16.04	AVERAGE
0.71	21.87	0.54	22.41	46.00	-23.59	AVERAGE
0.71	31.74	0.54	32.28	56.00	-23.72	QP
23.13	43.44	0.73	44.17	60.00	-15.83	QP
23.13	39.10	0.73	39.83	50.00	-10.17	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11g CH1  
 Memo : DSA-0131F-12

Pol/Phase : NEUTRAL  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	21.80	0.32	22.12	55.99	-33.87	AVERAGE
0.15	39.43	0.32	39.75	65.99	-26.24	QP
0.27	39.30	0.34	39.64	60.99	-21.35	QP
0.27	21.93	0.34	22.27	50.99	-28.72	AVERAGE
0.40	35.30	0.50	35.80	57.76	-21.96	QP
0.40	31.00	0.50	31.50	47.76	-16.26	AVERAGE
0.53	32.26	0.50	32.76	56.00	-23.24	QP
0.53	27.50	0.50	28.00	46.00	-18.00	AVERAGE
0.81	30.50	0.50	31.00	56.00	-25.00	QP
0.81	14.40	0.50	14.90	46.00	-31.10	AVERAGE
2.82	31.30	0.60	31.90	56.00	-24.10	QP
2.82	28.80	0.60	29.40	46.00	-16.60	AVERAGE
23.13	44.45	0.80	45.25	60.00	-14.75	QP
23.13	39.80	0.80	40.60	50.00	-9.40	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11g CH1  
 Memo : DSA-0131F-12

Pol/Phase : LINE  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	36.50	0.38	36.88	65.87	-28.99	QP
0.15	24.55	0.38	24.93	55.87	-30.94	AVERAGE
0.26	38.39	0.41	38.80	61.50	-22.70	QP
0.26	20.93	0.41	21.34	51.50	-30.16	AVERAGE
0.41	36.88	0.60	37.48	57.74	-20.26	QP
0.41	31.60	0.60	32.20	47.74	-15.54	AVERAGE
0.53	36.35	0.57	36.92	56.00	-19.08	QP
0.53	29.50	0.57	30.07	46.00	-15.93	AVERAGE
0.71	21.99	0.54	22.53	46.00	-23.47	AVERAGE
0.71	31.80	0.54	32.34	56.00	-23.66	QP
23.13	43.50	0.73	44.23	60.00	-15.77	QP
23.13	39.00	0.73	39.73	50.00	-10.27	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11g CH6  
 Memo : DSA-0131F-12

Pol/Phase : NEUTRAL  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	21.94	0.32	22.26	55.99	-33.73	AVERAGE
0.15	39.40	0.32	39.72	65.99	-26.27	QP
0.27	39.55	0.34	39.89	60.99	-21.10	QP
0.27	22.06	0.34	22.40	50.99	-28.59	AVERAGE
0.40	35.54	0.50	36.04	57.76	-21.72	QP
0.40	31.50	0.50	32.00	47.76	-15.76	AVERAGE
0.53	32.33	0.50	32.83	56.00	-23.17	QP
0.53	27.77	0.50	28.27	46.00	-17.73	AVERAGE
0.81	30.42	0.50	30.92	56.00	-25.08	QP
0.81	14.30	0.50	14.80	46.00	-31.20	AVERAGE
2.82	31.57	0.60	32.17	56.00	-23.83	QP
2.82	28.90	0.60	29.50	46.00	-16.50	AVERAGE
23.13	44.45	0.80	45.25	60.00	-14.75	QP
23.13	39.80	0.80	40.60	50.00	-9.40	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11g CH6  
 Memo : DSA-0131F-12

Pol/Phase : LINE  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	36.66	0.38	37.04	65.87	-28.83	QP
0.15	24.59	0.38	24.97	55.87	-30.90	AVERAGE
0.26	38.45	0.41	38.86	61.50	-22.64	QP
0.26	20.90	0.41	21.31	51.50	-30.19	AVERAGE
0.41	36.90	0.60	37.50	57.74	-20.24	QP
0.41	31.65	0.60	32.25	47.74	-15.49	AVERAGE
0.53	36.44	0.57	37.01	56.00	-18.99	QP
0.53	29.53	0.57	30.10	46.00	-15.90	AVERAGE
0.71	22.23	0.54	22.77	46.00	-23.23	AVERAGE
0.71	32.00	0.54	32.54	56.00	-23.46	QP
23.13	43.30	0.73	44.03	60.00	-15.97	QP
23.13	39.40	0.73	40.13	50.00	-9.87	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11g CH11  
 Memo : DSA-0131F-12

Pol/Phase : NEUTRAL  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	21.90	0.32	22.22	55.99	-33.77	AVERAGE
0.15	39.46	0.32	39.78	65.99	-26.20	QP
0.27	39.50	0.34	39.84	60.99	-21.15	QP
0.27	22.00	0.34	22.34	50.99	-28.65	AVERAGE
0.40	35.60	0.50	36.10	57.76	-21.66	QP
0.40	31.90	0.50	32.40	47.76	-15.36	AVERAGE
0.53	32.33	0.50	32.83	56.00	-23.17	QP
0.53	27.77	0.50	28.27	46.00	-17.73	AVERAGE
0.81	30.42	0.50	30.92	56.00	-25.08	QP
0.81	14.30	0.50	14.80	46.00	-31.20	AVERAGE
2.82	31.50	0.60	32.10	56.00	-23.90	QP
2.82	28.97	0.60	29.57	46.00	-16.43	AVERAGE
23.13	44.49	0.80	45.29	60.00	-14.71	QP
23.13	39.93	0.80	40.73	50.00	-9.27	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11g CH11  
 Memo : DSA-0131F-12

Pol/Phase : LINE  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	36.60	0.38	36.98	65.87	-28.89	QP
0.15	24.50	0.38	24.88	55.87	-30.99	AVERAGE
0.26	38.56	0.41	38.97	61.50	-22.53	QP
0.26	20.93	0.41	21.34	51.50	-30.16	AVERAGE
0.41	36.85	0.60	37.45	57.74	-20.29	QP
0.41	31.60	0.60	32.20	47.74	-15.54	AVERAGE
0.53	36.40	0.57	36.97	56.00	-19.03	QP
0.53	29.50	0.57	30.07	46.00	-15.93	AVERAGE
0.71	22.20	0.54	22.74	46.00	-23.26	AVERAGE
0.71	31.94	0.54	32.48	56.00	-23.52	QP
23.13	43.00	0.73	43.73	60.00	-16.27	QP
23.13	39.43	0.73	40.16	50.00	-9.84	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11sg CH6  
 Memo : DSA-0131F-12

Pol/Phase : NEUTRAL  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	21.85	0.32	22.17	55.99	-33.82	AVERAGE
0.15	39.40	0.32	39.72	65.99	-26.27	QP
0.27	39.20	0.34	39.54	60.99	-21.45	QP
0.27	21.87	0.34	22.21	50.99	-28.78	AVERAGE
0.40	35.50	0.50	36.00	57.76	-21.76	QP
0.40	31.80	0.50	32.30	47.76	-15.46	AVERAGE
0.53	32.33	0.50	32.83	56.00	-23.17	QP
0.53	27.77	0.50	28.27	46.00	-17.73	AVERAGE
0.81	30.40	0.50	30.90	56.00	-25.10	QP
0.81	14.30	0.50	14.80	46.00	-31.20	AVERAGE
2.82	31.22	0.60	31.82	56.00	-24.18	QP
2.82	28.60	0.60	29.20	46.00	-16.80	AVERAGE
23.13	44.75	0.80	45.55	60.00	-14.45	QP
23.13	40.15	0.80	40.95	50.00	-9.05	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11sg CH6  
 Memo : DSA-0131F-12

Pol/Phase : LINE  
 Temperature : 25 °C  
 Humidity : 70 %



Trace: (Discrete)


Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	36.47	0.38	36.85	65.87	-29.02	QP
0.15	24.32	0.38	24.70	55.87	-31.17	AVERAGE
0.26	38.50	0.41	38.91	61.50	-22.59	QP
0.26	20.84	0.41	21.25	51.50	-30.25	AVERAGE
0.41	36.80	0.60	37.40	57.74	-20.34	QP
0.41	31.47	0.60	32.07	47.74	-15.67	AVERAGE
0.53	36.21	0.57	36.78	56.00	-19.22	QP
0.53	29.26	0.57	29.83	46.00	-16.17	AVERAGE
0.71	22.14	0.54	22.68	46.00	-23.32	AVERAGE
0.71	31.90	0.54	32.44	56.00	-23.56	QP
23.13	43.00	0.73	43.73	60.00	-16.27	QP
23.13	39.43	0.73	40.16	50.00	-9.84	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

Test Adapter 2:

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11b CH1  
 Memo : ADS18B-W-120100

Pol/Phase : NEUTRAL  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.17	54.41	0.27	54.68	64.95	-10.27	QP
0.17	41.42	0.27	41.69	54.95	-13.26	AVERAGE
0.23	46.25	0.26	46.51	62.55	-16.05	QP
0.23	34.65	0.26	34.91	52.55	-17.65	AVERAGE
0.28	39.44	0.35	39.79	60.69	-20.90	QP
0.28	28.68	0.35	29.03	50.69	-21.66	AVERAGE
0.34	37.94	0.43	38.37	59.20	-20.83	QP
0.34	28.63	0.43	29.06	49.20	-20.14	AVERAGE
0.40	34.66	0.50	35.16	57.91	-22.75	QP
0.40	29.83	0.50	30.33	47.91	-17.58	AVERAGE
19.95	41.26	0.80	42.06	60.00	-17.94	QP
19.95	36.85	0.80	37.65	50.00	-12.35	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11b CH1  
 Memo : ADS18B-W-120100

Pol/Phase : LINE  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.17	54.96	0.35	55.31	64.98	-9.67	QP
0.17	41.71	0.35	42.06	54.98	-12.92	AVERAGE
0.23	47.11	0.35	47.46	62.56	-15.09	QP
0.23	35.22	0.35	35.57	52.56	-16.98	AVERAGE
0.28	40.01	0.45	40.46	60.70	-20.24	QP
0.28	29.20	0.45	29.65	50.70	-21.05	AVERAGE
0.34	38.21	0.53	38.74	59.20	-20.46	QP
0.34	28.39	0.53	28.92	49.20	-20.28	AVERAGE
0.40	35.55	0.60	36.15	57.92	-21.78	QP
0.40	31.48	0.60	32.08	47.92	-15.85	AVERAGE
19.95	39.65	0.60	40.25	60.00	-19.75	QP
19.95	34.52	0.60	35.12	50.00	-14.88	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11b CH6  
 Memo : ADS18B-W-120100

Pol/Phase : NEUTRAL  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.17	54.56	0.27	54.83	64.95	-10.12	QP
0.17	41.36	0.27	41.63	54.95	-13.32	AVERAGE
0.23	46.20	0.26	46.46	62.55	-16.10	QP
0.23	34.60	0.26	34.86	52.55	-17.70	AVERAGE
0.28	39.40	0.35	39.75	60.69	-20.94	QP
0.28	28.58	0.35	28.93	50.69	-21.76	AVERAGE
0.34	37.90	0.43	38.33	59.20	-20.87	QP
0.34	28.57	0.43	29.00	49.20	-20.20	AVERAGE
0.40	34.60	0.50	35.10	57.91	-22.81	QP
0.40	29.76	0.50	30.26	47.91	-17.65	AVERAGE
19.95	41.20	0.80	42.00	60.00	-18.00	QP
19.95	36.80	0.80	37.60	50.00	-12.40	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11b CH6  
 Memo : ADS18B-W-120100

Pol/Phase : LINE  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.17	54.90	0.35	55.25	64.98	-9.73	QP
0.17	41.66	0.35	42.01	54.98	-12.97	AVERAGE
0.23	47.16	0.35	47.51	62.56	-15.04	QP
0.23	35.26	0.35	35.61	52.56	-16.94	AVERAGE
0.28	40.30	0.45	40.75	60.70	-19.95	QP
0.28	29.32	0.45	29.77	50.70	-20.93	AVERAGE
0.34	38.14	0.53	38.67	59.20	-20.53	QP
0.34	28.26	0.53	28.79	49.20	-20.41	AVERAGE
0.40	35.50	0.60	36.10	57.92	-21.83	QP
0.40	31.40	0.60	32.00	47.92	-15.93	AVERAGE
19.95	39.44	0.60	40.04	60.00	-19.96	QP
19.95	34.44	0.60	35.04	50.00	-14.96	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11b CH11  
 Memo : ADS18B-W-120100

Pol/Phase : NEUTRAL  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.17	54.32	0.27	54.59	64.95	-10.36	QP
0.17	41.40	0.27	41.67	54.95	-13.28	AVERAGE
0.23	46.36	0.26	46.62	62.55	-15.94	QP
0.23	34.60	0.26	34.86	52.55	-17.70	AVERAGE
0.28	39.34	0.35	39.69	60.69	-21.00	QP
0.28	28.58	0.35	28.93	50.69	-21.76	AVERAGE
0.34	38.00	0.43	38.43	59.20	-20.77	QP
0.34	28.59	0.43	29.02	49.20	-20.18	AVERAGE
0.40	34.60	0.50	35.10	57.91	-22.81	QP
0.40	29.75	0.50	30.25	47.91	-17.66	AVERAGE
19.95	41.20	0.80	42.00	60.00	-18.00	QP
19.95	36.80	0.80	37.60	50.00	-12.40	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11b CH11  
 Memo : ADS18B-W-120100

Pol/Phase : LINE  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.17	54.90	0.35	55.25	64.98	-9.73	QP
0.17	41.64	0.35	41.99	54.98	-12.99	AVERAGE
0.23	47.04	0.35	47.39	62.56	-15.16	QP
0.23	35.20	0.35	35.55	52.56	-17.00	AVERAGE
0.28	40.26	0.45	40.71	60.70	-19.99	QP
0.28	29.33	0.45	29.78	50.70	-20.92	AVERAGE
0.34	38.20	0.53	38.73	59.20	-20.47	QP
0.34	28.40	0.53	28.93	49.20	-20.27	AVERAGE
0.40	35.47	0.60	36.07	57.92	-21.86	QP
0.40	31.40	0.60	32.00	47.92	-15.93	AVERAGE
19.95	39.47	0.60	40.07	60.00	-19.93	QP
19.95	34.50	0.60	35.10	50.00	-14.90	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11g CH1  
 Memo : ADS18B-W-120100

Pol/Phase : NEUTRAL  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.17	54.35	0.27	54.62	64.95	-10.33	QP
0.17	41.40	0.27	41.67	54.95	-13.28	AVERAGE
0.23	46.21	0.26	46.47	62.55	-16.09	QP
0.23	34.60	0.26	34.86	52.55	-17.70	AVERAGE
0.28	39.40	0.35	39.75	60.69	-20.94	QP
0.28	28.63	0.35	28.98	50.69	-21.71	AVERAGE
0.34	37.90	0.43	38.33	59.20	-20.87	QP
0.34	28.60	0.43	29.03	49.20	-20.17	AVERAGE
0.40	34.66	0.50	35.16	57.91	-22.75	QP
0.40	29.83	0.50	30.33	47.91	-17.58	AVERAGE
19.95	41.20	0.80	42.00	60.00	-18.00	QP
19.95	36.77	0.80	37.57	50.00	-12.43	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11g CH1  
 Memo : ADS18B-W-120100

Pol/Phase : LINE  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.17	54.90	0.35	55.25	64.98	-9.73	QP
0.17	41.64	0.35	41.99	54.98	-12.99	AVERAGE
0.23	46.98	0.35	47.33	62.56	-15.22	QP
0.23	35.14	0.35	35.49	52.56	-17.06	AVERAGE
0.28	40.22	0.45	40.67	60.70	-20.03	QP
0.28	29.36	0.45	29.81	50.70	-20.89	AVERAGE
0.34	38.20	0.53	38.73	59.20	-20.47	QP
0.34	28.47	0.53	29.00	49.20	-20.20	AVERAGE
0.40	35.50	0.60	36.10	57.92	-21.83	QP
0.40	31.41	0.60	32.01	47.92	-15.92	AVERAGE
19.95	39.60	0.60	40.20	60.00	-19.80	QP
19.95	34.52	0.60	35.12	50.00	-14.88	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11g CH6  
 Memo : ADS18B-W-120100

Pol/Phase : NEUTRAL  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.17	54.35	0.27	54.62	64.95	-10.33	QP
0.17	41.40	0.27	41.67	54.95	-13.28	AVERAGE
0.23	46.36	0.26	46.62	62.55	-15.94	QP
0.23	34.60	0.26	34.86	52.55	-17.70	AVERAGE
0.28	39.44	0.35	39.79	60.69	-20.90	QP
0.28	28.68	0.35	29.03	50.69	-21.66	AVERAGE
0.34	37.97	0.43	38.40	59.20	-20.80	QP
0.34	28.63	0.43	29.06	49.20	-20.14	AVERAGE
0.40	34.55	0.50	35.05	57.91	-22.86	QP
0.40	29.76	0.50	30.26	47.91	-17.65	AVERAGE
19.95	41.33	0.80	42.13	60.00	-17.87	QP
19.95	36.90	0.80	37.70	50.00	-12.30	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11g CH6  
 Memo : ADS18B-W-120100

Pol/Phase : LINE  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.17	55.11	0.35	55.46	64.98	-9.52	QP
0.17	41.65	0.35	42.00	54.98	-12.98	AVERAGE
0.23	47.40	0.35	47.75	62.56	-14.80	QP
0.23	35.20	0.35	35.55	52.56	-17.00	AVERAGE
0.28	40.06	0.45	40.51	60.70	-20.19	QP
0.28	29.20	0.45	29.65	50.70	-21.05	AVERAGE
0.34	38.26	0.53	38.79	59.20	-20.41	QP
0.34	28.44	0.53	28.97	49.20	-20.23	AVERAGE
0.40	35.50	0.60	36.10	57.92	-21.83	QP
0.40	31.43	0.60	32.03	47.92	-15.90	AVERAGE
19.95	39.65	0.60	40.25	60.00	-19.75	QP
19.95	34.50	0.60	35.10	50.00	-14.90	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11g CH11  
 Memo : ADS18B-W-120100

Pol/Phase : NEUTRAL  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.17	54.51	0.27	54.78	64.95	-10.17	QP
0.17	41.40	0.27	41.67	54.95	-13.28	AVERAGE
0.23	46.17	0.26	46.43	62.55	-16.13	QP
0.23	34.60	0.26	34.86	52.55	-17.70	AVERAGE
0.28	39.27	0.35	39.62	60.69	-21.07	QP
0.28	28.63	0.35	28.98	50.69	-21.71	AVERAGE
0.34	38.14	0.43	38.57	59.20	-20.63	QP
0.34	28.70	0.43	29.13	49.20	-20.07	AVERAGE
0.40	34.57	0.50	35.07	57.91	-22.84	QP
0.40	29.90	0.50	30.40	47.91	-17.51	AVERAGE
19.95	41.38	0.80	42.18	60.00	-17.82	QP
19.95	37.02	0.80	37.82	50.00	-12.18	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11g CH11  
 Memo : ADS18B-W-120100

Pol/Phase : LINE  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.17	54.90	0.35	55.25	64.98	-9.73	QP
0.17	41.88	0.35	42.23	54.98	-12.75	AVERAGE
0.23	47.24	0.35	47.59	62.56	-14.96	QP
0.23	35.44	0.35	35.79	52.56	-16.76	AVERAGE
0.28	40.16	0.45	40.61	60.70	-20.09	QP
0.28	29.27	0.45	29.72	50.70	-20.98	AVERAGE
0.34	38.12	0.53	38.65	59.20	-20.55	QP
0.34	28.20	0.53	28.73	49.20	-20.47	AVERAGE
0.40	35.50	0.60	36.10	57.92	-21.83	QP
0.40	31.42	0.60	32.02	47.92	-15.91	AVERAGE
19.95	39.59	0.60	40.19	60.00	-19.81	QP
19.95	34.60	0.60	35.20	50.00	-14.80	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11sg CH6  
 Memo : ADS18B-W-120100

Pol/Phase : NEUTRAL  
 Temperature : 25 °C  
 Humidity : 70 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.17	54.45	0.27	54.72	64.95	-10.23	QP
0.17	41.50	0.27	41.77	54.95	-13.18	AVERAGE
0.23	46.19	0.26	46.45	62.55	-16.11	QP
0.23	34.60	0.26	34.86	52.55	-17.70	AVERAGE
0.28	39.57	0.35	39.92	60.69	-20.77	QP
0.28	28.73	0.35	29.08	50.69	-21.61	AVERAGE
0.34	37.86	0.43	38.29	59.20	-20.91	QP
0.34	28.70	0.43	29.13	49.20	-20.07	AVERAGE
0.40	34.61	0.50	35.11	57.91	-22.80	QP
0.40	29.83	0.50	30.33	47.91	-17.58	AVERAGE
19.95	41.13	0.80	41.93	60.00	-18.07	QP
19.95	36.66	0.80	37.46	50.00	-12.54	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

EUT : FVG318  
 Power : AC 120V  
 Test Mode : 802.11sg CH6  
 Memo : ADS18B-W-120100

Pol/Phase : LINE  
 Temperature : 25 °C  
 Humidity : 70 %



Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.17	54.82	0.35	55.17	64.98	-9.81	QP
0.17	41.54	0.35	41.89	54.98	-13.09	AVERAGE
0.23	46.88	0.35	47.23	62.56	-15.32	QP
0.23	35.17	0.35	35.52	52.56	-17.03	AVERAGE
0.28	40.13	0.45	40.58	60.70	-20.12	QP
0.28	29.14	0.45	29.59	50.70	-21.11	AVERAGE
0.34	38.37	0.53	38.90	59.20	-20.30	QP
0.34	28.40	0.53	28.93	49.20	-20.27	AVERAGE
0.40	35.55	0.60	36.15	57.92	-21.78	QP
0.40	31.48	0.60	32.08	47.92	-15.85	AVERAGE
19.95	39.74	0.60	40.34	60.00	-19.66	QP
19.95	34.59	0.60	35.19	50.00	-14.81	AVERAGE

Remarks: 1. Level = Read Level + Factor  
 2. Factor = LISN(ISN) Factor + Cable Loss

Test engineer: Ben

4.5.1 Test Photographs

FRONT VIEW



REAR VIEW



## 5. Test of Radiated Emission

### 5.1 Test Limit

Radiated emissions from 30 MHz to 25 GHz were measured according to the methods defines in ANSI C63.4-2003. The EUT was placed, 0.8 meter above the ground plane, as shown in section 5.6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance Meters	Radiated ( $\mu$ V / M)	Radiated (dB $\mu$ V/ M)
30-88	3	100	40.0
88-216	3	150	43.5
216-960	3	200	46.0
Above 960	3	500	54.0


For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the above table.

Frequency (MHz)	Distance Meters	Radiated (dB $\mu$ V/ M)
30-230	10	30
230-1000	10	37

## 5.2 Test Procedures

1. The EUT was placed on a rotatable table top 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
5. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

### 5.3 Typical Test Setup




### 5.4 Measurement equipment

Instrument/Ancillary	Type	Manufacturer	Valid Date
EMI Receiver	8546A	HP	2006/04/13
Spectrum Analyzer	FSP40	R&S	2005/12/28
Horn Antenna	3115	EMCO	2006/02/21
Horn Antenna	3116	EMCO	2006/02/21
Bilog Antenna	CBL6112B	Schaffner	2006/04/12
Amplifier	8447D	Agilent	2006/02/14
Amplifier	8447D	Agilent	2006/02/22

### 5.5 Test Result and Data

Test Adapter 1: DSA-0131F-12

EUT	: FVG318	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 6	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11b/g		
Rate	: 11/54 Mbps		
Memo	: DSA-0131F-12		




Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
39.35	43.38	-8.60	34.78	40.00	-5.22	QP	250	100
125.05	43.84	-15.94	27.90	43.50	-15.60	Peak	300	100
150.73	48.84	-14.53	34.31	43.50	-9.19	Peak	360	100
200.01	53.91	-17.07	36.84	43.50	-6.66	Peak	360	100
249.73	56.61	-13.36	43.25	46.00	-2.75	QP	360	100
298.68	52.13	-11.32	40.81	46.00	-5.19	QP	200	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 6	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11b/g		
Rate	: 11/54 Mbps		
Memo	: DSA-0131F-12		



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
367.90	46.02	-9.87	36.15	46.00	-9.85	Peak	50	100
375.03	47.93	-9.56	38.37	46.00	-7.63	Peak	50	100
400.03	48.67	-8.88	39.79	46.00	-6.21	Peak	0	100
502.30	41.03	-6.88	34.15	46.00	-11.85	Peak	0	100
600.04	42.53	-4.52	38.01	46.00	-7.99	Peak	90	100
650.02	43.80	-3.97	39.83	46.00	-6.17	Peak	90	100
750.88	39.01	-1.40	37.61	46.00	-8.39	Peak	90	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 6  
 Modulation Type : 802.11b/g  
 Rate : 11/54 Mbps  
 Memo : DSA-0131F-12

Pol/Phase : VERTICAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
124.99	49.72	-15.95	33.77	43.50	-9.73	Peak	50	100
168.88	54.41	-16.63	37.78	43.50	-5.72	QP	50	100
184.00	53.53	-17.27	36.26	43.50	-7.24	Peak	120	100
190.05	50.64	-17.03	33.61	43.50	-9.89	Peak	0	100
197.75	52.76	-17.07	35.69	43.50	-7.81	Peak	80	100
249.73	56.95	-13.36	43.59	46.00	-2.41	QP	300	100
299.23	55.11	-11.32	43.79	46.00	-2.21	QP	300	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.


EUT	: FVG318	Pol/Phase	: VERTICAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 6	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11b/g		
Rate	: 11/54 Mbps		
Memo	: DSA-0131F-12		



Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
325.90	46.31	-10.87	35.43	46.00	-10.57	Peak	0	100
350.40	44.18	-10.43	33.75	46.00	-12.25	Peak	0	100
376.30	44.22	-9.49	34.72	46.00	-11.28	Peak	220	100
500.90	44.37	-6.95	37.42	46.00	-8.58	Peak	220	100
626.90	41.95	-4.24	37.71	46.00	-8.29	Peak	0	100
876.80	42.40	0.46	42.86	46.00	-3.14	QP	0	100

- Notes:
1. Result = Meter Reading + Corrected Factor
  2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
  3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
  4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
  5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
  6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 1	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11b		
Rate	: 11 Mbps		
Memo	: DSA-0131F-12		



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4824.16	42.40	8.12	50.52	74.00	-23.48	Peak	149	100
4824.16	31.91	8.12	40.03	54.00	-13.97	Average	149	100
7235.54	29.20	11.89	41.09	54.00	-12.91	Average	149	100
7235.54	42.17	11.89	54.06	74.00	-19.94	Peak	149	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 1  
 Modulation Type : 802.11b  
 Rate : 11 Mbps  
 Memo : DSA-0131F-12

Pol/Phase : VERTICAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4823.93	53.98	7.36	61.34	74.00	-12.66	Peak	117	100
4823.93	42.22	7.36	49.58	54.00	-4.42	Average	117	100
7235.57	39.41	11.05	50.46	54.00	-3.54	Average	117	100
7235.57	51.17	11.05	62.22	74.00	-11.78	Peak	117	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 6	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11b		
Rate	: 11 Mbps		
Memo	: DSA-0131F-12		




Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4874.05	30.31	8.32	38.63	54.00	-15.37	Average	149	100
4874.05	41.70	8.32	50.02	74.00	-23.98	Peak	149	100
7311.13	40.64	12.05	52.68	74.00	-21.32	Peak	149	100
7311.13	28.61	12.05	40.66	54.00	-13.34	Average	149	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: VERTICAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 6	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11b		
Rate	: 11 Mbps		
Memo	: DSA-0131F-12		




Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4874.04	40.23	7.54	47.77	54.00	-6.23	Average	117	100
4874.04	51.86	7.54	59.40	74.00	-14.60	Peak	117	100
7310.35	46.82	11.14	57.96	74.00	-16.04	Peak	117	100
7310.35	35.60	11.14	46.74	54.00	-7.26	Average	117	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 11	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11b		
Rate	: 11 Mbps		
Memo	: DSA-0131F-12		



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4924.08	33.60	8.51	42.11	54.00	-11.89	Average	149	100
4924.08	45.68	8.51	54.19	74.00	-19.81	Peak	149	100
7386.49	40.63	12.21	52.84	74.00	-21.16	Peak	149	100
7386.49	28.86	12.21	41.07	54.00	-12.93	Average	149	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 11  
 Modulation Type : 802.11b  
 Rate : 11 Mbps  
 Memo : DSA-0131F-12

Pol/Phase : VERTICAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4924.13	41.24	7.72	48.97	54.00	-5.03	Average	117	100
4924.13	52.64	7.72	60.36	74.00	-13.64	Peak	117	100
7388.04	44.29	11.22	55.51	74.00	-18.49	Peak	117	100
7388.04	32.15	11.22	43.38	54.00	-10.62	Average	117	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 1  
 Modulation Type : 802.11g  
 Rate : 54 Mbps  
 Memo : DSA-0131F-12

Pol/Phase : HORIZONTAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4824.09	27.62	8.12	35.75	54.00	-18.25	Average	149	100
4824.09	39.54	8.12	47.67	74.00	-26.33	Peak	149	100
7235.54	40.54	11.89	52.43	74.00	-21.57	Peak	149	100
7235.54	28.82	11.89	40.71	54.00	-13.29	Average	149	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: VERTICAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 1	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11g		
Rate	: 54 Mbps		
Memo	: DSA-0131F-12		




Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4823.56	32.56	7.36	39.92	54.00	-14.08	Average	117	100
4823.56	44.37	7.36	51.73	74.00	-22.27	Peak	117	100
7235.53	42.20	11.05	53.26	74.00	-20.74	Peak	117	100
7235.53	30.62	11.05	41.68	54.00	-12.32	Average	117	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 6  
 Modulation Type : 802.11g  
 Rate : 54 Mbps  
 Memo : DSA-0131F-12

Pol/Phase : HORIZONTAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg




Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4873.77	27.20	8.32	35.52	54.00	-18.48	Average	149	100
4873.77	38.95	8.32	47.27	74.00	-26.73	Peak	149	100
7311.33	40.71	12.05	52.76	74.00	-21.24	Peak	149	100
7311.33	28.40	12.05	40.45	54.00	-13.55	Average	149	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 6  
 Modulation Type : 802.11g  
 Rate : 54 Mbps  
 Memo : DSA-0131F-12

Pol/Phase : VERTICAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg




Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4875.81	31.00	7.55	38.55	54.00	-15.45	Average	117	100
4875.81	42.22	7.55	49.77	74.00	-24.23	Peak	117	100
7311.01	41.92	11.14	53.06	74.00	-20.94	Peak	117	100
7311.01	29.13	11.14	40.27	54.00	-13.73	Average	117	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 11	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11g		
Rate	: 54 Mbps		
Memo	: DSA-0131F-12		




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4924.08	27.60	8.51	36.10	54.00	-17.90	Average	149	100
4924.08	38.95	8.51	47.46	74.00	-26.54	Peak	149	100
7386.29	40.16	12.21	52.37	74.00	-21.63	Peak	149	100
7386.29	28.66	12.21	40.86	54.00	-13.14	Average	149	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: VERTICAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 11	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11g		
Rate	: 54 Mbps		
Memo	: DSA-0131F-12		



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4925.55	43.52	7.73	51.25	74.00	-22.75	Peak	117	100
4925.55	31.53	7.73	39.26	54.00	-14.74	Average	117	100
7385.25	28.63	11.22	39.86	54.00	-14.14	Average	117	100
7385.25	40.02	11.22	51.24	74.00	-22.76	Peak	117	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

```

EUT           : FVG318
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 6
Modulation Type : 802.11sg
Rate          : 108 Mbps
Memo          : DSA-0131F-12

Pol/Phase     : HORIZONTAL
Temperature   : 26 °C
Humidity      : 71 %
Atmospheric Pressure: 1008 mmHg
    
```




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
39.35	43.20	-8.60	34.60	40.00	-5.40	QP	250	100
125.05	43.44	-15.94	27.50	43.50	-16.00	Peak	300	100
150.73	48.85	-14.53	34.32	43.50	-9.18	Peak	360	100
200.01	53.96	-17.07	36.89	43.50	-6.61	Peak	360	100
249.73	56.78	-13.36	43.42	46.00	-2.58	QP	360	100
298.68	52.20	-11.32	40.88	46.00	-5.12	QP	200	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 6	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11sg		
Rate	: 108 Mbps		
Memo	: DSA-0131F-12		



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
367.90	46.49	-9.87	36.62	46.00	-9.38	Peak	50	100
375.03	48.02	-9.56	38.46	46.00	-7.54	Peak	50	100
400.03	48.70	-8.88	39.82	46.00	-6.18	Peak	0	100
502.30	41.48	-6.88	34.60	46.00	-11.40	Peak	0	100
600.04	42.70	-4.52	38.18	46.00	-7.82	Peak	90	100
650.02	44.14	-3.97	40.17	46.00	-5.83	Peak	90	100
750.88	39.26	-1.40	37.86	46.00	-8.14	Peak	90	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 6  
 Modulation Type : 802.11sg  
 Rate : 108 Mbps  
 Memo : DSA-0131F-12

Pol/Phase : VERTICAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
124.99	49.24	-15.95	33.29	43.50	-10.21	Peak	50	100
168.88	54.68	-16.63	38.04	43.50	-5.46	QP	50	100
184.00	53.82	-17.27	36.55	43.50	-6.95	Peak	120	100
190.05	50.39	-17.03	33.36	43.50	-10.14	Peak	0	100
197.75	52.60	-17.07	35.53	43.50	-7.97	Peak	80	100
249.73	56.98	-13.36	43.62	46.00	-2.38	QP	300	100
299.23	55.08	-11.32	43.76	46.00	-2.24	QP	300	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel : 6  
 Modulation Type : 802.11sg  
 Rate : 108 Mbps  
 Memo : DSA-0131F-12

Pol/Phase : VERTICAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure : 1008 mmHg



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
325.90	46.44	-10.87	35.57	46.00	-10.43	Peak	0	100
350.40	44.90	-10.43	34.46	46.00	-11.54	Peak	0	100
376.30	44.73	-9.49	35.23	46.00	-10.77	Peak	220	100
500.90	44.85	-6.95	37.90	46.00	-8.10	Peak	220	100
626.90	41.65	-4.24	37.41	46.00	-8.59	Peak	0	100
876.80	42.70	0.46	43.16	46.00	-2.84	QP	0	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

```

EUT           : FVG318
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 6
Modulation Type : 802.11sg
Rate         : 108 Mbps
Memo         : DSA-0131F-12

Pol/Phase    : HORIZONTAL
Temperature   : 26 °C
Humidity     : 71 %
Atmospheric Pressure: 1008 mmHg
    
```




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4873.80	29.05	8.32	37.36	54.00	-16.64	Average	149	100
4873.80	40.95	8.32	49.27	74.00	-24.73	Peak	149	100
7311.30	42.61	12.05	54.66	74.00	-19.34	Peak	149	100
7311.30	30.47	12.05	42.52	54.00	-11.48	Average	149	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: VERTICAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 6	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11sg		
Rate	: 108 Mbps		
Memo	: DSA-0131F-12		



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4875.80	33.27	7.55	40.82	54.00	-13.18	Average	117	100
4875.80	44.49	7.55	52.04	74.00	-21.96	Peak	117	100
7311.01	44.17	11.14	55.31	74.00	-18.69	Peak	117	100
7311.01	32.13	11.14	43.27	54.00	-10.73	Average	117	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

Test Adapter 2:

EUT	: FVG318	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 6	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11b/g		
Rate	: 11/54 Mbps		
Memo	: ADS18B-W-120100		




Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
39.35	43.44	-8.60	34.84	40.00	-5.16	QP	250	100
125.05	43.94	-15.94	28.00	43.50	-15.50	Peak	300	100
150.73	48.99	-14.53	34.46	43.50	-9.04	Peak	360	100
200.01	53.46	-17.07	36.39	43.50	-7.11	Peak	360	100
249.73	56.88	-13.36	43.52	46.00	-2.48	QP	360	100
298.68	52.15	-11.32	40.83	46.00	-5.17	QP	200	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 6	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11b/g		
Rate	: 11/54 Mbps		
Memo	: ADS18B-W-120100		




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
367.90	46.37	-9.87	36.49	46.00	-9.51	Peak	50	100
375.03	48.25	-9.56	38.69	46.00	-7.31	Peak	50	100
400.03	48.78	-8.88	39.90	46.00	-6.10	Peak	0	100
502.30	41.39	-6.88	34.51	46.00	-11.49	Peak	0	100
600.04	42.49	-4.52	37.97	46.00	-8.03	Peak	90	100
650.02	43.58	-3.97	39.61	46.00	-6.39	Peak	90	100
750.88	39.38	-1.40	37.98	46.00	-8.02	Peak	90	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: VERTICAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 6	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11b/g		
Rate	: 11/54 Mbps		
Memo	: ADS18B-W-120100		



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
124.99	49.66	-15.95	33.71	43.50	-9.79	Peak	50	100
168.88	54.43	-16.63	37.80	43.50	-5.70	QP	50	100
184.00	53.91	-17.27	36.64	43.50	-6.86	Peak	120	100
190.05	50.67	-17.03	33.65	43.50	-9.85	Peak	0	100
197.75	52.96	-17.07	35.89	43.50	-7.61	Peak	80	100
249.73	57.28	-13.36	43.92	46.00	-2.08	QP	300	100
299.23	55.18	-11.32	43.86	46.00	-2.14	QP	300	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 6  
 Modulation Type : 802.11b/g  
 Rate : 11/54 Mbps  
 Memo : ADS18B-W-120100

Pol/Phase : VERTICAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
325.90	46.22	-10.87	35.35	46.00	-10.65	Peak	0	100
350.40	43.91	-10.43	33.48	46.00	-12.52	Peak	0	100
376.30	43.91	-9.49	34.42	46.00	-11.58	Peak	220	100
500.90	44.18	-6.95	37.23	46.00	-8.77	Peak	220	100
626.90	42.03	-4.24	37.79	46.00	-8.21	Peak	0	100
876.80	42.17	0.46	42.63	46.00	-3.37	QP	0	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 1  
 Modulation Type : 802.11b  
 Rate : 11 Mbps  
 Memo : ADS18B-W-120100

Pol/Phase : HORIZONTAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4824.16	42.57	8.12	50.69	74.00	-23.31	Peak	149	100
4824.16	31.81	8.12	39.93	54.00	-14.07	Average	149	100
7235.54	30.05	11.89	41.94	54.00	-12.06	Average	149	100
7235.54	42.17	11.89	54.06	74.00	-19.94	Peak	149	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: VERTICAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 1	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11b		
Rate	: 11 Mbps		
Memo	: ADS18B-W-120100		




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4823.93	54.50	7.36	61.86	74.00	-12.14	Peak	117	100
4823.93	42.82	7.36	50.18	54.00	-3.82	Average	117	100
7235.57	39.46	11.05	50.51	54.00	-3.49	Average	117	100
7235.57	51.67	11.05	62.72	74.00	-11.28	Peak	117	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 6  
 Modulation Type : 802.11b  
 Rate : 11 Mbps  
 Memo : ADS18B-W-120100  
 Pol/Phase : HORIZONTAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4874.05	30.54	8.32	38.85	54.00	-15.15	Average	149	100
4874.05	41.77	8.32	50.09	74.00	-23.91	Peak	149	100
7311.13	40.95	12.05	53.00	74.00	-21.00	Peak	149	100
7311.13	28.80	12.05	40.85	54.00	-13.15	Average	149	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: VERTICAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 6	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11b		
Rate	: 11 Mbps		
Memo	: ADS18B-W-120100		




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4874.04	40.67	7.54	48.21	54.00	-5.79	Average	117	100
4874.04	51.93	7.54	59.47	74.00	-14.53	Peak	117	100
7310.35	46.90	11.14	58.04	74.00	-15.96	Peak	117	100
7310.35	35.57	11.14	46.71	54.00	-7.29	Average	117	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 11	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11b		
Rate	: 11 Mbps		
Memo	: ADS18B-W-120100		



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4924.08	33.97	8.51	42.48	54.00	-11.52	Average	149	100
4924.08	45.88	8.51	54.39	74.00	-19.61	Peak	149	100
7386.49	40.70	12.21	52.91	74.00	-21.09	Peak	149	100
7386.49	28.86	12.21	41.07	54.00	-12.93	Average	149	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

```

EUT           : FVG318
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 11
Modulation Type : 802.11b
Rate          : 11 Mbps
Memo          : ADS18B-W-120100

Pol/Phase    : VERTICAL
Temperature   : 26 °C
Humidity      : 71 %
Atmospheric Pressure: 1008 mmHg
    
```




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4924.13	41.42	7.72	49.14	54.00	-4.86	Average	117	100
4924.13	52.67	7.72	60.39	74.00	-13.61	Peak	117	100
7388.04	44.40	11.22	55.62	74.00	-18.38	Peak	117	100
7388.04	32.47	11.22	43.69	54.00	-10.31	Average	117	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 1  
 Modulation Type : 802.11g  
 Rate : 54 Mbps  
 Memo : ADS18B-W-120100  
 Pol/Phase : HORIZONTAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4824.09	27.62	8.12	35.75	54.00	-18.25	Average	149	100
4824.09	39.54	8.12	47.67	74.00	-26.33	Peak	149	100
7235.54	40.54	11.89	52.43	74.00	-21.57	Peak	149	100
7235.54	28.82	11.89	40.71	54.00	-13.29	Average	149	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

```

EUT           : FVG318
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 1
Modulation Type : 802.11g
Rate         : 54 Mbps
Memo         : ADS18B-W-120100

Pol/Phase    : VERTICAL
Temperature   : 26 °C
Humidity     : 71 %
Atmospheric Pressure: 1008 mmHg
    
```



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4823.56	32.47	7.36	39.83	54.00	-14.17	Average	117	100
4823.56	44.58	7.36	51.93	74.00	-22.07	Peak	117	100
7235.53	42.28	11.05	53.33	74.00	-20.67	Peak	117	100
7235.53	30.64	11.05	41.69	54.00	-12.31	Average	117	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

```

EUT           : FVG318
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 6
Modulation Type : 802.11g
Rate          : 54 Mbps
Memo          : ADS18B-W-120100

Pol/Phase     : HORIZONTAL
Temperature   : 26 °C
Humidity      : 71 %
Atmospheric Pressure: 1008 mmHg
    
```



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4873.77	27.36	8.32	35.68	54.00	-18.32	Average	149	100
4873.77	39.16	8.32	47.48	74.00	-26.52	Peak	149	100
7311.33	40.79	12.05	52.84	74.00	-21.16	Peak	149	100
7311.33	28.47	12.05	40.52	54.00	-13.48	Average	149	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 6  
 Modulation Type : 802.11g  
 Rate : 54 Mbps  
 Memo : ADS18B-W-120100

Pol/Phase : VERTICAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4875.81	31.63	7.55	39.17	54.00	-14.83	Average	117	100
4875.81	42.89	7.55	50.44	74.00	-23.56	Peak	117	100
7311.01	41.97	11.14	53.11	74.00	-20.89	Peak	117	100
7311.01	29.35	11.14	40.49	54.00	-13.51	Average	117	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 11  
 Modulation Type : 802.11g  
 Rate : 54 Mbps  
 Memo : ADS18B-W-120100  
 Pol/Phase : HORIZONTAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4924.08	27.96	8.51	36.47	54.00	-17.53	Average	149	100
4924.08	39.25	8.51	47.76	74.00	-26.24	Peak	149	100
7386.29	40.64	12.21	52.85	74.00	-21.15	Peak	149	100
7386.29	28.86	12.21	41.06	54.00	-12.94	Average	149	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 11  
 Modulation Type : 802.11g  
 Rate : 54 Mbps  
 Memo : ADS18B-W-120100  
 Pol/Phase : VERTICAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4925.55	43.80	7.73	51.53	74.00	-22.47	Peak	117	100
4925.55	31.88	7.73	39.61	54.00	-14.39	Average	117	100
7385.25	28.35	11.22	39.57	54.00	-14.43	Average	117	100
7385.25	40.02	11.22	51.24	74.00	-22.76	Peak	117	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 6	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11sg		
Rate	: 108 Mbps		
Memo	: ADS18B-W-120100		




Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
39.35	43.24	-8.60	34.64	40.00	-5.36	QP	250	100
125.05	43.93	-15.94	27.99	43.50	-15.51	Peak	300	100
150.73	48.99	-14.53	34.46	43.50	-9.04	Peak	360	100
200.01	54.01	-17.07	36.94	43.50	-6.56	Peak	360	100
249.73	56.58	-13.36	43.22	46.00	-2.78	QP	360	100
298.68	52.02	-11.32	40.70	46.00	-5.30	QP	200	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 6  
 Modulation Type : 802.11sg  
 Rate : 108 Mbps  
 Memo : ADS18B-W-120100  
 Pol/Phase : HORIZONTAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
367.90	46.82	-9.87	36.95	46.00	-9.05	Peak	50	100
375.03	48.15	-9.56	38.59	46.00	-7.41	Peak	50	100
400.03	48.72	-8.88	39.84	46.00	-6.16	Peak	0	100
502.30	41.85	-6.88	34.97	46.00	-11.03	Peak	0	100
600.04	43.01	-4.52	38.49	46.00	-7.51	Peak	90	100
650.02	44.54	-3.97	40.57	46.00	-5.43	QP	90	100
750.88	39.26	-1.40	37.86	46.00	-8.14	Peak	90	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel : 6  
 Modulation Type : 802.11sg  
 Rate : 108 Mbps  
 Memo : ADS18B-W-120100

Pol/Phase : VERTICAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure : 1008 mmHg



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
124.99	49.35	-15.95	33.41	43.50	-10.09	Peak	50	100
168.88	55.08	-16.63	38.45	43.50	-5.05	QP	50	100
184.00	53.81	-17.27	36.54	43.50	-6.96	Peak	120	100
190.05	50.67	-17.03	33.64	43.50	-9.86	Peak	0	100
197.75	52.41	-17.07	35.34	43.50	-8.16	Peak	80	100
249.73	57.03	-13.36	43.67	46.00	-2.33	QP	300	100
299.23	55.24	-11.32	43.92	46.00	-2.08	QP	300	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 6  
 Modulation Type : 802.11sg  
 Rate : 108 Mbps  
 Memo : ADS18B-W-120100

Pol/Phase : VERTICAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
325.90	46.61	-10.87	35.74	46.00	-10.26	Peak	0	100
350.40	45.07	-10.43	34.64	46.00	-11.36	Peak	0	100
376.30	44.91	-9.49	35.42	46.00	-10.58	Peak	220	100
500.90	44.88	-6.95	37.93	46.00	-8.07	Peak	220	100
626.90	41.77	-4.24	37.53	46.00	-8.47	Peak	0	100
876.80	43.17	0.46	43.63	46.00	-2.37	QP	0	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT : FVG318  
 Power : AC 120V  
 Test Mode : Transmit/Receive  
 Operation Channel: 6  
 Modulation Type : 802.11sg  
 Rate : 108 Mbps  
 Memo : ADS18B-W-120100

Pol/Phase : HORIZONTAL  
 Temperature : 26 °C  
 Humidity : 71 %  
 Atmospheric Pressure: 1008 mmHg




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4873.80	29.47	8.32	37.78	54.00	-16.22	Average	149	100
4873.80	41.32	8.32	49.64	74.00	-24.36	Peak	149	100
7311.30	42.15	12.05	54.20	74.00	-19.80	Peak	149	100
7311.30	30.40	12.05	42.45	54.00	-11.55	Average	149	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

EUT	: FVG318	Pol/Phase	: VERTICAL
Power	: AC 120V	Temperature	: 26 °C
Test Mode	: Transmit/Receive	Humidity	: 71 %
Operation Channel	: 6	Atmospheric Pressure	: 1008 mmHg
Modulation Type	: 802.11sg		
Rate	: 108 Mbps		
Memo	: ADS18B-W-120100		



Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4875.80	33.57	7.55	41.12	54.00	-12.88	Average	117	100
4875.80	44.62	7.55	52.17	74.00	-21.83	Peak	117	100
7311.01	44.62	11.14	55.75	74.00	-18.25	Peak	117	100
7311.01	32.87	11.14	44.01	54.00	-9.99	Average	117	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too below to be measured.

5.5.1 Test Photographs

FRONT VIEW



REAR VIEW



## 6. 6dB Bandwidth Measurement Data


### 6.1 Test Limit

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

### 6.2 Test Procedures

1. The transmitter output was connected to the spectrum analyzer.
2. Set RBW of spectrum analyzer to 100 KHz and VBW to 100 KHz.
3. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

### 6.3 Test Setup Layout



### 6.4 Measurement equipment

Instrument/Ancillary	Type	Manufacturer	Serial No.	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2005/12/28

### 6.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Aug. 23, 2005    Temperature: 25    Humidity: 70%    Atmospheric pressure: 1012 mmHg

Channel	Frequency (MHz)	6dB Bandwidth (MHz)
01	2412	11.30
06	2437	11.20
11	2462	11.10

(2) Modulation Standard: IEEE 802.11g (54Mbps)

Test Date: Aug. 23, 2005    Temperature: 25    Humidity: 70%    Atmospheric pressure: 1012 mmHg

Channel	Frequency (MHz)	6dB Bandwidth (MHz)
01	2412	16.50
06	2437	16.50
11	2462	16.50


(3) Modulation Standard: IEEE 802.11 Super g (108Mbps)

Test Date: Aug. 23, 2005    Temperature: 25    Humidity: 70%    Atmospheric pressure: 1012 mmHg

Channel	Frequency (MHz)	6dB Bandwidth (MHz)
06	2437	31.80


Modulation Standard: 802.11b (11Mbps)

Channel: 01




Date: 23.AUG.2005 15:21:56

Channel:06




Date: 23.AUG.2005 15:23:15

Channel:11




Date: 23.AUG.2005 15:26:54

Modulation Standard:802.11g (54Mbps)  
 Channel:01




Date: 23.AUG.2005 15:07:29

Channel:06




Date: 23.AUG.2005 15:09:02

Channel:11



Date: 23.AUG.2005 15:10:20

Modulation Standard:802.11 Super g (108Mbps)  
Channel:06



Date: 31.AUG.2005 11:51:16

## 7. Maximum Peak Output Power


### 7.1 Test Limit

The Maximum Peak Output Power Measurement is 30dBm.

### 7.2 Test Procedures

The antenna port( RF output )of the EUT was connected to the input( RF input )of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

### 7.3 Test Setup Layout



### 7.4 List of Measuring Equipment Used

Instrument/Ancillary	Type	Manufacturer	Serial No.	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2005/12/28

### 7.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Aug. 24, 2005 Temperature: 26 Humidity: 70% Atmospheric pressure: 1022 mmHg

Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
01	2412	17.23	52.845
06	2437	17.77	59.841
11	2462	17.68	58.614

(2) Modulation Standard: IEEE 802.11g (54Mbps)

Test Date: Aug. 24, 2005 Temperature: 26 Humidity: 70% Atmospheric pressure: 1022 mmHg

Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
01	2412	15.83	38.282
06	2437	15.94	39.264
11	2462	15.89	38.815


(3) Modulation Standard: IEEE 802.11 Super g (108Mbps)

Test Date: Aug. 24, 2005 Temperature: 26 Humidity: 70% Atmospheric pressure: 1022 mmHg

Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
06	2437	15.94	39.264


Note: Conducted Power = Reading Value + Cable Loss

Modulation Standard:802.11b (11Mbps)  
 Channel:01




Date: 24.AUG.2005 13:44:38

Channel:06




Date: 24.AUG.2005 13:41:55

Channel:11




Date: 24.AUG.2005 13:42:50

Modulation Standard:802.11g (54Mbps)  
Channel:01




Date: 24.AUG.2005 13:58:50

Channel:06




Date: 24.AUG.2005 13:54:31

Channel:11



Date: 24.AUG.2005 13:57:22

Modulation Standard:802.11 Super g (108Mbps)  
 Channel:06



Date: 31.AUG.2005 11:48:28

## 8. Band Edges Measurement


### 8.1 Test Limit

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 8.2 Test Procedure :

- 1.The transmitter output was connected to the spectrum analyzer via a low lose cable.
- 2.Set both RBW and VBW of spectrum analyzer to 100 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- 3.The band edges was measured and recorded.

### 8.3 Test Setup Layout



### 8.4 List of Measuring Equipment Used

Instrument/Ancillary	Type	Manufacturer	Serial No.	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2005/12/28

### 8.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Aug 23, 2005 Temperature: 25 Humidity: 70% Atmospheric pressure: 1012 mmHg

Channel	Frequency	maximum value in frequency (MHz)	maximum value is (dBm)
01	2412	2397.60	-32.05
11	2462	2510.50	-46.18


(2) Modulation Standard: IEEE 802.11g (54Mbps)

Test Date: Aug 23, 2005 Temperature: 25 Humidity: 70% Atmospheric pressure: 1012 mmHg


Channel	Frequency	maximum value in frequency (MHz)	maximum value is (dBm)
01	2412	2400.00	-35.02
11	2462	2483.70	-49.21

Modulation Standard:802.11b (11Mbps)

Channel:01




Date: 23.AUG.2005 15:29:25




Date: 23.AUG.2005 15:30:25

Channel:11




Date: 23.AUG.2005 15:32:39




Date: 23.AUG.2005 15:34:04

Modulation Standard:802.11g (54Mbps)

Channel:01




Date: 23.AUG.2005 15:36:53




Date: 23.AUG.2005 15:37:51

Channel:11



Date: 23.AUG.2005 15:39:40



Date: 23.AUG.2005 15:40:35

**8.6 Restrict band emission Measurement Data**

The test mode include two kind of adapter:

Adapter model 1 : DSA-0131F-12

Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Aug. 26, 2005    Temperature: 26    Humidity: 71%    Atmospheric pressure: 1008 mmHg

a) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2386.704	H	48.89	1.24	50.13	Peak	74	54	-23.87	149	1.1
2389.254	H	37.79	1.25	39.04	Ave	74	54	-14.96	149	1.1
2319.894	V	53.65	0.31	53.96	Peak	74	54	-20.04	117	1.0
2320.914	V	42.47	0.31	42.78	Ave	74	54	-11.22	117	1.0

b) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2494.566	H	49.05	1.61	50.66	Peak	74	54	-23.34	149	1.1
2483.508	H	37.71	1.57	39.28	Ave	74	54	-14.72	149	1.1
2485.066	V	50.76	0.88	51.64	Peak	74	54	-22.36	117	1.0
2483.508	V	39.33	0.87	40.20	Ave	74	54	-13.80	117	1.0

Modulation Standard: 802.11g (54Mbps)

Test Date: Aug. 26, 2005    Temperature: 26    Humidity: 71%    Atmospheric pressure: 1008 mmHg

a) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2372.424	H	49.13	1.19	50.32	Peak	74	54	-23.68	149	1.1
2389.968	H	37.67	1.25	38.92	Ave	74	54	-15.08	149	1.1
2320.098	V	55.09	0.31	55.40	Peak	74	54	-18.60	117	1.0
2321.118	V	43.13	0.31	34.44	Ave	74	54	-10.56	117	1.0

b) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2484.192	H	51.06	1.58	52.64	Peak	74	54	-21.36	149	1.1
2483.508	H	39.16	1.57	40.73	Ave	74	54	-13.27	149	1.1
2483.508	V	53.27	0.87	54.14	Peak	74	54	-19.86	117	1.0
2483.508	V	41.73	0.87	42.60	Ave	74	54	-11.40	117	1.0

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz

Adapter model 2 : ADS18B-W

Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Aug. 26, 2005    Temperature: 26    Humidity: 71%    Atmospheric pressure: 1008 mmHg

c) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2386.704	H	48.89	1.24	50.13	Peak	74	54	-23.87	149	1.1
2389.254	H	36.93	1.25	38.18	Ave	74	54	-15.82	149	1.1
2319.984	V	53.59	0.31	53.90	Peak	74	54	-20.10	117	1.0
2320.914	V	42.00	0.31	42.31	Ave	74	54	-11.69	117	1.0

d) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2494.566	H	48.76	1.61	50.37	Peak	74	54	-23.63	149	1.1
2483.508	H	36.59	1.57	38.16	Ave	74	54	-15.84	149	1.1
2485.466	V	51.45	0.88	55.33	Peak	74	54	-18.67	117	1.0
2483.508	V	39.59	0.87	40.46	Ave	74	54	-13.54	117	1.0

Modulation Standard: 802.11g (54Mbps)

Test Date: Aug. 26, 2005    Temperature: 26    Humidity: 71%    Atmospheric pressure: 1008 mmHg

c) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2372.424	H	50.08	1.19	51.27	Peak	74	54	-22.73	149	1.1
2389.968	H	38.48	1.25	39.73	Ave	74	54	-14.27	149	1.1
2320.098	V	55.14	0.31	55.45	Peak	74	54	-18.55	117	1.0
2321.118	V	43.76	0.31	44.07	Ave	74	54	-9.93	117	1.0

d) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2484.192	H	51.33	1.58	52.91	Peak	74	54	-21.09	149	1.1
2483.508	H	39.66	1.57	41.23	Ave	74	54	-12.77	149	1.1
2483.508	V	53.35	0.87	54.22	Peak	74	54	-19.78	117	1.0
2483.508	V	41.96	0.87	42.83	Ave	74	54	-11.17	117	1.0

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz

## 9. Power Spectral Density


### 9.1 Test Limit

The Maximum of Power Spectral Density Measurement is 8dBm.

### 9.2 Test Procedures

- 1.The transmitter output was connected to spectrum analyzer.
- 2.The spectrum analyzer's resolution bandwidth were set at 3KHz RBW and 30KHz VBW as that of the fundamental frequency. Set the sweep time=span/3KHz.
- 3.The power spectral density was measured and recorded.
- 4.The Sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

### 9.3 Test Setup Layout :



### 9.4 List of Measuring Equipment Used

Instrument/Ancillary	Type	Manufacturer	Serial No.	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2005/12/28

### 9.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Aug. 23, 2005 Temperature: 25 Humidity: 70% Atmospheric pressure: 1012 mmHg

Channel	Frequency	Maximum Power Density of 3 kHz Bandwidth (dBm)
01	2412	-7.84
06	2437	-7.23
11	2462	-7.33

(2) Modulation Standard: IEEE 802.11g (54Mbps)

Test Date: Aug. 23, 2005 Temperature: 25 Humidity: 70% Atmospheric pressure: 1012 mmHg


Channel	Frequency	Maximum Power Density of 3 kHz Bandwidth (dBm)
01	2412	-16.81
06	2437	-16.92
11	2462	-16.53

(3) Modulation Standard: IEEE 802.11 Super g (108Mbps)

Test Date: Aug. 11, 2005 Temperature: 25 Humidity: 70% Atmospheric pressure: 1012 mmHg


Channel	Frequency	Maximum Power Density of 3 kHz Bandwidth (dBm)
06	2437	-22.26

Modulation Standard: 802.11b (11Mbps)  
Channel: 01




Date: 23.AUG.2005 15:48:34

Channel:06




Date: 23.AUG.2005 15:50:37

Channel:11




Date: 23.AUG.2005 15:52:24

Modulation Standard:802.11g (54Mbps)  
 Channel:01




Date: 23.AUG.2005 15:46:14

Channel: 06




Date: 23.AUG.2005 15:44:42

Channel:11



Date: 23.AUG.2005 15:43:10

Modulation Standard:802.11g (108Mbps)  
Channel:06



Date: 31.AUG.2005 11:55:53

## 10. Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

\*\* : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

### 10.1 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.