



# FCC TEST REPORT

**REPORT NO.:** RF950418L04

**MODEL NO.:** EVA700

**RECEIVED:** Apr. 18, 2006

**TESTED:** Apr. 18 ~ Apr. 21, 2006

**ISSUED:** Apr. 26, 2006

**APPLICANT:** NETGEAR, Inc.

**ADDRESS:** 4500 Great America Parkway, Santa Clara, CA  
95054 USA

**ISSUED BY:** Advance Data Technology Corporation

**LAB ADDRESS:** 47 14<sup>th</sup> Lin, Chiapau Tsun, Linko, Taipei,  
Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2<sup>nd</sup> Rd., Kueishan, Taoyuan,  
Taiwan, R.O.C.

This test report consists of 63 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.





## Table of Contents

1	CERTIFICATION.....	4
2	SUMMARY OF TEST RESULTS.....	5
2.1	MEASUREMENT UNCERTAINTY.....	5
3	GENERAL INFORMATION .....	6
3.1	GENERAL DESCRIPTION OF EUT .....	6
3.2	DESCRIPTION OF TEST MODES .....	7
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST .....	7
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL .....	8
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS.....	10
3.4	DESCRIPTION OF SUPPORT UNITS.....	10
4	TEST TYPES AND RESULTS.....	11
4.1	CONDUCTED EMISSION MEASUREMENT.....	11
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	11
4.1.2	TEST INSTRUMENTS .....	11
4.1.3	TEST PROCEDURES .....	12
4.1.4	DEVIATION FROM TEST STANDARD .....	12
4.1.5	TEST SETUP.....	13
4.1.6	EUT OPERATING CONDITIONS.....	13
4.1.7	TEST RESULTS .....	14
4.2	RADIATED EMISSION MEASUREMENT.....	20
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	20
4.2.2	TEST INSTRUMENTS .....	21
4.2.3	TEST PROCEDURES .....	22
4.2.4	DEVIATION FROM TEST STANDARD .....	22
4.2.5	TEST SETUP.....	23
4.2.6	EUT OPERATING CONDITIONS.....	23
4.2.7	TEST RESULTS .....	24
4.3	6dB BANDWIDTH MEASUREMENT .....	31
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT .....	31
4.3.2	TEST INSTRUMENTS .....	31
4.3.3	TEST PROCEDURE.....	32
4.3.4	DEVIATION FROM TEST STANDARD .....	32
4.3.5	TEST SETUP.....	32
4.3.6	EUT OPERATING CONDITIONS.....	32
4.3.7	TEST RESULTS .....	33
4.4	MAXIMUM PEAK OUTPUT POWER .....	39
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	39



4.4.2 TEST INSTRUMENTS .....	39
4.4.3 TEST PROCEDURES .....	40
4.4.4 DEVIATION FROM TEST STANDARD .....	40
4.4.5 TEST SETUP.....	40
4.4.6 EUT OPERATING CONDITIONS.....	40
4.4.7 TEST RESULTS .....	41
4.5 POWER SPECTRAL DENSITY MEASUREMENT.....	42
4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT.....	42
4.5.2 TEST INSTRUMENTS.....	42
4.5.3 TEST PROCEDURE.....	43
4.5.4 DEVIATION FROM TEST STANDARD .....	43
4.5.5 TEST SETUP.....	43
4.5.6 EUT OPERATING CONDITIONS.....	43
4.5.7 TEST RESULTS .....	44
4.6 BAND EDGES MEASUREMENT.....	50
4.6.1 LIMITS OF BAND EDGES MEASUREMENT.....	50
4.6.2 TEST INSTRUMENTS.....	50
4.6.3 TEST PROCEDURE.....	50
4.6.4 DEVIATION FROM TEST STANDARD .....	50
4.6.5 EUT OPERATING CONDITION .....	50
4.6.6 TEST RESULTS .....	51
4.7 ANTENNA REQUIREMENT .....	59
4.7.1 STANDARD APPLICABLE.....	59
4.7.2 ANTENNA CONNECTED CONSTRUCTION.....	59
5 PHOTOGRAPHS OF THE TEST CONFIGURATION.....	60
6 INFORMATION ON THE TESTING LABORATORIES .....	62
APPENDIX-A .....	A-1



## 1 CERTIFICATION

**PRODUCT :** Digital Entertainer  
**MODEL NO.:** EVA700  
**BRAND:** NETGEAR  
**APPLICANT :** NETGEAR, Inc.  
**TESTED:** Apr. 18 ~ Apr. 21, 2006  
**TEST SAMPLE:** ENGINEERING SAMPLE  
**STANDARDS :** FCC Part 15, Subpart C (Section 15.247),  
ANSI C63.4-2003

The above equipment have been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Jessie Wang, DATE: Apr. 26, 2006  
Jessie Wang

**TECHNICAL  
ACCEPTANCE** : Long Chen, DATE: Apr. 26, 2006  
Responsible for RF Long Chen

**APPROVED BY** : Gary Chang, DATE: Apr. 26, 2006  
Gary Chang / Supervisor



## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -21.30dB at 2.680 / 2.637MHz.
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit : min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.15dB at 2483.50MHz.
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20 dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

Measurement	Frequency	Uncertainty
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.73 dB
	200MHz ~1000MHz	3.74 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Digital Entertainer
<b>MODEL NO.</b>	EVA700
<b>FCC ID</b>	PY305300019
<b>POWER SUPPLY</b>	5Vdc from internal power supply
<b>MODULATION TYPE</b>	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
<b>MODULATION TECHNOLOGY</b>	DSSS, OFDM
<b>TRANSFER RATE</b>	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps
<b>FREQUENCY RANGE</b>	2412MHz ~ 2462MHz
<b>NUMBER OF CHANNEL</b>	11
<b>MAXIMUM OUTPUT POWER</b>	51.050mW
<b>ANTENNA TYPE</b>	Dipole antenna with 2dBi gain
<b>I/O PORTS</b>	Refer to user's manual
<b>DATA CABLE</b>	NA

#### NOTE:

1. The EUT is powered by the following internal power supply.

<b>Brand</b>	DEE VAN ENTERPRISE CO., LTD.
<b>Model</b>	DSO-15W-05
<b>Input Power</b>	100~240Vac
<b>Output Power</b>	5Vdc, 3A


2. The EUT, operates in the 2.4GHz frequency range, lets you connect IEEE 802.11g or IEEE 802.11b devices to the network. With its high-speed data transmissions of up to 54Mbps.
3. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### **3.2 DESCRIPTION OF TEST MODES**

Eleven channels are provided to this EUT for normal mode.

<b>Channel</b>	<b>Frequency</b>	<b>Channel</b>	<b>Frequency</b>
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

#### **3.2.1 CONFIGURATION OF SYSTEM UNDER TEST**





### 3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
-	✓	✓	✓	✓	-

Where PLC: Power Line Conducted Emission

RE<1G: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

#### Power Line Conducted Emission Test:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

#### Radiated Emission Test (Below 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11g	1 to 11	11	OFDM	BPSK	6

#### Radiated Emission Test (Above 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6



**Bandedge Measurement:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 11	OFDM	BPSK	6

**Antenna Port Conducted Measurement:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6



### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. (15.247)**  
**ANSI C63.4-2003**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	LCD TV MONITOR	APLUS	LT1531	M1-010439	VERIFICATION
2	VIDEO MONITOR	SONY	PVM-14L2	2102922	FCC DoC Approved
3	5.1CH SPEAKER	Logitech	Z-680	6444477-0000	NA
4	FIREWIRE HARD DRIVE	Terasys	F12-UF	A0100222-5390001	FCC DoC Approved
5	EARPHONE	PHILIPS	SBC HL125	H2-010066	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	1.8m shielded cable
2	1.8m shielded cable
3	1.8m shielded cable
4	1.8m shielded cable
5	1.2m shielded cable

**NOTE:** All power cords of the above support units are non shielded (1.8m).



## 4 TEST TYPES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
0.15-0.5 0.5-5 5-30	Quasi-peak	Average
	66 to 56	56 to 46
	56	46
	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100291	Nov. 11, 2006
RF signal cable Woken	5D-FB	Cable-HYC01-01	Jan. 06, 2007
LISN ROHDE & SCHWARZ	ESH3-Z5	100312	Feb. 15, 2007
LISN ROHDE & SCHWARZ	ESH2-Z5	100104	Feb. 07, 2007
Software ADT	ADT_Cond_V3	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in HwaYa Shielded Room 1.
  3. The VCCI Site Registration No. is C-2040.




#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under Limit - 20dB was not recorded.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.5 TEST SETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power of EUT and was placed on the test table.
- b. The EUT ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- c. The EUT communicated messages with the external HDD.
- d. The EUT sent image signal to monitor.
- e. The EUT sent audio signal to the speaker and earphone.
- f. Steps c ~ e were repeated.

#### 4.1.7 TEST RESULTS

##### CONDUCTED WORST-CASE DATA

EUT TEST CONDITION			MEASUREMENT DETAIL		
<b>CHANNEL</b>		Channel 1			Line 1
<b>MODULATION TYPE</b>		BPSK			6dB BANDWIDTH 9 kHz
<b>TRANSFER RATE</b>		6Mbps			INPUT POWER (SYSTEM) 120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>		20deg. C, 60%RH, 991hPa			TESTED BY Match Tsui

No	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
			Factor	[dB (uV)]	[dB (uV)]	[dB (uV)]	(dB)			
	[MHz]	(dB)		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.193	0.10	37.87	-	37.97	-	63.91	53.91	-25.94	-
2	0.298	0.10	28.30	-	28.40	-	60.29	50.29	-31.89	-
3	0.634	0.14	27.33	-	27.47	-	56.00	46.00	-28.53	-
4	2.578	0.28	30.64	-	30.92	-	56.00	46.00	-25.08	-
5	4.547	0.47	19.81	-	20.28	-	56.00	46.00	-35.72	-
6	16.969	0.71	13.81	-	14.52	-	60.00	50.00	-45.48	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.


2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

3. The emission levels of other frequencies were very low against the limit.

4. Margin value = Emission level - Limit value

5. Correction factor = Insertion loss + Cable loss

6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION		MEASUREMENT DETAIL			
<b>CHANNEL</b>		Channel 1		<b>PHASE</b>	Line 2
<b>MODULATION TYPE</b>		BPSK		<b>6dB BANDWIDTH</b>	9 kHz
<b>TRANSFER RATE</b>		6Mbps		<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>		20deg. C, 60%RH, 991hPa		<b>TESTED BY</b>	Match Tsui

No	Freq. [MHz]	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.197	0.10	39.91	-	40.01	-	63.75	53.75	-23.74	-
2	0.295	0.10	27.88	-	27.98	-	60.40	50.40	-32.42	-
3	0.916	0.10	21.04	-	21.14	-	56.00	46.00	-34.86	-
4	2.504	0.24	33.43	-	33.67	-	56.00	46.00	-22.33	-
5	4.383	0.38	19.00	-	19.38	-	56.00	46.00	-36.62	-
6	17.191	0.57	16.34	-	16.91	-	60.00	50.00	-43.09	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION		MEASUREMENT DETAIL			
<b>CHANNEL</b>		Channel 6		<b>PHASE</b>	Line 1
<b>MODULATION TYPE</b>		BPSK		<b>6dB BANDWIDTH</b>	9 kHz
<b>TRANSFER RATE</b>		6Mbps		<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>		20deg. C, 60%RH, 991hPa		<b>TESTED BY</b>	Match Tsui

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.189	0.10	33.81	-	33.91	-	64.08	54.08	-30.17	-
2	0.296	0.10	27.91	-	28.01	-	60.36	50.36	-32.35	-
3	0.904	0.18	27.77	-	27.95	-	56.00	46.00	-28.05	-
4	2.563	0.28	30.02	-	30.30	-	56.00	46.00	-25.70	-
5	4.508	0.47	19.76	-	20.23	-	56.00	46.00	-35.77	-
6	28.023	1.21	12.34	-	13.55	-	60.00	50.00	-46.45	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION		MEASUREMENT DETAIL			
CHANNEL	Channel 6	PHASE		Line 2	
MODULATION TYPE	BPSK	6dB BANDWIDTH		9 kHz	
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)		120Vac, 60 Hz	
ENVIRONMENTAL CONDITIONS	20deg. C, 60%RH, 991hPa	TESTED BY		Match Tsui	

No	Freq. [MHz]	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.197	0.10	39.95	-	40.05	-	63.74	53.74	-23.69	-
2	0.295	0.10	27.74	-	27.84	-	60.40	50.40	-32.56	-
3	0.845	0.10	21.67	-	21.77	-	56.00	46.00	-34.23	-
4	2.152	0.21	27.88	-	28.09	-	56.00	46.00	-27.91	-
<b>5</b>	<b>2.680</b>	<b>0.26</b>	<b>34.44</b>	-	<b>34.70</b>	-	<b>56.00</b>	<b>46.00</b>	<b>-21.30</b>	-
6	15.551	0.54	15.65	-	16.19	-	60.00	50.00	-43.81	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION		MEASUREMENT DETAIL			
<b>CHANNEL</b>		Channel 11		<b>PHASE</b>	Line 1
<b>MODULATION TYPE</b>		BPSK		<b>6dB BANDWIDTH</b>	9 kHz
<b>TRANSFER RATE</b>		6Mbps		<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>		20deg. C, 60%RH, 991hPa		<b>TESTED BY</b>	Match Tsui

No	Freq. [MHz]	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.196	0.10	39.49	-	39.59	-	63.80	53.80	-24.21	-
2	0.298	0.10	28.54	-	28.64	-	60.29	50.29	-31.65	-
3	0.947	0.19	28.31	-	28.50	-	56.00	46.00	-27.50	-
4	2.605	0.28	30.39	-	30.67	-	56.00	46.00	-25.33	-
5	4.344	0.47	19.67	-	20.14	-	56.00	46.00	-35.86	-
6	25.645	1.07	13.06	-	14.13	-	60.00	50.00	-45.87	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




EUT TEST CONDITION		MEASUREMENT DETAIL			
<b>CHANNEL</b>		Channel 11		<b>PHASE</b>	Line 2
<b>MODULATION TYPE</b>		BPSK		<b>6dB BANDWIDTH</b>	9 kHz
<b>TRANSFER RATE</b>		6Mbps		<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>ENVIRONMENTAL CONDITIONS</b>		20deg. C, 60%RH, 991hPa		<b>TESTED BY</b>	Match Tsui

No	Freq. [MHz]	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.
1	0.199	0.10	39.67	-	39.77	-	63.65	53.65	-23.88	-
2	0.295	0.10	27.34	-	27.44	-	60.40	50.40	-32.96	-
3	0.927	0.10	20.92	-	21.02	-	56.00	46.00	-34.98	-
<b>4</b>	<b>2.637</b>	<b>0.25</b>	<b>34.45</b>	-	<b>34.70</b>	-	<b>56.00</b>	<b>46.00</b>	<b>-21.30</b>	-
5	4.273	0.37	19.02	-	19.39	-	56.00	46.00	-36.61	-
6	17.109	0.57	16.51	-	17.08	-	60.00	50.00	-42.92	-

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB<sub>uV</sub>/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



#### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESIB7	100188	Dec. 20, 2006
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100039	Nov. 27, 2006
BILOG Antenna SCHWARZBECK	VULB9168	9168-157	Jan. 15, 2007
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-407	Jan. 22, 2007
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170147	Jan. 26, 2007
Preamplifier Agilent	8449B	3008A01961	Oct. 23, 2006
Preamplifier Agilent	8447D	2944A10629	Oct. 27, 2006
RF signal cable HUBER+SUHNER	SUCOFLEX 104	214380/4	Jan. 16, 2007
RF signal cable HUBER+SUHNER	SUCOFLEX 104	219266/4	Jan. 16, 2007
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower ADT.	AT100	AT93021702	NA
Turn Table ADT.	TT100.	TT93021702	NA
Controller ADT.	SC100.	SC93021702	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in HwaYa Chamber 1.
  3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  4. The IC Site Registration No. is IC4924-2.



#### 4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 1kHz for Average detection (AV) at frequency above 1GHz.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6



#### 4.2.7 TEST RESULTS

##### RADIATED WORST-CASE DATA: BELOW 1GHz

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 11	FREQUENCY RANGE	Below 1000MHz
MODULATION TYPE	BPSK	DETECTOR FUNCTION	Quasi-Peak
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
ENVIRONMENTAL CONDITIONS	22deg. C, 69%RH, 991hPa	TESTED BY	Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	80.54	31.14 QP	40.00	-8.86	1.00 H	82	20.67	10.46
2	98.04	31.81 QP	43.50	-11.69	2.00 H	1	22.79	9.02
3	131.08	38.23 QP	43.50	-5.27	2.00 H	1	25.96	12.27
4	162.18	32.64 QP	43.50	-10.86	2.50 H	358	19.37	13.27
5	296.31	33.24 QP	46.00	-12.76	2.00 H	1	17.80	15.44
6	333.25	33.88 QP	46.00	-12.12	1.50 H	289	17.82	16.06
7	389.62	37.20 QP	46.00	-8.80	1.00 H	58	19.60	17.59
8	665.65	33.74 QP	46.00	-12.26	2.00 H	358	10.37	23.38

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	61.10	33.85 QP	40.00	-6.15	1.00 V	187	20.50	13.35
2	78.60	37.69 QP	40.00	-2.31	1.00 V	244	26.97	10.72
3	98.04	36.70 QP	43.50	-6.80	1.00 V	205	27.67	9.02
4	154.41	31.86 QP	43.50	-11.64	1.00 V	82	18.44	13.42
5	162.18	32.04 QP	43.50	-11.46	1.50 V	178	18.77	13.27
6	387.68	35.54 QP	46.00	-10.46	1.00 V	49	18.01	17.53
7	465.43	32.03 QP	46.00	-13.97	1.00 V	211	12.74	19.30
8	622.89	32.15 QP	46.00	-13.85	1.00 V	187	9.41	22.73
9	665.65	33.77 QP	46.00	-12.23	1.00 V	214	10.40	23.38
10	900.86	33.58 QP	46.00	-12.42	1.00 V	34	6.46	27.12

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.



### 802.11b DSSS MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 1		FREQUENCY RANGE
MODULATION TYPE		DBPSK		Peak(PK) Average (AV)
TRANSFER RATE		1Mbps		ENVIRONMENTAL CONDITIONS
INPUT POWER (SYSTEM)		120Vac, 60 Hz		TESTED BY
				Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	54.18 PK	74.00	-19.82	1.47 H	7	22.79	31.39
1	2390.00	43.69 AV	54.00	-10.31	1.47 H	7	12.30	31.39
2	*2412.00	101.22 PK			1.43 H	8	69.76	31.46
2	*2412.00	97.89 AV			1.43 H	8	66.43	31.46

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.00	59.44 PK	74.00	-14.56	1.26 V	175	28.07	31.37
1	2386.00	51.50 AV	54.00	-2.50	1.26 V	175	20.13	31.37
2	*2412.00	105.89 PK			1.28 V	150	74.43	31.46
2	*2412.00	103.65 AV			1.28 V	150	72.19	31.46
3	3216.00	51.16 PK	85.89	-34.73	1.34 V	53	18.05	33.11
3	3216.00	38.94 AV	83.65	-44.71	1.34 V	53	5.83	33.11
4	4824.00	45.85 PK	74.00	-28.15	1.14 V	7	8.72	37.13
4	4824.00	34.20 AV	54.00	-19.80	1.14 V	7	-2.93	37.13

**RMARKS:** 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)

2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)

3. The other emission levels were very low against the limit.

4. Margin value = Emission level – Limit value.

5. “ \* ” : Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		Channel 6		FREQUENCY RANGE
MODULATION TYPE		DBPSK		DETECTOR FUNCTION
TRANSFER RATE		1Mbps		ENVIRONMENTAL CONDITIONS
INPUT POWER (SYSTEM)		120Vac, 60 Hz		TESTED BY
				Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	102.31 PK			1.62 H	25	70.77	31.54
1	*2437.00	98.74 AV			1.62 H	25	67.20	31.54
2	4874.00	43.50 PK	74.00	-30.50	1.28 H	220	6.21	37.29
2	4874.00	33.12 AV	54.00	-20.88	1.28 H	220	-4.17	37.29

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	107.41 PK			1.90 V	20	75.87	31.54
1	*2437.00	104.05 AV			1.90 V	20	72.51	31.54
2	3248.00	51.23 PK	87.41	-36.18	1.38 V	325	18.04	33.19
2	3248.00	38.97 AV	84.05	-45.08	1.38 V	325	5.78	33.19
3	4874.00	45.62 PK	74.00	-28.38	1.21 V	310	8.33	37.29
3	4874.00	34.24 AV	54.00	-19.76	1.21 V	310	-3.05	37.29

- RMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “\*”: Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL		
<b>CHANNEL</b>		<b>FREQUENCY RANGE</b>		1 ~ 25GHz
<b>MODULATION TYPE</b>		<b>DETECTOR FUNCTION</b>		Peak(PK) Average (AV)
<b>TRANSFER RATE</b>		<b>ENVIRONMENTAL CONDITIONS</b>		22deg. C, 69%RH, 991hPa
<b>INPUT POWER (SYSTEM)</b>		<b>TESTED BY</b>		Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	102.45 PK			1.85 H	106	70.83	31.62
1	*2462.00	98.88 AV			1.85 H	106	67.26	31.62
2	2488.00	57.75 PK	74.00	-16.25	1.82 H	111	26.04	31.71
2	2488.00	47.07 AV	54.00	-6.93	1.82 H	111	15.36	31.71

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	107.67 PK			1.24 V	206	76.05	31.62
1	*2462.00	104.22 AV			1.24 V	206	72.60	31.62
2	2488.00	59.39 PK	74.00	-14.61	1.02 V	149	27.68	31.71
2	2488.00	52.01 AV	54.00	-1.99	1.02 V	149	20.30	31.71
3	3282.00	51.20 PK	87.67	-36.47	1.40 V	248	17.93	33.27
3	3282.00	38.46 AV	84.22	-45.76	1.40 V	248	5.19	33.27
4	4924.00	46.13 PK	74.00	-27.87	1.24 V	148	8.69	37.44
4	4924.00	34.17 AV	54.00	-19.83	1.24 V	148	-3.27	37.44

- RMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “\*”: Fundamental frequency.



### 802.11g OFDM MODULATION

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL		FREQUENCY RANGE		1 ~ 25GHz
MODULATION TYPE		DETECTOR FUNCTION		Peak(PK) Average (AV)
TRANSFER RATE		ENVIRONMENTAL CONDITIONS		22deg. C, 69%RH, 991hPa
INPUT POWER (SYSTEM)		TESTED BY		Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	58.83 PK	74.00	-15.17	1.10 H	198	27.44	31.39
1	2390.00	45.76 AV	54.00	-8.24	1.10 H	198	14.37	31.39
2	*2412.00	103.56 PK			1.39 H	193	72.10	31.46
2	*2412.00	94.66 AV			1.39 H	193	63.20	31.46
3	3216.00	46.55 PK	83.56	-37.01	1.46 H	78	13.44	33.11
3	3216.00	39.20 AV	74.66	-35.46	1.46 H	78	6.09	33.11

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	69.74 PK	74.00	-4.26	1.31 V	175	38.35	31.39
1	2390.00	52.23 AV	54.00	-1.77	1.31 V	175	20.84	31.39
2	*2412.00	109.74 PK			1.01 V	187	78.28	31.46
2	*2412.00	100.50 AV			1.01 V	187	69.04	31.46
3	3216.00	50.72 PK	87.74	-37.02	1.41 V	319	17.61	33.11
3	3216.00	43.89 AV	80.50	-36.61	1.41 V	319	10.78	33.11
4	4824.00	45.72 PK	74.00	-28.28	1.38 V	31	8.59	37.13
4	4824.00	32.80 AV	54.00	-21.20	1.38 V	31	-4.33	37.13

- RMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ” : Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL		
<b>CHANNEL</b>		Channel 6		FREQUENCY RANGE
<b>MODULATION TYPE</b>		BPSK		DETECTOR FUNCTION
<b>TRANSFER RATE</b>		6Mbps		ENVIRONMENTAL CONDITIONS
<b>INPUT POWER (SYSTEM)</b>		120Vac, 60 Hz		TESTED BY
				Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	103.44 PK			1.18 H	106	71.90	31.54
1	*2437.00	94.52 AV			1.18 H	106	62.98	31.54
2	4874.00	44.28 PK	74.00	-29.72	1.25 H	220	6.99	37.29
2	4874.00	31.14 AV	54.00	-22.86	1.25 H	220	-6.15	37.29

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	109.48 PK			1.84 V	337	77.94	31.54
1	*2437.00	100.22 AV			1.84 V	337	68.68	31.54
2	3248.00	50.80 PK	89.48	-38.68	1.00 V	351	17.61	33.19
2	3248.00	43.65 AV	80.22	-36.57	1.00 V	351	10.46	33.19
3	4874.00	45.67 PK	74.00	-28.33	1.36 V	218	8.38	37.29
3	4874.00	32.63 AV	54.00	-21.37	1.36 V	218	-4.66	37.29

- RMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “\*”: Fundamental frequency.



EUT TEST CONDITION		MEASUREMENT DETAIL		
<b>CHANNEL</b>		Channel 11		<b>FREQUENCY RANGE</b>
<b>MODULATION TYPE</b>		BPSK		<b>DETECTOR FUNCTION</b>
<b>TRANSFER RATE</b>		6Mbps		<b>ENVIRONMENTAL CONDITIONS</b>
<b>INPUT POWER (SYSTEM)</b>		120Vac, 60 Hz		<b>TESTED BY</b>
				Lori Chiu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	103.28 PK			1.86 H	104	71.66	31.62
1	*2462.00	94.33 AV			1.86 H	104	62.71	31.62
2	2483.50	61.96 PK	74.00	-12.04	1.81 H	108	30.26	31.70
2	2483.50	48.05 AV	54.00	-5.95	1.81 H	108	16.35	31.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	109.09 PK			1.20 V	200	77.47	31.62
1	*2462.00	99.68 AV			1.20 V	200	68.06	31.62
2	2483.50	69.35 PK	74.00	-4.65	1.22 V	201	37.65	31.70
2	<b>2483.50</b>	<b>52.85 AV</b>	<b>54.00</b>	<b>-1.15</b>	<b>1.22 V</b>	<b>201</b>	<b>21.15</b>	<b>31.70</b>
3	3282.00	50.61 PK	89.09	-38.48	1.08 V	56	17.34	33.27
3	3282.00	43.77 AV	79.68	-35.91	1.08 V	56	10.50	33.27
4	4924.00	45.68 PK	74.00	-28.32	1.26 V	308	8.24	37.44
4	4924.00	32.72 AV	54.00	-21.28	1.26 V	308	-4.72	37.44

- RMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “\*”: Fundamental frequency.



## 4.3 6dB BANDWIDTH MEASUREMENT

### 4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

### 4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.




#### 4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.3.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

#### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.





#### 4.3.7 TEST RESULTS


##### 802.11b DSSS MODULATION

MODULATION TYPE	DBPSK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	22deg.C, 69%RH, 991hPa
TESTED BY	Match Tsui		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	12.04	0.5	PASS
6	2437	12.00	0.5	PASS
11	2462	12.04	0.5	PASS

**CH1**

**CH6**


CH11








### 802.11g OFDM MODULATION

MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	22deg.C, 69%RH, 991hPa
TESTED BY	Match Tsui		

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.44	0.5	PASS
6	2437	16.44	0.5	PASS
11	2462	16.40	0.5	PASS

**CH1**

**CH6**


CH11





## 4.4 MAXIMUM PEAK OUTPUT POWER

### 4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm. .

### 4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006
AGILENT SIGNAL GENERATOR	E8257C	MY43320668	Dec. 07, 2006
DIGITAL RT OSCILLOSCOPE	TDS1012	C037299	Nov. 28, 2006
NARDA DETECTOR	4503A	FSCM99899	NA

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to peak the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same peak reading on oscilloscope. Record the power level.

#### 4.4.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.4.5 TEST SETUP



#### 4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6



#### 4.4.7 TEST RESULTS

##### 802.11b DSSS MODULATION

MODULATION TYPE	DBPSK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	22deg.C, 69%RH, 991hPa
TESTED BY	Match Tsui		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	31.696	15.01	30	PASS
6	2437	40.365	16.06	30	PASS
11	2462	40.458	16.07	30	PASS

##### 802.11g OFDM MODULATION

MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	22deg.C, 69%RH, 991hPa
TESTED BY	Match Tsui		

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	50.466	17.03	30	PASS
6	2437	50.582	17.04	30	PASS
11	2462	51.050	17.08	30	PASS



## 4.5 POWER SPECTRAL DENSITY MEASUREMENT

### 4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.




#### 4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time=span/3kHz. The power spectral density was measured and recorded.  
The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

#### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.5.5 TEST SETUP



#### 4.5.6 EUT OPERATING CONDITIONS

Same as 4.3.6




#### 4.5.7 TEST RESULTS

##### 802.11b DSSS MODULATION


<b>MODULATION TYPE</b>	DBPSK	<b>TRANSFER RATE</b>	1Mbps
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>ENVIRONMENTAL CONDITIONS</b>	22deg.C, 69%RH, 991hPa
<b>TESTED BY</b>	Match Tsui		

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz )</b>	<b>RF POWER LEVEL IN 3 kHz BW (dBm)</b>	<b>MAXIMUM LIMIT (dBm)</b>	<b>PASS/FAIL</b>
1	2412	-10.41	8	PASS
6	2437	-9.39	8	PASS
11	2462	-9.18	8	PASS


## CH1



## CH6



CH11








### 802.11g OFDM MODULATION

MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	22deg.C, 69%RH, 991hPa
TESTED BY	Match Tsui		

CHANNEL	CHANNEL FREQUENCY (MHz )	RF POWER LEVEL IN 3 kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-12.92	8	PASS
6	2437	-12.71	8	PASS
11	2462	-12.82	8	PASS

**CH1**

**CH6**


CH11





## 4.6 BAND EDGES MEASUREMENT

### 4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

**NOTE:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100kHz with suitable frequency span including 100MHz bandwidth from band edge. The band edges was measured and recorded. The spectrum plots (Peak RBW=VBW=100kHz; Average RBW=1MHz, VBW=1kHz) are attached on the following pages.

### 4.6.4 DEVIATION FROM TEST STANDARD

No deviation

### 4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6



#### 4.6.6 TEST RESULTS

The spectrum plots are attached on the following 12 images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

#### 802.11b DSSS MODULATION



**NOTE 1:** The band edge emission plot of DSSS technique on the next page shows 52.20dBc between carrier maximum power and local maximum emission in restrict band (2.38624GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 105.89dBuV/m (Peak), so the maximum field strength in restrict band is  $105.89 - 52.20 = 53.69$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot of DSSS technique on the next page shows 52.87dBc between carrier maximum power and local maximum emission in restrict band (2.38620GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 103.65dBuV/m (Average), so the maximum field strength in restrict band is  $103.65 - 52.87 = 50.78$ dBuV/m which is under 54dBuV/m limit.



**NOTE 2:** The band edge emission plot of DSSS technique on the next second page shows 51.63dBc between carrier maximum power and local maximum emission in restrict band (2.49370GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 107.67dBuV/m (Peak), so the maximum field strength in restrict band is  $107.67 - 51.63 = 56.04$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of DSSS technique on the next third page shows 54.02dBc between carrier maximum power and local maximum emission in restrict band (2.48790GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 104.22dBuV/m (Average), so the maximum field strength in restrict band is  $104.22 - 54.02 = 50.20$ dBuV/m which is under 54dBuV/m limit.

## 802.11b DSSS MODULATION









## 802.11g OFDM MODULATION



**NOTE 1:** The band edge emission plot of OFDM technique on the next page shows 46.73dBc between carrier maximum power and local maximum emission in restrict band (2.38740GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 109.74dBuV/m (Peak), so the maximum field strength in restrict band is  $109.74 - 46.73 = 63.01$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot of OFDM technique on the next page shows 48.26dBc between carrier maximum power and local maximum emission in restrict band (2.39000GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 100.50dBuV/m (Average), so the maximum field strength in restrict band is  $100.50 - 48.26 = 52.24$ dBuV/m which is under 54dBuV/m limit.



**NOTE 2:** The band edge emission plot of OFDM technique on the next second page shows 47.00dBc between carrier maximum power and local maximum emission in restrict band (2.48350GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 109.09dBuV/m (Peak), so the maximum field strength in restrict band is  $109.09 - 47.00 = 62.09$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot of OFDM technique on the next third page shows 48.88dBc between carrier maximum power and local maximum emission in restrict band (2.48350GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 99.68dBuV/m (Average), so the maximum field strength in restrict band is  $99.68 - 48.88 = 50.80$ dBuV/m which is under 54dBuV/m limit.

## 802.11g OFDM MODULATION









## **4.7 ANTENNA REQUIREMENT**

### **4.7.1 STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **4.7.2 ANTENNA CONNECTED CONSTRUCTION**


The antenna used in this product is Dipole antenna without connector. The maximum Gain of the antenna is 2dBi.

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

### CONDUCTED EMISSION TEST



## RADIATED EMISSION TEST





## 6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025

<b>USA</b>	FCC, UL, A2LA
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>Norway</b>	NEMKO
<b>Canada</b>	INDUSTRY CANADA , CSA
<b>R.O.C.</b>	CNLA, BSMI, DGT
<b>Netherlands</b>	Telefication
<b>Singapore</b>	PSB , GOST-ASIA(MOU)
<b>Russia</b>	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml). If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180  
Fax: 886-2-26052943

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety/Telecom Lab:**

Tel: 886-3-3183232  
Fax: 886-3-3185050

**Linko RF Lab.**

Tel: 886-3-3270910  
Fax: 886-3-3270892

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.



## APPENDIX-A

### MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.