

FCC TEST REPORT

according to

FCC Rules and Regulations

Part 15 Subpart C

Applicant	Netgear Inc.
Address	4500 Great America Parkway Santa Clara California 95054 USA
Equipment	Mobile Broadband Router
Model No.	MBR814X
FCC ID	PY306200047
Trade Name	NETGEAR

Laboratory Accreditation



1332

- The test result refers exclusively to the test presented test model / sample.,
- Without written approval of *Exclusive Certification Corp.* the test report shall not be reproduced except in full.
- The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

Contents

CERTIFICATE OF COMPLIANCE	4
1. Report of Measurements and Examinations	5
1.1 List of Measurements and Examinations	5
2. Test Configuration of Equipment under Test	6
2.1 Feature of Equipment under Test.....	6
2.2 RF Specifications	6
2.3 Test Mode and Test Software.....	7
2.4 Description of Test System.....	7
2.5 Connection Diagram of Test System.....	8
2.6 General Information of Test.....	9
2.7 History of this test report	9
3. Antenna Requirements	10
3.1 Standard Applicable	10
3.2 Antenna Construction and Directional Gain.....	10
4. Test of Conducted Emission	11
4.1 Test Limit	11
4.2 Test Procedures	11
4.3 Typical Test Setup	12
4.4 Measurement equipment	12
4.5 Test Result and Data.....	13
4.6 Test Photographs	18
5. Test of Radiated Emission	19
5.1 Test Limit	19
5.2 Test Procedures	20
5.3 Typical Test Setup	21
5.4 Measurement equipment	21
5.5 Test Result and Data.....	22
5.6 Test Photographs	54
6. 6dB Bandwidth Measurement Data	55
6.1 Test Limit	55
6.2 Test Procedures	55
6.3 Test Setup Layout	55
6.4 Measurement equipment	55
6.5 Test Result and Data.....	55
7. Maximum Peak Output Power	59
7.1 Test Limit	59
7.2 Test Procedures	59
7.3 Test Setup Layout	59
7.4 Measurement equipment	59
7.5 Test Result and Data.....	59
8. Band Edges Measurement	63
8.1 Test Limit	63
8.2 Test Procedure :	63
8.3 Test Setup Layout	63
8.4 Measurement equipment	63
8.5 Test Result and Data.....	63

8.6 Restrict band emission Measurement Data68

9. Power Spectral Density70

9.1 Test Limit70

9.2 Test Procedures70

9.3 Test Setup Layout :70

9.4 List of Measuring Equipment Used70

9.5 Test Result and Data70

10. Restricted Bands of Operation74

10.1 Labeling Requirement74

Appendix A. Photographs of EUT.....A1 ~ A10

CERTIFICATE OF COMPLIANCE

according to

FCC Rules and Regulations

Part 15 Subpart C


Applicant	Netgear Inc.
Address	4500 Great America Parkway Santa Clara California 95054 USA
Equipment	Mobile Broadband Router
Model No.	MBR814X
FCC ID	PY306200047

I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4** The equipment was **passed** the test performed according to **FCC Rules and Regulations Part 15 Subpart C (2003)**.

The test was carried out on May. 15, 2006 at **Exclusive Certification Corp.**

Signature


Anson Chou / Manager

1. Report of Measurements and Examinations

1.1 List of Measurements and Examinations

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	Pass
15.207	. Conducted Emission	Pass
15.209	. Radiated Emission	Pass
15.247(a)(2)	. 6dB Bandwidth	Pass
15.247(b)	. Maximum Peak Output Power	Pass
15.247(c)	. 100kHz Bandwidth of Frequency Band Edges	Pass
15.247(d)	. Power Spectral Density	Pass
1.1307 1.1310 2.1091 2.1093	. RF Exposure Compliance	Pass

Test engineer: _____

Jerry

2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Network Protocol and Standards Compatibility

Data and Routing Protocols: TCP/IP, RIP-1, RIP-2, DHCP, RFC 1483 Bridged or Routed Ethernet

Power Adapter

North America: 120V, 60 Hz, input
 United Kingdom, Australia: 240V, 50 Hz, input
 Europe: 230V, 50 Hz, input
 Japan: 100V, 50/60 Hz, input
 All regions (output): 15 V AC @ 1.0A output, 24W maximum 12V DC @ 1.2A

Physical Specifications

Dimensions: 10" x 6.7" x 1.3" 255 mm x 169 mm x 34 mm
 Weight: 1.4 lbs.
 0.62 kg

Environmental Specifications

Operating temperature: 0° to 40° C (32° to 104° F)
 Operating humidity: 90% maximum relative humidity, noncondensing

2.2 RF Specifications

TX power out B mode @ 11Mbps	16dBm +/-1.5 dB
TX power out G mode @ 54Mbps	14dBm +/-1dB
RX sensitivity (8% PER) B mode on channels 1, 6, and 11	-91dBm @ 1Mbps
	-89dBm @ 2Mbps
	-88dBm @ 5.5Mbps
	-86dBm @ 11Mbps
RX sensitivity (10% PER) G mode on channels 1, 6, and 11	-88dBm @ 6Mbps
	-87dBm @ 9Mbps
	-84dBm @ 12Mbps
	-82dBm @ 18Mbps
	-80dBm @ 24Mbps
	-75dBm @ 36Mbps
	-72dBm @ 48Mbps
Transmit Sidelobe Level	-70dBm @ 54Mbps
	-30 dBr beyond ±11 MHz and -50dBr beyond 22 MHz for 802.11b -20 dBr at 11 MHz, -28 dBr at 20MHz, and -40 dBr beyond 30 MHz for 802.11g
Frequency Accuracy	+/- 25ppm
Pre EMI Scan	3 dB below FCC limit
Error Vector Magnitude (EVM)	1, 2, 5.5, 11Mbps < 8%
	6, 9, 12, 18, 24, 36Mbps < 12%
	48Mbps < 8%
	54Mbps < 6%

2.3 Test Mode and Test Software

The following test mode and test software was performed for conduction and radiation test:

- 802.11b (CH01: 2412MHz) • 802.11b (CH06: 2437MHz) • 802.11b (CH11: 2462MHz)
- 802.11g (CH01: 2412MHz) • 802.11g (CH06: 2437MHz) • 802.11g (CH11: 2462MHz)
- An executive programs, "Telnet.exe" Application under WIN XP.
- modulation type: DSSS / OFDM .

The test mode include two kind of adapter:

Adapter model 1 : DSA-20P-10 US 120144

Adapter model 2 : DV-151A-1


2.4 Description of Test System

Device	Manufacturer	Model No.	Description
PC	IBM	IGV	Power Cable, Unshielding 1.8 m
Monitor	SlimAGE	510A	Power Cable, Adapter Unshielding 1.8 m Data Cable, VGA shielding 1.35 m
Keyboard	IBM	KB-0225	Data Cable, PS2 shielding 1.85 m
Mouse	IBM	MO28VO	Data Cable, USB shielding 1.85 m
Modem	ACEXX	DM-1414	Power Cable, Adapter Unshielding 1.8 m Data Cable, RS232 Unshielding 1.35 m
Printer	HP	Desk Jet400	Power Cable, Adapter Unshielding 1.8 m Data Cable, PRINT Shielding 1.6 m

Use Cable:

Cable	Description
RJ-45*3	Unshielding, 0.5m
RJ-45*1	Unshielding, 1.5m

2.5 Connection Diagram of Test System



1. The RJ45 cable is connected from PC to the EUT.
2. The I/O cable is connected from PC to the Modem.
3. The I/O cable is connected from PC to the Printer.
4. The I/O cable is connected from PC to the Monitor.
5. The I/O cable is connected from PC to the Mouse.
6. The I/O cable is connected from PC to the Keyboard.
7. There cables are floating.

2.6 General Information of Test

Test Site:	Exclusive Certification Corp. 4F-2, No. 28, Lane 78, Xing-Ai Rd. Nei-hu, Taipei City 114 Taiwan R.O.C.
Test Site Location (OATS1-SD):	No.68-1, Shihbachongsi, shihding Township, Taipei City 223, Taiwan, R.O.C.
Registration Number:	632249
Test Voltage:	AC 120V/ 60Hz
Test in Compliance with:	ANSI C63.4-2003 FCC Part 15 Subpart C
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 24620MHz
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.

2.7 History of this test report

ORIGINAL.

3. Antenna Requirements

3.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

3.2 Antenna Construction and Directional Gain

Antenna type: Integral, Dipole Antenna

Antenna Gain: 2dBi.

.

4. Test of Conducted Emission

4.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2003 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.


Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

*Decreases with the logarithm of the frequency.

4.2 Test Procedures

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connecting to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

4.3 Typical Test Setup



4.4 Measurement equipment


Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Valid Date
Receiver	SCR3501	Schaffner	437	2006/11/03
LISN	NNB-2/16Z	MESS TEC	02/10191	2007/03/30
LISN	NNB-2/16Z	ROLF HEINE	03/10058	2007/04/26

4.5 Test Result and Data

Adapter model 1 : DSA-20P-10 US 120144

EUT : MBR814X
 Power : AC 120V
 Test Mode : 802.11g CH1
 Memo : DSA-20P-10 US 120144

Pol/Phase : NEUTRAL
 Temperature : 25 °C
 Humidity : 56 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.16	55.80	0.30	56.10	65.56	-9.46	QP
0.16	26.82	0.30	27.12	55.56	-28.44	AVERAGE
0.17	54.47	0.28	54.75	65.07	-10.33	QP
0.17	24.83	0.28	25.11	55.07	-29.97	AVERAGE
0.18	53.06	0.25	53.31	64.66	-11.35	QP
0.18	26.35	0.25	26.60	54.66	-28.06	AVERAGE
0.20	51.71	0.20	51.91	63.67	-11.76	QP
0.20	32.11	0.20	32.31	53.67	-21.36	AVERAGE
0.22	50.86	0.24	51.10	62.88	-11.78	QP
0.22	26.89	0.24	27.13	52.88	-25.75	AVERAGE
0.24	48.62	0.27	48.89	62.26	-13.37	QP
0.24	25.43	0.27	25.70	52.26	-26.56	AVERAGE
0.26	47.97	0.31	48.28	61.55	-13.27	QP
0.26	18.23	0.31	18.54	51.55	-33.01	AVERAGE
0.29	46.91	0.37	47.28	60.41	-13.13	QP
0.29	36.18	0.37	36.55	50.41	-13.86	AVERAGE
0.32	44.25	0.40	44.65	59.78	-15.13	QP
0.32	18.51	0.40	18.91	49.78	-30.87	AVERAGE
0.36	42.66	0.45	43.11	58.79	-15.68	QP
0.36	18.17	0.45	18.62	48.79	-30.17	AVERAGE
0.40	40.90	0.50	41.40	57.90	-16.50	QP
0.40	25.35	0.50	25.85	47.90	-22.05	AVERAGE
0.44	40.05	0.50	40.55	57.03	-16.48	QP
0.44	29.45	0.50	29.95	47.03	-17.08	AVERAGE
0.49	42.84	0.50	43.34	56.17	-12.83	QP
0.49	34.78	0.50	35.28	46.17	-10.89	AVERAGE

- Remarks:
- Level = Read Level + Factor
 - Factor = LISN(ISN) Factor + Cable Loss
 - All emission below 1GHz at 802.11b/g mode are all the same,so the 802.11g mode chosen as representative in final test.
 - According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.
 - The data is worse case.

EUT : MBR814X
 Power : AC 120V
 Test Mode : 802.11g CH1
 Memo : DSA-20P-10 US 120144

Pol/Phase : LINE
 Temperature : 25 °C
 Humidity : 56 %



Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.15	55.60	0.38	55.98	65.91	-9.93	QP
0.15	34.09	0.38	34.47	55.91	-21.44	AVERAGE
0.17	53.68	0.35	54.03	64.99	-10.96	QP
0.17	26.54	0.35	26.89	54.99	-28.10	AVERAGE
0.18	52.99	0.33	53.32	64.62	-11.29	QP
0.18	27.48	0.33	27.81	54.62	-26.80	AVERAGE
0.20	51.68	0.31	51.99	63.78	-11.80	QP
0.20	37.41	0.31	37.72	53.78	-16.07	AVERAGE
0.22	31.09	0.34	31.43	52.79	-21.35	AVERAGE
0.22	50.13	0.34	50.47	62.79	-12.31	QP
0.24	48.86	0.37	49.23	62.26	-13.03	QP
0.24	30.70	0.37	31.07	52.26	-21.19	AVERAGE
0.25	48.28	0.39	48.67	61.83	-13.16	QP
0.25	39.51	0.39	39.90	51.83	-11.93	AVERAGE
0.26	25.89	0.42	26.31	51.38	-25.07	AVERAGE
0.26	47.16	0.42	47.58	61.38	-13.80	QP
0.29	41.99	0.47	42.46	50.39	-7.94	AVERAGE
0.29	47.93	0.47	48.40	60.39	-12.00	QP
0.32	16.20	0.51	16.71	49.61	-32.90	AVERAGE
0.32	42.93	0.51	43.44	59.61	-16.17	QP
0.35	35.70	0.54	36.24	48.96	-12.72	AVERAGE
0.35	42.80	0.54	43.34	58.96	-15.62	QP
0.39	29.99	0.59	30.58	48.12	-17.55	AVERAGE


0.39	42.80	0.59	43.39	58.12	-14.74	QP
0.40	25.39	0.60	25.99	47.83	-21.84	AVERAGE
0.40	39.96	0.60	40.56	57.83	-17.27	QP
0.44	37.03	0.59	37.62	47.02	-9.40	AVERAGE
0.44	43.45	0.59	44.04	57.02	-12.98	QP
0.49	46.71	0.58	47.29	56.16	-8.87	QP
0.49	41.80	0.58	42.38	46.16	-3.78	AVERAGE
0.54	43.60	0.57	44.17	56.00	-11.83	QP
0.54	34.80	0.57	35.37	46.00	-10.63	AVERAGE
0.57	44.11	0.56	44.67	56.00	-11.33	QP
0.57	30.35	0.56	30.91	46.00	-15.09	AVERAGE
0.97	39.24	0.50	39.74	56.00	-16.26	QP
0.97	24.86	0.50	25.36	46.00	-20.64	AVERAGE
1.10	34.58	0.53	35.11	56.00	-20.89	QP
1.10	13.82	0.53	14.35	46.00	-31.65	AVERAGE
1.28	40.34	0.57	40.91	56.00	-15.09	QP
1.28	28.88	0.57	29.45	46.00	-16.55	AVERAGE
1.37	30.93	0.59	31.52	46.00	-14.48	AVERAGE
1.37	43.26	0.59	43.85	56.00	-12.15	QP

- Remarks:
1. Level = Read Level + Factor
 2. Factor = LISN(ISN) Factor + Cable Loss
 3. All emission below 1GHz at 802.11b/g mode are all the same,so the 802.11g mode chosen as representative in final test.
 4. According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.
 5. The data is worse case.

Adapter model 2 : DV-151A-1

EUT : MBR814X
 Power : AC 120V
 Test Mode : 802.11g CH1
 Memo : DV-151A-1

Pol/Phase : NEUTRAL
 Temperature : 25 °C
 Humidity : 56 %




Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.16	21.15	0.00	21.15	55.72	-34.57	AVERAGE
0.16	25.74	0.00	25.74	65.72	-39.98	QP
0.22	24.33	0.00	24.33	52.76	-28.43	AVERAGE
0.22	29.14	0.00	29.14	62.76	-33.62	QP
0.34	29.96	0.00	29.96	59.14	-29.18	QP
0.34	28.26	0.00	28.26	49.14	-20.88	AVERAGE
0.40	31.97	0.00	31.97	47.75	-15.78	AVERAGE
0.40	33.74	0.00	33.74	57.75	-24.01	QP
2.48	27.76	0.00	27.76	46.00	-18.24	AVERAGE
2.48	33.88	0.00	33.88	56.00	-22.12	QP
2.80	9.11	0.00	9.11	46.00	-36.89	AVERAGE
2.80	18.00	0.00	18.00	56.00	-38.00	QP

- Remarks:
1. Level = Read Level + Factor
 2. Factor = LISN(ISN) Factor + Cable Loss
 3. All emission below 1GHz at 802.11b/g mode are all the same,so the 802.11g mode chosen as representative in final test.
 4. According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.
 5. The data is worse case.

EUT : MBR814X
 Power : AC 120V
 Test Mode : 802.11g CH1
 Memo : DV-151A-1

Pol/Phase : LINE
 Temperature : 25 °C
 Humidity : 56 %



Trace: (Discrete)

Freq	Read Level	Factor	Level	Limit	Over Limit	Remark
MHz	dBuV	dB	dBuV	dBuV	dBuV	
0.22	30.26	0.34	30.60	62.76	-32.15	QP
0.22	25.36	0.34	25.70	52.76	-27.05	AVERAGE
0.28	25.39	0.45	25.84	50.81	-24.97	AVERAGE
0.28	26.37	0.45	26.82	60.81	-33.99	QP
0.34	30.55	0.53	31.08	59.14	-28.05	QP
0.34	28.93	0.53	29.46	49.14	-19.67	AVERAGE
0.40	33.99	0.60	34.59	47.76	-13.17	AVERAGE
0.40	35.36	0.60	35.96	57.76	-21.80	QP
0.47	25.80	0.58	26.38	46.57	-20.18	AVERAGE
0.47	28.01	0.58	28.59	56.57	-27.97	QP
0.53	25.02	0.57	25.59	56.00	-30.41	QP
0.53	23.37	0.57	23.94	46.00	-22.06	AVERAGE

- Remarks:
- Level = Read Level + Factor
 - Factor = LISN(ISN) Factor + Cable Loss
 - All emission below 1GHz at 802.11g mode are all the same,so the 802.11g mode chosen as representative in final test.
 - According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.
 - The data is worse case.


Test engineer: Ben

4.6 Test Photographs

Front View



Rear View



5. Test of Radiated Emission

5.1 Test Limit

Radiated emissions from 30 MHz to 25 GHz were measured according to the methods defines in ANSI C63.4-2003. The EUT was placed, 0.8 meter above the ground plane, as shown in section 5.6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance Meters	Radiated (μ V / M)	Radiated (dB μ V/ M)
30-88	3	100	40.0
88-216	3	150	43.5
216-960	3	200	46.0
Above 960	3	500	54.0


For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the above table.

Frequency (MHz)	Distance Meters	Radiated (dB μ V/ M)
30-230	10	30
230-1000	10	37

5.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

5.3 Typical Test Setup




5.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Valid Date
EMI Receiver	8546A	HP	3807A00454	2007/05/11
Spectrum Analyzer	FSP40	R&S	10047	2007/01/16
Horn Antenna	3115	EMCO	31589	2007/02/12
Horn Antenna	3116	EMCO	31970	2007/02/09
Bilog Antenna	CBL6112B	Schaffner	2840	2007/04/19
Amplifier	8449B	Agilent	3008A01954	2007/01/08
Amplifier	8447D	Agilent	2944A10531	2006/08/09

5.5 Test Result and Data

Adapter model 1 : DSA-20P-10 US 120144

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 1
 Modulation Type : 802.11g
 Rate : 6 Mbps
 Memo : DSA-20P-10 US 120144
 Pol/Phase : HORIZONTAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure: 1013 hPa




Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
51.73	51.88	-19.16	32.72	40.00	-7.28	Peak	0	200
62.75	54.80	-21.30	33.50	40.00	-6.50	Peak	0	200
110.30	45.12	-16.47	28.65	43.50	-14.85	Peak	80	200
124.50	47.94	-15.66	32.28	43.50	-11.22	Peak	80	200
133.40	46.61	-15.75	30.86	43.50	-12.64	Peak	326	200
150.20	50.12	-16.41	33.71	43.50	-9.79	Peak	360	200
171.33	49.63	-17.53	32.10	43.50	-11.40	Peak	360	200
180.15	48.73	-18.24	30.49	43.50	-13.01	Peak	182	200
200.25	53.81	-18.01	35.80	43.50	-7.70	Peak	200	200
249.75	56.88	-14.06	42.82	46.00	-3.18	QP	351	200
300.05	49.52	-13.21	36.31	46.00	-9.69	Peak	140	200

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1, 6, 11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 1
 Modulation Type : 802.11g
 Rate : 6 Mbps
 Memo : DSA-20P-10 US 120144
 Pol/Phase : HORIZONTAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure: 1013 hPa



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
316.80	47.33	-12.65	34.68	46.00	-11.32	Peak	0	200
374.90	44.68	-10.76	33.92	46.00	-12.08	Peak	36	200
400.10	45.76	-10.12	35.64	46.00	-10.36	Peak	99	200
498.80	48.79	-6.63	42.16	46.00	-3.84	QP	247	200
566.00	45.74	-4.16	41.58	46.00	-4.42	QP	250	200
631.80	44.43	-3.40	41.03	46.00	-4.97	QP	333	200
766.90	40.74	-1.43	39.31	46.00	-6.69	Peak	333	200
799.80	44.40	-1.53	42.87	46.00	-3.13	QP	0	200
899.90	42.10	0.22	42.32	46.00	-3.68	QP	0	200
960.10	41.99	1.28	43.27	54.00	-10.73	Peak	0	200

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same,so the 802.11g mode chosen as representative in final test.
5. According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel : 1
 Modulation Type : 802.11g
 Rate : 6 Mbps
 Memo : DSA-20P-10 US 120144

Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure : 1013 hPa



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
40.20	50.23	-13.25	36.98	40.00	-3.02	QP	63	100
54.50	55.92	-19.97	35.95	40.00	-4.05	QP	89	100
80.90	56.27	-19.50	36.77	40.00	-3.23	QP	89	100
110.30	53.50	-16.47	37.03	43.50	-6.47	Peak	0	100
124.99	50.70	-15.68	35.02	43.50	-8.48	Peak	0	100
133.34	54.57	-15.75	38.82	43.50	-4.68	QP	145	100
149.70	50.32	-16.38	33.94	43.50	-9.56	Peak	300	100
160.10	51.17	-16.61	34.56	43.50	-8.94	Peak	300	100
179.60	51.83	-18.21	33.62	43.50	-9.88	Peak	360	100
200.00	53.36	-18.01	35.35	43.50	-8.15	Peak	56	100
250.03	56.90	-14.02	42.88	46.00	-3.12	QP	56	100
300.05	48.88	-13.21	35.67	46.00	-10.33	Peak	0	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same,so the 802.11g mode chosen as representative in final test.
5. According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 1
 Modulation Type : 802.11g
 Rate : 6 Mbps
 Memo : DSA-20P-10 US 120144

Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure: 1013 hPa



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
374.90	48.49	-10.76	37.73	46.00	-8.27	Peak	211	100
399.50	47.66	-10.13	37.53	46.00	-8.47	Peak	30	100
449.80	47.35	-8.21	39.14	46.00	-6.86	Peak	30	100
480.00	48.20	-7.26	40.94	46.00	-5.06	QP	0	100
498.90	48.44	-6.63	41.81	46.00	-4.19	QP	0	100
565.30	44.74	-4.18	40.56	46.00	-5.44	QP	74	100
798.50	40.16	-1.53	38.63	46.00	-7.37	Peak	93	100
985.30	43.60	1.32	44.92	54.00	-9.08	Peak	93	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same,so the 802.11g mode chosen as representative in final test.
5. According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel : 1
 Modulation Type : 802.11b
 Rate : 11 Mbps
 Memo : DSA-20P-10 US 120144

Pol/Phase : HORIZONTAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure: 1013 hPa




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4823.88	36.76	5.71	42.46	54.00	-11.54	Average	72	100
4823.88	48.76	5.71	54.47	74.00	-19.53	Peak	72	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT	: MBR814X	Pol/Phase	: VERTICAL
Power	: AC 120V	Temperature	: 25 °C
Test Mode	: Transmit/Receive	Humidity	: 70 %
Operation Channel	: 1	Atmospheric Pressure	: 1013 hPa
Modulation Type	: 802.11b		
Rate	: 11 Mbps		
Memo	: DSA-20P-10 US 120144		



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4824.15	36.85	5.71	42.56	54.00	-11.44	Average	174	100
4824.15	48.71	5.71	54.42	74.00	-19.58	Peak	174	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

```

EUT           : MBR814X
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 6
Modulation Type : 802.11b
Rate         : 11 Mbps
Memo         : DSA-20P-10 US 120144

Pol/Phase    : HORIZONTAL
Temperature   : 25 °C
Humidity     : 70 %
Atmospheric Pressure: 1013 hPa
    
```




Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4874.15	37.06	5.85	42.91	54.00	-11.09	Average	72	100
4874.15	48.60	5.85	54.45	74.00	-19.55	Peak	72	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 6
 Modulation Type : 802.11b
 Rate : 11 Mbps
 Memo : DSA-20P-10 US 120144

Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure: 1013 hPa



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4874.03	36.93	5.85	42.78	54.00	-11.22	Average	174	100
4874.03	48.68	5.85	54.53	74.00	-19.47	Peak	174	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 11
 Modulation Type : 802.11b
 Rate : 11 Mbps
 Memo : DSA-20P-10 US 120144

Pol/Phase : HORIZONTAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure: 1013 hPa



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4923.73	36.86	5.99	42.85	54.00	-11.15	Average	72	100
4923.73	48.58	5.99	54.57	74.00	-19.43	Peak	72	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel : 11
 Modulation Type : 802.11b
 Rate : 11 Mbps
 Memo : DSA-20P-10 US 120144

Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure : 1013 hPa




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4924.00	36.78	5.99	42.77	54.00	-11.23	Average	174	100
4924.00	48.50	5.99	54.49	74.00	-19.51	Peak	174	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel : 1
 Modulation Type : 802.11g
 Rate : 6 Mbps
 Memo : DSA-20P-10 US 120144
 Pol/Phase : HORIZONTAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure : 1013 hPa



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4824.08	36.87	5.71	42.58	54.00	-11.42	Average	72	100
4824.08	48.55	5.71	54.26	74.00	-19.74	Peak	72	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

```

EUT           : MBR814X
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 1
Modulation Type : 802.11g
Rate          : 6 Mbps
Memo          : DSA-20P-10 US 120144

Pol/Phase     : VERTICAL
Temperature   : 25 °C
Humidity      : 70 %
Atmospheric Pressure: 1013 hPa
    
```



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4824.15	36.87	5.71	42.58	54.00	-11.42	Average	174	100
4824.15	48.96	5.71	54.67	74.00	-19.33	Peak	174	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

```

EUT           : MBR814X
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 6
Modulation Type : 802.11g
Rate          : 6 Mbps
Memo          : DSA-20P-10 US 120144

Pol/Phase    : HORIZONTAL
Temperature   : 25 °C
Humidity     : 70 %
Atmospheric Pressure: 1013 hPa
    
```




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4874.13	36.76	5.85	42.60	54.00	-11.40	Average	72	100
4874.13	48.75	5.85	54.60	74.00	-19.40	Peak	72	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 6
 Modulation Type : 802.11g
 Rate : 6 Mbps
 Memo : DSA-20P-10 US 120144
 Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure: 1013 hPa



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4874.05	36.84	5.85	42.69	54.00	-11.31	Average	174	100
4874.05	48.76	5.85	54.61	74.00	-19.39	Peak	174	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

```

EUT           : MBR814X
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 11
Modulation Type : 802.11g
Rate         : 6 Mbps
Memo         : DSA-20P-10 US 120144

Pol/Phase    : HORIZONTAL
Temperature  : 25 °C
Humidity     : 70 %
Atmospheric Pressure: 1013 hPa
    
```



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4923.83	36.90	5.99	42.88	54.00	-11.12	Average	72	100
4923.83	48.63	5.99	54.62	74.00	-19.38	Peak	72	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

```

EUT           : MBR814X
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 11
Modulation Type : 802.11g
Rate         : 6 Mbps
Memo         : DSA-20P-10 US 120144

Pol/Phase    : VERTICAL
Temperature   : 25 °C
Humidity     : 70 %
Atmospheric Pressure: 1013 hPa
    
```



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4924.10	36.94	5.99	42.93	54.00	-11.07	Average	174	100
4924.10	48.65	5.99	54.64	74.00	-19.36	Peak	174	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

Adapter model 2 : DV-151A-1

EUT	: MBR814X	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 25 °C
Test Mode	: Transmit/Receive	Humidity	: 70 %
Operation Channel	: 1	Atmospheric Pressure	: 1013 hPa
Modulation Type	: 802.11g		
Rate	: 6 Mbps		
Memo	: DV-151A-1		




Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
51.73	51.53	-19.16	32.37	40.00	-7.63	Peak	0	200
62.75	54.85	-21.30	33.55	40.00	-6.45	Peak	0	200
110.30	44.96	-16.47	28.49	43.50	-15.01	Peak	80	200
124.50	47.90	-15.66	32.24	43.50	-11.26	Peak	80	200
133.40	46.67	-15.75	30.92	43.50	-12.58	Peak	326	200
150.20	50.05	-16.41	33.64	43.50	-9.86	Peak	360	200
171.33	49.60	-17.53	32.07	43.50	-11.43	Peak	360	200
180.15	48.70	-18.24	30.46	43.50	-13.04	Peak	182	200
200.25	53.79	-18.01	35.78	43.50	-7.72	Peak	200	200
249.75	56.88	-14.06	42.82	46.00	-3.18	QP	351	200
300.05	48.90	-13.21	35.69	46.00	-10.31	Peak	140	200

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1, 6, 11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel : 1
 Modulation Type : 802.11g
 Rate : 6 Mbps
 Memo : DV-151A-1
 Pol/Phase : HORIZONTAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure : 1013 hPa




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
316.80	47.38	-12.65	34.73	46.00	-11.27	Peak	0	200
374.90	44.60	-10.76	33.84	46.00	-12.16	Peak	36	200
400.10	45.53	-10.12	35.41	46.00	-10.59	Peak	99	200
498.80	48.77	-6.63	42.14	46.00	-3.86	QP	247	200
566.00	45.87	-4.16	41.71	46.00	-4.29	QP	250	200
631.80	44.33	-3.40	40.93	46.00	-5.07	QP	333	200
766.90	40.69	-1.43	39.26	46.00	-6.74	Peak	333	200
799.80	44.51	-1.53	42.98	46.00	-3.02	QP	0	200
899.90	42.14	0.22	42.36	46.00	-3.64	QP	0	200
960.10	41.99	1.28	43.27	54.00	-10.73	Peak	0	200

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 1
 Modulation Type : 802.11g
 Rate : 6 Mbps
 Memo : DV-151A-1
 Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure: 1013 hPa




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
40.20	50.02	-13.25	36.77	40.00	-3.23	QP	63	100
54.50	55.88	-19.97	35.91	40.00	-4.09	QP	89	100
80.90	56.45	-19.50	36.95	40.00	-3.05	QP	89	100
110.30	53.54	-16.47	37.07	43.50	-6.43	Peak	0	100
124.99	50.71	-15.68	35.03	43.50	-8.47	Peak	0	100
133.34	54.90	-15.75	39.15	43.50	-4.35	QP	145	100
149.70	50.00	-16.38	33.62	43.50	-9.88	Peak	300	100
160.10	51.25	-16.61	34.64	43.50	-8.86	Peak	300	100
179.60	50.83	-18.21	32.62	43.50	-10.88	Peak	360	100
200.00	53.36	-18.01	35.35	43.50	-8.15	Peak	56	100
250.03	56.98	-14.02	42.96	46.00	-3.04	QP	56	100
300.05	48.88	-13.21	35.67	46.00	-10.33	Peak	0	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same,so the 802.11g mode chosen as representative in final test.
5. According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

EUT	: MBR814X	Pol/Phase	: VERTICAL
Power	: AC 120V	Temperature	: 25 °C
Test Mode	: Transmit/Receive	Humidity	: 70 %
Operation Channel	: 1	Atmospheric Pressure	: 1013 hPa
Modulation Type	: 802.11g		
Rate	: 6 Mbps		
Memo	: DV-151A-1		



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
374.90	48.57	-10.76	37.81	46.00	-8.19	Peak	211	100
399.50	47.61	-10.13	37.48	46.00	-8.52	Peak	30	100
449.80	47.30	-8.21	39.09	46.00	-6.91	Peak	30	100
480.00	48.22	-7.26	40.96	46.00	-5.04	QP	0	100
498.90	48.22	-6.63	41.59	46.00	-4.41	QP	0	100
565.30	44.41	-4.18	40.23	46.00	-5.77	QP	74	100
798.50	40.16	-1.53	38.63	46.00	-7.37	Peak	93	100
985.30	43.68	1.32	45.00	54.00	-9.00	Peak	93	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same,so the 802.11g mode chosen as representative in final test.
5. According to technical experiences,all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz,so that the channel 1 was chosen as representative in final test.
6. The data is worse case.

```

EUT           : MBR814X
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 1
Modulation Type : 802.11b
Rate         : 11 Mbps
Memo         : DV-151A-1

Pol/Phase    : HORIZONTAL
Temperature   : 25 °C
Humidity     : 70 %
Atmospheric Pressure: 1013 hPa
    
```



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4823.88	36.87	5.71	42.58	54.00	-11.42	Average	72	100
4823.88	48.71	5.71	54.41	74.00	-19.59	Peak	72	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

```

EUT           : MBR814X
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 1
Modulation Type : 802.11b
Rate         : 11 Mbps
Memo         : DV-151A-1

Pol/Phase    : VERTICAL
Temperature   : 25 °C
Humidity     : 70 %
Atmospheric Pressure: 1013 hPa
    
```



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4824.15	36.85	5.71	42.56	54.00	-11.44	Average	174	100
4824.15	48.63	5.71	54.33	74.00	-19.67	Peak	174	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

```

EUT           : MBR814X
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 6
Modulation Type : 802.11b
Rate         : 11 Mbps
Memo         : DV-151A-1

Pol/Phase     : HORIZONTAL
Temperature   : 25 °C
Humidity      : 70 %
Atmospheric Pressure: 1013 hPa
    
```




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4874.15	36.88	5.85	42.73	54.00	-11.27	Average	72	100
4874.15	48.61	5.85	54.45	74.00	-19.55	Peak	72	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT	: MBR814X	Pol/Phase	: VERTICAL
Power	: AC 120V	Temperature	: 25 °C
Test Mode	: Transmit/Receive	Humidity	: 70 %
Operation Channel	: 6	Atmospheric Pressure	: 1013 hPa
Modulation Type	: 802.11b		
Rate	: 11 Mbps		
Memo	: DV-151A-1		




Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4874.03	36.89	5.85	42.73	54.00	-11.27	Average	174	100
4874.03	48.66	5.85	54.50	74.00	-19.50	Peak	174	100

- Notes:
1. Result = Meter Reading + Corrected Factor
 2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
 3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
 5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
 6. The other emissions is too low to be measured.

```

EUT           : MBR814X
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 11
Modulation Type : 802.11b
Rate         : 11 Mbps
Memo         : DV-151A-1

Pol/Phase    : HORIZONTAL
Temperature   : 25 °C
Humidity     : 70 %
Atmospheric Pressure: 1013 hPa
    
```



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4923.73	36.89	5.99	42.88	54.00	-11.12	Average	72	100
4923.73	48.65	5.99	54.63	74.00	-19.37	Peak	72	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

```

EUT           : MBR814X
Power         : AC 120V
Test Mode    : Transmit/Receive
Operation Channel: 11
Modulation Type : 802.11b
Rate         : 11 Mbps
Memo         : DV-151A-1

Pol/Phase    : VERTICAL
Temperature   : 25 °C
Humidity     : 70 %
Atmospheric Pressure: 1013 hPa
    
```




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4924.00	36.85	5.99	42.84	54.00	-11.16	Average	174	100
4924.00	48.55	5.99	54.53	74.00	-19.47	Peak	174	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 1
 Modulation Type : 802.11g
 Rate : 6 Mbps
 Memo : DV-151A-1
 Pol/Phase : HORIZONTAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure: 1013 hPa



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4824.08	36.85	5.71	42.56	54.00	-11.44	Average	72	100
4824.08	48.55	5.71	54.25	74.00	-19.75	Peak	72	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 1
 Modulation Type : 802.11g
 Rate : 6 Mbps
 Memo : DV-151A-1

Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure: 1013 hPa




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4824.15	36.85	5.71	42.56	54.00	-11.44	Average	174	100
4824.15	48.70	5.71	54.40	74.00	-19.60	Peak	174	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT	: MBR814X	Pol/Phase	: HORIZONTAL
Power	: AC 120V	Temperature	: 25 °C
Test Mode	: Transmit/Receive	Humidity	: 70 %
Operation Channel	: 6	Atmospheric Pressure	: 1013 hPa
Modulation Type	: 802.11g		
Rate	: 6 Mbps		
Memo	: DV-151A-1		



Trace: (Discrete)


Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4874.13	36.88	5.85	42.73	54.00	-11.27	Average	72	100
4874.13	48.79	5.85	54.63	74.00	-19.37	Peak	72	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT : MBR814X
 Power : AC 120V
 Test Mode : Transmit/Receive
 Operation Channel: 6
 Modulation Type : 802.11g
 Rate : 6 Mbps
 Memo : DV-151A-1

Pol/Phase : VERTICAL
 Temperature : 25 °C
 Humidity : 70 %
 Atmospheric Pressure: 1013 hPa



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4874.05	36.84	5.85	42.68	54.00	-11.32	Average	174	100
4874.05	48.67	5.85	54.51	74.00	-19.49	Peak	174	100


Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

```

EUT           : MBR814X
Power         : AC 120V
Test Mode     : Transmit/Receive
Operation Channel: 11
Modulation Type : 802.11g
Rate         : 6 Mbps
Memo         : DV-151A-1

Pol/Phase     : HORIZONTAL
Temperature   : 25 °C
Humidity      : 70 %
Atmospheric Pressure: 1013 hPa
    
```




Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBUV)	Corrected Factor (dBUV/m)	Result (dBUV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4923.83	36.86	5.99	42.84	54.00	-11.16	Average	72	100
4923.83	48.58	5.99	54.56	74.00	-19.44	Peak	72	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

EUT	: MBR814X	Pol/Phase	: VERTICAL
Power	: AC 120V	Temperature	: 25 °C
Test Mode	: Transmit/Receive	Humidity	: 70 %
Operation Channel	: 11	Atmospheric Pressure	: 1013 hPa
Modulation Type	: 802.11g		
Rate	: 6 Mbps		
Memo	: DV-151A-1		



Trace: (Discrete)

Frequency (MHz)	Meter Reading (dBuV)	Corrected Factor (dBuV/m)	Result (dBuV/m)	Limit (dB)	Margin (dB)	Remark	Table Deg.	Ant High (cm)
4924.10	36.84	5.99	42.83	54.00	-11.17	Average	174	100
4924.10	48.62	5.99	54.60	74.00	-19.40	Peak	174	100

Notes:

1. Result = Meter Reading + Corrected Factor
2. Corrected Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

5.6 Test Photographs

Front View



Rear View



6. 6dB Bandwidth Measurement Data


6.1 Test Limit

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

6.2 Test Procedures

- The transmitter output was connected to the spectrum analyzer.
- Set RBW of spectrum analyzer to 100 KHz and VBW to 100 KHz.
- The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

6.3 Test Setup Layout



6.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2007/01/16

6.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Apr. 22, 2006 Temperature: 26 Humidity: 65% Atmospheric pressure: 1022 hPa


Channel	Frequency (MHz)	6dB Bandwidth (MHz)
01	2412	13.1
06	2437	12.2
11	2462	12.2

(2) Modulation Standard: IEEE 802.11g (6Mbps)

Test Date: Apr. 22, 2006 Temperature: 26 Humidity: 65% Atmospheric pressure: 1022 hPa


Channel	Frequency (MHz)	6dB Bandwidth (MHz)
01	2412	13.7
06	2437	16.3
11	2462	15.8

Modulation Standard: 802.11b (11Mbps)
 Channel: 01




Date: 22.APR.2006 11:08:12

Channel:06




Date: 22.APR.2006 11:15:58

Channel:11




Date: 22.APR.2006 11:18:37

Modulation Standard:802.11g (6Mbps)
Channel:01




Date: 22.APR.2006 11:40:08

Channel:06



Date: 22.APR.2006 11:44:58

Channel:11



Date: 22.APR.2006 11:50:18

7. Maximum Peak Output Power


7.1 Test Limit

The Maximum Peak Output Power Measurement is 30dBm.

7.2 Test Procedures

The antenna port(RF output)of the EUT was connected to the input(RF input)of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

7.3 Test Setup Layout



7.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2007/01/16

7.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Apr. 22, 2006 Temperature: 26 Humidity: 65% Atmospheric pressure: 1022 hPa


Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
01	2412	15.06	32.1
06	2437	15.06	32.1
11	2462	15.18	33.0

(2) Modulation Standard: IEEE 802.11g (6Mbps)

Test Date: Apr. 22, 2006 Temperature: 26 Humidity: 65% Atmospheric pressure: 1022 hPa


Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
01	2412	12.40	17.4
06	2437	14.14	25.9
11	2462	14.31	27.0

Modulation Standard: 802.11b (11Mbps)
 Channel: 01




Date: 24.APR.2006 09:45:06

Channel:06




Date: 24.APR.2006 09:43:18

Channel: 11




Date: 24.APR.2006 09:40:36

Modulation Standard:802.11g (6Mbps)
Channel:01




Date: 24.APR.2006 09:56:51

Channel: 06



Date: 24.APR.2006 09:54:41

Channel:11



Date: 24.APR.2006 09:50:40

8. Band Edges Measurement


8.1 Test Limit

Below -20dB of the highest emission level of operating band
(in 100kHz Resolution Bandwidth).

8.2 Test Procedure :

- 1.The transmitter output was connected to the spectrum analyzer via a low lose cable.
- 2.Set both RBW and VBW of spectrum analyzer to 100 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- 3.The band edges was measured and recorded.

8.3 Test Setup Layout



8.4 Measurement equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2007/01/16

8.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Apr. 22, 2006 Temperature: 26 Humidity: 65% Atmospheric pressure: 1022 hPa

Channel	Frequency	maximum value in frequency (MHz)	maximum value is (dBm)
01	2412	2396.60	-37.25
11	2462	3085.00	-54.12


(2) Modulation Standard: IEEE 802.11g (6Mbps)

Test Date: Apr. 22, 2006 Temperature: 26 Humidity: 65% Atmospheric pressure: 1022 hPa


Channel	Frequency	maximum value in frequency (MHz)	maximum value is (dBm)
01	2412	2400.00	-36.38
11	2462	2483.50	-54.23

Modulation Standard: 802.11b (11Mbps)

Channel: 01




Date: 22.APR.2006 11:09:41




Date: 22.APR.2006 11:10:13

Channel: 11




Date: 22.APR.2006 11:20:04




Date: 22.APR.2006 11:20:46

Modulation Standard: 802.11g (6Mbps)

Channel: 01




Date: 22.APR.2006 11:41:35




Date: 22.APR.2006 11:42:17

Channel: 11



Date: 22.APR.2006 11:52:11



Date: 22.APR.2006 11:52:52

8.6 Restrict band emission Measurement Data

Adapter model 1 : DSA-20P-10 US 120144

Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Apr. 27, 2006 Temperature: 25 Humidity: 70% Atmospheric pressure: 1013 hPa

a) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2384.255	H	49.85	-0.77	49.08	Peak	74	54	-24.92	72	1.1
2319.894	H	38.14	-0.98	37.16	Ave	74	54	-16.84	72	1.1
2384.255	V	52.17	-0.77	51.40	Peak	74	54	-22.60	174	1.0
2319.894	V	40.33	-0.98	39.35	Ave	74	54	-14.65	174	1.0

b) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2491.146	H	49.55	-0.43	49.12	Peak	74	54	-24.88	72	1.1
2483.508	H	37.84	-0.45	37.39	Ave	74	54	-16.61	72	1.1
2487.802	V	53.58	-0.45	53.14	Peak	74	54	-20.86	174	1.0
2483.508	V	41.76	-0.45	41.31	Ave	74	54	-12.69	174	1.0

Modulation Standard: 802.11g (6Mbps)

Test Date: Apr. 27, 2006 Temperature: 25 Humidity: 70% Atmospheric pressure: 1013 hPa

a) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2389.768	H	49.59	-0.75	48.84	Peak	74	54	-25.16	72	1.1
2319.984	H	37.75	-0.91	36.84	Ave	74	54	-17.16	72	1.1
2389.968	V	53.88	-0.75	53.13	Peak	74	54	-20.87	174	1.0
2319.984	V	42.19	-0.91	41.28	Ave	74	54	-12.72	174	1.0

c) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2490.196	H	50.25	-0.43	49.82	Peak	74	54	-24.18	72	1.1
2483.508	H	38.37	-0.45	37.92	Ave	74	54	-16.08	72	1.1
2483.812	V	52.36	-0.45	51.91	Peak	74	54	-22.09	174	1.0
2483.508	V	40.58	-0.45	40.13	Ave	74	54	-13.87	174	1.0

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz

Adapter model 2 : DV-151A-1

Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Apr. 27, 2006 Temperature: 25 Humidity: 70% Atmospheric pressure: 1013 hPa

d) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2382.828	H	50.79	-0.77	52.02	Peak	74	54	-23.98	72	1.1
2319.894	H	38.96	-0.98	37.92	Ave	74	54	-16.08	72	1.1
2385.378	V	52.08	-0.77	51.31	Peak	74	54	-22.69	174	1.0
2319.894	V	43.04	-0.98	42.06	Ave	74	54	-11.94	174	1.0

e) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2491.146	H	49.94	-0.43	49.51	Peak	74	54	-24.49	72	1.1
2491.906	H	37.88	-0.43	37.45	Ave	74	54	-26.55	72	1.1
2487.802	V	52.23	-0.44	51.79	Peak	74	54	-22.21	174	1.0
2487.802	V	40.63	-0.44	40.19	Ave	74	54	-13.81	174	1.0

Modulation Standard: 802.11g (6Mbps)

Test Date: Apr. 27, 2006 Temperature: 25 Humidity: 70% Atmospheric pressure: 1013 hPa

b) Channel 1

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2386.194	H	49.34	-0.76	48.58	Peak	74	54	-25.42	72	1.1
2319.894	H	38.84	-0.98	37.86	Ave	74	54	-16.14	72	1.1
2389.968	V	53.35	-0.75	52.60	Peak	74	54	-21.40	174	1.0
2319.894	V	41.64	-0.98	40.66	Ave	74	54	-13.34	174	1.0

f) Channel 11

Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2490.196	H	50.03	-0.43	49.60	Peak	74	54	-24.40	72	1.1
2483.508	H	38.67	-0.45	37.62	Ave	74	54	-16.38	72	1.1
2483.812	V	52.17	-0.45	51.72	Peak	74	54	-22.28	174	1.0
2483.622	V	40.54	-0.45	40.09	Ave	74	54	-13.91	174	1.0

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz

9. Power Spectral Density


9.1 Test Limit

The Maximum of Power Spectral Density Measurement is 8dBm.

9.2 Test Procedures

- a. The transmitter output was connected to spectrum analyzer.
- b. The spectrum analyzer's resolution bandwidth were set at 3KHz RBW and 30KHz VBW as that of the fundamental frequency. Set the sweep time=span/3KHz.
- c. The power spectral density was measured and recorded.
- d. The Sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

9.3 Test Setup Layout :



9.4 List of Measuring Equipment Used

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Valid Date.
Spectrum Analyzer	FSP40	R&S	100047	2007/01/16

9.5 Test Result and Data

(1) Modulation Standard: IEEE 802.11b (11Mbps)

Test Date: Apr. 22, 2006 Temperature: 26 Humidity: 65% Atmospheric pressure: 1022 hPa


Channel	Frequency	Maximum Power Density of 3 kHz Bandwidth (dBm)
01	2412	-12.66
06	2437	-12.84
11	2462	-12.98

(2) Modulation Standard: IEEE 802.11g (6Mbps)

Test Date: Apr. 22, 2006 Temperature: 26 Humidity: 65% Atmospheric pressure: 1022 hPa


Channel	Frequency	Maximum Power Density of 3 kHz Bandwidth (dBm)
01	2412	-17.10
06	2437	-15.53
11	2462	-15.97

Modulation Standard: 802.11b (11Mbps)
Channel: 01




Date: 22.APR.2006 11:12:04

Channel:06




Date: 22.APR.2006 11:14:37

Channel: 11




Date: 22.APR.2006 11:22:07

Modulation Standard:802.11g (6Mbps)
Channel:01




Date: 22.APR.2006 11:38:35

Channel: 06



Date: 22.APR.2006 11:46:22

Channel:11



Date: 22.APR.2006 11:48:44

10. Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

** : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

10.1 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.