



# SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.  
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

## FCC RADIO TEST REPORT

Applicant's company	NETGEAR, Inc.
Applicant Address	4500 Great America Parkway, Santa Clara, CA 95054, USA
FCC ID	PY306400057
Manufacturer's company	Ambit Microsystems (Shanghai) Ltd.
Manufacturer Address	No. 1925, Nanle Road, Songjiang Export Processing Zone, Shanghai, China

Product Name	54MBPS WIRELESS ROUTER
Brand Name	NETGEAR
Model Name	WGR614v8
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Jan. 24, 2007
Final Test Date	Mar. 30, 2007
Submission Type	Original Equipment



### Statement

**Test result included is only for the 802.11b/g part of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

## Table of Contents

<b>1. CERTIFICATE OF COMPLIANCE .....</b>	<b>1</b>
<b>2. SUMMARY OF THE TEST RESULT .....</b>	<b>2</b>
<b>3. GENERAL INFORMATION .....</b>	<b>3</b>
3.1. Product Details.....	3
3.2. Accessories.....	3
3.3. Table for Filed Antenna.....	3
3.4. Table for Carrier Frequencies .....	3
3.5. Table for Test Modes.....	4
3.6. Table for Testing Locations.....	4
3.7. Table for Supporting Units .....	4
3.8. Table for Parameters of Test Software Setting .....	5
3.9. Test Configurations .....	6
<b>4. TEST RESULT .....</b>	<b>9</b>
4.1. AC Power Line Conducted Emissions Measurement.....	9
4.2. Maximum Peak Output Power Measurement .....	13
4.3. Power Spectral Density Measurement .....	15
4.4. 6dB Spectrum Bandwidth Measurement .....	20
4.5. Radiated Emissions Measurement .....	25
4.6. Band Edge Emissions Measurement .....	43
4.7. Antenna Requirements .....	50
<b>5. LIST OF MEASURING EQUIPMENTS .....</b>	<b>51</b>
<b>6. TEST LOCATION.....</b>	<b>53</b>
<b>APPENDIX A. PHOTOGRAPHS OF EUT.....</b>	<b>A1 ~ A12</b>
<b>APPENDIX B. TEST PHOTOS.....</b>	<b>B1 ~ B5</b>
<b>APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....</b>	<b>C1 ~C3</b>

## History of This Test Report

Original Issue Date: Apr. 03, 2007

Report No.: FR730102

No additional attachment.

Additional attachment were issued as following record:

Attachment No.	Issue Date	Description



## 1. CERTIFICATE OF COMPLIANCE

Product Name : 54MBPS WIRELESS ROUTER  
Brand Name : NETGEAR  
Model Name : WGR614v8  
Applicant : NETGEAR, Inc.  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jan. 24, 2007 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Wayne Hsu 4/4/07'.

Wayne Hsu

SPORTON INTERNATIONAL INC.

## 2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	2.94 dB
4.2	15.247(b)(3)	Maximum Peak Conducted Output Power	Complies	6.03 dB
4.3	15.247(e)	Power Spectral Density	Complies	13.05 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	3.22 dB
4.6	15.247(d)	Band Edge Emissions	Complies	2.83 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 <sup>-8</sup>	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

### 3. GENERAL INFORMATION

#### 3.1. Product Details

Items	Description
Power Type	Power Adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 11.96 MHz ; 11g: 16.44 MHz
Conducted Output Power	11b: 20.80 dBm ; 11g: 24.02 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

#### 3.2. Accessories

Power	Brand	Model	Rating
Adapter 1	NETGEAR	RHQ-120100-1	Input: 100-120V, 50/60Hz, 0.3A Output: 12V, 1A
Adapter 2	NETGEAR	DSA-12R-12AUS12 0120	Input: 100-120V, 50/60Hz, 0.3A Output: +12V, 1A

#### 3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Function
1	WHA YU	C107-510446-A	Dipole Antenna	NA	1.00	TX/RX
2	WHA YU	C107-510314-A	Dipole Antenna	UFL	1.00	TX/RX
3	FOXCONN	ANT13S0	Printed Antenna	NA	1.98	RX

Note: The EUT has three antennas. Ant. 3 is only for receiving purpose. Ant.1 / Ant.2 is transmitter antenna.

Ant 1 generated the worst test result, so it was recorded in this report.

#### 3.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	11 Mbps	6	1
Maximum Peak Conducted Output Power Power Spectral Density 6dB Spectrum Bandwidth	11b/CCK	11 Mbps	1/6/11	NA
	11g/BPSK	6 Mbps	1/6/11	NA
Radiated Emissions 9kHz~1GHz	11g/BPSK	6 Mbps	6	1
Radiated Emissions 1GHz~10 <sup>th</sup> Harmonic	11b/CCK	11 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
Band Edge Emissions	11b/CCK	11 Mbps	1/11	1
	11g/BPSK	6 Mbps	1/11	1

Test Mode:

Mode 1: Ant 1 +Adapter 1

Mode 2: Ant 1 +Adapter 2

Mode 1 generated the worst test result, so it was recorded in this report.

### 3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

### 3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D520	E2KWM3945ABG
Notebook	DELL	D520	E2KWM3945ABG
Notebook	DELL	D400	E2K24GBRL

### 3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters of IEEE 802.11b/g

Test Software Version	Hyperterminal		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	14	15	21
IEEE 802.11g	18	24	33

During the test, the following programs under WIN XP were executed:

Executed "ping.exe" to link with the remote workstation to receive and transmit data by LAN and WLAN.




### 3.9. Test Configurations


#### 3.9.1. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz

Test Mode: Mode 1 / Mode 2




Test Configuration: above 1GHz



### 3.9.2. AC Power Line Conduction Emissions Test Configuration

Test Mode: Mode 1 / Mode 2



## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

#### 4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

#### 4.1.4. Test Setup Layout



#### LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in  $50 \Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

#### 4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	20°C	Humidity	59%
Test Engineer	Barry Chen	Phase	Line
Configuration	Mode 1		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.23040	45.40	-17.04	62.44	45.10	0.10	0.20	QP	LINE
2	0.23040	42.33	-10.11	52.44	42.03	0.10	0.20	AVERAGE	LINE
3	0.46122	39.60	-7.07	46.67	39.31	0.09	0.20	AVERAGE	LINE
4	0.46122	40.75	-15.92	56.67	40.46	0.09	0.20	QP	LINE
5	0.68990	43.06	-2.94	46.00	42.81	0.05	0.20	AVERAGE	LINE
6	0.68990	44.91	-11.09	56.00	44.66	0.05	0.20	QP	LINE
7	0.92330	43.54	-12.46	56.00	43.33	0.01	0.20	QP	LINE
8	0.92330	37.10	-8.90	46.00	36.89	0.01	0.20	AVERAGE	LINE
9	1.153	42.81	-13.19	56.00	42.65	0.00	0.16	QP	LINE
10	1.153	34.95	-11.05	46.00	34.79	0.00	0.16	AVERAGE	LINE
11	1.839	34.39	-11.61	46.00	34.22	0.00	0.17	AVERAGE	LINE
12	1.839	41.00	-15.00	56.00	40.83	0.00	0.17	QP	LINE

Temperature	20°C	Humidity	59%
Test Engineer	Barry Chen	Phase	Neutral
Configuration	Mode 1		



	Freq	Level	Over	Limit	Read	LISN	Cable	Remark	Pol/Phase
	MHz	dBuV	Limit	Line	Level	Factor	Loss		
			dB	dBuV	dBuV	dB	dB		
1	0.23162	45.56	-16.83	62.39	45.18	0.18	0.20	QP	NEUTRAL
2	0.23162	43.06	-9.33	52.39	42.68	0.18	0.20	AVERAGE	NEUTRAL
3	0.46122	42.24	-14.43	56.67	41.94	0.10	0.20	QP	NEUTRAL
4	0.46122	41.39	-5.28	46.67	41.09	0.10	0.20	AVERAGE	NEUTRAL
5	0.68626	43.88	-12.12	56.00	43.58	0.10	0.20	QP	NEUTRAL
6	0.68626	38.53	-7.47	46.00	38.23	0.10	0.20	AVERAGE	NEUTRAL
7	1.377	44.32	-11.68	56.00	44.10	0.10	0.12	QP	NEUTRAL
8	1.377	31.75	-14.25	46.00	31.53	0.10	0.12	AVERAGE	NEUTRAL
9	1.610	41.21	-14.79	56.00	40.99	0.10	0.12	QP	NEUTRAL
10	1.610	36.58	-9.42	46.00	36.36	0.10	0.12	AVERAGE	NEUTRAL
11	2.077	30.69	-15.31	46.00	30.39	0.10	0.20	AVERAGE	NEUTRAL
12	2.077	39.70	-16.30	56.00	39.40	0.10	0.20	QP	NEUTRAL

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Maximum Peak Output Power Measurement

### 4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	NRV-Z32 (model 04)

### 4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.



#### 4.2.7. Test Result of Maximum Peak Output Power

<b>Temperature</b>	22°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	LEO HUNG	<b>Configurations</b>	802.11b/g

##### Configuration IEEE 802.11b

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	19.88	30.00	Complies
6	2437 MHz	20.10	30.00	Complies
11	2462 MHz	19.92	30.00	Complies

##### Configuration IEEE 802.11g

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	24.01	30.00	Complies
6	2437 MHz	24.02	30.00	Complies
11	2462 MHz	23.97	30.00	Complies

### 4.3. Power Spectral Density Measurement

#### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

#### 4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

#### 4.3.4. Test Setup Layout



#### 4.3.5. Test Deviation

There is no deviation with the original standard.

#### 4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Power Spectral Density

<b>Temperature</b>	22°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	LEO HUNG	<b>Configurations</b>	802.11b/g


##### Configuration IEEE 802.11b

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-5.05	8.00	Complies
6	2437 MHz	-6.45	8.00	Complies
11	2462 MHz	-5.90	8.00	Complies

##### Configuration IEEE 802.11g


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-9.46	8.00	Complies
6	2437 MHz	-8.52	8.00	Complies
11	2462 MHz	-10.30	8.00	Complies

### Power Density Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 26.JAN.2007 15:24:05

### Power Density Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 26.JAN.2007 15:28:40

**Power Density Plot on Configuration IEEE 802.11b / 2462 MHz**




Date: 26.JAN.2007 15:29:37

**Power Density Plot on Configuration IEEE 802.11g / 2412 MHz**




Date: 26.JAN.2007 15:58:35

### Power Density Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 26.JAN.2007 15:37:39

### Power Density Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 26.JAN.2007 15:38:48

#### 4.4. 6dB Spectrum Bandwidth Measurement

##### 4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

##### 4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

##### 4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

##### 4.4.4. Test Setup Layout



##### 4.4.5. Test Deviation

There is no deviation with the original standard.

##### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

## 4.4.7. Test Result of 6dB Spectrum Bandwidth

<b>Temperature</b>	22°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	LEO HUNG	<b>Configurations</b>	802.11b/g

## Configuration IEEE 802.11b


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	10.04	11.96	500	Complies
6	2437 MHz	10.08	11.92	500	Complies
11	2462 MHz	10.04	11.96	500	Complies

## Configuration IEEE 802.11g

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.40	16.44	500	Complies
6	2437 MHz	16.32	16.32	500	Complies
11	2462 MHz	16.36	16.40	500	Complies




6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 26.JAN.2007 15:23:40

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 26.JAN.2007 15:28:24

### 6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 26.JAN.2007 15:29:20

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 26.JAN.2007 15:58:10

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 26.JAN.2007 15:37:23

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 26.JAN.2007 15:38:33

## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100KHz / 100KHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

#### 4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

#### 4.5.5. Test Deviation

There is no deviation with the original standard.

#### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

<b>Temperature</b>	22°C	<b>Humidity</b>	65%
<b>Test Engineer</b>	Jordan Hsiao		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	22°C	Humidity	65%
Test Engineer	Jordan Hsiao	Configurations	802.11g CH 6 / Mode 1 (Adapter 1)


Horizontal



	Read Freq	Read Level	Read Level	Limit Line	Over Limit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1 !	268.620	56.35	40.97	46.00	-5.03	13.46	31.34	2.50	Peak	---	---	HORIZONTAL
2 *	299.660	57.90	42.78	46.00	-3.22	14.00	31.32	2.20	Peak	100	235	HORIZONTAL
3	378.230	51.48	39.01	46.00	-6.99	16.08	31.12	2.57	Peak	---	---	HORIZONTAL
4 !	443.220	53.67	42.73	46.00	-3.27	17.12	30.93	2.88	Peak	---	---	HORIZONTAL
5 !	479.110	52.61	42.41	46.00	-3.59	17.60	30.93	3.13	Peak	---	---	HORIZONTAL
6	660.500	46.51	39.33	46.00	-6.67	19.64	30.35	3.52	Peak	---	---	HORIZONTAL



**Vertical**



	Read	Limit	Over	Antenna	Preamp	Cable		Ant	Table	
	Freq	Level	Line	Limit	Factor	Factor	Loss	Pos	Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	cm	deg	
1 !	153.190	56.49	37.88	43.50	-5.62	11.02	31.53	1.90	Peak	--- VERTICAL
2 !	172.590	58.95	39.37	43.50	-4.13	10.14	31.59	1.87	Peak	--- VERTICAL
3	265.710	52.65	37.45	46.00	-8.55	13.64	31.34	2.50	Peak	--- VERTICAL
4 !	320.030	55.58	41.14	46.00	-4.86	14.57	31.29	2.28	Peak	--- VERTICAL
5	358.830	50.45	37.32	46.00	-8.68	15.61	31.20	2.46	Peak	--- VERTICAL
6 !	479.110	50.42	40.23	46.00	-5.77	17.60	30.93	3.13	Peak	--- VERTICAL

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)


Temperature	22°C	Humidity	65%
Test Engineer	Jordan Hsiao	Configurations	802.11b CH 1

Horizontal




	Read Freq	Read Level	Read Level	Limit Line	Over Limit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1	4824.048	41.71	43.90	54.00	-10.10	33.06	35.16	4.30	AVERAGE	100	310	HORIZONTAL
2	4824.120	48.21	50.40	74.00	-23.60	33.06	35.16	4.30	PEAK	100	310	HORIZONTAL

Vertical




	Freq	Read Level	Level	Limit Line	Over Limit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1 !	4824.068	46.53	48.72	54.00	-5.28	33.06	35.16	4.30	AVERAGE	101	249	VERTICAL
2	4824.088	50.40	52.59	74.00	-21.41	33.06	35.16	4.30	PEAK	101	249	VERTICAL

Temperature	22°C	Humidity	65%
Test Engineer	Jordan Hsiao	Configurations	802.11b CH 6

**Horizontal**



	Read Freq	Read Level	Read Level	Limit Line	Over Limit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1	4873.956	46.92	49.23	74.00	-24.77	33.16	35.15	4.30	PEAK	100	161	HORIZONTAL
2	4874.048	40.10	42.41	54.00	-11.59	33.16	35.15	4.30	AVERAGE	100	161	HORIZONTAL
3	7308.360	35.94	42.23	54.00	-11.77	35.92	35.19	5.56	AVERAGE	111	245	HORIZONTAL
4	7308.400	45.70	51.99	74.00	-22.01	35.92	35.19	5.56	PEAK	111	245	HORIZONTAL

**Vertical**




	Read	Limit	Over	Antenna	Preamp	Cable		Ant	Table	
	Freq	Level	Line	Limit	Factor	Factor	Loss	Pos	Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dB	dB/m	dB	dB	cm	deg	
1	4873.856	49.72	52.02	74.00	-21.98	33.16	35.15	4.30	249	VERTICAL
2	4873.992	45.13	47.44	54.00	-6.56	33.16	35.15	4.30	249	VERTICAL
3	7313.800	41.44	47.74	54.00	-6.26	35.92	35.18	5.56	343	VERTICAL
4	7314.340	47.95	54.25	74.00	-19.75	35.92	35.18	5.56	343	VERTICAL

Temperature	22°C	Humidity	65%
Test Engineer	Jordan Hsiao	Configurations	802.11b CH 11

**Horizontal**


	Read Freq	Read Level	Read Level	Limit Line	Over Limit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1	4924.070	41.34	43.76	54.00	-10.24	33.26	35.14	4.30	AVERAGE	105	313	HORIZONTAL
2	4924.070	52.36	54.78	74.00	-19.22	33.26	35.14	4.30	PEAK	105	313	HORIZONTAL
3	7387.580	46.32	52.85	74.00	-21.15	36.09	35.17	5.61	PEAK	100	335	HORIZONTAL
4	7388.320	32.68	39.22	54.00	-14.78	36.09	35.16	5.61	AVERAGE	100	335	HORIZONTAL


Vertical



	Read Freq	Read Level	Read Level	Limit Line	Over Limit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1	4924.032	43.86	46.28	54.00	-7.72	33.26	35.14	4.30	AVERAGE	142	95	VERTICAL
2	4924.048	49.10	51.52	74.00	-22.48	33.26	35.14	4.30	PEAK	142	95	VERTICAL
3	7387.000	45.88	52.41	74.00	-21.59	36.09	35.17	5.61	PEAK	109	341	VERTICAL
4	7388.880	38.18	44.72	54.00	-9.28	36.09	35.16	5.61	AVERAGE	109	341	VERTICAL

Temperature	22°C	Humidity	65%
Test Engineer	Jordan Hsiao	Configurations	802.11g CH 1


**Horizontal**



	Read Freq	Read Level	Read Level	Limit Line	OverLimit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1	1199.930	46.49	38.64	54.00	-15.36	24.71	34.46	1.90	AVERAGE	100	61	HORIZONTAL
2	1200.150	51.84	43.99	74.00	-30.01	24.71	34.46	1.90	PEAK	100	61	HORIZONTAL




**Vertical**



	Read Freq	Read Level	Read Level	Limit Line	Over Limit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1	1199.990	50.05	42.20	74.00	-31.80	24.71	34.46	1.90	PEAK	100	50	VERTICAL
2	1200.010	44.38	36.53	54.00	-17.47	24.71	34.46	1.90	AVERAGE	100	50	VERTICAL


Temperature	22°C	Humidity	65%
Test Engineer	Jordan Hsiao	Configurations	802.11g CH 6

**Horizontal**




	Read Freq	Read Level	Read Level	Limit Line	Over Limit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1	1199.950	46.78	38.93	54.00	-15.07	24.71	34.46	1.90	AVERAGE	100	60	HORIZONTAL
2	1200.060	51.56	43.71	74.00	-30.29	24.71	34.46	1.90	PEAK	100	60	HORIZONTAL

**Vertical**




	Read Freq	Read Level	Limit Level	Limit Line	OverLimit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1	1199.970	44.14	36.29	54.00	-17.71	24.71	34.46	1.90	AVERAGE	100	52	VERTICAL
2	1200.210	49.58	41.73	74.00	-32.27	24.71	34.46	1.90	PEAK	100	52	VERTICAL

Temperature	22°C	Humidity	65%
Test Engineer	Jordan Hsiao	Configurations	802.11g CH 11

**Horizontal**


	Freq	Read Level	Limit Level	Limit Line	OverLimit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1	1199.950	51.52	43.67	74.00	-30.33	24.71	34.46	1.90	PEAK	100	58	HORIZONTAL
2	1200.110	46.24	38.39	54.00	-15.61	24.71	34.46	1.90	AVERAGE	100	58	HORIZONTAL

**Vertical**



	Freq	Read Level	Level	Limit Line	Over Limit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1	1199.990	44.23	36.38	54.00	-17.62	24.71	34.46	1.90	AVERAGE	100	48	VERTICAL
2	1200.070	49.33	41.48	74.00	-32.52	24.71	34.46	1.90	PERK	100	48	VERTICAL

**Note:**

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.6. Band Edge Emissions Measurement

### 4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micovolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

### 4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

### 4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

### 4.6.5. Test Deviation

There is no deviation with the original standard.


### 4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	22°C	Humidity	65%
Test Engineer	Jordan Hsiao	Configurations	802.11b CH 1, 11


Channel 1



	Read Freq	Read Level	Read Level	Limit Line	OverLimit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1 !	2390.000	18.15	49.09	54.00	-4.91	28.17	0.00	2.76	AVERAGE	100	267	VERTICAL
2	2390.000	27.37	58.31	74.00	-15.69	28.17	0.00	2.76	PEAK	100	267	VERTICAL
3 *	2414.600	78.58	109.58			28.21	0.00	2.79	PEAK	100	267	VERTICAL
4 *	2414.800	75.05	106.05			28.21	0.00	2.79	AVERAGE	100	267	VERTICAL

Item 3, 4 are fundamental frequency at 2412 MHz.

Channel 11




	Read Freq	Read Level	Read Level	Limit Line	OverLimit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1 *	2462.200	76.36	107.49			28.32	0.00	2.81	PEAK	100	252	VERTICAL
2 *	2464.800	72.14	103.28			28.32	0.00	2.81	AVERAGE	100	252	VERTICAL
3 *	2483.500	19.75	50.95	54.00	-3.05	28.36	0.00	2.84	AVERAGE	100	252	VERTICAL
4	2484.300	31.53	62.73	74.00	-11.27	28.36	0.00	2.84	PEAK	100	252	VERTICAL

Item 1, 2 are fundamental frequency at 2462 MHz.



Temperature	22°C	Humidity	65%
Test Engineer	Jordan Hsiao	Configurations	802.11g CH 1, 11


Channel 1



	Read Freq	Read Level	Read Level	Limit Line	OverLimit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1	2389.400	36.70	67.64	74.00	-6.36	28.17	0.00	2.76	PEAK	100	263	VERTICAL
2 !	2390.000	18.10	49.04	54.00	-4.96	28.17	0.00	2.76	AVERAGE	100	263	VERTICAL
3 *	2408.000	67.54	98.54			28.21	0.00	2.79	AVERAGE	100	263	VERTICAL
4 *	2408.200	79.36	110.36			28.21	0.00	2.79	PEAK	100	263	VERTICAL

Item 3, 4 are fundamental frequency at 2412 MHz.

Channel 11



	Read Freq	Read Level	Limit Level	Limit Line	Over Limit	Antenna Factor	Preamp Factor	Cable Loss	Remark	Ant Pos	Table Pos	Pol/Phase
	MHz	dBuV	dBuV/m	dBuV/m	dB	dB/m	dB	dB		cm	deg	
1 *	2464.200	78.01	109.14			28.32	0.00	2.81	PEAK	100	265	VERTICAL
2 *	2467.000	66.55	97.69			28.32	0.00	2.81	AVERAGE	100	265	VERTICAL
3 *	2483.500	19.97	51.17	54.00	-2.83	28.36	0.00	2.84	AVERAGE	100	265	VERTICAL
4 !	2483.900	38.62	69.82	74.00	-4.18	28.36	0.00	2.84	PEAK	100	265	VERTICAL

Item 1, 2 are fundamental frequency at 2462 MHz.


Note:

Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 26.JAN.2007 15:24:13

High Band Edge Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 26.JAN.2007 15:29:45

### Low Band Edge Plot on Configuration IEEE 802.11g / 2412 MHz



Date: 26.JAN.2007 15:58:43

### High Band Edge Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 26.JAN.2007 15:38:56

## 4.7. Antenna Requirements

### 4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further,

### 4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

## 5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100359	9kHz – 2.75GHz	Sep. 21, 2006	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 28, 2007	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 17, 2007	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2006	Conduction (CO04-HY)
ISN	SCHAFFNER	ISN T400	21653	9kHz –30MHz	Mar. 27, 2007	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 15, 2006	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	CPA9231A	1886	9 kHz - 2 GHz	Jan. 22, 2007	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	May 29, 2006	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	923364	26.5 GHz - 40 GHz	Jan. 22, 2007*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100004/040	9 kHz - 40 GHz	Sep. 21, 2006	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 23, 2006*	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 24, 2006	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	Apr. 27, 2006	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	NCR	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec. 02, 2006	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec. 02, 2006	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Dec. 17, 2006	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100764	DC ~ 40GHz	Jul. 20, 2006	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100666	DC ~ 40GHz	Jul. 20, 2006	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jun. 10, 2006	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Apr. 21, 2005*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 03, 2007	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 02, 2006	Conducted (TH01-HY)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2006	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2006	Conducted (TH01-HY)
Oscilloscope	Tektronix	TDS1012	CO38515	100MHz / 1GS/s	Jun. 20, 2006	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 07, 2007	Conducted (TH01-HY)
Data Generator	Tektronix	DG2030	063-2920-50	0.1Hz~400MHz	Jun. 16, 2006	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Note: \*Calibration Interval of instruments listed above is two year.

## 6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085