

1.1. Test Result of RF Exposure Evaluation

- . Product: Prosafe Wireless ADSL Modem VPN Firewall Router
- . Test Item: RF Exposure Evaluation Data
- . Test site: OATSI-SD
- . Test Mode: Normal Operation

1.1.1. Antenna Gain

The maximum Gain is 5 dBi.

1.1.2. EUT Operation condition

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

1.1.3. Output Power into Antenna & RF Exposure Evaluation Distance

Test Mode1:

Modulation Standard: IEEE 802.11b

Test Date: May. 21, 2007 Temperature: 25 Humidity: 68%

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density (S) (mW/cm ²)
01	2412	24.80	0.190
06	2437	24.83	0.191
11	2462	24.78	0.189

Modulation Standard: IEEE 802.11g

Test Date: May. 21, 2007 Temperature: 25 Humidity: 68%

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density (S) (mW/cm ²)
01	2412	23.79	0.151
06	2437	23.89	0.154
11	2462	23.87	0.153

Test Mode2:

Modulation Standard: IEEE 802.11b

Test Date: May. 21, 2007 Temperature: 25 Humidity: 68%

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density (S) (mW/cm ²)
01	2412	24.85	0.192
06	2437	24.80	0.190
11	2462	24.71	0.186

Modulation Standard: IEEE 802.11g

Test Date: May. 21, 2007 Temperature: 25 Humidity: 68%

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density (S) (mW/cm ²)
01	2412	23.87	0.153
06	2437	23.90	0.154
11	2462	23.95	0.156

The MPE is calculated as $0.192 \text{ mW} / \text{cm}^2 < \text{limit } 1 \text{ mW} / \text{cm}^2$. So, RF exposure limit warning or SAR test are not required.

For 2412-2462 MHz, the EUT will only be used with a separation of 20cm or greater between the antenna and nearby persons and can therefore be considered a mobile transmitter per 47CFR2.1091 (b).

The RF Exposure Information page from the manual is included here for reference.