

## FCC RADIO TEST REPORT

|                        |   |
|------------------------|---|
| Applicant's company    | NETGEAR, Inc.   |
| Applicant Address      | 4500 Great America Parkway, Santa Clara, CA 95054, USA                  |
| FCC ID                 | PY307300074   |
| Manufacturer's company | Ambit Microsystems (Shanghai) Ltd.                                      |
| Manufacturer Address   | No. 1925, Nanle Road, Songjiang Export Processing Zone, Shanghai, China |

|                  |                                       |
|------------------|---------------------------------------|
| Product Name     | RangeMax™ Wireless-N Gigabit Router   |
| Brand Name       | NETGEAR                               |
| Model Name       | WNR3500                               |
| Test Rule        | 47 CFR FCC Part 15 Subpart C § 15.247 |
| Test Freq. Range | 2400 ~ 2483.5MHz                      |
| Received Date    | Nov. 14, 2007                         |
| Final Test Date  | Dec. 24, 2007                         |
| Submission Type  | Original Equipment                    |



### Statement

**Test result included is only for the 802.11b/g part of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

## Table of Contents

|  |                 |
|--|-----------------|
| <b>1. CERTIFICATE OF COMPLIANCE .....</b>                | <b>1</b>        |
| <b>2. SUMMARY OF THE TEST RESULT .....</b>               | <b>2</b>        |
| <b>3. GENERAL INFORMATION .....</b>                      | <b>3</b>        |
| 3.1. Product Details.....                                | 3               |
| 3.2. Accessories.....                                    | 3               |
| 3.3. Table for Filed Antenna.....                        | 4               |
| 3.4. Table for Carrier Frequencies .....                 | 4               |
| 3.5. Table for Test Modes .....                          | 5               |
| 3.6. Table for Testing Locations.....                    | 5               |
| 3.7. Table for Supporting Units .....                    | 5               |
| 3.8. Table for Parameters of Test Software Setting ..... | 6               |
| 3.9. Test Configurations .....                           | 7               |
| <b>4. TEST RESULT .....</b>                              | <b>9</b>        |
| 4.1. AC Power Line Conducted Emissions Measurement.....  | 9               |
| 4.2. Maximum Peak Output Power Measurement .....         | 13              |
| 4.3. Power Spectral Density Measurement .....            | 16              |
| 4.4. 6dB Spectrum Bandwidth Measurement .....            | 21              |
| 4.5. Radiated Emissions Measurement .....                | 26              |
| 4.6. Band Edge Emissions Measurement .....               | 44              |
| 4.7. Antenna Requirements .....                          | 49              |
| <b>5. LIST OF MEASURING EQUIPMENTS .....</b>             | <b>50</b>       |
| <b>6. TEST LOCATION.....</b>                             | <b>52</b>       |
| <b>7. TAF CERTIFICATE OF ACCREDITATION .....</b>         | <b>53</b>       |
| <b>APPENDIX A. PHOTOGRAPHS OF EUT.....</b>               | <b>A1 ~ A17</b> |
| <b>APPENDIX B. TEST PHOTOS.....</b>                      | <b>B1 ~ B5</b>  |
| <b>APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....</b>     | <b>C1 ~C3</b>   |

## History of This Test Report

Original Issue Date: Dec. 24, 2007

Report No.: FR7N1402AB

☒ No additional attachment.

☐ Additional attachment were issued as following record:


| Attachment No. | Issue Date | Description |
|----------------|------------|-------------|
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |



## 1. CERTIFICATE OF COMPLIANCE

Product Name : RangeMax™ Wireless-N Gigabit Router  
Brand Name : NETGEAR  
Model Name : WNR3500  
Applicant : NETGEAR, Inc.  
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Nov. 14, 2007 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

  
Wayne Hsu

SPORTON INTERNATIONAL INC.



## 2. SUMMARY OF THE TEST RESULT

| Applied Standard: 47 CFR FCC Part 15 Subpart C |              |                                     |          |             |
|--|--------------|-------------------------------------|----------|-------------|
| Part   | Rule Section | Description of Test                 | Result   | Under Limit |
| 4.1  | 15.207       | AC Power Line Conducted Emissions   | Complies | 7.56 dB     |
| 4.2  | 15.247(b)(3) | Maximum Peak Conducted Output Power | Complies | 0.09 dB     |
| 4.3  | 15.247(e)    | Power Spectral Density              | Complies | 9.99 dB     |
| 4.4  | 15.247(a)(2) | 6dB Spectrum Bandwidth              | Complies | -           |
| 4.5  | 15.247(d)    | Radiated Emissions                  | Complies | 0.20 dB     |
| 4.6  | 15.247(d)    | Band Edge Emissions                 | Complies | 0.46 dB     |
| 4.7  | 15.203       | Antenna Requirements                | Complies | -           |

| Test Items                                  | Uncertainty               | Remark                   |
|---|---------------------------|--------------------------|
| AC Power Line Conducted Emissions           | $\pm 2.3\text{dB}$        | Confidence levels of 95% |
| Maximum Peak Conducted Output Power         | $\pm 0.8\text{dB}$        | Confidence levels of 95% |
| Power Spectral Density                      | $\pm 0.5\text{dB}$        | Confidence levels of 95% |
| 6dB Spectrum Bandwidth                      | $\pm 8.5 \times 10^{-8}$  | Confidence levels of 95% |
| Radiated Emissions (9kHz~30MHz)             | $\pm 0.8\text{dB}$        | Confidence levels of 95% |
| Radiated Emissions (30MHz~1000MHz)          | $\pm 1.9\text{dB}$        | Confidence levels of 95% |
| Radiated / Band Edge Emissions (1GHz~18GHz) | $\pm 1.9\text{dB}$        | Confidence levels of 95% |
| Radiated Emissions (18GHz~40GHz)            | $\pm 1.9\text{dB}$        | Confidence levels of 95% |
| Temperature                                 | $\pm 0.7^{\circ}\text{C}$ | Confidence levels of 95% |
| Humidity                                    | $\pm 3.2\%$               | Confidence levels of 95% |
| DC / AC Power Source                        | $\pm 1.4\%$               | Confidence levels of 95% |

### 3. GENERAL INFORMATION

#### 3.1. Product Details

| Items                    | Description   |
|--------------------------|---|
| Product Type             | WLAN (2TX, 3RX)   |
| Radio Type               | Intentional Transceiver                                       |
| Power Type               | From Adapter  |
| Modulation               | DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g                 |
| Data Modulation          | DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM) |
| Data Rate (Mbps)         | DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)            |
| Frequency Range          | 2400 ~ 2483.5MHz  |
| Channel Number           | 11  |
| Channel Band Width (99%) | 11b: 13.87 MHz ; 11g: 16.63 MHz                               |
| Conducted Output Power   | 11b: 28.76 dBm ; 11g: 29.91 dBm                               |
| Carrier Frequencies      | Please refer to section 3.4                                   |
| Antenna                  | Please refer to section 3.3                                   |

#### Antenna & Band width

| Antenna         | Single (TX) |        | Two (TX) |        |
|-----------------|-------------|--------|----------|--------|
| Band width Mode | 20 MHz      | 40 MHz | 20 MHz   | 40 MHz |
| 802.11b         | X           | X      | V        | X      |
| 802.11g         | X           | X      | V        | X      |

#### 3.2. Accessories

| Power     | Brand   | Model                | Rating  |
|-----------|---------|----------------------|---|
| Adapter 1 | NETGEAR | MU18-2120150-A1      | Input: 100-240V, 50/60Hz, 0.6A<br>Output: 12V, 1.5A |
| Adapter 2 | NETGEAR | DSA-20P-10 US 120180 | Input: 100-240V, 50/60Hz, 0.7A<br>Output: 12V, 1.5A |

Note: Due to Adapter 1 generated the worst test result, so it was recorded in this report.

### 3.3. Table for Filed Antenna


| Ant. | Brand | Model Name | Antenna Type    | Connector | Gain (dBi) | Remark       |
|------|-------|------------|-----------------|-----------|------------|--------------|
| A    | -     | -          | Printed Antenna | NA        | 2.62       | TX / RX Ant. |
| B    | -     | -          | Printed Antenna | N/A       | 2.62       | TX / RX Ant. |
| C    | -     | -          | Printed Antenna | N/A       | -          | RX Ant.      |

For 802.11b/g

The EUT has three antennas.

Antenna A, B can be used as transmitting antenna.

Antenna A, B, C is used as the receiving antenna.



### 3.4. Table for Carrier Frequencies

| Frequency Band | Channel No. | Frequency | Channel No. | Frequency |
|----------------|-------------|-----------|-------------|-----------|
| 2400~2483.5MHz | 1           | 2412 MHz  | 7           | 2442 MHz  |
|                | 2           | 2417 MHz  | 8           | 2447 MHz  |
|                | 3           | 2422 MHz  | 9           | 2452 MHz  |
|                | 4           | 2427 MHz  | 10          | 2457 MHz  |
|                | 5           | 2432 MHz  | 11          | 2462 MHz  |
|                | 6           | 2437 MHz  |             |           |

### 3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

| Test Items  | Mode        | Data Rate | Channel | Antenna |
|---|-------------|-----------|---------|---------|
| AC Power Line Conducted Emissions                 | Normal Link | Auto      | -       | A+B     |
| Maximum Peak Conducted Output Power               | 11b/BPSK    | 1 Mbps    | 1/6/11  | A+B     |
| Power Spectral Density                            | 11g/BPSK    | 6 Mbps    | 1/6/11  | A+B     |
| 6dB Spectrum Bandwidth                            |             |           |         |         |
| Radiated Emissions 9kHz~1GHz                      | Normal Link | Auto      | -       | A+B     |
| Radiated Emissions 1GHz~10 <sup>th</sup> Harmonic | 11b/BPSK    | 1 Mbps    | 1/6/11  | A+B     |
|   | 11g/BPSK    | 6 Mbps    | 1/6/11  | A+B     |
| Band Edge Emissions                               | 11b/BPSK    | 1 Mbps    | 1/11    | A+B     |
|   | 11g/BPSK    | 6 Mbps    | 1/11    | A+B     |

### 3.6. Table for Testing Locations

| Test Site No. | Site Category | Location | FCC Reg. No. | IC File No. | VCCI Reg. No |
|---------------|---------------|----------|--------------|-------------|--------------|
| 03CH03-HY     | SAC           | Hwa Ya   | 101377       | IC 4088     | -            |
| CO04-HY       | Conduction    | Hwa Ya   | 101377       | IC 4088     | -            |
| TH01-HY       | OVEN Room     | Hwa Ya   | -            | -           | -            |

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

### 3.7. Table for Supporting Units

| Support Unit | Brand | Model     | FCC ID    |
|--------------|-------|-----------|-----------|
| Notebook     | DELL  | D505      | E2K24GBRL |
| Notebook     | DELL  | D505      | E2K24GBRL |
| Notebook     | DELL  | D400      | E2K24GBRL |
| HUB          | CNET  | CSH-1600E | DoC       |



### 3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

#### Power Parameters of IEEE 802.11b/g

| Test Software Version | DOS      |          |          |
|-----------------------|----------|----------|----------|
| Frequency             | 2412 MHz | 2437 MHz | 2462 MHz |
| IEEE 802.11b          | 67/6a    | 67/6a    | 61/63    |
| IEEE 802.11g          | 65/68    | 67/6a    | 61/64    |

At the same time, the following programs were executed:


Executed "DOS" to control the EUT continuously transmit RF signal.

Executed "ping.exe" to link with the remote workstation to receive and transmit signal by WLAN.


### 3.9. Test Configurations

#### 3.9.1. Radiation Emissions Test Configuration


Test Configuration: 9KHz~1GHz



Test Configuration: Above 1GHz



### 3.9.2. AC Power Line Conduction Emissions Test Configuration



## 4. TEST RESULT

### 4.1. AC Power Line Conducted Emissions Measurement

#### 4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

| Frequency (MHz) | QP Limit (dBuV) | AV Limit (dBuV) |
|-----------------|-----------------|-----------------|
| 0.15~0.5        | 66~56           | 56~46           |
| 0.5~5           | 56              | 46              |
| 5~30            | 60              | 50              |

#### 4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 KHz    |

#### 4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in  $50\ \Omega$ . LISN can be placed on top of, or immediately beneath, reference ground plane.
  - (3.1) All other equipment powered from additional LISN(s).
  - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
  - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.



#### 4.1.5. Test Deviation


There is no deviation with the original standard.

#### 4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


#### 4.1.7. Results of AC Power Line Conducted Emissions Measurement

|               |               |          |      |
|---------------|---------------|----------|------|
| Temperature   | 23°C          | Humidity | 54%  |
| Test Engineer | Johnson Chang | Phase    | Line |
| Configuration | Normal Link   |          |      |



|    | Freq    | Level | Over   | Limit | Read  | LISN   | Cable |         |           |
|----|---------|-------|--------|-------|-------|--------|-------|---------|-----------|
|    | MHz     | dBuV  | Limit  | Line  | Level | Factor | Loss  | Remark  | Pol/Phase |
|    |         |       | dB     | dBuV  | dBuV  | dB     | dB    |         |           |
| 1  | 0.18838 | 54.55 | -9.56  | 64.11 | 54.20 | 0.15   | 0.20  | QP      | LINE      |
| 2  | 0.18838 | 43.70 | -10.41 | 54.11 | 43.35 | 0.15   | 0.20  | AVERAGE | LINE      |
| 3  | 0.25211 | 45.87 | -15.82 | 61.69 | 45.57 | 0.10   | 0.20  | QP      | LINE      |
| 4  | 0.25211 | 35.40 | -16.29 | 51.69 | 35.10 | 0.10   | 0.20  | AVERAGE | LINE      |
| 5  | 0.37512 | 43.23 | -15.16 | 58.39 | 42.93 | 0.10   | 0.20  | QP      | LINE      |
| 6  | 0.37512 | 40.83 | -7.56  | 48.39 | 40.53 | 0.10   | 0.20  | AVERAGE | LINE      |
| 7  | 2.251   | 33.64 | -22.36 | 56.00 | 33.44 | 0.00   | 0.20  | QP      | LINE      |
| 8  | 2.251   | 31.99 | -14.01 | 46.00 | 31.79 | 0.00   | 0.20  | AVERAGE | LINE      |
| 9  | 3.881   | 32.99 | -23.01 | 56.00 | 32.69 | 0.00   | 0.30  | QP      | LINE      |
| 10 | 3.881   | 28.27 | -17.73 | 46.00 | 27.97 | 0.00   | 0.30  | AVERAGE | LINE      |
| 11 | 18.256  | 34.83 | -25.17 | 60.00 | 34.23 | 0.10   | 0.50  | QP      | LINE      |
| 12 | 18.256  | 28.48 | -21.52 | 50.00 | 27.88 | 0.10   | 0.50  | AVERAGE | LINE      |

|               |               |          |         |
|---------------|---------------|----------|---------|
| Temperature   | 23°C          | Humidity | 54%     |
| Test Engineer | Johnson Chang | Phase    | Neutral |
| Configuration | Normal Link   |          |         |



|    | Freq    | Level | Over   | Limit | Read  | LISN   | Cable |         |           |
|----|---------|-------|--------|-------|-------|--------|-------|---------|-----------|
|    | MHz     | dBuV  | Limit  | Line  | Level | Factor | Loss  | Remark  | Pol/Phase |
|    |         |       | dB     | dBuV  | dBuV  | dB     | dB    |         |           |
| 1  | 0.18838 | 54.56 | -9.55  | 64.11 | 54.11 | 0.25   | 0.20  | QP      | NEUTRAL   |
| 2  | 0.18838 | 41.72 | -12.39 | 54.11 | 41.27 | 0.25   | 0.20  | AVERAGE | NEUTRAL   |
| 3  | 0.25078 | 45.79 | -15.94 | 61.73 | 45.41 | 0.18   | 0.20  | QP      | NEUTRAL   |
| 4  | 0.25078 | 33.43 | -18.30 | 51.73 | 33.05 | 0.18   | 0.20  | AVERAGE | NEUTRAL   |
| 5  | 0.37512 | 40.21 | -18.18 | 58.39 | 39.91 | 0.10   | 0.20  | QP      | NEUTRAL   |
| 6  | 0.37512 | 37.57 | -10.82 | 48.39 | 37.27 | 0.10   | 0.20  | AVERAGE | NEUTRAL   |
| 7  | 0.43742 | 35.66 | -21.45 | 57.11 | 35.36 | 0.10   | 0.20  | QP      | NEUTRAL   |
| 8  | 0.43742 | 32.18 | -14.93 | 47.11 | 31.88 | 0.10   | 0.20  | AVERAGE | NEUTRAL   |
| 9  | 3.565   | 35.30 | -20.70 | 56.00 | 34.90 | 0.10   | 0.30  | QP      | NEUTRAL   |
| 10 | 3.565   | 33.22 | -12.78 | 46.00 | 32.82 | 0.10   | 0.30  | AVERAGE | NEUTRAL   |
| 11 | 7.196   | 34.21 | -25.79 | 60.00 | 33.76 | 0.10   | 0.35  | QP      | NEUTRAL   |
| 12 | 7.196   | 30.47 | -19.53 | 50.00 | 30.02 | 0.10   | 0.35  | AVERAGE | NEUTRAL   |

Note:

Level = Read Level + LISN Factor + Cable Loss.

## 4.2. Maximum Peak Output Power Measurement

### 4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

| Spectrum Parameter | Setting  |
|--------------------|--|
| Attenuation        | Auto   |
| Span Frequency     | Encompass the entire emissions bandwidth (EBW) of the signal |
| RB                 | 1000 kHz   |
| VB                 | 3000 kHz   |
| Detector           | PEAK   |
| Trace              | MAX HOLD   |
| Sweep Time         | 20ms   |

### 4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Test was performed in accordance with FCC Conference Call, June 10, 2003.
3. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

### 4.2.4. Test Setup Layout



### 4.2.5. Test Deviation

There is no deviation with the original standard.

### 4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.2.7. Test Result of Maximum Peak Output Power

|               |         |                |           |
|---------------|---------|----------------|-----------|
| Temperature   | 23°C    | Humidity       | 54%       |
| Test Engineer | Beck Wu | Configurations | 802.11b/g |

##### Configuration IEEE 802.11b Ant. A

| Channel | Frequency | Conducted Power (dBm) | Max. Limit (dBm) | Result   |
|---------|-----------|-----------------------|------------------|----------|
| 1       | 2412 MHz  | 23.25                 | 30.00            | Complies |
| 6       | 2437 MHz  | 24.54                 | 30.00            | Complies |
| 11      | 2462 MHz  | 21.82                 | 30.00            | Complies |

##### Configuration IEEE 802.11b Ant. B

| Channel | Frequency | Conducted Power (dBm) | Max. Limit (dBm) | Result   |
|---------|-----------|-----------------------|------------------|----------|
| 1       | 2412 MHz  | 25.20                 | 30.00            | Complies |
| 6       | 2437 MHz  | 26.69                 | 30.00            | Complies |
| 11      | 2462 MHz  | 23.71                 | 30.00            | Complies |

##### Configuration IEEE 802.11b Ant. A + Ant. B

| Channel | Frequency | Conducted Power (dBm) | Max. Limit (dBm) | Result   |
|---------|-----------|-----------------------|------------------|----------|
| 1       | 2412 MHz  | 27.34                 | 30.00            | Complies |
| 6       | 2437 MHz  | 28.76                 | 30.00            | Complies |
| 11      | 2462 MHz  | 25.88                 | 30.00            | Complies |

**Configuration IEEE 802.11g Ant. A**

| Channel | Frequency | Conducted Power (dBm) | Max. Limit (dBm) | Result   |
|---------|-----------|-----------------------|------------------|----------|
| 1       | 2412 MHz  | 22.63                 | 30.00            | Complies |
| 6       | 2437 MHz  | 25.32                 | 30.00            | Complies |
| 11      | 2462 MHz  | 22.62                 | 30.00            | Complies |

**Configuration IEEE 802.11g Ant. B**

| Channel | Frequency | Conducted Power (dBm) | Max. Limit (dBm) | Result   |
|---------|-----------|-----------------------|------------------|----------|
| 1       | 2412 MHz  | 26.31                 | 30.00            | Complies |
| 6       | 2437 MHz  | 28.06                 | 30.00            | Complies |
| 11      | 2462 MHz  | 26.34                 | 30.00            | Complies |

**Configuration IEEE 802.11g Ant. A + Ant. B**

| Channel | Frequency | Conducted Power (dBm) | Max. Limit (dBm) | Result   |
|---------|-----------|-----------------------|------------------|----------|
| 1       | 2412 MHz  | 27.86                 | 30.00            | Complies |
| 6       | 2437 MHz  | 29.91                 | 30.00            | Complies |
| 11      | 2462 MHz  | 27.88                 | 30.00            | Complies |



### 4.3. Power Spectral Density Measurement

#### 4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

| Spectrum Parameter | Setting  |
|--------------------|----------|
| Attenuation        | Auto     |
| Span Frequency     | 1.5MHz   |
| RB                 | 3 kHz    |
| VB                 | 30 kHz   |
| Detector           | Peak     |
| Trace              | Max Hold |
| Sweep Time         | 500s     |

#### 4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

#### 4.3.4. Test Setup Layout



#### 4.3.5. Test Deviation

There is no deviation with the original standard.

#### 4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.3.7. Test Result of Power Spectral Density

|               |         |                |           |
|---------------|---------|----------------|-----------|
| Temperature   | 23°C    | Humidity       | 54%       |
| Test Engineer | Beck Wu | Configurations | 802.11b/g |


##### Configuration IEEE 802.11b Ant. A + Ant. B

| Channel | Frequency | Power Density (dBm) | Max. Limit (dBm) | Result   |
|---------|-----------|---------------------|------------------|----------|
| 1       | 2412 MHz  | -1.99               | 8.00             | Complies |
| 6       | 2437 MHz  | -2.12               | 8.00             | Complies |
| 11      | 2462 MHz  | -3.47               | 8.00             | Complies |

##### Configuration IEEE 802.11g Ant. A + Ant. B


| Channel | Frequency | Power Density (dBm) | Max. Limit (dBm) | Result   |
|---------|-----------|---------------------|------------------|----------|
| 1       | 2412 MHz  | -6.43               | 8.00             | Complies |
| 6       | 2437 MHz  | -4.66               | 8.00             | Complies |
| 11      | 2462 MHz  | -7.29               | 8.00             | Complies |

### Power Density Plot on Configuration IEEE 802.11b Ant. A + Ant. B / 2412 MHz




Date: 16.NOV.2007 13:14:55

### Power Density Plot on Configuration IEEE 802.11b Ant. A + Ant. B / 2437 MHz




Date: 24.DEC.2007 15:42:44

### Power Density Plot on Configuration IEEE 802.11b Ant. A + Ant. B / 2462 MHz




Date: 16.NOV.2007 13:17:37

### Power Density Plot on Configuration IEEE 802.11g Ant. A + Ant. B / 2412 MHz




Date: 16.NOV.2007 13:21:37

### Power Density Plot on Configuration IEEE 802.11g Ant. A + Ant. B / 2437 MHz



Date: 16.NOV.2007 13:20:29

### Power Density Plot on Configuration IEEE 802.11g Ant. A + Ant. B / 2462 MHz



Date: 16.NOV.2007 13:19:06



#### 4.4. 6dB Spectrum Bandwidth Measurement

##### 4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

##### 4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

| Spectrum Parameters | Setting         |
|---------------------|-----------------|
| Attenuation         | Auto            |
| Span Frequency      | > 6dB Bandwidth |
| RB                  | 100 kHz         |
| VB                  | 100 kHz         |
| Detector            | Peak            |
| Trace               | Max Hold        |
| Sweep Time          | Auto            |

##### 4.4.3. Test Procedures

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
- Measured the spectrum width with power higher than 6dB below carrier.

##### 4.4.4. Test Setup Layout



#### 4.4.5. Test Deviation

There is no deviation with the original standard.

#### 4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.4.7. Test Result of 6dB Spectrum Bandwidth

|               |         |                |           |
|---------------|---------|----------------|-----------|
| Temperature   | 23°C    | Humidity       | 54%       |
| Test Engineer | Beck Wu | Configurations | 802.11b/g |


##### Configuration IEEE 802.11b Ant. A+ Ant. B

| Channel | Frequency | 6dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Min. Limit (kHz) | Test Result |
|---------|-----------|---------------------|------------------------------|------------------|-------------|
| 1       | 2412 MHz  | 10.06               | 13.23                        | 500              | Complies    |
| 6       | 2437 MHz  | 10.06               | 13.87                        | 500              | Complies    |
| 11      | 2462 MHz  | 10.06               | 13.17                        | 500              | Complies    |

##### Configuration IEEE 802.11g Ant. A+ Ant. B


| Channel | Frequency | 6dB Bandwidth (MHz) | 99% Occupied Bandwidth (MHz) | Min. Limit (kHz) | Test Result |
|---------|-----------|---------------------|------------------------------|------------------|-------------|
| 1       | 2412 MHz  | 16.53               | 16.63                        | 500              | Complies    |
| 6       | 2437 MHz  | 15.06               | 15.92                        | 500              | Complies    |
| 11      | 2462 MHz  | 16.57               | 16.60                        | 500              | Complies    |

### 6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. A+ Ant. B / 2412 MHz




Date: 16.NOV.2007 13:14:29

### 6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. A+ Ant. B / 2437 MHz




Date: 16.NOV.2007 13:16:19

### 6 dB Bandwidth Plot on Configuration IEEE 802.11b Ant. A+ Ant. B / 2462 MHz




Date: 16.NOV.2007 13:17:21

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. A + Ant. B / 2412 MHz




Date: 16.NOV.2007 13:21:11

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. A + Ant. B / 2437 MHz



Date: 16.NOV.2007 13:20:13

### 6 dB Bandwidth Plot on Configuration IEEE 802.11g Ant. A + Ant. B / 2462 MHz



Date: 16.NOV.2007 13:18:50



## 4.5. Radiated Emissions Measurement

### 4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies<br>(MHz) | Field Strength<br>(micorvolts/meter) | Measurement Distance<br>(meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490          | 2400/F(KHz)                          | 300                              |
| 0.490~1.705          | 24000/F(KHz)                         | 30                               |
| 1.705~30.0           | 30                                   | 30                               |
| 30~88                | 100                                  | 3                                |
| 88~216               | 150                                  | 3                                |
| 216~960              | 200                                  | 3                                |
| Above 960            | 500                                  | 3                                |

### 4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter                        | Setting  |
|---|--|
| Attenuation                               | Auto   |
| Start Frequency                           | 1000 MHz                                       |
| Stop Frequency                            | 10th carrier harmonic                          |
| RB / VB (Emission in restricted band)     | 1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average |
| RB / VB (Emission in non-restricted band) | 100KHz / 100KHz for peak                       |


| Receiver Parameter     | Setting                          |
|------------------------|----------------------------------|
| Attenuation            | Auto                             |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP    |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP    |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |

#### 4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

#### 4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

#### 4.5.5. Test Deviation

There is no deviation with the original standard.

#### 4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.5.7. Results of Radiated Emissions (9kHz~30MHz)

|                      |            |                       |             |
|----------------------|------------|-----------------------|-------------|
| <b>Temperature</b>   | 23℃        | <b>Humidity</b>       | 54%         |
| <b>Test Engineer</b> | Barry Chen | <b>Configurations</b> | Normal Link |

| <b>Freq.<br/>(MHz)</b> | <b>Level<br/>(dBuV)</b> | <b>Over Limit<br/>(dB)</b> | <b>Limit Line<br/>(dBuV)</b> | <b>Remark</b> |
|------------------------|-------------------------|----------------------------|------------------------------|---------------|
| -                      | -                       | -                          | -                            | See Note      |

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

#### 4.5.8. Results of Radiated Emissions (30MHz~1GHz)


|               |            |                |             |
|---------------|------------|----------------|-------------|
| Temperature   | 23℃        | Humidity       | 54%         |
| Test Engineer | Barry Chen | Configurations | Normal Link |

##### Horizontal



|     | Freq    | Level  | Over Limit | Limit Line | ReadAntenna Level | Preamp Factor | Cable Loss | Remark    | Table Pos | Ant Pos | Pol/Phase  |
|-----|---------|--------|------------|------------|-------------------|---------------|------------|-----------|-----------|---------|------------|
|     | MHz     | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m          | dB         |           | deg       | cm      |            |
| 1   | 249.220 | 37.99  | -8.01      | 46.00      | 51.54             | 11.56         | 27.00      | 1.90 Peak | 0         | 100     | HORIZONTAL |
| 2   | 374.350 | 34.65  | -11.35     | 46.00      | 45.03             | 14.79         | 27.42      | 2.25 Peak | 0         | 100     | HORIZONTAL |
| 3 ! | 498.510 | 41.87  | -4.13      | 46.00      | 50.02             | 17.24         | 28.09      | 2.70 Peak | 0         | 100     | HORIZONTAL |
| 4   | 749.740 | 35.95  | -10.05     | 46.00      | 40.18             | 20.07         | 27.80      | 3.50 Peak | 0         | 100     | HORIZONTAL |
| 5   | 801.150 | 38.11  | -7.89      | 46.00      | 42.46             | 19.95         | 27.60      | 3.30 Peak | 0         | 100     | HORIZONTAL |
| 6   | 874.870 | 39.93  | -6.07      | 46.00      | 43.47             | 20.42         | 27.45      | 3.50 Peak | 0         | 100     | HORIZONTAL |

## Vertical



|   | Freq    | Level  | Over   | Limit  | Read  | Antenna | Preamp | Cable | Table | Ant |           |
|---|---------|--------|--------|--------|-------|---------|--------|-------|-------|-----|-----------|
|   | MHz     | dBuV/m | Limit  | Line   | Level | Factor  | Factor | Loss  | Pos   | Pos | Pol/Phase |
|   |         |        | dB     | dBuV/m | dBuV  | dB/m    | dB     | dB    | deg   | cm  |           |
| 1 | 62.500  | 37.96  | -2.04  | 40.00  | 60.00 | 4.85    | 27.75  | 0.86  | 360   | 200 | VERTICAL  |
| 2 | 164.830 | 34.60  | -8.90  | 43.50  | 51.50 | 8.85    | 27.27  | 1.52  | 0     | 400 | VERTICAL  |
| 3 | 198.780 | 31.64  | -11.86 | 43.50  | 48.15 | 8.90    | 27.11  | 1.70  | 0     | 400 | VERTICAL  |
| 4 | 249.220 | 38.64  | -7.36  | 46.00  | 52.19 | 11.56   | 27.00  | 1.90  | 0     | 400 | VERTICAL  |
| 5 | 498.510 | 39.33  | -6.67  | 46.00  | 47.48 | 17.24   | 28.09  | 2.70  | 0     | 400 | VERTICAL  |
| 6 | 625.580 | 38.23  | -7.77  | 46.00  | 44.20 | 19.05   | 28.07  | 3.05  | 0     | 400 | VERTICAL  |

### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

#### 4.5.9. Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)


|               |            |                |                              |
|---------------|------------|----------------|------------------------------|
| Temperature   | 23°C       | Humidity       | 54%                          |
| Test Engineer | Barry Chen | Configurations | 802.11b CH 1 Ant. A + Ant. B |

*Horizontal*



|   | Freq     | Level  | Over Limit | Limit Line | Remark  | Pol/Phase  | Distance | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor |
|---|----------|--------|------------|------------|---------|------------|----------|-------------------|----------------|------------|---------------|
|   | MHz      | dBuV/m | dB         | dBuV/m     |         |            | m        | dBuV              | dB/m           | dB         | dB            |
| 1 | 4823.870 | 57.14  | -16.86     | 74.00      | PEAK    | HORIZONTAL | 3        | 52.85             | 33.06          | 6.40       | 35.16         |
| 2 | 4823.970 | 53.42  | -0.58      | 54.00      | AVERAGE | HORIZONTAL | 3        | 49.14             | 33.06          | 6.40       | 35.16         |

# Vertical




|   | Freq     | Level  | Over Limit | Limit Line | Remark  | Pol/Phase | Distance | ReadAntenna Level | Antenna Factor | Cable Loss | Preamplifier |
|---|----------|--------|------------|------------|---------|-----------|----------|-------------------|----------------|------------|--------------|
|   | MHz      | dBuV/m | dB         | dBuV/m     |         |           | m        | dBuV              | dB/m           | dB         | dB           |
| 1 | 4823.770 | 52.30  | -21.70     | 74.00      | PEAK    | VERTICAL  | 3        | 48.01             | 33.06          | 6.40       | 35.16        |
| 2 | 4823.990 | 46.85  | -7.15      | 54.00      | AVERAGE | VERTICAL  | 3        | 42.56             | 33.06          | 6.40       | 35.16        |




|               |            |                |                              |
|---------------|------------|----------------|------------------------------|
| Temperature   | 23°C       | Humidity       | 54%                          |
| Test Engineer | Barry Chen | Configurations | 802.11b CH 6 Ant. A + Ant. B |

### Horizontal



|   | Freq     | Level  | Over   | Limit  | Remark  | Pol/Phase  | Distance | ReadAntenna |        | Cable Preamp |        |
|---|----------|--------|--------|--------|---------|------------|----------|-------------|--------|--------------|--------|
|   |          |        | Limit  | Line   |         |            |          | Level       | Factor | Loss         | Factor |
|   | MHz      | dBuV/m | dB     | dBuV/m |         |            | m        | dBuV        | dB/m   | dB           | dB     |
| 1 | 4873.970 | 53.80  | -0.20  | 54.00  | AVERAGE | HORIZONTAL | 3        | 49.38       | 33.16  | 6.42         | 35.15  |
| 2 | 4874.000 | 57.17  | -16.83 | 74.00  | PEAK    | HORIZONTAL | 3        | 52.74       | 33.16  | 6.42         | 35.15  |


**Vertical**



|   | Freq     | Level  | Over   | Limit  |         |           |          | ReadAntenna | Cable  | Preamp |
|---|----------|--------|--------|--------|---------|-----------|----------|-------------|--------|--------|
|   | MHz      | dBuV/m | Limit  | Line   | Remark  | Pol/Phase | Distance | Level       | Factor | Loss   |
|   | MHz      | dBuV/m | dB     | dBuV/m |         |           | m        | dBuV        | dB/m   | dB     |
| 1 | 4873.980 | 52.03  | -21.97 | 74.00  | PEAK    | VERTICAL  | 3        | 47.61       | 33.16  | 6.42   |
| 2 | 4873.990 | 46.29  | -7.71  | 54.00  | AVERAGE | VERTICAL  | 3        | 41.87       | 33.16  | 6.42   |


|               |            |                |                               |
|---------------|------------|----------------|-------------------------------|
| Temperature   | 23°C       | Humidity       | 54%                           |
| Test Engineer | Barry Chen | Configurations | 802.11b CH 11 Ant. A + Ant. B |

### Horizontal



|   | Freq     | Level  | Over Limit | Limit Line | Remark  | Pol/Phase  | Distance | Read Level | Antenna Factor | Cable Loss | Preamp Factor |
|---|----------|--------|------------|------------|---------|------------|----------|------------|----------------|------------|---------------|
|   | MHz      | dBuV/m | dB         | dBuV/m     |         |            | m        | dBuV       | dB/m           | dB         | dB            |
| 1 | 4923.940 | 56.96  | -17.04     | 74.00      | PEAK    | HORIZONTAL | 3        | 52.40      | 33.26          | 6.44       | 35.14         |
| 2 | 4923.990 | 52.43  | -1.57      | 54.00      | AVERAGE | HORIZONTAL | 3        | 47.88      | 33.26          | 6.44       | 35.14         |


# Vertical



|   | Freq     | Level  | Over   | Limit  |         |           |          | ReadAntenna | Cable  | Preamp |
|---|----------|--------|--------|--------|---------|-----------|----------|-------------|--------|--------|
|   | MHz      | dBuV/m | Limit  | Line   | Remark  | Pol/Phase | Distance | Level       | Factor | Loss   |
|   |          |        | dB     | dBuV/m |         |           | m        | dBuV        | dB/m   | dB     |
| 1 | 4923.970 | 49.62  | -4.38  | 54.00  | AVERAGE | VERTICAL  | 3        | 45.06       | 33.26  | 6.44   |
| 2 | 4924.000 | 54.35  | -19.65 | 74.00  | PEAK    | VERTICAL  | 3        | 49.79       | 33.26  | 6.44   |


|               |            |                |                              |
|---------------|------------|----------------|------------------------------|
| Temperature   | 23°C       | Humidity       | 54%                          |
| Test Engineer | Barry Chen | Configurations | 802.11g CH 1 Ant. A + Ant. B |

### Horizontal



|   | Freq     | Level  | Over Limit | Limit  | Line Remark | Pol/Phase  | Distance | ReadAntenna | Cable | Preamp     |
|---|----------|--------|------------|--------|-------------|------------|----------|-------------|-------|------------|
|   | MHz      | dBuV/m | dB         | dBuV/m |             |            | m        | Level       | Loss  | Factor     |
|   |          |        |            |        |             |            |          | dBuV        | dB/m  | dB         |
| 1 | 4821.120 | 57.87  | -16.13     | 74.00  | PEAK        | HORIZONTAL | 3        | 53.58       | 33.06 | 6.40 35.16 |
| 2 | 4821.400 | 45.36  | -8.64      | 54.00  | AVERAGE     | HORIZONTAL | 3        | 41.08       | 33.06 | 6.40 35.16 |


# Vertical



|   | Freq     | Level  | Over Limit | Limit Line | Remark  | Pol/Phase | Distance | ReadAntenna Level | Antenna Factor | Cable Loss | Preamplifier |
|---|----------|--------|------------|------------|---------|-----------|----------|-------------------|----------------|------------|--------------|
|   | MHz      | dBuV/m | dB         | dBuV/m     |         |           | m        | dBuV              | dB/m           | dB         | dB           |
| 1 | 4824.720 | 40.73  | -13.27     | 54.00      | AVERAGE | VERTICAL  | 3        | 36.44             | 33.06          | 6.40       | 35.16        |
| 2 | 4830.200 | 53.68  | -20.32     | 74.00      | PEAK    | VERTICAL  | 3        | 49.39             | 33.06          | 6.40       | 35.16        |


|               |            |                |                              |
|---------------|------------|----------------|------------------------------|
| Temperature   | 23°C       | Humidity       | 54%                          |
| Test Engineer | Barry Chen | Configurations | 802.11g CH 6 Ant. A + Ant. B |

### Horizontal



|   | Freq     | Level  | Over Limit | Limit  | Line    | Remark     | Pol/Phase | Distance | ReadAntenna | Cable Preamp |      |        |
|---|----------|--------|------------|--------|---------|------------|-----------|----------|-------------|--------------|------|--------|
|   | MHz      | dBuV/m | dB         | dBuV/m |         |            |           | m        | Level       | Factor       | Loss | Factor |
|   |          |        |            |        |         |            |           |          | dBuV        | dB/m         | dB   | dB     |
| 1 | 4872.360 | 43.80  | -10.20     | 54.00  | AVERAGE | HORIZONTAL |           | 3        | 39.37       | 33.16        | 6.42 | 35.15  |
| 2 | 4879.960 | 57.93  | -16.07     | 74.00  | PEAK    | HORIZONTAL |           | 3        | 53.51       | 33.16        | 6.42 | 35.15  |

# Vertical




|   | Freq     | Level  | Over Limit | Limit Line | Remark  | Pol/Phase | Distance | ReadAntenna | Cable Preamp |      |        |
|---|----------|--------|------------|------------|---------|-----------|----------|-------------|--------------|------|--------|
|   | MHz      | dBuV/m | dB         | dBuV/m     |         |           | m        | Level       | Factor       | Loss | Factor |
|   |          |        |            |            |         |           |          | dBuV        | dB/m         | dB   | dB     |
| 1 | 4874.960 | 41.00  | -13.00     | 54.00      | AVERAGE | VERTICAL  | 3        | 36.58       | 33.16        | 6.42 | 35.15  |
| 2 | 4879.880 | 57.35  | -16.65     | 74.00      | PEAK    | VERTICAL  | 3        | 52.93       | 33.16        | 6.42 | 35.15  |




|               |            |                |                               |
|---------------|------------|----------------|-------------------------------|
| Temperature   | 23°C       | Humidity       | 54%                           |
| Test Engineer | Barry Chen | Configurations | 802.11g CH 11 Ant. A + Ant. B |

### Horizontal



|   | Freq     | Level  | Over Limit | Limit Line | Remark  | Pol/Phase  | Distance | ReadAntenna Level Factor | Cable Loss | Preamp Factor |
|---|----------|--------|------------|------------|---------|------------|----------|--------------------------|------------|---------------|
|   | MHz      | dBuV/m | dB         | dBuV/m     |         |            | m        | dBuV                     | dB/m       | dB            |
| 1 | 4922.040 | 58.34  | -15.66     | 74.00      | PEAK    | HORIZONTAL | 3        | 53.78                    | 33.26      | 6.44          |
| 2 | 4922.240 | 44.10  | -9.90      | 54.00      | AVERAGE | HORIZONTAL | 3        | 39.54                    | 33.26      | 6.44          |

### Vertical



|   | Freq     | Level  | Over   | Limit  | Remark  | Pol/Phase | Distance | ReadAntenna |        | Cable Preamp |        |
|---|----------|--------|--------|--------|---------|-----------|----------|-------------|--------|--------------|--------|
|   |          |        | Limit  | Line   |         |           |          | Level       | Factor | Loss         | Factor |
|   | MHz      | dBuV/m | dB     | dBuV/m |         |           | m        | dBuV        | dB/m   | dB           | dB     |
| 1 | 4924.800 | 41.62  | -12.38 | 54.00  | AVERAGE | VERTICAL  | 3        | 37.06       | 33.26  | 6.44         | 35.14  |
| 2 | 4929.880 | 56.11  | -17.89 | 74.00  | PEAK    | VERTICAL  | 3        | 51.55       | 33.26  | 6.44         | 35.14  |

### Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

## 4.6. Band Edge Emissions Measurement

### 4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies<br>(MHz) | Field Strength<br>(micorvolts/meter) | Measurement Distance<br>(meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490          | 2400/F(KHz)                          | 300                              |
| 0.490~1.705          | 24000/F(KHz)                         | 30                               |
| 1.705~30.0           | 30                                   | 30                               |
| 30~88                | 100                                  | 3                                |
| 88~216               | 150                                  | 3                                |
| 216~960              | 200                                  | 3                                |
| Above 960            | 500                                  | 3                                |

### 4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

| Spectrum Parameter                        | Setting   |
|---|---|
| Attenuation                               | Auto  |
| Span Frequency                            | 100 MHz   |
| RB / VB (Emission in restricted band)     | 1 MHz / 1MHz for Peak, 1 MHz / 10Hz for Average |
| RB / VB (Emission in non-restricted band) | 100 KHz /100 KHz for Peak                       |

### 4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

### 4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

### 4.6.5. Test Deviation

There is no deviation with the original standard.

### 4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

#### 4.6.7. Test Result of Band Edge and Fundamental Emissions

|               |            |                |                                     |
|---------------|------------|----------------|-------------------------------------|
| Temperature   | 23°C       | Humidity       | 54%                                 |
| Test Engineer | Barry Chen | Configurations | 802.11b CH 1, 6, 11 Ant. A + Ant. B |

##### Channel 1

|     | Freq     | Level  | Over Limit | Limit Line | Remark  | Pol/Phase | Distance | ReadAntenna Level | Antenna Factor | Cable Loss | Preamplifier |
|-----|----------|--------|------------|------------|---------|-----------|----------|-------------------|----------------|------------|--------------|
|     | MHz      | dBuV/m | dB         | dBuV/m     |         |           | m        | dBuV              | dB/m           | dB         | dB           |
| 1 ! | 2390.000 | 53.41  | -0.59      | 54.00      | AVERAGE | VERTICAL  | 3        | 21.08             | 28.17          | 4.15       | 0.00         |
| 2   | 2390.000 | 63.12  | -10.88     | 74.00      | PEAK    | VERTICAL  | 3        | 30.79             | 28.17          | 4.15       | 0.00         |
| 3 @ | 2411.200 | 110.90 |            |            | AVERAGE | VERTICAL  | 3        | 78.53             | 28.21          | 4.15       | 0.00         |
| 4   | 2413.200 | 114.77 |            |            | PEAK    | VERTICAL  | 3        | 82.40             | 28.21          | 4.15       | 0.00         |

Item 3, 4 are the fundamental frequency at 2412 MHz.

##### Channel 6

|     | Freq     | Level  | Over Limit | Limit Line | Remark  | Pol/Phase | Distance | ReadAntenna Level | Antenna Factor | Cable Loss | Preamplifier |
|-----|----------|--------|------------|------------|---------|-----------|----------|-------------------|----------------|------------|--------------|
|     | MHz      | dBuV/m | dB         | dBuV/m     |         |           | m        | dBuV              | dB/m           | dB         | dB           |
| 1   | 2435.600 | 118.87 |            |            | PEAK    | VERTICAL  | 3        | 86.44             | 28.25          | 4.18       | 0.00         |
| 2 @ | 2436.200 | 113.71 |            |            | AVERAGE | VERTICAL  | 3        | 81.29             | 28.25          | 4.18       | 0.00         |

Item 1, 2 are the fundamental frequency at 2437MHz.

##### Channel 11

|     | Freq     | Level  | Over Limit | Limit Line | Remark  | Pol/Phase | Distance | ReadAntenna Level | Antenna Factor | Cable Loss | Preamplifier |
|-----|----------|--------|------------|------------|---------|-----------|----------|-------------------|----------------|------------|--------------|
|     | MHz      | dBuV/m | dB         | dBuV/m     |         |           | m        | dBuV              | dB/m           | dB         | dB           |
| 1 @ | 2462.800 | 112.25 |            |            | AVERAGE | VERTICAL  | 3        | 79.73             | 28.32          | 4.20       | 0.00         |
| 2   | 2463.200 | 116.11 |            |            | PEAK    | VERTICAL  | 3        | 83.59             | 28.32          | 4.20       | 0.00         |
| 3   | 2483.500 | 62.63  | -11.37     | 74.00      | PEAK    | VERTICAL  | 3        | 30.04             | 28.36          | 4.23       | 0.00         |
| 4 ! | 2483.500 | 53.30  | -0.70      | 54.00      | AVERAGE | VERTICAL  | 3        | 20.71             | 28.36          | 4.23       | 0.00         |

Item 1, 2 are the fundamental frequency at 2462 MHz.

|               |            |                |                                     |
|---------------|------------|----------------|-------------------------------------|
| Temperature   | 23°C       | Humidity       | 54%                                 |
| Test Engineer | Barry Chen | Configurations | 802.11g CH 1, 6, 11 Ant. A + Ant. B |

#### Channel 1

|     | Freq     | Level  | Over Limit | Limit Line | Remark  | Pol/Phase | Distance | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor |
|-----|----------|--------|------------|------------|---------|-----------|----------|-------------------|----------------|------------|---------------|
|     | MHz      | dBuV/m | dB         | dBuV/m     |         |           | m        | dBuV              | dB/m           | dB         | dB            |
| 1 ! | 2390.000 | 72.70  | -1.30      | 74.00      | PEAK    | VERTICAL  | 3        | 40.37             | 28.17          | 4.15       | 0.00          |
| 2 ! | 2390.000 | 53.42  | -0.58      | 54.00      | AVERAGE | VERTICAL  | 3        | 21.09             | 28.17          | 4.15       | 0.00          |
| 3   | 2410.000 | 104.85 |            |            | AVERAGE | VERTICAL  | 3        | 72.49             | 28.21          | 4.15       | 0.00          |
| 4   | 2410.000 | 114.56 |            |            | PEAK    | VERTICAL  | 3        | 82.19             | 28.21          | 4.15       | 0.00          |

Item 3, 4 are the fundamental frequency at 2412 MHz.

#### Channel 6

|   | Freq     | Level  | Over Limit | Limit Line | Remark  | Pol/Phase | Distance | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor |
|---|----------|--------|------------|------------|---------|-----------|----------|-------------------|----------------|------------|---------------|
|   | MHz      | dBuV/m | dB         | dBuV/m     |         |           | m        | dBuV              | dB/m           | dB         | dB            |
| 1 | 2444.000 | 108.47 |            |            | AVERAGE | VERTICAL  | 3        | 75.98             | 28.29          | 4.20       | 0.00          |
| 2 | 2444.400 | 117.50 |            |            | PEAK    | VERTICAL  | 3        | 85.01             | 28.29          | 4.20       | 0.00          |

Item 1, 2 are the fundamental frequency at 2437 MHz.

#### Channel 11

|     | Freq     | Level  | Over Limit | Limit Line | Remark  | Pol/Phase | Distance | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor |
|-----|----------|--------|------------|------------|---------|-----------|----------|-------------------|----------------|------------|---------------|
|     | MHz      | dBuV/m | dB         | dBuV/m     |         |           | m        | dBuV              | dB/m           | dB         | dB            |
| 1 @ | 2463.000 | 106.58 |            |            | AVERAGE | VERTICAL  | 3        | 74.06             | 28.32          | 4.20       | 0.00          |
| 2   | 2463.000 | 115.97 |            |            | PEAK    | VERTICAL  | 3        | 83.44             | 28.32          | 4.20       | 0.00          |
| 3 ! | 2483.500 | 71.46  | -2.54      | 74.00      | PEAK    | VERTICAL  | 3        | 38.87             | 28.36          | 4.23       | 0.00          |
| 4 ! | 2483.500 | 53.54  | -0.46      | 54.00      | AVERAGE | VERTICAL  | 3        | 20.95             | 28.36          | 4.23       | 0.00          |

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


# For Emission not in Restricted Band

## Low Band Edge Plot on Configuration IEEE 802.11b Ant. A + Ant. B / 2412 MHz




Date: 16.NOV.2007 13:15:03

## High Band Edge Plot on Configuration IEEE 802.11b Ant. A + Ant. B / 2462 MHz




Date: 16.NOV.2007 13:17:46

### Low Band Edge Plot on Configuration IEEE 802.11g Ant. A + Ant. B / 2412 MHz



Date: 16.NOV.2007 13:21:46

### High Band Edge Plot on Configuration IEEE 802.11g Ant. A + Ant. B / 2462 MHz



Date: 16.NOV.2007 13:19:14

## 4.7. Antenna Requirements

### 4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

### 4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.



## 5. LIST OF MEASURING EQUIPMENTS

| Instrument               | Manufacturer      | Model No.      | Serial No.  | Characteristics      | Calibration Date | Remark                |
|--------------------------|-------------------|----------------|-------------|----------------------|------------------|-----------------------|
| EMC Receiver             | R&S               | ESCS 30        | 100359      | 9kHz – 2.75GHz       | Mar. 01, 2007    | Conduction (CO04-HY)  |
| LISN                     | MessTec           | NNB-2/16Z      | 99079       | 9kHz – 30MHz         | Mar. 31, 2007    | Conduction (CO04-HY)  |
| LISN (Support Unit)      | EMCO              | 3810/2NM       | 9703-1839   | 9kHz – 30MHz         | Mar. 22, 2007    | Conduction (CO04-HY)  |
| RF Cable-CON             | UTIFLEX           | 3102-26886-4   | CB049       | 9kHz – 30MHz         | Apr. 20, 2007    | Conduction (CO04-HY)  |
| ISN                      | SCHAFFNER         | ISN T400       | 21653       | 9kHz – 30MHz         | May 09, 2007     | Conduction (CO04-HY)  |
| EMI Filter               | LINDGREN          | LRE-2030       | 2651        | < 450 Hz             | N/A              | Conduction (CO04-HY)  |
| Isolation Transformer    | Erika Fiedler OHG | D-65396 Walluf | 58          | 45MHz-2.15GHz        | N/A              | Conduction (CO04-HY)  |
| 3m Semi Anechoic Chamber | SIDT FRANKONIA    | SAC-3M         | 03CH03-HY   | 30 MHz - 1 GHz<br>3m | Jun. 14, 2007    | Radiation (03CH03-HY) |
| Amplifier                | SCHAFFNER         | CPA9231A       | 1886        | 9 kHz - 2 GHz        | Jan. 22, 2007    | Radiation (03CH03-HY) |
| Amplifier                | Agilent           | 8449B          | 3008A02120  | 1 GHz - 26.5 GHz     | Jun. 07, 2007    | Radiation (03CH03-HY) |
| Amplifier                | MITEQ             | AMF-6F-260400  | 923364      | 26.5 GHz - 40 GHz    | Jan. 22, 2007*   | Radiation (03CH03-HY) |
| Spectrum Analyzer        | R&S               | FSP40          | 100305      | 9 kHz - 40 GHz       | Sep. 27, 2007    | Radiation (03CH03-HY) |
| Loop Antenna             | R&S               | HFH2-Z2        | 860004/001  | 9 kHz - 30 MHz       | May 23, 2006*    | Radiation (03CH03-HY) |
| Bilog Antenna            | SCHAFFNER         | CBL 6112D      | 22237       | 30 MHz – 1 GHz       | Jul. 21, 2007    | Radiation (03CH03-HY) |
| Horn Antenna             | EMCO              | 3115           | 6741        | 1GHz ~ 18GHz         | May 04, 2007     | Radiation (03CH03-HY) |
| Horn Antenna             | SCHWARZBECK       | BBHA9170       | BBHA9170154 | 15 GHz - 40 GHz      | NCR              | Radiation (03CH03-HY) |
| RF Cable-R03m            | Jye Bao           | RG142          | CB021       | 30 MHz - 1 GHz       | Dec. 03, 2007    | Radiation (03CH03-HY) |
| RF Cable-HIGH            | SUHNER            | SUCOFLEX 106   | 03CH03-HY   | 1 GHz - 40 GHz       | Dec. 03, 2007    | Radiation (03CH03-HY) |
| Turn Table               | HD                | DS 420         | 420/650/00  | 0 – 360 degree       | N/A              | Radiation (03CH03-HY) |
| Antenna Mast             | HD                | MA 240         | 240/560/00  | 1 m - 4 m            | N/A              | Radiation (03CH03-HY) |
| Spectrum Analyzer        | R&S               | FSP30          | 100023      | 9kHz ~ 30GHz         | Dec. 17, 2007    | Conducted (TH01-HY)   |
| Power Meter              | R&S               | NRVS           | 100444      | DC ~ 40GHz           | Jun. 27, 2007    | Conducted (TH01-HY)   |
| Power Sensor             | R&S               | NRV-Z51        | 100458      | DC ~ 30GHz           | Jun. 27, 2007    | Conducted (TH01-HY)   |
| Power Sensor             | R&S               | NRV-Z32        | 100057      | 30MHz ~ 6GHz         | Jun. 27, 2007    | Conducted (TH01-HY)   |
| AC Power Source          | HPC               | HPA-500W       | HPA-9100024 | AC 0 ~ 300V          | May 04, 2007*    | Conducted (TH01-HY)   |
| DC Power Source          | G.W.              | GPC-6030D      | C671845     | DC 1V ~ 60V          | Mar. 03, 2007    | Conducted (TH01-HY)   |

| Instrument                 | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Remark              |
|----------------------------|--------------|-----------|------------|-----------------|------------------|---------------------|
| Temp. and Humidity Chamber | KSON         | THS-C3L   | 612        | N/A             | Oct. 01, 2007    | Conducted (TH01-HY) |
| RF CABLE-1m                | Jye Bao      | RG142     | CB034-1m   | 20MHz ~ 7GHz    | Dec. 01, 2007    | Conducted (TH01-HY) |
| RF CABLE-2m                | Jye Bao      | RG142     | CB035-2m   | 20MHz ~ 1GHz    | Dec. 01, 2007    | Conducted (TH01-HY) |
| Signal Generator           | R&S          | SMR40     | 100116     | 10MHz ~ 40GHz   | Mar. 07, 2007    | Conducted (TH01-HY) |

Note: Calibration Interval of instruments listed above is one year.

\* Calibration Interval of instruments listed above is two year.

NCR means Non-Calibration required.

## 6. TEST LOCATION

|        |  |
|--------|--|
| SHIJR  | ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C.<br>TEL : 886-2-2696-2468<br>FAX : 886-2-2696-2255 |
| HWA YA | ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.<br>TEL : 886-3-327-3456<br>FAX : 886-3-318-0055         |
| LINKOU | ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C<br>TEL : 886-2-2601-1640<br>FAX : 886-2-2601-1695               |
| DUNGHU | ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C.<br>TEL : 886-2-2631-4739<br>FAX : 886-2-2631-9740            |
| JUNGHE | ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C.<br>TEL : 886-2-8227-2020<br>FAX : 886-2-8227-2626           |
| NEIHU  | ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C.<br>TEL : 886-2-2794-8886<br>FAX : 886-2-2794-9777         |
| JHUBEI | ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C.<br>TEL : 886-3-656-9065<br>FAX : 886-3-656-9085       |

## 7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : LI190-070110

財團法人全國認證基金會  
Taiwan Accreditation Foundation

### Certificate of Accreditation

This is to certify that

**Sporton International Inc.**

**EMC & Wireless Communications Laboratory**

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

is accredited in respect of laboratory

|                                |  |
|--------------------------------|--|
| Accreditation Criteria         | : ISO/IEC 17025:2005   |
| Accreditation Number           | : 1190   |
| Originally Accredited          | : December 15, 2003  |
| Effective Period               | : January 10, 2007 to January 09, 2010   |
| Accredited Scope               | : Testing Field, see described in the Appendix   |
| Specific Accreditation Program | : Accreditation Program for Designated Testing Laboratory<br>for Commodities Inspection<br>Accreditation Program for Telecommunication Equipment<br>Testing Laboratory |



Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : January 10, 2007

PI, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.