



FCC TEST REPORT

According to

FCC Rules and Regulations Part 15 Subpart C

Applicant	:	Netgear Inc.
Address	:	350 East Plumeria Drive, San Jose, CA 95134, U.S.A.
Equipment	:	Wireless-N 150 ADSL2+ Modem Router
Model No.	:	DGN1000, DGN1000B, DGN1000SP, DGN1000SB
FCC ID	:	PY309300114
Trade Name	:	NETGEAR

Laboratory Accreditation



- The test result refers exclusively to the test presented test model / sample.,
- Without written approval of **Cerpass Technology Corp.** the test report shall not be reproduced except in full.
- The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.



Contents

1. Report of Measurements and Examinations	4
1.1 List of Measurements and Examinations	5
2. Test Configuration of Equipment under Test	6
2.1 Feature of Equipment under Test.....	6
2.2 Carrier Frequency of Channels.....	7
2.3 Test Mode and Test Software.....	7
2.4 Description of Test System.....	8
2.5 Connection Diagram of Test System.....	9
2.6 General Information of Test.....	10
2.7 Measurement Uncertainty	10
2.8 History of this test report	11
3. Antenna Requirements.....	12
3.1 Standard Applicable	12
3.2 Antenna Construction and Directional Gain.....	12
4. Test of Conducted Emission.....	13
4.1 Test Limit	13
4.2 Test Procedures	13
4.3 Typical Test Setup	14
4.4 Measurement Equipment.....	14
4.5 Test Result and Data.....	15
4.6 Test Photographs	21
5. Test of Radiated Emission	22
5.1 Test Limit	22
5.2 Test Procedures	22
5.3 Typical Test Setup	23
5.4 Measurement Equipment.....	23
5.5 Test Result and Data.....	24
5.6 Test Photographs	60
6. 6dB Bandwidth Measurement Data.....	61
6.1 Test Limit	61
6.2 Test Procedures	61
6.3 Test Setup Layout	61
6.4 Measurement Equipment.....	61
6.5 Test Result and Data.....	61
7. Maximum Peak Output Power	68
7.1 Test Limit	68
7.2 Test Procedures	68
7.3 Test Setup Layout	68
7.4 Measurement Equipment.....	68
7.5 Test Result and Data.....	68
8. Band Edges Measurement	75
8.1 Test Limit	75
8.2 Test Procedure	75



8.3	Test Setup Layout	75
8.4	Measurement Equipment.....	75
8.5	Test Result and Data.....	75
8.6	Restrict Band Emission Measurement Data	84
9.	Power Spectral Density	88
9.1	Test Limit	88
9.2	Test Procedures	88
9.3	Test Setup Layout	88
9.4	Measurement Equipment.....	88
9.5	Test Result and Data.....	88
10.	Restricted Bands of Operation	95
10.1	Labeling Requirement.....	95
Appendix A. Photographs of EUT.....		A1 ~ A10



CERTIFICATE OF COMPLIANCE

According to

FCC Rules and Regulations Part 15 Subpart C


Applicant	: Netgear Inc.
Address	: 350 East Plumeria Drive, San Jose, CA 95134, U.S.A.
Equipment	: Wireless-N 150 ADSL2+ Modem Router
Model No.	: DGN1000, DGN1000B, DGN1000SP, DGN1000SB
FCC ID	: PY309300114

I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4**. The equipment was **passed** the test performed according to **FCC Rules and Regulations Part 15 Subpart C (2007)**.

The test was carried out on Aug. 31, 2009 at **Cerpass Technology Corp.**

Signature



Jonson Lee
EMC/RF B.U. Senior Manager



1. Report of Measurements and Examinations

1.1 List of Measurements and Examinations

FCC Rule	Description of Test	Result
15.203	. Antenna Requirement	Pass
15.207	. Conducted Emission	Pass
15.209 15.247(d)	. Radiated Emission	Pass
15.247(a)(2)	. 6dB Bandwidth	Pass
15.247(b)	. Maximum Peak Output Power	Pass
15.247(d)	. 100kHz Bandwidth of Frequency Band Edges	Pass
15.247(e)	. Power Spectral Density	Pass
1.1307 1.1310 2.1091 2.1093	. RF Exposure Compliance	Pass



2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Spreading	: 802.11b: DSSS, CCK(QPSK, BPSK) 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)
Frequency Range	: 802.11b/g/n: 2.4~2.4835GHz
Number of Channels	: USA, Canada, and Taiwan: 1~11 Japan: 1~14 Most European Countries: 1~13 France: 10~13
Data Rate	: 802.11b: 11, 5.5, 2, 1Mbps 802.11g: 54, 48, 36, 24, 18, 12, 9, 6 Mbps 802.11n: HT40 mode: 270/15, 243/14, 216/13, 162/12, 108/11, 81/10, 54/9, 27/8, 135/7, 121.5/6, 108/5, 81/4, 54/3, 40.5/2, 27/1, 13.5/0Mbps HT20 mode: 130/15, 117/14, 104/13, 78/12, 52/11, 39/10, 26/9, 13/8, 65/7, 58.5/6, 52/5, 39/4, 26/3, 19.5/2, 13/1, 6.5/0Mbps
Modulation	: 802.11n: OFDM 802.11g: OFDM 802.11b: CCK, DQPSK, DBPSK
Antenna	: 1/2λ Dipole Antenna/ Gain: 2dBi
Security	: IEEE802.1x and WPA (available in the future) WEP 64 bit, 128 bit
Transmit Power	: FCC: 802.11b: 17~18dBm(Average) 802.11g: 54M = 13dBm(Average) 36M~48M = 14~16dBm(Average) 6M~24M=17dBm~18dBm(Average) 802.11n: HT40 mode: 13.5M, 27M, 40.5M, 54M, 27M, 81M, 180M = 15~17dBm(Average) 81M, 180M, 121.5M, 135M, 162M, 216M, 243M, 270M =12~14dBm(Average) HT20 mode: 6.5M, 13M, 19.5M, 26M, 39M, 52M = 15~17dBm(Average) 39M, 52M, 58.5M, 65M, 78M, 104M, 117M =13~15dBm(Average) ETSI: 802.11b: 18~19dBm(Average) 802.11g: 48M~54M=13dBm~15dBm(Average) 6M~36M=16dBm~18dBm(Average) 802.11n: HT40 mode: 13.5M, 27M, 40.5M, 54M, 27M, 81M, 180M = 15~17dBm(Average) 81M, 180M, 121.5M, 135M, 162M, 216M, 243M, 270M =12~14dBm(Average) HT20 mode: 6.5M, 13M, 19.5M, 26M, 39M, 52M = 15~17dBm(Average) 39M, 52M, 58.5M, 65M, 78M, 104M, 117M =13~15dBm(Average)



2.2 Carrier Frequency of Channels

802.11b, 802.11g, 802.11n, HT20

Channel	Frequency(MHz)	Channel	Frequency(MHz)
01	2412	07	2442
02	2417	08	2447
03	2422	09	2452
04	2427	10	2457
05	2432	11	2462
06	2437	12	---

802.11n, HT40

Channel	Frequency(MHz)	Channel	Frequency(MHz)
01	---	07	2442
02	---	08	2447
03	2422	09	2452
04	2427	10	---
05	2432	11	---
06	2437	---	---

2.3 Test Mode and Test Software

- a. During testing, the interface cables and equipment positions were varied according to ANSI C63.4.
- b. The complete test system included remote workstation, PC, Monitor, Mouse, Keyboard, Modem, Printer, Flash Memory and EUT for RF test. The remote workstation included Notebook and DSLAN.
- c. An executive program, "Ping.exe" under WIN XP, which transmits and receives data to the remote workstation through LAN (100M) and Wireless (13.5M).
- d. The following test mode and test software was performed for conduction and radiation test:

Test Mode 1: Adapter: T012LF1209 16100-2LF

- 802.11b/g, 802.11n, HT20: CH01: 2412MHz, CH06: 2437MHz, CH11: 2462MHz
- 802.11n, HT40: CH03: 2422MHz, CH06: 2437MHz, CH09: 2452MHz

Test Mode 2: Adapter: FA-1201000SUC

- 802.11b/g, 802.11n, HT20: CH01: 2412MHz, CH06: 2437MHz, CH11: 2462MHz
- 802.11n, HT40: CH03: 2422MHz, CH06: 2437MHz, CH09: 2452MHz

The test mode 2 was the worst case; it was reported as final data.



2.4 Description of Test System


Device	Manufacturer	Model No.	Description
PC	IBM	IGV	Power Cable, Unshielding 1.8 m
Monitor	ViewSonic	G90fB	Power Cable, Adapter Unshielding 1.8 m Data Cable, VGA Shielding 1.35 m
Keyboard	IBM	KB-0225	Data Cable, PS2 Shielding 1.85 m
Mouse	IBM	MU29J	Data Cable, PS2 Shielding 1.85 m
Modem	ACEXX	DM-1414	Power Cable, Adapter Unshielding 1.8 m Data Cable, RS232 Shielding 1.35 m
Printer	HP	Desk Jet 400	Power Cable, Adapter Unshielding 1.8 m Data Cable, Print Shielding 1.6 m
Flash Memory	TranScend	JF150 1GB	N/A
Remote workstation			
Notebook	DELL	PP10L	Power Cable, Adapter Unshielding 1.8 m
Notebook	TOSHIBA	PSA50T-05M 00C	Power Cable, Adapter Unshielding 1.8 m
DSL AN	2YXZL	IES-1000	Power Cable, Unshielding 1.8 m

Use Cable:

Cable	Quantity	Description
RJ45	3	Unshielding, 3.0m
RJ45	1	Unshielding, 10m
RJ11	1	Unshielding, 10m



2.5 Connection Diagram of Test System



1. The VGA cable is connected from PC to Monitor.
 2. The PS2 cable is connected from PC to the Mouse.
 3. The PS2 cable is connected from PC to the Keyboard.
 4. The RJ45 cable is connected from PC to the EUT.
 5. The Flash Memory is connected to the EUT.
 6. These RJ45 cables (*3) are floating.
 7. The RJ11 Cable is connected from EUT to the Remote workstation.
 8. The RS232 cable is connected from PC to the Modem.
 9. The Print cable is connected from PC to the Printer.
- * The EUT keeps to transmit and receive data to remote workstation by Wireless.



2.6 General Information of Test

Test Site :	Cerpass Technology Corp. 2F-11, No. 3, Yuan Qu St., (Nankang Software Park), Taipei, Taiwan 115, R.O.C.
Test Site Location (OATS1-SD):	No. 7-2, Moshihkeng, Fongtian Village, Shihding Township, Taipei County, Taiwan, R.O.C.
FCC Registration Number :	TW1049, 982971, 488071
IC Registration Number :	4934C-1, 4934D-1
VCCI Registration Number :	T-543 for Telecommunication Test C-3328 for Conducted emission test R-3013 for Radiated emission test
Test Voltage:	AC 120V / 60Hz
Test in Compliance with:	ANSI C63.4-2003 FCC Part 15 Subpart C
Frequency Range Investigated:	Conducted: from 150kHz to 30MHz Radiation: from 30MHz to 24620MHz
Test Distance:	The test distance of radiated emission from antenna to EUT is 3 M.

2.7 Measurement Uncertainty

Measurement Item	Measurement Frequency	Polarization	Uncertainty
Conducted Emission	9 kHz ~ 30 MHz	LINE/NEUTRAL	2.71 dB
Radiated Emission	30 MHz ~ 25GHz	Vertical	4.11 dB
		Horizontal	4.10 dB
6 dB Bandwidth	---	---	7500 Hz
Maximum Peak Output Power	---	---	1.4 dB
100kHz Bandwidth of Frequency Band Edges	---	---	2.2 dB
Power Spectral Density	---	---	2.2 dB



2.8 History of this test report

ORIGINAL.

Additional attachment as following record:

Attachment No.	Issue Date	Description



3. Antenna Requirements

3.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

3.2 Antenna Construction and Directional Gain

Antenna type: Dipole Antenna

Antenna Gain: 2 dBi



4. Test of Conducted Emission

4.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz on the 120 VAC power and return leads of the EUT according to the methods defined in ANSI C63.4-2003 Section 3.1. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 2.2. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50


*Decreases with the logarithm of the frequency.

4.2 Test Procedures

- a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- c. All the support units are connecting to the other LISN.
- d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- e. The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- f. Both sides of AC line were checked for maximum conducted interference.
- g. The frequency range from 150 kHz to 30 MHz was searched.
- h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.



4.3 Typical Test Setup




4.4 Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
EMI Receiver	R&S	ESCI	100443	2008/09/27	2009/09/26
LISN	NSLK 8127	Schwarzbeck	8127-516	2009/05/15	2010/05/14
LISN	Rolf Heine	NNB-2/16Z	03/10058	2009/04/18	2010/04/17



4.5 Test Result and Data

Power	: AC 120V	Pol/Phase	: LINE
Test Mode 2	: 802.11g CH1	Temperature	: 24 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 62 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	
1	0.18	38.27	0.07	38.34	54.59	-16.25	Average
2	0.18	52.16	0.07	52.23	64.59	-12.36	QP
3	0.24	38.33	0.07	38.40	52.17	-13.77	Average
4	0.24	43.89	0.07	43.96	62.17	-18.21	QP
5	0.47	42.07	0.08	42.15	46.58	-4.43	Average
6	0.47	44.58	0.08	44.66	56.58	-11.92	QP
7	17.01	27.90	0.51	28.41	50.00	-21.59	Average
8	17.01	35.93	0.51	36.44	60.00	-23.56	QP
9	19.92	32.87	0.52	33.39	50.00	-16.61	Average
10	19.92	41.34	0.52	41.86	60.00	-18.14	QP
11	21.58	18.69	0.56	19.25	50.00	-30.75	Average
12	21.58	40.03	0.56	40.59	60.00	-19.41	QP

Notes:

1. Result = Read Value + Factor
2. Factor = LISN Factor + Cable Loss
3. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
4. According to technical experiences, all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
5. The data is worse case.



Power :	AC 120V	Pol/Phase :	NEUTRAL
Test Mode 2 :	802.11g CH1	Temperature :	24 °C
Memo :	Adapter: FA-1201000SUC	Humidity :	62 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV/m		dB	dBuV/m	dBuV/m	
1	0.18	39.65	0.07	39.72	54.42	-14.70	Average
2	0.18	52.91	0.07	52.98	64.42	-11.44	QP
3	0.24	32.91	0.07	32.98	52.08	-19.10	Average
4	0.24	44.95	0.07	45.02	62.08	-17.06	QP
5	0.47	40.50	0.08	40.58	46.59	-6.01	Average
6	0.47	42.61	0.08	42.69	56.59	-13.90	QP
7	17.67	24.23	0.49	24.72	50.00	-25.28	Average
8	17.67	41.03	0.49	41.52	60.00	-18.48	QP
9	19.26	36.67	0.51	37.18	50.00	-12.82	Average
10	19.26	39.47	0.51	39.98	60.00	-20.02	QP
11	21.59	31.55	0.55	32.10	50.00	-17.90	Average
12	21.59	41.48	0.55	42.03	60.00	-17.97	QP

Notes:

1. Result = Read Value + Factor
2. Factor = LISN Factor + Cable Loss
3. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
4. According to technical experiences, all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
5. The data is worse case.



Power	: AC 120V	Pol/Phase	: LINE
Test Mode 2	: 802.11n, HT20, CH1	Temperature	: 24 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 62 %




Item	Freq	Read		Result	Limit	Margin	Remark
		Value	Factor				
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	
1	0.18	38.21	0.07	38.28	54.59	-16.31	Average
2	0.18	52.64	0.07	52.71	64.59	-11.88	QP
3	0.24	38.29	0.07	38.36	52.17	-13.81	Average
4	0.24	43.86	0.07	43.93	62.17	-18.24	QP
5	0.47	42.68	0.08	42.76	46.58	-3.82	Average
6	0.47	44.54	0.08	44.62	56.58	-11.96	QP
7	17.01	27.90	0.51	28.41	50.00	-21.59	Average
8	17.01	35.93	0.51	36.44	60.00	-23.56	QP
9	19.92	32.81	0.52	33.33	50.00	-16.67	Average
10	19.92	41.34	0.52	41.86	60.00	-18.14	QP
11	21.58	18.88	0.56	19.44	50.00	-30.56	Average
12	21.58	40.03	0.56	40.59	60.00	-19.41	QP

Notes:

1. Result = Read Value + Factor
2. Factor = LISN Factor + Cable Loss
3. According to technical experiences, all spurious emission of 802.11n mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
4. The data is worse case.



Power	: AC 120V	Pol/Phase	: NEUTRAL
Test Mode 2	: 802.11n, HT20, CH1	Temperature	: 24 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 62 %




Item	Freq	Read		Result	Limit	Margin	Remark
		Value	Factor				
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	
1	0.18	39.65	0.07	39.72	54.42	-14.70	Average
2	0.18	52.97	0.07	53.04	64.42	-11.38	QP
3	0.24	32.91	0.07	32.98	52.08	-19.10	Average
4	0.24	44.45	0.07	44.52	62.08	-17.56	QP
5	0.47	40.50	0.08	40.58	46.59	-6.01	Average
6	0.47	42.11	0.08	42.19	56.59	-14.40	QP
7	17.67	24.24	0.49	24.73	50.00	-25.27	Average
8	17.67	41.03	0.49	41.52	60.00	-18.48	QP
9	19.26	36.68	0.51	37.19	50.00	-12.81	Average
10	19.26	39.47	0.51	39.98	60.00	-20.02	QP
11	21.59	31.55	0.55	32.10	50.00	-17.90	Average
12	21.59	41.44	0.55	41.99	60.00	-18.01	QP

Notes:

1. Result = Read Value + Factor
2. Factor = LISN Factor + Cable Loss
3. According to technical experiences, all spurious emission of 802.11n mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
4. The data is worse case.



Power	: AC 120V	Pol/Phase	: LINE
Test Mode 2	: 802.11n, HT40, CH3	Temperature	: 24 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 62 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	
1	0.18	38.41	0.07	38.48	54.59	-16.11	Average
2	0.18	52.16	0.07	52.23	64.59	-12.36	QP
3	0.24	38.29	0.07	38.36	52.17	-13.81	Average
4	0.24	43.89	0.07	43.96	62.17	-18.21	QP
5	0.47	42.07	0.08	42.15	46.58	-4.43	Average
6	0.47	44.34	0.08	44.42	56.58	-12.16	QP
7	17.01	27.90	0.51	28.41	50.00	-21.59	Average
8	17.01	35.93	0.51	36.44	60.00	-23.56	QP
9	19.92	32.81	0.52	33.33	50.00	-16.67	Average
10	19.92	41.41	0.52	41.93	60.00	-18.07	QP
11	21.58	18.69	0.56	19.25	50.00	-30.75	Average
12	21.58	40.03	0.56	40.59	60.00	-19.41	QP

Notes:

1. Result = Read Value + Factor
2. Factor = LISN Factor + Cable Loss
3. According to technical experiences, all spurious emission of 802.11n mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
4. The data is worse case.



Power :	AC 120V	Pol/Phase :	NEUTRAL
Test Mode 2 :	802.11n, HT40, CH3	Temperature :	24 °C
Memo :	Adapter: FA-1201000SUC	Humidity :	62 %



Item	Freq	Read		Result	Limit	Margin	Remark
		Value	Factor				
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	
1	0.18	39.25	0.07	39.32	54.42	-15.10	Average
2	0.18	52.97	0.07	53.04	64.42	-11.38	QP
3	0.24	32.91	0.07	32.98	52.08	-19.10	Average
4	0.24	44.35	0.07	44.42	62.08	-17.66	QP
5	0.47	40.50	0.08	40.58	46.59	-6.01	Average
6	0.47	42.11	0.08	42.19	56.59	-14.40	QP
7	17.67	24.23	0.49	24.72	50.00	-25.28	Average
8	17.67	41.23	0.49	41.72	60.00	-18.28	QP
9	19.26	36.67	0.51	37.18	50.00	-12.82	Average
10	19.26	39.45	0.51	39.96	60.00	-20.04	QP
11	21.59	31.55	0.55	32.10	50.00	-17.90	Average
12	21.59	41.38	0.55	41.93	60.00	-18.07	QP

Notes:

1. Result = Read Value + Factor
2. Factor = LISN Factor + Cable Loss
3. According to technical experiences, all spurious emission of 802.11n mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
4. The data is worse case.

Test engineer: Ben




4.6 Test Photographs

Front View



Rear View





5. Test of Radiated Emission

5.1 Test Limit

Radiated emissions from 30 MHz to 25 GHz were measured according to the methods defines in ANSI C63.4-2003. The EUT was placed, 0.8 meter above the ground plane, as shown in section 5.6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance Meters	Radiated (μ V / M)	Radiated (dB μ V / M)
30-88	3	100	40.0
88-216	3	150	43.5
216-960	3	200	46.0
Above 960	3	500	54.0

For unintentional device, according to CISPR PUB.22, for Class B digital devices, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 10 meters shall not exceed the below table.


Frequency (MHz)	Distance Meters	Radiated (dB μ V / M)
30-230	10	30
230-1000	10	37

5.2 Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- i. "Cone of radiation" has been considered to be 3dB beamwidth of the measurement antenna.



5.3 Typical Test Setup




5.4 Measurement Equipment

Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
Bilog Antenna	Schaffner	CBL6112B	2840	2009/05/14	2010/05/13
Signal Generator	HP	8648B	3629U00612	2008/10/08	2009/10/07
Amplifier	Agilent	8447D	2944A10593	2009/05/21	2010/05/20
EMI Receiver	R&S	ESCI	100443	2008/12/19	2009/12/18
Spectrum Analyzer	R&S	FSP40	100047	2009/03/26	2010/03/25
Horn Antenna	EMCO	3115	31589	2009/05/04	2010/05/03
Preamplifier	Agilent	8449B	3008A01954	2009/02/27	2010/02/26



5.5 Test Result and Data

Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11g CH1	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %



Item	Freq	Read		Result	Limit	Margin	Remark	Ant	Tab
		Value	Factor					Pos	Pos


	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	60.25	42.88	-12.85	30.03	40.00	-9.97	Peak	100	360
2	80.05	44.39	-14.36	30.03	40.00	-9.97	Peak	100	360
3	100.13	43.65	-11.62	32.03	43.50	-11.47	Peak	100	360
4	120.20	37.36	-10.19	27.17	43.50	-16.33	Peak	100	360
5	133.95	34.71	-9.67	25.04	43.50	-18.46	Peak	100	360
6	267.05	44.57	-12.54	32.03	46.00	-13.97	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11g CH1	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %



Item	Freq	Read		Result	Limit	Margin	Remark	Ant	Tab
		Value	Factor					Pos	Pos


	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	399.40	42.00	-6.97	35.03	46.00	-10.97	Peak	100	0
2	485.50	43.57	-7.92	35.65	46.00	-10.35	Peak	100	0
3	534.50	36.68	-6.64	30.04	46.00	-15.96	Peak	100	0
4	667.50	33.98	-3.94	30.04	46.00	-15.96	Peak	100	0
5	749.40	30.27	-0.91	29.36	46.00	-16.64	Peak	100	0
6	833.40	34.98	0.67	35.65	46.00	-10.35	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11g CH1	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read		Result	Limit	Margin	Remark	Ant	Tab
		Value	Factor					Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	54.20	32.43	-16.40	16.03	40.00	-23.97	Peak	100	360
2	133.95	28.76	-16.76	12.00	43.50	-31.50	Peak	100	360
3	214.80	31.92	-16.59	15.33	43.50	-28.17	Peak	100	360
4	230.20	37.51	-16.18	21.33	46.00	-24.67	Peak	100	360
5	267.05	46.86	-13.53	33.33	46.00	-12.67	Peak	100	360
6	278.88	35.24	-13.21	22.03	46.00	-23.97	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11g CH1	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	399.40	41.54	-10.51	31.03	46.00	-14.97	Peak	100	0
2	490.40	44.01	-4.98	39.03	46.00	-6.97	Peak	100	0
3	510.00	41.79	-5.12	36.67	46.00	-9.33	Peak	100	0
4	667.50	28.76	-3.73	25.03	46.00	-20.97	Peak	100	0
5	749.40	32.88	-1.85	31.03	46.00	-14.97	Peak	100	0
6	811.00	34.57	-0.31	34.26	46.00	-11.74	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. All emission below 1GHz at 802.11b/g mode are all the same, so the 802.11g mode chosen as representative in final test.
5. According to technical experiences, all spurious emission of 802.11g mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
6. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11b CH1	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Read			Result	Limit	Margin	Remark	Ant	Tab
	Freq	Value	Factor					Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4824.63	35.62	7.69	43.31	54.00	-10.69	Average	100	188
2	4825.25	44.93	7.72	52.65	74.00	-21.35	Peak	100	188

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11b CH1	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Read			Result	Limit	Margin	Remark	Ant	Tab
	Freq	Value	Factor					Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4822.25	35.52	7.69	43.21	54.00	-10.79	Average	100	166
2	4824.13	43.34	7.69	51.03	74.00	-22.97	Peak	100	166

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11b CH6	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read		Result	Limit	Margin	Remark	Ant	Tab
		Value	Factor					Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.25	35.45	7.86	43.31	54.00	-10.69	Average	107	188
2	4874.38	44.17	7.86	52.03	74.00	-21.97	Peak	107	188

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11b CH6	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Read			Margin	Remark	Ant	Tab
	Freq	Value	Factor				
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	cm Deg
1	4875.25	35.14	7.89	43.03	54.00	-10.97	Average 100 175
2	4875.75	44.14	7.89	52.03	74.00	-21.97	Peak 100 175

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11b CH11	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Read			Margin	Remark	Ant	Tab	
	Freq	Value	Factor				Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	cm	Deg
1	4924.50	35.00	8.03	43.03	54.00	-10.97	Average	108 191
2	4925.00	43.98	8.05	52.03	74.00	-21.97	Peak	108 191

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11b CH11	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Read			Margin	Remark	Ant	Tab
	Freq	Value	Factor				
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	cm
1	4923.00	46.00	8.03	54.03	74.00	-19.97	Peak 113 207
2	4924.75	35.00	8.03	43.03	54.00	-10.97	Average 113 207

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11g CH1	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Read					Ant	Tab		
	Freq	Value	Factor	Result	Limit			Pos	Pos
1	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4825.13	44.31	7.72	52.03	74.00	-21.97	Peak	105	192
2	4825.50	35.31	7.72	43.03	54.00	-10.97	Average	105	192

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11g CH1	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Read				Ant	Tab			
	Freq	Value	Factor	Result			Remark	Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4825.88	35.31	7.72	43.03	54.00	-10.97	Average	100	179
2	4826.13	44.29	7.72	52.01	74.00	-21.99	Peak	100	179

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power :	AC 120V	Pol/Phase :	VERTICAL
Test Mode 2 :	802.11g CH6	Temperature :	26 °C
Memo :	Adapter: FA-1201000SUC	Humidity :	66 %




Item	Read			Result	Limit	Margin	Remark	Ant	Tab
	Freq	Value	Factor					Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.63	35.26	7.86	43.12	54.00	-10.88	Average	109	192
2	4877.38	45.14	7.89	53.03	74.00	-20.97	Peak	109	192

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power :	AC 120V	Pol/Phase :	HORIZONTAL
Test Mode 2 :	802.11g CH6	Temperature :	26 °C
Memo :	Adapter: FA-1201000SUC	Humidity :	66 %




Item	Read			Limit	Margin	Remark	Ant	Tab
	Freq	Value	Factor				Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	cm	Deg
1	4874.00	44.17	7.86	52.03	74.00	-21.97	Peak	105 184
2	4874.75	37.45	7.86	45.31	54.00	-8.69	Average	105 184

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11g CH11	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read			Margin	Remark	Ant	Tab
		Value	Factor	Result				
		MHz	dBuV/m	dB	dBuV/m	dB	cm	Deg
1	4925.75	34.97	8.06	43.03	54.00	-10.97	Average	100
2	4927.13	43.97	8.06	52.03	74.00	-21.97	Peak	100

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11g CH11	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Read			Result	Limit	Margin	Remark	Ant	Tab
	Freq	Value	Factor					Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4925.63	34.95	8.06	43.01	54.00	-10.99	Average	107	187
2	4927.63	43.95	8.06	52.01	74.00	-21.99	Peak	107	187

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11n, HT20 CH1	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read			Ant			Tab	
		Value	Factor	Result	Limit	Margin	Remark	Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	60.25	44.88	-12.85	32.03	40.00	-7.97	Peak	100	360
2	80.05	44.39	-14.36	30.03	40.00	-9.97	Peak	100	360
3	90.50	43.58	-12.54	31.04	43.50	-12.46	Peak	100	360
4	133.95	36.00	-9.67	26.33	43.50	-17.17	Peak	100	360
5	140.00	39.82	-11.17	28.65	43.50	-14.85	Peak	100	360
6	267.05	45.77	-12.54	33.23	46.00	-12.77	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
5. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11n, HT20 CH1	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	399.40	42.20	-6.97	35.23	46.00	-10.77	Peak	100	0
2	490.40	39.41	-8.38	31.03	46.00	-14.97	Peak	100	0
3	534.50	36.68	-6.64	30.04	46.00	-15.96	Peak	100	0
4	667.50	32.49	-3.94	28.55	46.00	-17.45	Peak	100	0
5	749.40	32.94	-0.91	32.03	46.00	-13.97	Peak	100	0
6	811.00	32.03	-1.00	31.03	46.00	-14.97	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
5. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n, HT20 CH1	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read		Result	Limit	Margin	Remark	Ant	Tab
		Value	Factor					Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	133.95	28.79	-16.76	12.03	43.50	-31.47	Peak	100	360
2	159.80	31.18	-16.15	15.03	43.50	-28.47	Peak	100	360
3	214.80	31.62	-16.59	15.03	43.50	-28.47	Peak	100	360
4	240.38	34.46	-15.81	18.65	46.00	-27.35	Peak	100	360
5	267.05	46.56	-13.53	33.03	46.00	-12.97	Peak	100	360
6	278.88	35.24	-13.21	22.03	46.00	-23.97	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
5. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n, HT20 CH1	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	399.40	40.54	-10.51	30.03	46.00	-15.97	Peak	100	0
2	510.00	44.15	-5.12	39.03	46.00	-6.97	Peak	100	0
3	534.50	36.46	-5.43	31.03	46.00	-14.97	Peak	100	0
4	667.50	33.76	-3.73	30.03	46.00	-15.97	Peak	100	0
5	749.40	32.86	-1.85	31.01	46.00	-14.99	Peak	100	0
6	802.60	32.72	-0.69	32.03	46.00	-13.97	Peak	100	0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 1,6,11 are almost the same below 1GHz, so that the channel 1 was chosen as representative in final test.
5. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11n, HT20 CH1	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Read			Margin	Remark	Ant	Tab	
	Freq	Value	Factor				Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m		cm	Deg
1	4822.63	44.96	7.69	52.65	74.00	-21.35	Peak	100 173
2	4824.50	35.32	7.69	43.01	54.00	-10.99	Average	100 173

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n, HT20 CH1	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4822.75	42.34	7.69	50.03	74.00	-23.97	Peak	106	183
2	4823.38	35.34	7.69	43.03	54.00	-10.97	Average	106	183

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11n, HT20 CH6	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read			Margin	Remark	Ant	Tab
		Value	Factor	Result				
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	cm	Deg
1	4874.13	44.17	7.86	52.03	74.00	-21.97	Peak	115 195
2	4875.50	35.14	7.89	43.03	54.00	-10.97	Average	115 195

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n, HT20 CH6	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4876.00	35.14	7.89	43.03	54.00	-10.97	Average	110	183
2	4877.63	44.14	7.89	52.03	74.00	-21.97	Peak	110	183

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11n, HT20 CH11	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuW/m	dB	dBuV/m	dBuV/m	dB	cm	Deg
1	4924.13	35.00	8.03	43.03	54.00	-10.97	Average	105 169
2	4924.25	44.00	8.03	52.03	74.00	-21.97	Peak	105 169

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n, HT20 CH11	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Read			Limit	Margin	Remark	Ant	Tab
	Freq	Value	Factor				Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dB		cm	Deg
1	4924.13	35.00	8.03	43.03	54.00	-10.97	Average	108 159
2	4926.88	43.96	8.06	52.02	74.00	-21.98	Peak	108 159

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power :	AC 120V	Pol/Phase :	VERTICAL
Test Mode 2 :	802.11n, HT40 CH3	Temperature :	26 °C
Memo :	Adapter: FA-1201000SUC	Humidity :	66 %




Item	Freq	Read		Result	Limit	Margin	Remark	Ant	Tab
		Value	Factor					Pos	Pos
		MHz	dBuV/m	dB	dBuV/m	dB		cm	Deg
1	60.25	44.89	-12.85	32.04	40.00	-7.96	Peak	100	360
2	80.05	44.40	-14.36	30.04	40.00	-9.96	Peak	100	360
3	90.50	42.57	-12.54	30.03	43.50	-13.47	Peak	100	360
4	100.13	40.39	-11.62	28.77	43.50	-14.73	Peak	100	360
5	133.95	35.70	-9.67	26.03	43.50	-17.47	Peak	100	360
6	267.05	44.58	-12.54	32.04	46.00	-13.96	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 3,6,9 are almost the same below 1GHz, so that the channel 3 was chosen as representative in final test.
5. The data is worse case.



Power :	AC 120V	Pol/Phase :	VERTICAL
Test Mode 2 :	802.11n, HT40 CH3	Temperature :	26 °C
Memo :	Adapter: FA-1201000SUC	Humidity :	66 %




Item	Freq	Read			Margin	Remark	Ant	Tab
		Value	Factor	Result				
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1	399.40	42.20	-6.97	35.23	46.00	-10.77	Peak	100 0
2	490.40	43.61	-8.38	35.23	46.00	-10.77	Peak	100 0
3	534.50	36.67	-6.64	30.03	46.00	-15.97	Peak	100 0
4	667.50	31.97	-3.94	28.03	46.00	-17.97	Peak	100 0
5	749.40	30.95	-0.91	30.04	46.00	-15.96	Peak	100 0
6	802.60	33.16	-1.12	32.04	46.00	-13.96	Peak	100 0

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 3,6,9 are almost the same below 1GHz, so that the channel 3 was chosen as representative in final test.
5. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n, HT40 CH3	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read Value	Factor	Result	Limit	Margin	Remark	Ant Pos	Tab Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	78.13	34.61	-21.59	13.02	40.00	-26.98	Peak	100	360
2	133.95	28.79	-16.76	12.03	43.50	-31.47	Peak	100	360
3	214.80	34.83	-16.59	18.24	43.50	-25.26	Peak	100	360
4	230.20	36.21	-16.18	20.03	46.00	-25.97	Peak	100	360
5	250.00	30.54	-15.28	15.26	46.00	-30.74	Peak	100	360
6	267.05	45.56	-13.53	32.03	46.00	-13.97	Peak	100	360

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 3,6,9 are almost the same below 1GHz, so that the channel 3 was chosen as representative in final test.
5. The data is worse case.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n, HT40 CH3	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read			Margin	Remark	Ant	Tab
		Value	Factor	Result				
1	399.40	40.64	-10.51	30.13	46.00	-15.87	Peak	100
2	492.50	40.83	-4.98	35.85	46.00	-10.15	Peak	100
3	510.00	40.77	-5.12	35.65	46.00	-10.35	Peak	100
4	667.50	33.38	-3.73	29.65	46.00	-16.35	Peak	100
5	749.40	31.98	-1.85	30.13	46.00	-15.87	Peak	100
6	802.60	31.72	-0.69	31.03	46.00	-14.97	Peak	100

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. According to technical experiences, all spurious emission of 802.11MIMO mode at channel 3,6,9 are almost the same below 1GHz, so that the channel 3 was chosen as representative in final test.
5. The data is worse case.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11n, HT40 CH3	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read			Limit	Margin	Remark	Ant	Tab
		Value	Factor	Result				Pos	Pos
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	cm	Deg
1	4844.50	35.26	7.77	43.03	54.00	-10.97	Average	102	190
2	4845.50	44.26	7.77	52.03	74.00	-21.97	Peak	102	190

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n, HT40 CH3	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read		Result	Limit	Margin	Remark	Ant	Tab
		Value	Factor					Pos	Pos
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	cm	Deg
1	4845.50	35.26	7.77	43.03	54.00	-10.97	Average	108	200
2	4846.13	43.26	7.77	51.03	74.00	-22.97	Peak	108	200

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11n, HT40 CH6	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read		Result	Limit	Margin	Remark	Ant	Tab
		Value	Factor					Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		cm	Deg
1	4874.75	43.17	7.86	51.03	74.00	-22.97	Peak	112	182
2	4875.75	35.11	7.89	43.00	54.00	-11.00	Average	112	182

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n, HT40 CH6	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read			Limit	Margin	Remark	Ant	Tab
		Value	Factor	Result					
	MHz	dBuV/m		dB	dBuV/m	dBuV/m	dB	cm	Deg
1	4872.00	35.19	7.86	43.05	54.00	-10.95	Average	105	165
2	4877.25	43.14	7.89	51.03	74.00	-22.97	Peak	105	165

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: VERTICAL
Test Mode 2	: 802.11n, HT40 CH9	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %




Item	Freq	Read			Result	Limit	Margin	Remark	Ant	Tab
		Value	Factor	dB					Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB			cm	Deg
1	4905.63	35.25	7.98	43.23	54.00	-10.77	Average	108	186	
2	4905.88	44.05	7.98	52.03	74.00	-21.97	Peak	108	186	

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.



Power	: AC 120V	Pol/Phase	: HORIZONTAL
Test Mode 2	: 802.11n, HT40 CH9	Temperature	: 26 °C
Memo	: Adapter: FA-1201000SUC	Humidity	: 66 %



Item	Freq	Read			Margin	Remark	Ant Pos	Tab Pos
		Value	Factor	Result				
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	cm
1	4902.13	44.07	7.96	52.03	74.00	-21.97	Peak	100 206
2	4905.50	35.07	7.98	43.05	54.00	-10.95	Average	100 206

Notes:

1. Result = Read Value + Factor
2. Factor = Antenna Factor + Cable Loss - Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 120KHz and video bandwidth is 300kHz for Peak detection and Quasi-peak detection at frequency below 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz.
6. The other emissions is too low to be measured.

Test engineer : Ben



5.6 Test Photographs

Front View



Rear View





6. 6dB Bandwidth Measurement Data


6.1 Test Limit

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

6.2 Test Procedures

- a. The transmitter output was connected to the spectrum analyzer.
- b. Set RBW of spectrum analyzer to 100 KHz and VBW to 100 KHz.
- c. The 6 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6 dB.

6.3 Test Setup Layout



6.4 Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	FSP40	R&S	10047	2009/03/26	2010/03/25

6.5 Test Result and Data

Test Date: Aug. 27, 2009

Temperature: 26


Atmospheric pressure: 1010 hPa

Humidity: 65%


Modulation Standard	Channel	Frequency (MHz)	6dB Bandwidth (MHz)
802.11b (11Mbps)	01	2412	11.9
	06	2437	12.1
	11	2462	11.6
802.11g (6Mbps)	01	2412	16.4
	06	2437	16.6
	11	2462	16.4
802.11n, HT20 (6.5Mbps)	01	2412	17.8
	06	2437	17.8
	11	2462	17.8
802.11n, HT40 (13.5Mbps)	03	2422	36.4
	06	2437	36.4
	09	2452	36.4



Modulation Standard: 802.11b (11Mbps)
Channel: 01




Modulation Standard: 802.11b (11Mbps)
Channel: 06






Modulation Standard: 802.11b (11Mbps)
Channel: 11




Modulation Standard: 802.11g (6Mbps)
Channel: 01






Modulation Standard: 802.11g (6Mbps)
Channel: 06




Modulation Standard: 802.11g (6Mbps)
Channel: 11






Modulation Standard: 802.11n HT20 (6.5Mbps)
Channel: 01




Modulation Standard: 802.11n HT20 (6.5Mbps)
Channel: 06






Modulation Standard: 802.11n HT20 (6.5Mbps)
Channel: 11




Modulation Standard: 802.11n HT40 (13.5Mbps)
Channel: 03






Modulation Standard: 802.11n HT40 (13.5Mbps)
Channel: 06



Modulation Standard: 802.11n HT40 (13.5Mbps)
Channel: 9





7. Maximum Peak Output Power

7.1 Test Limit


The Maximum Peak Output Power Measurement is 30dBm.

7.2 Test Procedures

The antenna port(RF output)of the EUT was connected to the input(RF input)of a power meter.

Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

7.3 Test Setup Layout



7.4 Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	FSP40	R&S	10047	2009/03/26	2010/03/25

7.5 Test Result and Data

Test Date: Aug. 27, 2009

Temperature: 26

Atmospheric pressure: 1010 hPa


Humidity: 65%

Modulation Standard	Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
802.11b (11Mbps)	01	2412	17.32	54.0
	06	2437	17.02	50.4
	11	2462	17.40	55.0
802.11g (6Mbps)	01	2412	17.07	50.9
	06	2437	17.45	55.6
	11	2462	17.01	50.2


Modulation Standard	Channel	Frequency (MHz)	Peak Power Output (dBm)	Peak Power Output (mW)
802.11n HT20 (6.5Mbps)	01	2412	15.58	36.1
	06	2437	15.59	36.2
	11	2462	15.38	34.5
802.11n HT40 (13.5Mbps)	03	2422	15.45	35.1
	06	2437	15.27	33.7
	09	2452	15.09	32.3



Modulation Standard: 802.11b (11Mbps)
Channel: 01




Modulation Standard: 802.11b (11Mbps)
Channel: 06






Modulation Standard: 802.11b (11Mbps)
Channel: 11




Modulation Standard: 802.11g (6Mbps)
Channel: 01






Modulation Standard: 802.11g (6Mbps)
Channel: 06




Modulation Standard: 802.11g (6Mbps)
Channel: 11






Modulation Standard: 802.11n HT20 (6.5Mbps)
Channel: 01




Modulation Standard: 802.11n HT20 (6.5Mbps)
Channel: 06






Modulation Standard: 802.11n HT20 (6.5Mbps)
Channel: 11




Modulation Standard: 802.11n HT40 (13.5Mbps)
Channel: 03






Modulation Standard: 802.11n HT40 (13.5Mbps)
Channel: 06



Modulation Standard: 802.11n HT40 (13.5Mbps)
Channel: 09





8. Band Edges Measurement


8.1 Test Limit

Below -20dB of the highest emission level of operating band (In 100 kHz Resolution Bandwidth)

8.2 Test Procedure

- a. The transmitter output was connected to the spectrum analyzer via a low loss cable.
- b. Set both RBW and VBW of spectrum analyzer to 100 KHz with convenient frequency span including 100 KHz bandwidth from band edge.
- c. The band edges was measured and recorded.

8.3 Test Setup Layout



8.4 Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	FSP40	R&S	10047	2009/03/26	2010/03/25

8.5 Test Result and Data

Test Date: Aug. 31, 2009

Temperature: 27



Atmospheric pressure: 1012 hPa

Humidity: 66%

Modulation Standard	Channel	Frequency (MHz)	maximum value in frequency (MHz)	maximum value (dBm)
802.11b (11Mbps)	01	2412	2399.70	-44.44
	11	2462	2502.96	-55.82
802.11g (6Mbps)	01	2412	2399.90	-27.55
	11	2462	2483.92	-47.06
802.11n HT20 (6.5Mbps)	01	2412	2399.90	-31.38
	11	2462	2483.92	-48.11
802.11n HT40 (13.5Mbps)	03	2422	2399.60	-33.13
	09	2452	2484.16	-46.55





Modulation Standard: 802.11b (11Mbps)
Channel: 01







Modulation Standard: 802.11b (11Mbps)
Channel: 11







Modulation Standard: 802.11g (6Mbps)
Channel: 01







Modulation Standard: 802.11g (6Mbps)
Channel: 11







Modulation Standard: 802.11n HT20 (6.5Mbps)
Channel: 01







Modulation Standard: 802.11n HT20 (6.5Mbps)

Channel: 11







Modulation Standard: 802.11n HT40 (13.5Mbps)
Channel: 03





Modulation Standard: 802.11n HT40 (13.5Mbps)
Channel: 09





8.6 Restrict Band Emission Measurement Data

Test Date : Aug. 28, 2009
 Temperature : 26
 Humidity : 57%
 Atmospheric Pressure : 1021 hPa
 Adapter : T012LF1209 16100-2LF

Modulation Standard: IEEE 802.11b (11Mbps)

Channel 1							Fundamental Frequency: 2412 MHz			
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2389.36	H	50.70	-0.67	50.03	Peak	74	54	-23.97	196	100
2390.00	H	38.74	-0.67	38.07	Ave	74	54	-15.93	196	100
2389.05	V	51.18	-0.67	50.51	Peak	74	54	-23.49	199	104
2390.00	V	39.25	-0.67	38.58	Ave	74	54	-15.42	199	104
Channel 11							Fundamental Frequency: 2462 MHz			
2488.79	H	50.51	-0.25	50.26	Peak	74	54	-23.74	210	127
2483.50	H	38.45	-0.27	38.18	Ave	74	54	-15.82	210	127
2484.42	V	51.12	-0.26	50.86	Peak	74	54	-23.14	185	105
2483.50	V	38.63	-0.27	38.36	Ave	74	54	-15.64	185	105

Modulation Standard: IEEE 802.11g (6Mbps)

Channel 1							Fundamental Frequency: 2412 MHz			
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2389.76	H	56.54	-0.67	55.87	Peak	74	54	-18.13	208	100
2390.00	H	41.11	-0.67	40.44	Ave	74	54	-13.56	208	100
2389.97	V	56.81	-0.67	56.14	Peak	74	54	-17.86	170	134
2390.00	V	42.05	-0.67	41.38	Ave	74	54	-12.62	170	134
Channel 11							Fundamental Frequency: 2462 MHz			
2483.74	H	59.20	-0.27	58.93	Peak	74	54	-15.07	211	100
2483.50	H	42.77	-0.27	42.50	Ave	74	54	-11.50	211	100
2483.58	V	59.77	-0.27	59.50	Peak	74	54	-14.50	194	100
2483.50	V	43.47	-0.27	43.20	Ave	74	54	-10.80	194	100

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz



Test Date : Aug. 28, 2009
 Temperature : 26
 Humidity : 57%
 Atmospheric Pressure : 1021 hPa
 Adapter : T012LF1209 16100-2LF

Modulation Standard: IEEE 802.11n, HT20 (6.5Mbps)

Channel 1							Fundamental Frequency: 2412 MHz			
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2389.97	H	53.44	-0.67	52.77	Peak	74	54	-21.23	199	100
2390.00	H	37.12	-0.67	36.45	Ave	74	54	-17.55	199	100
2389.97	V	55.55	-0.67	54.88	Peak	74	54	-19.12	197	100
2390.00	V	40.22	-0.67	39.55	Ave	74	54	-14.45	197	100
Channel 11							Fundamental Frequency: 2462 MHz			
2483.58	H	54.97	-0.27	54.70	Peak	74	54	-19.30	204	100
2483.50	H	40.99	-0.27	40.72	Ave	74	54	-13.28	204	100
2484.04	V	56.53	-0.27	56.26	Peak	74	54	-17.74	197	100
2483.50	V	42.45	-0.27	42.18	Ave	74	54	-11.82	197	100

Modulation Standard: IEEE 802.11n, HT40 (13.5Mbps)

Channel 3							Fundamental Frequency: 2422 MHz			
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2389.76	H	57.88	-0.67	57.21	Peak	74	54	-16.79	148	100
2390.00	H	42.32	-0.67	41.65	Ave	74	54	-12.35	148	100
2389.97	V	62.12	-0.67	61.45	Peak	74	54	-12.55	191	111
2390.00	V	46.35	-0.67	45.68	Ave	74	54	-8.32	191	111
Channel 9							Fundamental Frequency: 2452 MHz			
2483.66	H	60.45	-0.27	60.18	Peak	74	54	-13.82	209	123
2483.50	H	43.55	-0.27	43.28	Ave	74	54	-10.72	209	123
2483.96	V	62.18	-0.27	61.91	Peak	74	54	-12.09	193	104
2483.50	V	45.17	-0.27	44.90	Ave	74	54	-9.10	193	104

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz



Test Date : Aug. 28, 2009
 Temperature : 26
 Humidity : 57%
 Atmospheric Pressure : 1021 hPa
 Adapter : FA-1201000SUC

Modulation Standard: IEEE 802.11b (11Mbps)

Channel 1							Fundamental Frequency: 2412 MHz			
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2389.78	H	51.65	-0.67	50.98	Peak	74	54	-23.02	184	102
2390.00	H	39.69	-0.67	39.02	Ave	74	54	-14.98	184	102
2389.32	V	52.13	-0.67	51.46	Peak	74	54	-22.54	201	110
2390.00	V	40.20	-0.67	39.53	Ave	74	54	-14.47	201	110
Channel 11							Fundamental Frequency: 2462 MHz			
2488.61	H	51.46	-0.25	51.21	Peak	74	54	-22.79	211	121
2483.50	H	39.40	-0.27	39.13	Ave	74	54	-14.87	211	121
2484.55	V	52.07	-0.26	51.81	Peak	74	54	-22.19	186	104
2483.50	V	39.58	-0.27	39.31	Ave	74	54	-14.69	186	104

Modulation Standard: IEEE 802.11g(6Mbps)

Channel 1							Fundamental Frequency: 2412 MHz			
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2389.64	H	57.49	-0.67	56.82	Peak	74	54	-17.18	213	122
2390.00	H	42.06	-0.67	41.39	Ave	74	54	-12.61	213	122
2389.88	V	57.76	-0.67	57.09	Peak	74	54	-16.91	179	101
2390.00	V	43.00	-0.67	42.33	Ave	74	54	-11.67	179	101
Channel 11							Fundamental Frequency: 2462 MHz			
2483.72	H	60.15	-0.27	59.88	Peak	74	54	-14.12	206	105
2483.50	H	43.72	-0.27	43.45	Ave	74	54	-10.55	206	105
2483.66	V	60.72	-0.27	60.45	Peak	74	54	-13.55	200	103
2483.50	V	44.42	-0.27	44.15	Ave	74	54	-9.85	200	103

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz



Test Date : Aug. 28, 2009
 Temperature : 26
 Humidity : 57%
 Atmospheric Pressure : 1021 hPa
 Adapter : FA-1201000SUC

Modulation Standard: IEEE 802.11n, HT20 (6.5Mbps)

Channel 1							Fundamental Frequency: 2412 MHz			
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2389.74	H	54.39	-0.67	53.72	Peak	74	54	-20.28	192	107
2390.00	H	38.07	-0.67	37.40	Ave	74	54	-16.60	192	107
2389.56	V	56.50	-0.67	55.83	Peak	74	54	-18.17	195	120
2390.00	V	41.17	-0.67	40.50	Ave	74	54	-13.50	195	120
Channel 11							Fundamental Frequency: 2462 MHz			
2483.97	H	55.92	-0.27	55.65	Peak	74	54	-18.35	201	111
2483.50	H	41.94	-0.27	41.67	Ave	74	54	-12.33	201	111
2484.76	V	57.48	-0.27	57.21	Peak	74	54	-16.79	189	100
2483.50	V	43.40	-0.27	43.13	Ave	74	54	-10.87	189	100

Modulation Standard: IEEE 802.11n, HT40 (13.5Mbps)

Channel 3							Fundamental Frequency: 2422 MHz			
Frequency (MHz)	Ant-Pol H/V	Meter Reading	Corrected Factor	Result (dBuV/m)	Remark	Limit@3m (dBuV/m)		Margin (dB)	Table (Deg.)	Ant High (m)
						Peak	Ave.			
2389.68	H	58.83	-0.67	58.16	Peak	74	54	-15.84	156	100
2390.00	H	43.27	-0.67	42.60	Ave	74	54	-11.40	156	100
2389.93	V	63.07	-0.67	62.40	Peak	74	54	-11.60	181	115
2390.00	V	47.30	-0.67	46.63	Ave	74	54	-7.37	181	115
Channel 9							Fundamental Frequency: 2452 MHz			
2483.76	H	61.40	-0.27	61.13	Peak	74	54	-12.87	202	128
2483.50	H	44.50	-0.27	44.23	Ave	74	54	-9.77	202	128
2483.97	V	63.13	-0.27	62.86	Peak	74	54	-11.14	188	109
2483.50	V	46.12	-0.27	45.85	Ave	74	54	-8.15	188	109

Notes:

1. Result = Meter Reading + Factor
2. Factor = Antenna Factor + Cable Loss – Amplifier
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3 MHz for Peak detection at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average detection at frequency above 1GHz



9. Power Spectral Density


9.1 Test Limit

The Maximum of Power Spectral Density Measurement is 8dBm.

9.2 Test Procedures

- a. The transmitter output was connected to spectrum analyzer.
- b. The spectrum analyzer's resolution bandwidth were set at 3KHz RBW and 30KHz VBW as that of the fundamental frequency. Set the sweep time=span/3KHz.
- c. The power spectral density was measured and recorded.
- d. The Sweep time is allowed to be longer than span/3KHz for a full response of the mixer in the spectrum analyzer.

9.3 Test Setup Layout



9.4 Measurement Equipment

Instrument/Ancillary	Model No.	Manufacturer	Serial No.	Calibration Date	Valid Date
Spectrum Analyzer	FSP40	R&S	10047	2009/03/26	2010/03/25

9.5 Test Result and Data

Test Date: Aug. 31, 2009

Temperature: 27


Atmospheric pressure: 1012 hPa

Humidity: 66%


Modulation Standard	Channel	Frequency (MHz)	Maximum Power Density of 3 kHz Bandwidth (dBm)
802.11b (11Mbps)	01	2412	-10.68
	06	2437	-11.52
	11	2462	-8.97
802.11g (6Mbps)	01	2412	-14.99
	06	2437	-14.57
	11	2462	-16.09
802.11n HT20 (6.5Mbps)	01	2412	-17.19
	06	2437	-17.95
	11	2462	-18.24
802.11n HT40 (13.5Mbps)	03	2422	-18.69
	06	2437	-19.77
	09	2452	-20.01



Modulation Standard: 802.11b (11Mbps)
Channel: 01




Modulation Standard: 802.11b (11Mbps)
Channel: 06






Modulation Standard: 802.11b (11Mbps)
Channel: 11




Modulation Standard: 802.11g (6Mbps)
Channel: 01






Modulation Standard: 802.11g (6Mbps)
Channel: 06




Modulation Standard: 802.11g (6Mbps)
Channel: 11






Modulation Standard: 802.11n HT20 (6.5Mbps)
Channel: 01




Modulation Standard: 802.11n HT20 (6.5Mbps)
Channel: 06






Modulation Standard: 802.11n HT20 (6.5Mbps)
Channel: 11




Modulation Standard: 802.11n HT40 (13.5Mbps)
Channel: 03






Modulation Standard: 802.11n HT40 (13.5Mbps)
Channel: 06



Modulation Standard: 802.11n HT40 (13.5Mbps)
Channel: 09





10. Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

**: Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

10.1 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.