



# FCC TEST REPORT (15.407)

**REPORT NO.:** RF120420C08D R1

**MODEL NO.:** WNDR3700v4

**FCC ID:** PY312100186

**RECEIVED:** Jun. 21, 2012

**TESTED:** Jul. 05, 2012 ~ Apr. 25, 2013

**ISSUED:** Apr. 26, 2013

**APPLICANT:** NETGEAR, INC.

**ADDRESS:** 350 East Plumeria Drive San Jose, CA 95134

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,  
New Taipei City, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



# TABLE OF CONTENTS

RELEASE CONTROL RECORD .....	4
1. CERTIFICATION.....	5
2. SUMMARY OF TEST RESULTS .....	6
2.1 MEASUREMENT UNCERTAINTY .....	6
3. GENERAL INFORMATION.....	7
3.1 GENERAL DESCRIPTION OF EUT .....	7
3.2 DESCRIPTION OF TEST MODES.....	9
3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	10
3.3 DUTY CYCLE OF TEST SIGNAL.....	12
3.4 DESCRIPTION OF SUPPORT UNITS .....	13
3.4.1 CONFIGURATION OF SYSTEM UNDER TEST .....	13
3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS .....	15
4. TEST TYPES AND RESULTS .....	16
4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT .....	16
4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT.....	16
4.1.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS .....	16
4.1.3 TEST INSTRUMENTS.....	17
4.1.4 TEST PROCEDURES .....	19
4.1.5 DEVIATION FROM TEST STANDARD .....	19
4.1.6 TEST SETUP.....	20
4.1.7 EUT OPERATING CONDITION .....	20
4.1.8 TEST RESULTS .....	21
4.2 CONDUCTED EMISSION MEASUREMENT .....	40
4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	40
4.2.2 TEST INSTRUMENTS.....	40
4.2.3 TEST PROCEDURES .....	41
4.2.4 DEVIATION FROM TEST STANDARD .....	41
4.2.5 TEST SETUP.....	41
4.2.6 EUT OPERATING CONDITIONS .....	41
4.2.7 TEST RESULTS .....	42
4.3 PEAK TRANSMIT POWER MEASUREMENT .....	46
4.3.1 LIMITS OF PEAK TRANSMIT POWER MEASUREMENT .....	46
4.3.2 TEST SETUP.....	46
4.3.3 TEST INSTRUMENTS.....	47
4.3.4 TEST PROCEDURE.....	47
4.3.5 DEVIATION FROM TEST STANDARD .....	47
4.3.6 EUT OPERATING CONDITIONS .....	47
4.3.7 TEST RESULTS .....	48
4.4 PEAK POWER SPECTRAL DENSITY MEASUREMENT .....	51
4.4.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT .....	51
4.4.2 TEST SETUP.....	51
4.4.3 TEST INSTRUMENTS.....	51
4.4.4 TEST PROCEDURES .....	51
4.4.5 DEVIATION FROM TEST STANDARD .....	51
4.4.6 EUT OPERATING CONDITIONS .....	52
4.4.7 TEST RESULTS .....	53
4.5 PEAK POWER EXCURSION MEASUREMENT .....	55



A D T

4.5.1	LIMITS OF PEAK POWER EXCURSION MEASUREMENT .....	55
4.5.2	TEST SETUP .....	55
4.5.3	TEST INSTRUMENTS.....	55
4.5.4	TEST PROCEDURE.....	55
4.5.5	DEVIATION FROM TEST STANDARD .....	55
4.5.6	EUT OPERATING CONDITIONS .....	55
4.5.7	TEST RESULTS .....	56
4.6	FREQUENCY STABILITY .....	59
4.6.1	LIMITS OF FREQUENCY STABILITY MEASUREMENT.....	59
4.6.2	TEST SETUP.....	59
4.6.3	TEST INSTRUMENTS.....	59
4.6.4	TEST PROCEDURE.....	60
4.6.5	DEVIATION FROM TEST STANDARD .....	60
4.6.6	EUT OPERATING CONDITION .....	60
4.6.7	TEST RESULTS .....	61
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION .....	62
6.	INFORMATION ON THE TESTING LABORATORIES.....	63
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB .....	64



A D T

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF120420C08D	Original release	Feb. 18, 2013
RF120420C08D R1	Re-evaluated conducted power of EUT	Apr. 26, 2013



# 1. CERTIFICATION

**PRODUCT:** N600 Wireless Dual Band Gigabit Router

**MODEL:** WNDR3700v4

**BRAND:** NETGEAR

**APPLICANT:** NETGEAR, INC.

**TESTED:** Jul. 05, 2012 ~ Apr. 25, 2013

**TEST SAMPLE:** ENGINEERING SAMPLE

**STANDARDS: FCC Part 15, Subpart E (Section 15.407)**

ANSI C63.10-2009

The above equipment (model: WNDR3700v4) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY :** Celine Chou , **DATE :** Apr. 26, 2013  
Celine Chou / Specialist

**APPROVED BY :** Ken Liu , **DATE :** Apr. 26, 2013  
Ken Liu / Senior Manager

## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART E (SECTION 15.407)			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
15.407(b)(6)	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -7.77dB at 0.59531MHz.
15.407(b/1/2/3) (b)(6)	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -0.5dB at 5470.00MHz.
15.407(a/1/2)	Max Average Transmit Power	PASS	Meet the requirement of limit.
15.407(a)(6)	Peak Power Excursion	PASS	Meet the requirement of limit.
15.407(a/1/2)	Peak Power Spectral Density	PASS	Meet the requirement of limit.
15.407(g)	Frequency Stability	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is UFL not a standard connector.

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	2.93 dB
	200MHz ~ 1000MHz	2.95 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>EUT</b>	N600 Wireless Dual Band Gigabit Router
<b>MODEL NO.</b>	WNDR3700v4
<b>POWER SUPPLY</b>	12Vdc (Adapter)
<b>MODULATION TYPE</b>	64QAM, 16QAM, QPSK, BPSK
<b>MODULATION TECHNOLOGY</b>	OFDM
<b>TRANSFER RATE</b>	802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps 802.11n: up to 300.0Mbps
<b>OPERATING FREQUENCY</b>	5260 ~ 5320MHz & 5500 ~ 5700MHz
<b>NUMBER OF CHANNEL</b>	5260 ~ 5320MHz: 4 for 802.11a, 802.11n (20MHz) 2 for 802.11n (40MHz) 5500 ~ 5700MHz: 7 for 802.11a, 802.11n (20MHz) 3 for 802.11n (40MHz)
<b>OUTPUT POWER</b>	165.818mW for 5260 ~ 5320MHz 222.146mW for 5500 ~ 5700MHz
<b>ANTENNA TYPE</b>	Printed antenna with 2.50dBi gain
<b>ANTENNA CONNECTOR</b>	UFL
<b>DATA CABLE</b>	N/A
<b>I/O PORTS</b>	RJ45, USB
<b>ACCESSORY DEVICES</b>	Adapter

**NOTE:**

1. This report is prepared for FCC class II permissive change. The difference compared with the original report is adding frequency band from 5.26 to 5.32GHz and 5.50 to 5.70GHz by software.
2. The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitters and two receivers.

MODULATION MODE	TX FUNCTION
802.11b	2TX
802.11g	2TX
802.11a	2TX
802.11n (20MHz)	2TX
802.11n (40MHz)	2TX

3. The EUT uses following adapters:

<b>ADAPTER 1</b>	
<b>BRAND</b>	NETGEAR
<b>MODEL</b>	MU30-5120250-A1
<b>P/N</b>	332-10234-01
<b>INPUT POWER</b>	100-240Vac, 50/60Hz, 0.8A
<b>OUTPUT POWER</b>	12Vdc, 2.5A
<b>POWER LINE</b>	1.8m non-shielded cable without core

<b>ADAPTER 2</b>	
<b>BRAND</b>	NETGEAR
<b>MODEL</b>	P030WF120B 11200-6LF
<b>P/N</b>	332-10200-02
<b>INPUT POWER</b>	100-240Vac, 50/60Hz, 1.0A
<b>OUTPUT POWER</b>	12Vdc, 2.5A
<b>POWER LINE</b>	1.8m non-shielded cable without core

\*Adapter 1 was the worst for the final tests.

4. The EUT has disabled the 5600-5650MHz band by S/W to avoid 5600-5650MHz band for FCC certification.
5. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.



### 3.2 DESCRIPTION OF TEST MODES

#### FOR 5260 ~ 5320MHz

4 channels are provided for 802.11a, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
52	5260 MHz	60	5300 MHz
56	5280 MHz	64	5320 MHz

2 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
54	5270 MHz	62	5310 MHz

#### FOR 5500 ~ 5700MHz

7 channels are provided for 802.11a, 802.11n (20MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
100	5500 MHz	116	5580 MHz
104	5520 MHz	136	5680 MHz
108	5540 MHz	140	5700 MHz
112	5560 MHz		

3 channels are provided for 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
102	5510 MHz	134	5670 MHz
110	5550 MHz		

### 3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz      **RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission      **APCM**: Antenna Port Conducted Measurement

**NOTE:**  
The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Y-plane**.

#### **RADIATED EMISSION TEST (ABOVE 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11a	5260-5320	52 to 64	52, 60, 64	OFDM	BPSK	6.0
-	802.11n (20MHz)		52 to 64	52, 60, 64	OFDM	BPSK	7.2
-	802.11n (40MHz)		54 to 62	54, 62	OFDM	BPSK	15.0
-	802.11a	5500-5700	100 to 140	100, 116, 140	OFDM	BPSK	6.0
-	802.11n (20MHz)		100 to 140	100, 116, 140	OFDM	BPSK	7.2
-	802.11n (40MHz)		102 to 134	102, 110, 134	OFDM	BPSK	15.0

#### **RADIATED EMISSION TEST (BELOW 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11n (20MHz)	5260-5320	52 to 64	52	OFDM	BPSK	7.2
-	802.11n (40MHz)	5500-5700	102 to 134	110	OFDM	BPSK	15.0

**POWER LINE CONDUCTED EMISSION TEST:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11n (20MHz)	5260-5320	52 to 64	52	OFDM	BPSK	7.2
-	802.11n (40MHz)	5500-5700	102 to 134	110	OFDM	BPSK	15.0

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
-	802.11a	5260-5320	52 to 64	52, 60, 64	OFDM	BPSK	6.0
-	802.11n (20MHz)		52 to 64	52, 60, 64	OFDM	BPSK	7.2
-	802.11n (40MHz)		54 to 62	54, 62	OFDM	BPSK	15.0
-	802.11a	5500-5700	100 to 140	100, 116, 140	OFDM	BPSK	6.0
-	802.11n (20MHz)		100 to 140	100, 116, 140	OFDM	BPSK	7.2
-	802.11n (40MHz)		102 to 134	102, 110, 134	OFDM	BPSK	15.0

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Anderson Hong Ted Chang
RE<1G	25deg. C, 64%RH	120Vac, 60Hz	Alan Wu
PLC	25deg. C, 60%RH	120Vac, 60Hz	Daniel Lee
APCM	25deg. C, 65%RH	120Vac, 60Hz	Nick Chen



A D T


### 3.3 DUTY CYCLE OF TEST SIGNAL

If duty cycle is < 98%, duty factor shall be considered.

**802.11a:** Duty cycle = 1.359/1.404 = 0.968, Duty factor =  $10 * \log(1/0.968) = 0.14$

**802.11n (20MHz):** Duty cycle = 1.271/1.316 = 0.966, Duty factor =  $10 * \log(1/0.966) = 0.15$

**802.11n (40MHz):** Duty cycle = 0.339/0.372 = 0.911, Duty factor =  $10 * \log(1/0.911) = 0.40$



### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	USB DONGLE	Transcend	N/A	N/A	N/A
2	NOTEBOOK	DELL	E5410	1HC2XM1	FCC DoC Approved
3	NOTEBOOK	DELL	E5410	6RP2YM1	FCC DoC Approved

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A
2	10m RJ45 UTP cable
3	10m RJ45 UTP cable

**NOTE:**

1. All power cords of the above support units are non shielded (1.8m).
2. Items 2~3 acted as communication partners to transfer data.

### 3.4.1 CONFIGURATION OF SYSTEM UNDER TEST



### 3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart E (15.407)**

**789033 D01 General UNII Test Procedures v01 r02**

**662911 D01 Multiple Transmitter Output v01 r02**

**ANSI C63.10-2009**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

## 4. TEST TYPES AND RESULTS

### 4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### 4.1.2 LIMITS OF UNWANTED EMISSION OUT OF THE RESTRICTED BANDS

APPLICABLE TO	LIMIT	
	FIELD STRENGTH AT 3m (dBµV/m)	
	PK	AV
	74	54
	EIRP LIMIT (dBm)	EQUIVALENT FIELD STRENGTH AT 3m (dBµV/m)
√	PK	PK
	-27	68.3

**NOTE:** The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).}$$





### 4.1.3 TEST INSTRUMENTS

**Tested Date: Jul. 18 ~ Jul. 25, 2012**

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100744	Apr. 19, 2012	Apr. 18, 2013
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100269	Jan. 28, 2012	Jan. 27, 2013
BILOG Antenna SCHWARZBECK	VULB9168	9168-156	Apr. 03, 2012	Apr. 02, 2013
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-209	Sep. 03, 2011	Sep. 02, 2012
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 11, 2012	Jul. 10, 2013
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier Agilent	8449B	3008A01911	Oct. 25, 2011	Oct. 24, 2012
Preamplifier Agilent	8447D	2944A10638	Oct. 25, 2011	Oct. 24, 2012
RF signal cable HUBER+SUHNER	SUCOFLEX 104	295013/4 283403/4	Aug. 28, 2012	Aug. 27, 2013
RF signal cable Worken	8D-FB	Cable-HYCH9-01	Aug. 11, 2012	Aug. 10, 2013
Software	ADT_Radiated_ V7.6.15.9.2	NA	NA	NA
Antenna Tower EMCO	2070/2080	512.835.4684	NA	NA
Turn Table EMCO	2087-2.03	NA	NA	NA
Antenna Tower & Turn Table Controller EMCO	2090	NA	NA	NA
26GHz ~ 40GHz Amplifier	EM26400	815221	Oct. 25, 2011	Oct. 24, 2012
High Speed Peak Power Meter	ML2495A	0824011	Jul. 30, 2011	Jul. 29, 2012
Power Sensor	MA2411B	0738171	Jul. 30, 2011	Jul. 29, 2012

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
  3. The test was performed in HwaYa Chamber 9.
  4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  5. The FCC Site Registration No. is 215374.
  6. The IC Site Registration No. is IC 7450F-9.



**Tested Date: Mar. 25 ~ Apr. 25, 2013**

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Aug. 21, 2012	Aug. 20, 2013
Spectrum Analyzer ROHDE & SCHWARZ	FSU 43	100115	Oct. 25, 2012	Oct. 24, 2013
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Mar. 25, 2013	Mar. 24, 2014
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-404	Dec. 22, 2012	Dec. 21, 2013
HORN Antenna SCHWARZBECK	BBHA 9170	148	Jul. 11, 2012	Jul. 10, 2013
Loop Antenna	HFH2-Z2	100070	Jan. 31, 2012	Jan. 30, 2014
Preamplifier Agilent	8449B	3008A01961	Oct. 25, 2012	Oct. 24, 2013
Preamplifier Agilent	8447D	2944A10738	Oct. 23, 2012	Oct. 22, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309220/4	Aug. 28, 2012	Aug. 27, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250724/4	Aug. 28, 2012	Aug. 27, 2013
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	295012/4	Aug. 28, 2012	Aug. 27, 2013
Software BV ADT	ADT_Radiated_ V7.6.15.9.2	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA	NA
Antenna Tower Controller inn-co GmbH	CO2000	019303	NA	NA
Turn Table BV ADT	TT100.	TT93021704	NA	NA
Turn Table Controller BV ADT	SC100.	SC93021704	NA	NA
26GHz ~ 40GHz Amplifier	EM26400	815221	Oct. 25, 2012	Oct. 24, 2013
High Speed Peak Power Meter	ML2495A	0824011	Jul. 30, 2011	Jul. 29, 2012
Power Sensor	MA2411B	0738171	Jul. 30, 2011	Jul. 29, 2012

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The calibration interval of the loop antenna is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
  3. The test was performed in HwaYa Chamber 4.
  4. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
  5. The FCC Site Registration No. is 460141.
  6. The IC Site Registration No. is IC7450F-4.

#### 4.1.4 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 1kHz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.1.6 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.7 EUT OPERATING CONDITION

- Placed the EUT on the testing table.
- Prepared two notebooks to act as communication partners and placed them outside of testing area.
- The communication partner connected with EUT via a RJ45 cable and run a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- The communication partner sent data to EUT by command "PING".

#### 4.1.8 TEST RESULTS

#### ABOVE 1GHz DATA :

#### 802.11a

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 52	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5000.00	55.7 PK	74.0	-18.3	1.10 H	218	17.80	37.90
2	5000.00	43.8 AV	54.0	-10.2	1.10 H	218	5.90	37.90
3	5150.00	55.4 PK	74.0	-18.6	1.04 H	221	17.20	38.20
4	5150.00	41.8 AV	54.0	-12.2	1.04 H	221	3.60	38.20
5	*5260.00	105.6 PK			1.04 H	221	67.30	38.30
6	*5260.00	96.5 AV			1.04 H	221	58.20	38.30
7	#10520.00	56.1 PK	68.3	-12.2	1.00 H	80	7.80	48.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5000.00	57.7 PK	74.0	-16.3	1.18 V	269	19.80	37.90
2	5000.00	48.5 AV	54.0	-5.5	1.18 V	269	10.60	37.90
3	5150.00	56.3 PK	74.0	-17.7	1.01 V	265	18.10	38.20
4	5150.00	43.0 AV	54.0	-11.0	1.01 V	265	4.80	38.20
5	*5260.00	116.6 PK			1.01 V	267	78.30	38.30
6	*5260.00	106.5 AV			1.01 V	267	68.20	38.30
7	#10520.00	57.1 PK	68.3	-11.2	1.27 V	334	8.80	48.30

#### REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 60	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5000.00	55.3 PK	74.0	-18.7	1.11 H	221	17.40	37.90
2	5000.00	43.4 AV	54.0	-10.6	1.11 H	221	5.50	37.90
3	*5300.00	105.3 PK			1.04 H	220	66.90	38.40
4	*5300.00	95.8 AV			1.04 H	220	57.40	38.40
5	10600.00	55.2 PK	74.0	-18.8	1.00 H	83	6.90	48.30
6	10600.00	42.3 AV	54.0	-11.7	1.00 H	83	-6.00	48.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5000.00	57.4 PK	74.0	-16.6	1.18 V	268	19.50	37.90
2	5000.00	47.4 AV	54.0	-6.6	1.18 V	268	9.50	37.90
3	*5300.00	117.4 PK			1.04 V	113	79.00	38.40
4	*5300.00	107.3 AV			1.04 V	113	68.90	38.40
5	10600.00	55.8 PK	74.0	-18.2	1.25 V	331	7.50	48.30
6	10600.00	43.2 AV	54.0	-10.8	1.25 V	331	-5.10	48.30

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 64	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5000.00	55.7 PK	74.0	-18.3	1.13 H	220	17.80	37.90
2	5000.00	43.7 AV	54.0	-10.3	1.13 H	220	5.80	37.90
3	*5320.00	103.6 PK			1.04 H	224	65.20	38.40
4	*5320.00	93.9 AV			1.04 H	224	55.50	38.40
5	5350.00	55.7 PK	74.0	-18.3	1.04 H	224	17.20	38.50
6	5350.00	43.7 AV	54.0	-10.3	1.04 H	224	5.20	38.50
7	10640.00	55.0 PK	74.0	-19.0	1.00 H	88	6.50	48.50
8	10640.00	42.0 AV	54.0	-12.0	1.00 H	88	-6.50	48.50
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5000.00	58.7 PK	74.0	-15.3	1.19 V	273	20.80	37.90
2	5000.00	46.8 AV	54.0	-7.2	1.19 V	273	8.90	37.90
3	*5320.00	115.6 PK			1.02 V	107	77.20	38.40
4	*5320.00	105.7 AV			1.02 V	107	67.30	38.40
5	5350.00	70.6 PK	74.0	-3.4	1.02 V	107	32.10	38.50
6	5350.00	53.0 AV	54.0	-1.0	1.02 V	107	14.50	38.50
7	10640.00	55.3 PK	74.0	-18.7	1.21 V	337	6.80	48.50
8	10640.00	42.7 AV	54.0	-11.3	1.21 V	337	-5.80	48.50

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 100	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Ted Chang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	59.6 PK	74.0	-14.4	1.00 H	282	20.06	39.57
2	5460.00	45.9 AV	54.0	-8.2	1.00 H	282	6.28	39.57
3	#5470.00	66.4 PK	68.3	-1.9	1.00 H	282	26.78	39.59
4	*5500.00	109.7 PK			1.00 H	285	70.03	39.67
5	*5500.00	99.9 AV			1.00 H	285	60.23	39.67
6	11000.00	63.9 PK	74.0	-10.2	1.00 H	325	10.63	53.22
7	11000.00	50.6 AV	54.0	-3.4	1.00 H	325	-2.64	53.22
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	62.8 PK	74.0	-11.3	1.15 V	290	23.18	39.57
2	5460.00	50.1 AV	54.0	-3.9	1.15 V	290	10.57	39.57
3	#5470.00	67.8 PK	68.3	-0.5	1.15 V	290	28.22	39.59
4	*5500.00	116.2 PK			1.11 V	270	76.52	39.67
5	*5500.00	106.0 AV			1.11 V	270	66.35	39.67
6	11000.00	61.5 PK	74.0	-12.6	1.15 V	330	8.23	53.22
7	11000.00	49.0 AV	54.0	-5.0	1.15 V	330	-4.23	53.22

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.





A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 116	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5000.00	54.7 PK	74.0	-19.3	1.12 H	217	16.80	37.90
2	5000.00	42.7 AV	54.0	-11.3	1.12 H	217	4.80	37.90
3	5440.00	55.7 PK	74.0	-18.3	1.00 H	231	17.10	38.60
4	5440.00	42.7 AV	54.0	-11.3	1.00 H	231	4.10	38.60
5	*5580.00	102.3 PK			1.00 H	104	63.40	38.90
6	*5580.00	92.4 AV			1.00 H	104	53.50	38.90
7	11600.00	55.7 PK	74.0	-18.3	1.00 H	124	6.60	49.10
8	11600.00	42.4 AV	54.0	-11.6	1.00 H	124	-6.70	49.10
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5000.00	56.9 PK	74.0	-17.1	1.00 V	269	19.00	37.90
2	5000.00	47.1 AV	54.0	-6.9	1.00 V	269	9.20	37.90
3	5440.00	61.7 PK	74.0	-12.3	1.00 V	120	23.10	38.60
4	5440.00	51.0 AV	54.0	-3.0	1.00 V	120	12.40	38.60
5	*5580.00	117.0 PK			1.07 V	122	78.10	38.90
6	*5580.00	106.7 AV			1.07 V	122	67.80	38.90
7	11600.00	55.7 PK	74.0	-18.3	1.00 V	83	6.60	49.10
8	11600.00	42.5 AV	54.0	-11.5	1.00 V	83	-6.60	49.10

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 140	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Ted Chang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5700.00	108.3 PK			1.14 H	282	68.25	40.07
2	*5700.00	98.6 AV			1.14 H	282	58.55	40.07
3	#5725.00	61.5 PK	68.3	-6.8	1.00 H	279	21.38	40.14
4	11400.00	60.3 PK	74.0	-13.7	1.00 H	236	7.45	52.85
5	11400.00	47.8 AV	54.0	-6.2	1.00 H	236	-5.02	52.85
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5700.00	116.0 PK			1.00 V	272	75.89	40.07
2	*5700.00	106.6 AV			1.00 V	272	66.50	40.07
3	#5725.00	67.6 PK	68.3	-0.7	1.01 V	273	27.42	40.14
4	11400.00	63.2 PK	74.0	-10.8	1.00 V	261	10.31	52.85
5	11400.00	50.1 AV	54.0	-3.9	1.00 V	261	-2.75	52.85

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11n (20MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 52	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5000.00	55.2 PK	74.0	-18.8	1.00 H	219	17.30	37.90
2	5000.00	43.4 AV	54.0	-10.6	1.00 H	219	5.50	37.90
3	5150.00	52.7 PK	74.0	-21.3	1.02 H	68	14.50	38.20
4	5150.00	41.3 AV	54.0	-12.7	1.02 H	68	3.10	38.20
5	*5260.00	104.4 PK			1.02 H	68	66.10	38.30
6	*5260.00	94.4 AV			1.02 H	68	56.10	38.30
7	#10520.00	55.4 PK	68.3	-12.9	1.00 H	123	7.10	48.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5000.00	58.2 PK	74.0	-15.8	1.00 V	268	20.30	37.90
2	5000.00	47.9 AV	54.0	-6.1	1.00 V	268	10.00	37.90
3	5150.00	55.5 PK	74.0	-18.5	1.04 V	114	17.30	38.20
4	5150.00	43.5 AV	54.0	-10.5	1.04 V	114	5.30	38.20
5	*5260.00	117.2 PK			1.04 V	114	78.90	38.30
6	*5260.00	106.9 AV			1.04 V	114	68.60	38.30
7	#10520.00	56.1 PK	68.3	-12.2	1.00 V	80	7.80	48.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 60	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5000.00	54.9 PK	74.0	-19.1	1.00 H	222	17.00	37.90
2	5000.00	43.1 AV	54.0	-10.9	1.00 H	222	5.20	37.90
3	*5300.00	102.6 PK			1.02 H	84	64.20	38.40
4	*5300.00	92.6 AV			1.02 H	84	54.20	38.40
5	10600.00	55.0 PK	74.0	-19.0	1.00 H	128	6.70	48.30
6	10600.00	42.0 AV	54.0	-12.0	1.00 H	128	-6.30	48.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5000.00	57.9 PK	74.0	-16.1	1.00 V	261	20.00	37.90
2	5000.00	47.6 AV	54.0	-6.4	1.00 V	261	9.70	37.90
3	*5300.00	116.4 PK			1.03 V	113	78.00	38.40
4	*5300.00	106.3 AV			1.03 V	113	67.90	38.40
5	10600.00	54.7 PK	74.0	-19.3	1.00 V	83	6.40	48.30
6	10600.00	41.8 AV	54.0	-12.2	1.00 V	83	-6.50	48.30

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 64	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Ted Chang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5320.00	112.3 PK			1.00 H	283	72.85	39.40
2	*5320.00	101.9 AV			1.00 H	283	62.52	39.40
3	5350.00	64.1 PK	74.0	-9.9	1.00 H	282	24.69	39.41
4	5350.00	48.3 AV	54.0	-5.7	1.00 H	282	8.92	39.41
5	10640.00	58.6 PK	74.0	-15.4	1.04 H	256	7.06	51.54
6	10640.00	45.8 AV	54.0	-8.2	1.04 H	256	-5.78	51.54
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5320.00	116.2 PK			1.00 V	293	76.76	39.40
2	*5320.00	106.5 AV			1.00 V	293	67.10	39.40
3	5350.00	72.6 PK	74.0	-1.4	1.00 V	275	33.23	39.41
4	5350.00	52.4 AV	54.0	-1.6	1.00 V	275	12.96	39.41
5	10640.00	58.9 PK	74.0	-15.1	1.04 V	163	7.36	51.54
6	10640.00	47.8 AV	54.0	-6.3	1.04 V	163	-3.79	51.54

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 100	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Ted Chang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	57.8 PK	74.0	-16.3	1.00 H	281	18.18	39.57
2	5460.00	45.2 AV	54.0	-8.8	1.00 H	281	5.59	39.57
3	#5470.00	64.8 PK	68.3	-3.5	1.00 H	281	25.19	39.59
4	*5500.00	109.3 PK			1.00 H	282	69.65	39.67
5	*5500.00	99.8 AV			1.00 H	282	60.14	39.67
6	11000.00	60.6 PK	74.0	-13.4	1.23 H	54	7.42	53.22
7	11000.00	47.6 AV	54.0	-6.4	1.23 H	54	-5.58	53.22
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	62.2 PK	74.0	-11.8	1.14 V	289	22.59	39.57
2	5460.00	48.5 AV	54.0	-5.5	1.14 V	289	8.93	39.57
3	#5470.00	67.8 PK	68.3	-0.6	1.14 V	289	28.16	39.59
4	*5500.00	115.1 PK			1.11 V	269	75.39	39.67
5	*5500.00	105.5 AV			1.11 V	269	65.80	39.67
6	11000.00	62.8 PK	74.0	-11.2	1.32 V	213	9.57	53.22
7	11000.00	49.5 AV	54.0	-4.5	1.32 V	213	-3.70	53.22

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 116	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	55.1 PK	74.0	-18.9	1.08 H	228	16.50	38.60
2	5440.00	42.3 AV	54.0	-11.7	1.08 H	228	3.70	38.60
3	*5580.00	106.1 PK			1.05 H	221	67.20	38.90
4	*5580.00	96.0 AV			1.05 H	221	57.10	38.90
5	11160.00	56.0 PK	74.0	-18.0	1.36 H	127	6.70	49.30
6	11160.00	45.5 AV	54.0	-8.5	1.36 H	127	-3.80	49.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5440.00	57.6 PK	74.0	-16.4	1.01 V	97	19.00	38.60
2	5440.00	49.0 AV	54.0	-5.0	1.01 V	97	10.40	38.60
3	*5580.00	116.9 PK			1.04 V	118	78.00	38.90
4	*5580.00	107.0 AV			1.04 V	118	68.10	38.90
5	11160.00	57.0 PK	74.0	-17.0	1.08 V	347	7.70	49.30
6	11160.00	46.2 AV	54.0	-7.8	1.08 V	347	-3.10	49.30

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 140	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Ted Chang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5700.00	105.9 PK			1.00 H	288	65.81	40.07
2	*5700.00	95.5 AV			1.00 H	288	55.38	40.07
3	#5725.00	60.6 PK	68.3	-7.7	1.18 H	297	20.44	40.14
4	11400.00	60.3 PK	74.0	-13.7	1.03 H	210	7.45	52.85
5	11400.00	47.6 AV	54.0	-6.4	1.03 H	210	-5.26	52.85
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5700.00	115.5 PK			1.00 V	291	75.43	40.07
2	*5700.00	105.7 AV			1.00 V	291	65.61	40.07
3	#5725.00	67.1 PK	68.3	-1.2	1.04 V	274	27.00	40.14
4	11400.00	63.2 PK	74.0	-10.8	1.00 V	241	10.31	52.85
5	11400.00	49.3 AV	54.0	-4.8	1.00 V	241	-3.60	52.85

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.





A D T

802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 54	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anderson Hong

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5270.00	102.1 PK			1.21 H	221	63.70	38.40
2	*5270.00	92.4 AV			1.21 H	221	54.00	38.40
3	5350.00	60.1 PK	74.0	-13.9	1.22 H	227	21.60	38.50
4	5350.00	47.2 AV	54.0	-6.8	1.22 H	227	8.70	38.50
5	5440.00	57.2 PK	74.0	-16.8	1.08 H	211	18.60	38.60
6	5440.00	47.1 AV	54.0	-6.9	1.08 H	211	8.50	38.60
7	#10540.00	54.8 PK	68.3	-13.5	1.05 H	107	6.50	48.30
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5270.00	113.1 PK			1.02 V	105	74.70	38.40
2	*5270.00	104.3 AV			1.02 V	105	65.90	38.40
3	5350.00	65.4 PK	74.0	-8.6	1.00 V	97	26.90	38.50
4	5350.00	52.8 AV	54.0	-1.2	1.00 V	97	14.30	38.50
5	5440.00	61.5 PK	74.0	-12.5	1.09 V	120	22.90	38.60
6	5440.00	51.6 AV	54.0	-2.4	1.09 V	120	13.00	38.60
7	#10540.00	56.0 PK	68.3	-12.3	1.24 V	269	7.70	48.30

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 62	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Ted Chang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5310.00	105.2 PK			1.00 H	284	65.78	39.39
2	*5310.00	92.2 AV			1.00 H	284	52.80	39.39
3	5350.00	64.6 PK	74.0	-9.4	1.00 H	283	25.21	39.41
4	5350.00	49.4 AV	54.0	-4.6	1.00 H	283	10.00	39.41
5	10620.00	58.8 PK	74.0	-15.2	1.23 H	331	7.25	51.51
6	10620.00	45.9 AV	54.0	-8.1	1.23 H	331	-5.60	51.51
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5310.00	109.3 PK			1.00 V	68	69.87	39.39
2	*5310.00	96.4 AV			1.00 V	68	57.04	39.39
3	5350.00	68.8 PK	74.0	-5.2	1.07 V	291	29.35	39.41
4	5350.00	53.0 AV	54.0	-1.0	1.07 V	291	13.59	39.41
5	10620.00	61.7 PK	74.0	-12.3	1.00 V	354	10.18	51.51
6	10620.00	47.8 AV	54.0	-6.2	1.00 V	354	-3.71	51.51

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 102	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Ted Chang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	59.7 PK	74.0	-14.3	1.00 H	284	20.16	39.57
2	5460.00	46.2 AV	54.0	-7.8	1.00 H	284	6.61	39.57
3	#5470.00	63.9 PK	68.3	-4.4	1.00 H	284	24.28	39.59
4	*5510.00	102.5 PK			1.00 H	284	62.81	39.69
5	*5510.00	91.8 AV			1.00 H	284	52.06	39.69
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	62.8 PK	74.0	-11.2	1.14 V	289	23.27	39.57
2	5460.00	49.1 AV	54.0	-4.9	1.14 V	289	9.51	39.57
3	#5470.00	67.8 PK	68.3	-0.5	1.14 V	289	28.17	39.59
4	*5510.00	109.8 PK			1.12 V	269	70.13	39.69
5	*5510.00	96.5 AV			1.12 V	269	56.81	39.69
6	11020.00	63.6 PK	74.0	-10.4	1.28 V	189	10.43	53.16
7	11020.00	49.9 AV	54.0	-4.1	1.28 V	189	-3.25	53.16

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 110	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Ted Chang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	63.0 PK	74.0	-11.0	1.00 H	283	23.43	39.57
2	5460.00	47.9 AV	54.0	-6.1	1.00 H	283	8.36	39.57
3	#5470.00	63.5 PK	68.3	-4.8	1.00 H	283	23.91	39.59
4	*5550.00	110.6 PK			1.00 H	284	70.81	39.75
5	*5550.00	97.86 PK			1.00 H	284	58.11	39.75
6	11100.00	60.0 PK	74.0	-14.0	1.45 H	218	7.07	52.93
7	11100.00	47.3 AV	54.0	-6.7	1.45 H	218	-5.61	52.93
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5460.00	65.4 PK	74.0	-8.6	1.26 V	289	25.79	39.57
2	5460.00	51.7 AV	54.0	-2.3	1.26 V	289	12.10	39.57
3	#5470.00	67.3 PK	68.3	-1.0	1.26 V	289	27.72	39.59
4	*5550.00	117.1 PK			1.12 V	270	77.32	39.75
5	*5550.00	103.99 PK			1.12 V	270	64.24	39.75
6	11100.00	63.3 PK	74.0	-10.7	1.00 V	39	10.40	52.93
7	11100.00	49.1 AV	54.0	-4.9	1.00 V	39	-3.80	52.93

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 134	FREQUENCY RANGE	1 ~ 40GHz
INPUT POWER	120Vac, 60Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Ted Chang

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5670.00	107.9 PK			1.16 H	281	67.88	40.00
2	*5670.00	94.7 AV			1.16 H	281	54.67	40.00
3	#5725.00	59.8 PK	68.3	-8.5	1.00 H	282	19.66	40.14
4	11340.00	60.4 PK	74.0	-13.6	1.37 H	107	7.50	52.94
5	11340.00	47.2 AV	54.0	-6.8	1.37 H	107	-5.74	52.94
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5670.00	114.5 PK			1.07 V	270	74.50	40.00
2	*5670.00	101.1 AV			1.07 V	270	61.11	40.00
3	#5725.00	67.5 PK	68.3	-0.8	1.09 V	273	27.37	40.14
4	11340.00	63.3 PK	74.0	-10.7	1.00 V	21	10.40	52.94
5	11340.00	50.0 AV	54.0	-4.0	1.00 V	21	-2.94	52.94

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

**BELOW 1GHz WORST-CASE DATA : 802.11n (20MHz)**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 52	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 64%RH	TESTED BY	Alan Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	72.67	33.6 QP	40.0	-6.4	2.00 H	207	21.80	11.80
2	125.17	34.2 QP	43.5	-9.3	2.00 H	98	21.60	12.60
3	249.60	34.6 QP	46.0	-11.4	1.00 H	269	21.00	13.60
4	500.42	39.9 QP	46.0	-6.1	1.75 H	127	18.80	21.10
5	624.85	35.4 QP	46.0	-10.6	1.00 H	176	11.70	23.70
6	751.23	40.4 QP	46.0	-5.6	1.00 H	87	14.60	25.80
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	61.01	36.7 QP	40.0	-3.3	1.50 V	118	23.20	13.50
2	74.62	36.7 QP	40.0	-3.3	1.50 V	137	25.30	11.40
3	125.17	37.4 QP	43.5	-6.1	1.00 V	238	24.80	12.60
4	500.42	39.3 QP	46.0	-6.7	1.00 V	83	18.20	21.10
5	599.58	40.3 QP	46.0	-5.7	1.00 V	122	16.80	23.50
6	751.23	39.6 QP	46.0	-6.4	1.25 V	46	13.80	25.80

**REMARKS:**

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



A D T

802.11n (40MHz)

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 110	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 64%RH	TESTED BY	Alan Wu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	74.62	30.5 QP	40.0	-9.5	2.00 H	241	19.10	11.40
2	125.17	34.4 QP	43.5	-9.1	1.50 H	113	21.80	12.60
3	249.60	35.0 QP	46.0	-11.0	1.00 H	254	21.40	13.60
4	290.43	33.2 QP	46.0	-12.8	1.00 H	223	17.90	15.30
5	500.42	39.5 QP	46.0	-6.5	1.75 H	137	18.40	21.10
6	751.23	40.9 QP	46.0	-5.1	1.00 H	153	15.10	25.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	61.01	36.3 QP	40.0	-3.7	1.00 V	158	22.80	13.50
2	72.67	36.5 QP	40.0	-3.5	1.25 V	129	24.70	11.80
3	125.17	37.3 QP	43.5	-6.2	1.00 V	231	24.70	12.60
4	500.42	39.6 QP	46.0	-6.4	1.00 V	149	18.50	21.10
5	751.23	39.6 QP	46.0	-6.4	1.25 V	352	13.80	25.80
6	875.67	38.4 QP	46.0	-7.6	3.00 V	191	10.20	28.20

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

## 4.2 CONDUCTED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 4.2.2 TEST INSTRUMENTS

**Tested Date: Jul. 05, 2012**

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100289	Nov. 16, 2011	Nov. 15, 2012
RF signal cable Woken	5D-FB	Cable-HYC01-01	Dec. 28, 2011	Dec. 27, 2012
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Jul. 02, 2012	Jul. 01, 2013
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Feb. 04, 2012	Feb. 03, 2013
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in HwaYa Shielded Room 1.
  3. The VCCI Site Registration No. is C-2040.



### 4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

### 4.2.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.

## 4.2.7 TEST RESULTS


### CONDUCTED WORST-CASE DATA : 802.11n (20MHz)

<b>PHASE</b>	Line 1	<b>6dB BANDWIDTH</b>	9kHz
<b>CHANNEL</b>	Channel 52		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	0.14	45.96	37.16	46.10	37.30	65.79	55.79	-19.68	-18.48
2	0.22422	0.22	41.66	28.33	41.88	28.55	62.66	52.66	-20.78	-24.11
3	0.59141	0.18	44.17	36.63	44.35	36.81	56.00	46.00	-11.65	-9.19
4	0.98594	0.21	30.25	23.50	30.46	23.71	56.00	46.00	-25.54	-22.29
5	1.94922	0.24	27.80	16.72	28.04	16.96	56.00	46.00	-27.96	-29.04
6	3.78125	0.33	28.57	19.96	28.90	20.29	56.00	46.00	-27.10	-25.71

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.






A D T

PHASE	Line 2	6dB BANDWIDTH	9kHz
CHANNEL	Channel 52		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.23	50.54	39.36	50.77	39.59	66.00	56.00	-15.23	-16.41
2	0.17484	0.27	49.40	38.45	49.67	38.72	64.73	54.73	-15.05	-16.00
3	0.21250	0.31	46.24	38.38	46.55	38.69	63.11	53.11	-16.56	-14.42
4	0.58359	0.27	46.24	34.62	46.51	34.89	56.00	46.00	-9.49	-11.11
5	0.87735	0.29	31.63	24.79	31.92	25.08	56.00	46.00	-24.08	-20.92
6	2.92578	0.39	31.57	24.95	31.96	25.34	56.00	46.00	-24.04	-20.66

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.





A D T


802.11n (40MHz)

PHASE	Line 1	6dB BANDWIDTH	9kHz
CHANNEL	Channel 110		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
			1	0.15000	0.14	50.25	39.00	50.39	39.14	66.00
2	0.17758	0.19	47.49	36.15	47.68	36.34	64.60	54.60	-16.92	-18.26
3	0.29844	0.20	33.39	20.67	33.59	20.87	60.29	50.29	-26.70	-29.42
4	<b>0.59531</b>	<b>0.18</b>	<b>44.13</b>	<b>38.05</b>	<b>44.31</b>	<b>38.23</b>	<b>56.00</b>	<b>46.00</b>	<b>-11.69</b>	<b>-7.77</b>
5	1.93750	0.24	25.67	17.92	25.91	18.16	56.00	46.00	-30.09	-27.84
6	2.74219	0.28	24.83	16.88	25.11	17.16	56.00	46.00	-30.89	-28.84

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.






A D T

PHASE	Line 2	6dB BANDWIDTH	9kHz
CHANNEL	Channel 110		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.23	51.81	39.67	52.04	39.90	66.00	56.00	-13.96	-16.10
2	0.17745	0.28	49.60	38.83	49.88	39.11	64.60	54.60	-14.73	-15.50
3	0.58359	0.27	46.34	35.11	46.61	35.38	56.00	46.00	-9.39	-10.62
4	0.91172	0.29	33.26	25.83	33.55	26.12	56.00	46.00	-22.45	-19.88
5	1.73438	0.33	32.69	25.45	33.02	25.78	56.00	46.00	-22.98	-20.22
6	3.08984	0.40	27.24	18.74	27.64	19.14	56.00	46.00	-28.36	-26.86

**REMARKS:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



### 4.3 PEAK TRANSMIT POWER MEASUREMENT

#### 4.3.1 LIMITS OF PEAK TRANSMIT POWER MEASUREMENT

FREQUENCY BAND	LIMIT
5.150 ~ 5.250GHz	The lesser of 50mW (17dBm) or 4dBm + 10logB
5.250 ~ 5.350GHz	The lesser of 250mW (24dBm) or 11dBm + 10logB
5.470 ~ 5.725GHz	The lesser of 250mW (24dBm) or 11dBm + 10logB

**NOTE:** Where B is the 26dB emission bandwidth in MHz.

Per KDB 662911 D01 Multiple Transmitter Output v01r02 Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for NANT ≤ 4;


Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any NANT;

Array Gain = 5 log(NANT/NSS) dB or 3 dB, whichever is less for 20-MHz channel widths with NANT ≥ 5.


For power measurements on all other devices: Array Gain = 10 log(NANT/NSS) dB.

#### 4.3.2 TEST SETUP

##### FOR POWER OUTPUT MEASUREMENT



##### FOR 26dB BANDWIDTH



### 4.3.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

### 4.3.4 TEST PROCEDURE

#### FOR AVERAGE POWER MEASUREMENT

##### 802.11a and 802.11n (20MHz)

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

##### 802.11n (40MHz)

Duty cycle of test signal is < 98 %. Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

#### FOR 26dB BANDWIDTH

- 1) Set RBW = approximately 1% of the emission bandwidth.
- 2) Set the VBW > RBW.
- 3) Detector = Peak.
- 4) Trace mode = max hold.
- 5) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

### 4.3.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.



### 4.3.7 TEST RESULTS

#### POWER OUTPUT:

##### 802.11a

CHAN.	CHAN. FREQ. (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	POWER LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
52	5260	19.46	18.33	156.385	21.94	24	PASS
60	5300	19.51	18.55	160.945	22.07	24	PASS
64	5320	17.58	16.52	102.155	20.09	24	PASS
100	5500	15.67	16.49	81.464	19.11	24	PASS
116	5580	18.69	18.01	137.202	21.37	24	PASS
140	5700	16.16	16.03	81.392	19.11	24	PASS

##### 802.11n (20MHz)

CHAN.	CHAN. FREQ. (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	POWER LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
52	5260	19.71	18.59	<b>165.818</b>	22.20	24	PASS
60	5300	19.44	18.41	157.245	21.97	24	PASS
64	5320	17.36	17.97	117.111	20.69	24	PASS
100	5500	15.85	16.71	85.340	19.31	24	PASS
116	5580	18.67	18.18	139.387	21.44	24	PASS
140	5700	15.09	15.41	67.039	18.26	24	PASS

##### 802.11n (40MHz)

CHAN.	CHAN. FREQ. (MHz)	AVERAGE POWER (dBm)		TOTAL POWER (mW)	TOTAL POWER (dBm)	POWER LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1				
54	5270	17.52	17.32	110.445	20.43	24	PASS
62	5310	13.43	13.52	44.520	16.49	24	PASS
102	5510	13.67	13.49	45.617	16.59	24	PASS
110	5550	20.22	20.68	<b>222.146</b>	23.47	24	PASS
134	5670	18.40	18.70	143.314	21.56	24	PASS





A D T

## 26dB BANDWIDTH:

### 802.11a

CHANNEL	CHANNEL FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)		PASS / FAIL
		CHAIN 0	CHAIN 1	
52	5260	38.00	30.08	PASS
60	5300	32.55	29.24	PASS
64	5320	26.04	25.51	PASS
100	5500	25.57	25.14	PASS
116	5580	26.22	25.60	PASS
140	5700	25.40	24.17	PASS

### 802.11n (20MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)		PASS / FAIL
		CHAIN 0	CHAIN 1	
52	5260	40.77	42.42	PASS
60	5300	37.99	40.69	PASS
64	5320	27.11	27.80	PASS
100	5500	26.00	26.11	PASS
116	5580	26.77	26.84	PASS
140	5700	26.14	25.63	PASS

### 802.11n (40MHz)

CHANNEL	CHANNEL FREQUENCY (MHz)	26dBc BANDWIDTH (MHz)		PASS / FAIL
		CHAIN 0	CHAIN 1	
54	5270	65.09	54.91	PASS
62	5310	52.73	51.84	PASS
102	5510	51.96	53.17	PASS
110	5550	85.05	85.35	PASS
134	5670	53.30	52.95	PASS

## EUT HIGHEST CONDUCTED POWER

### 802.11a

FREQUENCY BAND (MHz)	MAX. POWER	
	OUTPUT POWER (mW)	OUTPUT POWER (dBm)
5250~5350	160.945	22.07
5470~5725	137.202	21.37

**NOTE:** Manufacturer provides Transmit Power Control description to meet this requirement.

### 802.11n (20MHz)

FREQUENCY BAND (MHz)	MAX. POWER	
	OUTPUT POWER (mW)	OUTPUT POWER (dBm)
5250~5350	165.818	22.20
5470~5725	139.386	21.44

**NOTE:** Manufacturer provides Transmit Power Control description to meet this requirement.

### 802.11n (40MHz)

FREQUENCY BAND (MHz)	MAX. POWER	
	OUTPUT POWER (mW)	OUTPUT POWER (dBm)
5250~5350	110.445	20.43
5470~5725	222.146	23.47


**NOTE:** Manufacturer provides Transmit Power Control description to meet this requirement.

## 4.4 PEAK POWER SPECTRAL DENSITY MEASUREMENT

### 4.4.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT

FREQUENCY BAND	LIMIT
5.250 ~ 5.350GHz	11dBm
5.470 ~ 5.725GHz	11dBm

### 4.4.2 TEST SETUP



### 4.4.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

### 4.4.4 TEST PROCEDURES

Using method SA-2

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 30 KHz, Set VBW  $\geq$  1 MHz, Detector = RMS
- 3) Set Channel power measure = 1MHz
- 4) Sweep time = auto, trigger set to "free run".
- 5) Trace average at least 100 traces in power averaging mode.
- 6) Record the max value and add 10 log (1/duty cycle)

#### 4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.4.6 EUT OPERATING CONDITIONS

Same as 4.3.6.

#### 4.4.7 TEST RESULTS

##### 802.11a

CHAN.	CHAN. FREQ. (MHz)	PSD (dBm)		TOTAL PSD W/O DUTY FACTOR (dBm)	DUTY FACTOR	TOTAL PSD WITH DUTY FACTOR (dBm)	MAX. LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1					
52	5260	7.53	5.83	9.77	0.14	9.91	11	PASS
60	5300	6.74	6.34	9.55	0.14	9.69	11	PASS
64	5320	4.59	4.54	7.58	0.14	7.72	11	PASS
100	5500	3.93	4.34	7.15	0.14	7.29	11	PASS
116	5580	5.48	5.49	8.50	0.14	8.64	11	PASS
140	5700	4.01	4.07	7.05	0.14	7.19	11	PASS

- NOTE:** 1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $2.5\text{dBi} + 10\log(2) = 5.51\text{dBi} < 6\text{dBi}$  , so the power density limit not to be reduced.
3. Refer to section 3.3 for duty cycle spectrum plot.

##### 802.11n (20MHz)

CHAN.	CHAN. FREQ. (MHz)	PSD (dBm)		TOTAL PSD W/O DUTY FACTOR (dBm)	DUTY FACTOR	TOTAL PSD WITH DUTY FACTOR (dBm)	MAX. LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1					
52	5260	7.13	7.21	10.18	0.15	10.33	11	PASS
60	5300	6.42	6.30	9.37	0.15	9.52	11	PASS
64	5320	4.96	4.95	7.97	0.15	8.12	11	PASS
100	5500	3.49	3.45	6.48	0.15	6.63	11	PASS
116	5580	5.25	4.96	8.12	0.15	8.27	11	PASS
140	5700	2.67	3.02	5.86	0.15	6.01	11	PASS

- NOTE:** 1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $2.5\text{dBi} + 10\log(2) = 5.51\text{dBi} < 6\text{dBi}$  , so the power density limit not to be reduced.
3. Refer to section 3.3 for duty cycle spectrum plot.

**802.11n (40MHz)**

CHAN.	CHAN. FREQ. (MHz)	PSD (dBm)		TOTAL PSD W/O DUTY FACTOR (dBm)	DUTY FACTOR	TOTAL PSD WITH DUTY FACTOR (dBm)	MAX. LIMIT (dBm)	PASS / FAIL
		CHAIN 0	CHAIN 1					
54	5270	2.99	1.42	5.29	0.40	5.69	11	PASS
62	5310	-1.88	-3.07	0.58	0.40	0.98	11	PASS
102	5510	-2.58	-1.61	0.94	0.40	1.34	11	PASS
110	5550	4.04	5.20	7.67	0.40	8.07	11	PASS
134	5670	2.50	3.09	5.82	0.40	6.22	11	PASS


- NOTE:** 1. Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain =  $2.5\text{dBi} + 10\log(2) = 5.51\text{dBi} < 6\text{dBi}$  , so the power density limit not to be reduced.
3. Refer to section 3.3 for duty cycle spectrum plot.

## 4.5 PEAK POWER EXCURSION MEASUREMENT

### 4.5.1 LIMITS OF PEAK POWER EXCURSION MEASUREMENT

Shall not exceed 13 dB.

### 4.5.2 TEST SETUP



### 4.5.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

### 4.5.4 TEST PROCEDURE

- 1) Set RBW = 1 MHz, VBW  $\geq$  3 MHz, Detector = peak.
- 2) Trace mode = max-hold. Allow the sweeps to continue until the trace stabilizes.
- 3) Use the peak search function to find the peak of the spectrum.
- 4) Measure the PPSD.
- 5) Compute the ratio of the maximum of the peak-max-hold spectrum to the PPSD.

### 4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

### 4.5.6 EUT OPERATING CONDITIONS

Same as 4.2.6




A D T

## 4.5.7 TEST RESULTS

### 802.11a


CHAN.	CHAN. FREQ. (MHz)	PEAK VALUE (dBm)		PPSD WITHOUT DUTY FACTOR (dBm)		PPSD WITH DUTY FACTOR (dBm)		PEAK EXCURSION (dB)		LIMIT (dB)	PASS /FAIL
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1		
52	5260	18.05	17.85	7.53	5.83	7.67	5.97	10.38	11.88	13	PASS
60	5300	17.15	17.78	6.74	6.34	6.88	6.48	10.27	11.30	13	PASS
64	5320	15.86	16.24	4.59	4.54	4.73	4.68	11.13	11.56	13	PASS
100	5500	14.14	16.07	3.93	4.34	4.07	4.48	10.07	11.59	13	PASS
116	5580	16.03	17.62	5.48	5.49	5.62	5.63	10.41	11.99	13	PASS
140	5700	14.72	15.78	4.01	4.07	4.15	4.21	10.57	11.57	13	PASS





**802.11n (20MHz)**


CHAN.	CHAN. FREQ. (MHz)	PEAK VALUE (dBm)		PPSD WITHOUT DUTY FACTOR (dBm)		PPSD WITH DUTY FACTOR (dBm)		PEAK EXCURSION (dB)		LIMIT (dB)	PASS /FAIL
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1		
52	5260	18.05	18.20	7.13	7.21	7.28	7.36	10.77	10.84	13	PASS
60	5300	17.01	17.11	6.42	6.30	6.57	6.45	10.44	10.66	13	PASS
64	5320	15.64	15.48	4.96	4.95	5.11	5.10	10.53	10.38	13	PASS
100	5500	14.56	14.66	3.49	3.45	3.64	3.60	10.92	11.06	13	PASS
116	5580	16.05	15.54	5.25	4.96	5.40	5.11	10.65	10.43	13	PASS
140	5700	14.02	13.99	2.67	3.02	2.82	3.17	11.20	10.82	13	PASS





802.11n (40MHz)

CHAN.	CHAN. FREQ. (MHz)	PEAK VALUE (dBm)		PPSD WITHOUT DUTY FACTOR (dBm)		PPSD WITH DUTY FACTOR (dBm)		PEAK EXCURSION (dB)		LIMIT (dB)	PASS /FAIL
		CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1	CHAIN 0	CHAIN 1		
54	5270	14.77	13.86	2.99	1.42	3.39	1.82	11.38	12.04	13	PASS
62	5310	10.20	9.24	-1.88	-3.07	-1.48	-2.67	11.68	11.91	13	PASS
102	5510	9.74	10.86	-2.58	-1.61	-2.18	-1.21	11.92	12.07	13	PASS
110	5550	16.50	17.43	4.04	5.20	4.44	5.60	12.06	11.83	13	PASS
134	5670	14.93	15.36	2.50	3.09	2.90	3.49	12.03	11.87	13	PASS




## 4.6 FREQUENCY STABILITY

### 4.6.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

The frequency of the carrier signal shall be maintained within band of operation

### 4.6.2 TEST SETUP



### 4.6.3 TEST INSTRUMENTS

Refer to section 4.1.3 to get information of above instrument.

#### 4.6.4 TEST PROCEDURE

- a. The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- b. Turn the EUT on and couple its output to a spectrum analyzer.
- c. Turn the EUT off and set the chamber to the highest temperature specified.
- d. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- e. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
- f. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

#### 4.6.5 DEVIATION FROM TEST STANDARD

No deviation.

#### 4.6.6 EUT OPERATING CONDITION

Set the EUT transmit at un-modulation mode to test frequency stability.



A D T

#### 4.6.7 TEST RESULTS

FREQUENCY STABILITY VERSUS TEMP.									
OPERATING FREQUENCY: 5260MHz									
TEMP. (°C)	POWER SUPPLY (Vac)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
		Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)
60	120	5259.9867	-0.00025	5259.995	-0.00010	5259.9857	-0.00027	5259.9966	-0.00006
50	120	5259.9976	-0.00005	5259.9958	-0.00008	5259.9988	-0.00002	5259.9973	-0.00005
40	120	5259.9814	-0.00035	5259.9879	-0.00023	5259.9892	-0.00021	5259.9863	-0.00026
30	120	5259.9846	-0.00029	5259.9889	-0.00021	5259.9875	-0.00024	5259.9829	-0.00033
20	120	5259.9918	-0.00016	5259.9998	0.00000	5259.9948	-0.00010	5259.9966	-0.00006
10	120	5259.9851	-0.00028	5259.9776	-0.00043	5259.9809	-0.00036	5259.9749	-0.00048
0	120	5260.0101	0.00019	5260.0029	0.00006	5260.0052	0.00010	5260.0078	0.00015
-10	120	5259.9874	-0.00024	5259.9855	-0.00028	5259.9853	-0.00028	5259.9883	-0.00022
-20	120	5260.0024	0.00005	5260.0052	0.00010	5260.0029	0.00006	5259.9999	0.00000
-30	120	5259.9866	-0.00025	5259.9787	-0.00040	5259.9882	-0.00022	5259.9801	-0.00038

FREQUENCY STABILITY VERSUS VOLTAGE									
OPERATING FREQUENCY: 5260MHz									
TEMP. (°C)	POWER SUPPLY (Vac)	0 MINUTE		2 MINUTE		5 MINUTE		10 MINUTE	
		Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)	Measured Frequency (MHz)	Frequency Drift (%)
20	138	5259.9929	-0.00013	5259.9999	0.00000	5259.996	-0.00008	5259.9958	-0.00008
	120	5259.9918	-0.00016	5259.9998	0.00000	5259.9948	-0.00010	5259.9966	-0.00006
	102	5259.9923	-0.00015	5259.9994	-0.00001	5259.9952	-0.00009	5259.9962	-0.00007

## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



## 6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**  
Tel: 886-2-26052180  
Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab:**  
Tel: 886-3-5935343  
Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Telecom Lab:**  
Tel: 886-3-3183232  
Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)  
**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

## 7. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---