REV	DESCRIPTION OF REVISION	ENG APPD	DATE
01	INITIAL DOCUMENT CREATION		01JUN12

ProSafe 3x3 Single Radio, Dual Band Wireless-N Access Point M/N:WNDAP620 DC Input: DC 12 V== 1.5 A DEFAULT ACCESS IP: http://192.168.0.100 User Name: admin password: password DEFAULT ACCESS IP: http://192.168.0.100 User Name: admin password: password	Power ACTIVE LAN WPA Passphrase: SSID: SERIAL: MAC: Made in China 2.4 GHz GHz GHz
	7

Pantone 430C

NOTE:

- 1. REFER TO NETGEAR SPEC. FD-10360-01 FOR MATERIAL SPECIFICATIONS AND TOLERANCES.
- 2. MAC & SERIAL NUMBERS TO BE PRINTED BY THE ODM.
- 3. DIE LINES ARE MAGENTA COLOR AND DO NOT PRINT.
- 4. INK COLOR IS SHOWN TO THE RIGHT.
- 5. See NTGR DOC-00112 for SN standard.
- 6. NTGR SN and MAC address barcode to be encoded AIM USS Code39 and include printed characters below barcodes.
- 7. INSURE COUNTRY OF ORIGIN IS CORRECT.
 - A. IF COUNTRY OF ORIGIN IS PRE-PRINTED, UNHIDE THE APPROPRIATE COUNTRY OF ORIGIN LAYER AND INCLUDE COUNTRY OF ORIGIN ON LABEL.
 - B. IF COUNTRY OF ORIGIN IS POST-PRINTED USING A THERMAL PRINTER (OR EQUIVALENT), UNHIDE THE WHITE BOX LAYER AND INCLUDE WHITE BOX ON LABEL.

AUTHOR:	R HU	AW,WNDAP620, V1H1, PLBL	NETGEAR	
SHEET:	1 of 1	THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR WHEREWITH IS NOT TO BE REPRODUCED, USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF NETGEAR, INC.	P/N: AW-11769-01	REV: