REV	DESCRIPTION OF REVISION	ENG APPD	DATE
01	INITIAL DOCUMENT CREATION	R HU	29MAY12

ProSafe 3x3 Dual Radi Wireless Access Point WNDAP660  DC Input: DC 12 V === 1.5 A  DEFAULT ACCESS IP: http://192.168.0.100 User Name: admin password: password	_	Operation may not accept any	ACTIVE LAN1 LAN2 WPA Passphrase: SSID: SERIAL: MAC:	2.4 5 GHz GHz
( '	^		Made III Clinia	272-11426-01
				-7

Pantone 430C

## NOTE:

- 1. REFER TO NETGEAR SPEC. FD-10360-01 FOR MATERIAL SPECIFICATIONS AND TOLERANCES.
- 2. MAC & SERIAL NUMBERS TO BE PRINTED BY THE ODM.
- 3. DIE LINES ARE MAGENTA COLOR AND DO NOT PRINT.
- 4. INK COLOR IS SHOWN TO THE RIGHT.
- 5. See NTGR DOC-00112 for SN standard.
- 6. NTGR SN and MAC address barcode to be encoded AIM USS Code39 and include printed characters below barcodes.
- 7. INSURE COUNTRY OF ORIGIN IS CORRECT.
  - A. IF COUNTRY OF ORIGIN IS PRE-PRINTED, UNHIDE THE APPROPRIATE COUNTRY OF ORIGIN LAYER AND INCLUDE COUNTRY OF ORIGIN ON LABEL.
  - B. IF COUNTRY OF ORIGIN IS POST-PRINTED USING A THERMAL PRINTER (OR EQUIVALENT), UNHIDE THE WHITE BOX LAYER AND INCLUDE WHITE BOX ON LABEL.

AUTHOR: R HU	AW,WNDAP660, V1H1, PLBL	NETGEAR	
SHEET:	THIS DOCUMENT AND THE DATA DISCLOSED HEREIN OR WHEREWITH IS NOT TO BE REPRODUCED, USED OR DISCLOSED IN WHOLE OR IN PART TO ANYONE WITHOUT THE PERMISSION OF NETGEAR, INC.	P/N: AW-11779-01	REV: