

FCC Test Report

FCC ID : PY314200268

Equipment : Universal WiFi Range Extender

Model No. : WN3000RPv3

Brand Name : NETGEAR

Applicant : NETGEAR, Inc.

Address : 350 East Plumeria Drive, San Jose, California

95134, U.S.A.

Standard : 47 CFR FCC Part 15.247

Received Date : Jun. 06, 2014

Tested Date : Jun. 06 ~ Jul. 07, 2014

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

Gary Chang / Manager

Iac MRA



Report No.: FR461202-01 Report Version: Rev. 01 Page: 1 of 62



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	
1.3	Test Setup Chart	
1.4	The Equipment List	
1.5	Test Standards	g
1.6	Measurement Uncertainty	g
2	TEST CONFIGURATION	9
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS	11
3.1	Conducted Emissions	11
3.2	6dB and Occupied Bandwidth	14
3.3	RF Output Power	
3.4	Power Spectral Density	19
3.5	Unwanted Emissions into Restricted Frequency Bands	21
3.6	Emissions in non-restricted frequency bands	49
4	TEST LABORATORY INFORMATION	62



Release Record

Report No.	Version	Description	Issued Date
FR461202-01	Rev. 01	Initial issue	Jul. 25, 2014

Report No.: FR461202-01 Page: 3 of 62



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.186MHz 54.24 (Margin -9.96dB) - QP	Pass
15.247(d)	Radiated Emissions	[dBuV/m at 3m]: 2483.50MHz	Pass
15.209	Radiated Effissions	53.87 (Margin -0.13dB) - AV	F a 5 5
15.247(b)(3)	Fundamental Emission Output Power	Power [dBm]: 24.04	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Report No.: FR461202-01 Page: 4 of 62



1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information								
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	Data Rate / MCS			
2400-2483.5	b	2412-2462	1-11 [11]	2	1-11 Mbps			
2400-2483.5	g	2412-2462	1-11 [11]	2	6-54 Mbps			
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	2	MCS 0-15			
2400-2483.5	n (HT40)	2422-2452	3-9 [7]	2	MCS 0-15			

Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.

Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.

Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

1.1.2 Antenna Details

Ant. No.	Туре	Type Gain (dBi) Connector		Remark
1	Dipole	2.2	UFL	
2	Dipole	2.2	UFL	

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	100-240Vac, 50-60Hz, 0.1A
-------------------	---------------------------

1.1.4 Accessories

N/A

Report No.: FR461202-01 Page: 5 of 62



1.1.5 Channel List

Frequency	band (MHz)	2400~2483.5		
802.11 b /	g / n HT20	802.11n HT40		
Channel	Frequency(MHz)	Channel	Frequency(MHz)	
1	2412	3	2422	
2	2417	4	2427	
3	2422	5	2432	
4	2427	6	2437	
5	2432	7	2442	
6	2437	8	2447	
7	2442	9	2452	
8	2447			
9	2452			
10	2457			
11	2462			

1.1.6 Test Tool and Duty Cycle

Test Tool	MT7620QA, V1.0.6.0					
	Mode	Duty cycle (%)	Duty factor (dB)			
	11b 100.00%		0.00			
Duty Cycle and Duty Factor	11g	99.50%	0.02			
	HT20	98.74%	0.05			
	HT40	98.33%	0.07			

Report No.: FR461202-01 Page: 6 of 62




1.1.7 Power Setting

Modulation Mode	Test Frequency (MHz)	Power Set
11b	2412	18/18
11b	2437	21/20
11b	2462	19/19
11g	2412	10/10
11g	2437	23/23
11g	2462	0F/0F
HT20	2412	0E/0E
HT20	2437	23/23
HT20	2462	0E/0E
HT40	2422	0A/0A
HT40	2437	11/11
HT40	2452	07/07

1.2 Local Support Equipment List

	Support Equipment List								
No.	Equipment	Brand	Model	S/N	FCC ID	Signal cable / Length (m)			
1	Notebook	DELL	E6430		DoC	RJ45, 10m non-shielded cable w/o core.			

1.3 Test Setup Chart



Report No.: FR461202-01 Page: 7 of 62



1.4 The Equipment List

Conducted Emission Conduction room 1 / (CO01-WS)							
							Manufacturer Model No. Serial No. Calibration Date Calibration Until
R&S	ESCS 30	100169	Oct. 15, 2013	Oct. 14, 2014			
SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 23, 2013	Nov. 22, 2014			
SCHWARZBECK	Schwarzbeck 8127	8127-666	Dec. 04, 2013	Dec. 03, 2014			
RF Cable-CON Woken CFD200-NL CFD200-NL-001 Ap							
50 ohm terminal (Support Unit) NA 50 04 Apr. 18, 2014 Apr. 17, 2015							
- ()	Manufacturer R&S SCHWARZBECK SCHWARZBECK Woken	ManufacturerModel No.R&SESCS 30SCHWARZBECKSchwarzbeck 8127SCHWARZBECKSchwarzbeck 8127WokenCFD200-NL	Manufacturer Model No. Serial No. R&S ESCS 30 100169 SCHWARZBECK Schwarzbeck 8127 8127-667 SCHWARZBECK Schwarzbeck 8127 8127-666 Woken CFD200-NL CFD200-NL-001	Manufacturer Model No. Serial No. Calibration Date R&S ESCS 30 100169 Oct. 15, 2013 SCHWARZBECK Schwarzbeck 8127 8127-667 Nov. 23, 2013 SCHWARZBECK Schwarzbeck 8127 8127-666 Dec. 04, 2013 Woken CFD200-NL CFD200-NL-001 Apr. 23, 2014			

Test Item	Radiated Emission							
Test Site	966 chamber 2 / (03CH02-WS)							
Instrument	Manufacturer Model No. Serial No. Calibration Date Calibration Until							
Spectrum Analyzer	R&S	FSV40	101499	Feb. 08, 2014	Feb. 07, 2015			
Receiver	R&S	ESR3	101657	Jan. 18, 2014	Jan. 17, 2015			
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-524	Jan. 08, 2014	Jan. 07, 2015			
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1095	Jan. 07, 2014	Jan. 06, 2015			
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Dec. 27, 2013	Dec. 26, 2014			
Preamplifier	Burgeon	BPA-530	100218	Dec. 09, 2013	Dec. 08, 2014			
Preamplifier	Agilent	83017A	MY39501309	Dec. 09, 2013	Dec. 08, 2014			
Preamplifier	WM	TF-130N-R1	923365	Oct. 23, 2013	Oct. 22, 2014			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16140/4	Dec. 17, 2013	Dec. 16, 2014			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16018/4	Dec. 17, 2013	Dec. 16, 2014			
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16015/4	Dec. 17, 2013	Dec. 16, 2014			
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-003	Dec. 17, 2013	Dec. 16, 2014			
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-004	Dec. 17, 2013	Dec. 16, 2014			
Note: Calibration Inte	rval of instruments listed	d above is one year.						

Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014			
Note: Calibration Interval of instruments listed above is two year.								

Test Item	RF Conducted								
Test Site	(TH01-WS)								
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until				
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2014	Feb. 16, 2015				
Power Meter	Anritsu	ML2495A	1241002	Oct. 24, 2013	Oct. 23, 2014				
Power Sensor	Anritsu MA2411B 1207366 Oct. 24, 2013 Oct. 23, 2014								
Note: Calibration Interval of instruments listed above is one year.									

Report No.: FR461202-01 Page: 8 of 62



1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2009

FCC KDB 558074 D01 DTS Meas Guidance v03r02

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

Note: The EUT has been tested and complied with FCC part 15B requirement. FCC Part 15B test results are issued to another report.

1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty					
Parameters	Uncertainty				
Bandwidth	±34.134 Hz				
Conducted power	±0.808 dB				
Frequency error	±34.134 Hz				
Temperature	±0.6 °C				
Conducted emission	±2.670 dB				
AC conducted emission	±2.92 dB				
Radiated emission ≤ 1GHz	±3.26 dB				
Radiated emission > 1GHz	±4.94 dB				

Report No.: FR461202-01 Page: 9 of 62



2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	22°C / 60%	Skys Huang
Radiated Emissions	03CH02-WS	24-25°C / 65-66%	York Lin
RF Conducted	TH01-WS	21°C / 64%	Brad Wu

FCC site registration No.: 657002IC site registration No.: 10807A-2

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Frequency (MHz)	Data Rate (Mbps) / MCS	Test Configuration
Conducted Emissions	11b	2437	1 Mbps	
Radiated Emissions ≤1GHz	11b	2437	1 Mbps	
Radiated Emissions >1GHz	11b	2412 / 2437 / 2462	1 Mbps	
Fundamental Emission Output Power	11g	2412 / 2437 / 2462	6 Mbps	
6dB bandwidth	HT20	2412 / 2437 / 2462	MCS 0	
Power spectral density	HT40	2422 / 2437 / 2452	MCS 0	

NOTE:

Report No.: FR461202-01 Page: 10 of 62

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.



3 Transmitter Test Results

3.1 Conducted Emissions


3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit						
Frequency Emission (MHz) Quasi-Peak Average						
0.15-0.5 66 - 56 * 56 - 46 *						
0.5-5	56	46				
5-30 60 50						
Note 1: * Decreases with the logarithm of the frequency.						

3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V / 60Hz.

3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR461202-01 Page: 11 of 62




Test Result of Conducted Emissions 3.1.4



Report No.: FR461202-01 Page: 12 of 62





2: Over Limit (dB) = Level (dBuV) - Limit Line (dBuV).

Report No.: FR461202-01 Page: 13 of 62



3.2 6dB and Occupied Bandwidth


3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

3.2.2 Test Procedures

- 1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
- 2. Detector = Peak, Trace mode = max hold.
- 3. Sweep = auto couple, Allow the trace to stabilize.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

3.2.3 Test Setup




Report No.: FR461202-01 Page: 14 of 62



3.2.4 Test Result of 6dB and Occupied Bandwidth

Modulation	N	Erog (MUz)			Limit (kU=)		
Mode	N _{TX}	Freq. (MHz)	Chain 0	Chain 1	Chain 2	Chain 3	Limit (kHz)
11b	2	2412	10.09	10.09			500
11b	2	2437	10.09	10.09			500
11b	2	2462	10.09	10.09			500
11g	2	2412	16.35	16.35			500
11g	2	2437	16.35	16.35			500
11g	2	2462	16.35	16.35			500
HT20	2	2412	17.33	17.33			500
HT20	2	2437	17.10	17.22			500
HT20	2	2462	17.04	17.04			500
HT40	2	2422	36.29	36.29			500
HT40	2	2437	36.29	36.29			500
HT40	2	2452	36.29	36.29			500



Report No.: FR461202-01 Page: 15 of 62



Modulation	N.	Freq.		99% Occupied E	Bandwidth (MHz)	
Mode	N _{TX}	(MHz)	Chain 0	Chain 1	Chain 2	Chain 3
11b	2	2412	12.77	12.66		
11b	2	2437	13.93	13.42		
11b	2	2462	12.74	12.66		
11g	2	2412	17.04	17.04		
11g	2	2437	18.99	18.38		
11g	2	2462	17.04	17.00		
HT20	2	2412	17.80	17.76		
HT20	2	2437	18.99	18.74		
HT20	2	2462	17.76	17.76		
HT40	2	2422	36.86	36.92		
HT40	2	2437	36.92	36.86		
HT40	2	2452	36.86	36.79		



Report No.: FR461202-01 Page: 16 of 62



3.3 RF Output Power

3.3.1 Limit of RF Output Power

Cor	duct	ed po	ower shall not exceed 1Watt.
	Ante	enna	gain <= 6dBi, no any corresponding reduction is in output power limit.
	Ante	enna	gain > 6dBi
		The	Fixed, point to point operations. conducted output power from the intentional radiator shall be reduced by the amount in dE the directional gain of the antenna exceeds 6 dB
		Syst Ope	ed, point to point operations tems operations tems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-pointerations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 that the directional gain of the antenna exceeds 6 dBi.
			tems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point rations ,no any corresponding reduction is in transmitter peak output power
3.3.	2	Test	Procedures
	Max	kimun	n Peak Conducted Output Power
		Spe	ctrum analyzer
		1.	Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
		2.	Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
		3.	Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.
		Pow	ver meter
		1.	A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
\boxtimes	Max	kimun	n Conducted Output Power
	\boxtimes	Pow	ver meter
		1.	A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
3.3.	3	Test	Setup

Report No.: FR461202-01 Page: 17 of 62

Power Sensor

Power Meter

Report Version: Rev. 01

EUT



3.3.4 Test Result of Maximum Output Power

Modulation Mode	N _{TX}	Freq. (MHz)	Conduc		age) outpu Bm)	t power	Total Power	Total Power	Limit
Wiode		(IVITIZ)	Chain 0	Chain 1	Chain 2	Chain 3	(mW)	(dBm)	(dBm)
11b	2	2412	19.65	19.66			184.727	22.67	30.00
11b	2	2437	21.02	21.04			253.531	24.04	30.00
11b	2	2462	19.72	19.83			189.917	22.79	30.00
11g	2	2412	15.82	15.91			77.189	18.88	30.00
11g	2	2437	20.47	20.71			229.190	23.60	30.00
11g	2	2462	14.27	14.20			53.033	17.25	30.00
HT20	2	2412	14.61	14.69			58.351	17.66	30.00
HT20	2	2437	20.41	20.52			222.620	23.48	30.00
HT20	2	2462	13.61	13.75			46.675	16.69	30.00
HT40	2	2422	13.28	13.33			42.809	16.32	30.00
HT40	2	2437	15.31	15.42			68.796	18.38	30.00
HT40	2	2452	11.79	11.77			30.132	14.79	30.00

Report No.: FR461202-01 Page: 18 of 62



3.4 Power Spectral Density


3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

3.4.2 Test Procedures

- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
 - Set the RBW = 30kHz, VBW = 100kHz.
 - Detector = Peak, Sweep time = auto couple.
 - 3. Trace mode = max hold, allow trace to fully stabilize.
 - 4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
 - 1. Set the RBW = 30kHz, VBW = 100 kHz.
 - 2. Detector = RMS, Sweep time = auto couple.
 - 3. Employ trace averaging (RMS) mode over a minimum of 100 traces
 - 4. Use the peak marker function to determine the maximum amplitude level.

3.4.3 Test Setup




Report No.: FR461202-01 Page: 19 of 62



3.4.4 Test Result of Power Spectral Density

Modulation Mode	N _{TX}	Freq. (MHz)	Total Power Spectral Density (dBm/30kHz)	Limit (dBm/3kHz)
11b	2	2412	-0.31	8.00
11b	2	2437	1.37	8.00
11b	2	2462	-0.16	8.00
11g	2	2412	-5.27	8.00
11g	2	2437	-0.49	8.00
11g	2	2462	-5.44	8.00
HT20	2	2412	-5.39	8.00
HT20	2	2437	-0.09	8.00
HT20	2	2462	-6.05	8.00
HT40	2	2422	-10.20	8.00
HT40	2	2437	-7.54	8.00
HT40	2	2452	-11.81	8.00

Note: Test result is bin-by-bin summing measured value of each TX port.



Report No.: FR461202-01 Page: 20 of 62



3.5 Unwanted Emissions into Restricted Frequency Bands

3.5.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit							
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)				
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300				
0.490~1.705	24000/F(kHz)	33.8 - 23	30				
1.705~30.0	30	29	30				
30~88	100	40	3				
88~216	150	43.5	3				
216~960	200	46	3				
Above 960	500	54	3				

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2:**

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.5.2 Test Procedures

- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- 3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR461202-01 Page: 21 of 62




3.5.3 Test Setup



Report No.: FR461202-01 Page: 22 of 62



3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR461202-01 Page: 23 of 62



Modulation			11b			7	Test Free	q. (MHz)		2437		
Polarization		Vert	cal		•				•			
	90 Le	vel (dBu	V/m)							Time:	14:49:19	, 7
	80-											
	70											
	70											
	60									ECC C	LASS-B	
	50									1000	LA33-D	
	30								6			
	40											
	30	2	3					4	5			
								il				
	20											1
	10											
	030	100.	20	0. 30	0. 40	00. 50 Freque	0. 600 ncy (MHz)	0. 700.	800.	900.	. 100	00
		Fr	rea. I	mission	Limit	Margin	SA	Factor	Remark	C AN	T Tu	ırn
				level			reading			Hig	gh Ta	ble
		1	MHz	dBuV/m	dBuV/r	n dB	dBuV	dB		cm	de	g
	1	_	38.73	32.63	40.00	-7.37	49.77	-17.14	Peak			
	2		04.69			-15.75		-20.91	Peak			
	3	19	92.96	28.10	43.50	-15.40		-19.62	Peak			
	4			26.41				-8.65	Peak			
	5		73.99			-16.89	36.17		Peak			
•	6	83	14.73	40.47	46.00	-5.53	47.03	-6.56	Peak			

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR461202-01 Page: 24 of 62



3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11b



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 25 of 62



Modulation		11b			-	Test Fre	q. (MHz)		2412	
Polarization		Verti	cal		·					
90 <mark>Le</mark>	vel (dBu	ıV/m)								
80-										
70									FCC CLAS	SS-B
70										
60	4	g						FCC	CLASS-B (AVG)
50	2 3									-
40										
30										+
20										+
10										
010	000	4000.	6000. 80	000. 100		. 14000. ncy (MHz)	16000. 180	00. 20000.	22000.	25000
	F	rea. E	mission	Limit	Margin		Factor	Remark	ANT	Turn
			level			reading	3		High	Table
		MHz	dBuV/m	dBuV/	m dB	dBuV	dB		cm	deg
1	15	00.00	36.73	54.00	-17.27	43.20	-6.47	Average		
2		00.00			-24.37	56.10	-6.47	Peak		
3		90.00			-8.02	48.80	-2.82	Average		
4 5					-17.10 -0.20	59.72 48.71	-2.82 5.09	Peak Average		
6			56.44			51.35	5.09	Peak		


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 26 of 62

Report Version: Rev. 01





10.74

Peak

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

7311.00 55.85 74.00 -18.15 45.11

*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 27 of 62

Report Version: Rev. 01

8





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 28 of 62

Report Version: Rev. 01

5

6

7

8

4874.00

4874.00

7311.00

53.80

56.14

53.60

7311.00 58.97 74.00 -15.03

54.00 -0.20

74.00 -17.86

54.00 -0.40

48.62

50.96

42.86

48.23

5.18

5.18

10.74

10.74


Average

Average

Peak

Peak






Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 29 of 62





47.67

10.84

Peak

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain

7386.00 58.51 74.00 -15.49

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Report No.: FR461202-01 Page: 30 of 62

Report Version: Rev. 01

6



3.5.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11g



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 31 of 62



Modulation			11g			-	Test Fred	q. (MHz)	2	412	
Polarization			Verti	ical		•			•		
	90	Level	(dBuV/m)								$\overline{}$
	80										
	80		4							FCC CLAS	S-B
	70										
	60										
		2 :	6						FCC C	LASS-B (A	WG)
	50	Ť	Ť								
	40	4									
	30										
	20										-
	10										
	10										
	O	1000	4000.	6000. 80	000. 100	00. 12000). 14000. 1	6000. 180	00. 20000. 2	2000.	25000
						Freque	ency (MHz)				
			Freq. E	mission	Limit	Margin	SA	Factor	Remark	ANT	Turn
				level			reading			High	Table
			MHz	dBuV/m	dBuV/ı	n dB	dBuV	dB		CM	deg
	1		1500.00	37 15	5/ 00	-16 85	43.62	-6.47	Average		
	2		1500.00				56.73		Peak		
	3		2390.00				53.98	-2.82	Average		
			2200 00	74 74		0.50	74.43		5 .		

74.13

31.03

-2.82

5.09

5.09

Peak

Peak

Average

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain

2390.00 71.31 74.00 -2.69 74.13 4824.00 36.12 54.00 -17.88 31.03 4824.00 50.00 74.00 -24.00 44.91

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 32 of 62

Report Version: Rev. 01

5



3

4

5

6

7

8

Modulation			119	9		,	Test Fre	q. (MHz)		2437	
Polarization			Но	rizontal		<u>'</u>					
	90	Level	(dBuV/m)								
	80										
	00									FCC CLAS	S-B
	70										
	60		4								
				3 8					FCC	CLASS-B (A	WG)
	50		В								
	40			1	•						
	30										
	20										
	10										
	0										
	U	1000	4000.	6000.	8000. 100). 14000. ency (MHz)	16000. 180	00. 20000.	22000.	25000
			Frea.	Emissio	n Limit	Margir	s SA	Factor	Remark	ANT	Turn
			-	level		0	reading			High	Table
			MHz	dBuV/m	dBuV/	m dB	dBuV	dB		cm	deg
1	1		2390.0	0 40.15	54.00	-13.85	42.97	-2.82	Average	- 	

-2.39

-2.39

5.18

5.18

10.74

10.74

63.85

30.41

45.65

Average

Average

Average

Peak

Peak

Peak

2483.50 42.53 54.00 -11.47 44.92

7311.00 38.56 54.00 -15.44 27.82

7311.00 52.76 74.00 -21.24 42.02

2483.50 61.46 74.00 -12.54

4874.00 35.59 54.00 -18.41

4874.00 50.83 74.00 -23.17


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 33 of 62



Modulation	11g	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Ü	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	42.35	54.00	-11.65	45.17	-2.82	Average		
2	2390.00	60.01	74.00	-13.99	62.83	-2.82	Peak		
3	2483.50	44.79	54.00	-9.21	47.18	-2.39	Average		
4	2483.50	63.51	74.00	-10.49	65.90	-2.39	Peak		
5	4874.00	38.02	54.00	-15.98	32.84	5.18	Average		
6	4874.00	52.05	74.00	-21.95	46.87	5.18	Peak		
7	7311.00	41.19	54.00	-12.81	30.45	10.74	Average		
8	7311.00	56.74	74.00	-17.26	46.00	10.74	Peak		

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 34 of 62





Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 35 of 62



Modulation	11g	Τ	est Freq. (MHz)	24	62				
Polarization	Vertical								
90 Level (dE	BuV/m)								
80 2				F	CC CLASS-B				
70									
60									
	4 6			FCC CL	ASS-B (AVG)				
50									
40									
30									
30									
20									
10									
1000	4000. 6000. 80		14000. 16000. 1800 ncy (MHz)	0. 20000. 22	25000				
	Frea. Emission	Limit Margin	SA Factor	Remark	ANT Turr				
	level		reading		High Tab				
	MHz dBuV/m	dBuV/m dB	dBuV dB		cm deg				
1 2	483.50 52.23	54.00 -1.77	54.62 -2.39	Average					
	483.50 73.75	74.00 -0.25	76.14 -2.39	Peak					
	1924.00 36.51	54.00 -17.49	31.23 5.28	Average					
	1924.00 50.27		44.99 5.28	Peak					
5 7	386.00 38.51	54.00 -15.49	27.67 10.84	Average					

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 36 of 62

Report Version: Rev. 01



3.5.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR461202-01 Page: 37 of 62



Modulation	HT20	Test Freq. (MHz)	2412
Polarization	Vertical		




	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	1500.00	37.58	54.00	-16.42	44.05	-6.47	Average		
2	1500.00	50.67	74.00	-23.33	57.14	-6.47	Peak		
3	2390.00	52.48	54.00	-1.52	55.30	-2.82	Average		
4	2390.00	73.51	74.00	-0.49	76.33	-2.82	Peak		
5	4824.00	35.56	54.00	-18.44	30.47	5.09	Average		
6	4824.00	49.31	74.00	-24.69	44.22	5.09	Peak		

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 38 of 62



Modulation		HT20			Test	Freq.	(MHz))	24	2437		
Polarization		Horizor	ntal									
Lei	vel (dBu\	//m)										
80									F	C CLAS	S-B	




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Ū	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	40.63	54.00	-13.37	43.45	-2.82	Average		
2	2390.00	58.78	74.00	-15.22	61.60	-2.82	Peak		
3	2483.50	42.92	54.00	-11.08	45.31	-2.39	Average		
4	2483.50	62.03	74.00	-11.97	64.42	-2.39	Peak		
5	4874.00	35.08	54.00	-18.92	29.90	5.18	Average		
6	4874.00	49.90	74.00	-24.10	44.72	5.18	Peak		
7	7311.00	39.02	54.00	-14.98	28.28	10.74	Average		
8	7311.00	54.41	74.00	-19.59	43.67	10.74	Peak		

*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 39 of 62



Modulation	HT20	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	42.23	54.00	-11.77	45.05	-2.82	Average		
2	2390.00	59.25	74.00	-14.75	62.07	-2.82	Peak		
3	2483.50	45.00	54.00	-9.00	47.39	-2.39	Average		
4	2483.50	64.23	74.00	-9.77	66.62	-2.39	Peak		
5	4874.00	36.87	54.00	-17.13	31.69	5.18	Average		
6	4874.00	50.80	74.00	-23.20	45.62	5.18	Peak		
7	7311.00	40.42	54.00	-13.58	29.68	10.74	Average		
8	7311.00	55.96	74.00	-18.04	45.22	10.74	Peak		

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 40 of 62






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 41 of 62






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 42 of 62



3.5.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT40



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR461202-01 Page: 43 of 62



3

4

5

6

Modulation	HT40		Test Freq.	(MHz)	242	2
Polarization	Vertical	•			•	
90 Level (dBuV/m)					
80						
4					FCC	C CLASS-B
70						
60					ECC CLAS	SS-B (AVG)
50					FCC CLA	33-B (AVU)
	6					
40	5					
30						
20						
10						
0 <mark></mark> 1000	4000. 6000. 80	000. 10000. 12000 Freque	. 14000. 160 ency (MHz)	000. 18000. 20	0000. 2200	00. 25000
	Freq. Emission	Limit Margin	SA F	actor Rem	ıark	ANT Tur
	level		reading			High Tab
	MHz dBuV/m	dBuV/m dB	dBuV	dB		cm deg
1	1500.00 37.59	54.00 -16.41	44.06	-6.47 Ave	erage	
	1500.00 50.68					

56.58

76.37

-2.82

-2.82

5.13

5.13

Average

Average

Peak

Peak

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain

2390.00 53.76 54.00 -0.24 2390.00 73.55 74.00 -0.45


4844.00 32.63 54.00 -21.37 27.50 4844.00 45.52 74.00 -28.48 40.39

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 44 of 62



Modulation			HT40			Test	Test Freq. (MHz)				2437			
Polarization			Horizo	ntal										
	Leve	el (dBuV	/m)											
8														
8	u										F	C CLAS	S_B	




	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	46.68	54 00	-7.32	49.50	-2.82	Average		
2	2390.00			-4.88	71.94	-2.82	Peak		
3	2483.50	44.26	54.00	-9.74	46.65	-2.39	Average		
4	2483.50	63.09	74.00	-10.91	65.48	-2.39	Peak		
5	4874.00	32.00	54.00	-22.00	26.82	5.18	Average		
6	4874.00	45.72	74.00	-28.28	40.54	5.18	Peak		

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 45 of 62



Modulation	HT40	Test Freq. (MHz)	2437
Polarization	Vertical		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m		SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	49.74	54.00	-4.26	52.56	-2.82	Average		
2	2390.00	71.56	74.00	-2.44	74.38	-2.82	Peak		
3	2483.50	52.41	54.00	-1.59	54.80	-2.39	Average		
4	2483.50	71.38	74.00	-2.62	73.77	-2.39	Peak		
5	4874.00	33.99	54.00	-20.01	28.81	5.18	Average		
6	4874.00	46.72	74.00	-27.28	41.54	5.18	Peak		

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 46 of 62






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 47 of 62



Modulation	HT40	Tes	t Freq. (MHz)	2452		
Polarization	Vertical					
90 Level (dBuV/m)					



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m		SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	37.96	54 00	-16 04	44.43	-6.47	Average		
2		51.13			57.60	-6.47	Peak		
3	2483.50	53.65	54.00	-0.35	56.04	-2.39	Average		
4	2483.50	72.92	74.00	-1.08	75.31	-2.39	Peak		
5	4904.00	32.95	54.00	-21.05	27.71	5.24	Average		
6	4904.00	45.88	74.00	-28.12	40.64	5.24	Peak		

*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR461202-01 Page: 48 of 62



3.6 Emissions in Non-Restricted Frequency Bands

3.6.1 Emissions in Non-Restricted Frequency Bands Limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz

3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures


Reference level measurement

- 1. Set RBW=100kHz, VBW = 300kHz, Detector = Peak, Sweep time = Auto
- 2. Trace = max hold, Allow Trace to fully stabilize
- 3. Use the peak marker function to determine the maximum PSD level

Emission level measurement

- 1. Set RBW=100kHz, VBW = 300kHz, Detector = Peak, Sweep time = Auto
- 2. Trace = max hold, Allow Trace to fully stabilize
- 3. Scan Frequency range is up to 25GHz
- 4. Use the peak marker function to determine the maximum amplitude level

3.6.4 Test Setup



3.6.5 Test Result of Emissions in non-restricted frequency bands


This test item is performed on each TX output individually without summing or adding 10 $log(N_{ANT})$ since measurements are made relative to the in-band emissions on the individual outputs. Only worst test result of each operating mode is presented.

Report No.: FR461202-01 Page: 49 of 62




3.6.6 Unwanted Emissions into Non-Restricted Frequency Bands

802.11b




Report No.: FR461202-01 Report Version: Rev. 01






Report No.: FR461202-01 Page: 51 of 62






Report No.: FR461202-01 Page: 52 of 62






Report No.: FR461202-01 Page: 53 of 62





Report No.: FR461202-01 Page: 54 of 62






Report No.: FR461202-01 Page: 55 of 62




802.11n HT20




Report No.: FR461202-01 Page: 56 of 62





Report No.: FR461202-01 Page: 57 of 62






Report No.: FR461202-01 Page: 58 of 62




802.11n HT40




Report No.: FR461202-01 Page: 59 of 62





Report No.: FR461202-01 Page: 60 of 62





Report No.: FR461202-01 Page: 61 of 62



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website http://www.icertifi.com.tw.

Linkou Kwei Shan

Tel: 886-2-2601-1640 Tel: 886-3-271-8666

No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei
City, Taiwan, R.O.C.

No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan
Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==

Report No.: FR461202-01 Page: 62 of 62